

# BOSTIK ROLL 240

## Contact Dry Adhesives



### KEY BENEFITS

- Designed for PVC or rubber stairtreads with pre-shaped corner.
- Immediate grip and long-life bond.
- Ultra resistant.
- Odourless .
- Quick, easy and clean installation.
- Can accept foot traffic immediately.
- PVC softflooring material not affected.
- High temperature resistance (-40°C à +120°C).
- Compatible with central heating pipes and radiant underfloors.
- Non flammable.
- Phthalate-free & solvent-free.
- Very low VOC emissions : class A+, Emission EC1 PLUS.
- Comply with LEED & BREEAM requirements.

### DESCRIPTION

Double sided reinforced tape for the implementation of soft floor coverings in stairs. PVC, linoleum, rubber, carpets all types, needle-punched fabric.

- Stair tread with pre-shaped corner.
- Protective wall panels (for hospitals and health centers, schools, offices).
- Tread alert tactile surface and guide paths.
- Multi-subfloors, efficient alternative to solvent neoprene adhesives..

**Bostik Ltd.**  
Stafford, UK  
Phone : +44 (0) 1785 27 27 27  
Fax : +44 (0) 1785 22 26 65  
[www.bostik.co.uk](http://www.bostik.co.uk)

**Bostik S.A.**  
La Plaine Saint-Denis, France  
Phone : +33 (0)155 99 90 00  
Fax : +33 (0)155 99 90 01  
[www.bostik.fr](http://www.bostik.fr)

**Bostik GmbH**  
Borgholzhausen, Germany  
Phone : +49 (0)54 25/801-0  
Fax : +49 (0)54 25/801140  
[www.bostik.de](http://www.bostik.de)

**Bostik B.V.**  
's-Hertogenbosch, The Netherlands  
Phone : +31 (0)7 36 244 244  
Fax : +31 (0)7 36 244 344  
[www.bostik.nl](http://www.bostik.nl)

### On subfloors as :

- Concrete<sup>1</sup> slabs.
- Cement screeds<sup>1</sup>.
- Calcium sulphate screeds<sup>1</sup>.
- Selfleveling compounds.
- Plywood<sup>1</sup>, OSB<sup>1</sup>.
- Metal or non porous substrates.
- Suitable on central heating pipes and radiant underfloors.

Other cases, wall substrates as plasterboard, gypsum blocks, existing wall coverings.

<sup>1</sup>In case of porous surface, systematically used the dedicated primer Bostik. If the substrate is non-smooth, a Bostik selfleveling compound is used to correct it.

### PREPARATION

Ensure the subfloor is clean, sound, dry, and of adequate tensile and compression strength, free from laitance, cracks and structural defects. It needs to be conformed to the regulation. Any contaminants that may hinder adhesion, such as grease, dust, some curing compounds and moisture sensitive adhesive residues must be completely removed. If the subfloor is not smooth, apply a Bostik self leveling compound to correct the surface.

### APPLICATION

Unroll and apply the tape along on the subfloor or wall. Press on the entire surface of the protective paper, eliminate any air bubble and insure the adhesion everywhere. Pull protective paper and rub down the flooring or decoration.

On stairs the strip is installed perpendicular to the steps.

### TECHNICAL DATA

CHARACTERISTIC	
Adhesive type	Pre-coating based on synthetic resins and reinforced weft
Colour	Translucent
Waiting time	Without, immediate use
Working time	unlimited
Application temperature	+10°C to +30°C & HR< 70%
Temperature resistance	-40°C to +120°C
Set to traffic	Immediately after installation
Consumption	1 reel = 50 meters long

### STORAGE STABILITY

18 months in original package not opened between +10°C and +30°C, away from humidity

### PRECAUTIONS

Protect reels from dust and moisture.

Article	Gencod	Packaging	PCB
30607857	3549212475536	240mm x 25m	1

### FURTHER INFORMATION

The following publication is available on request:

- Material Safety Data Sheets (MSDS)

The information given and recommendations made herein are based on Bostik's research only and are not guaranteed to be accurate. The performance of the product, its shelf life, and application characteristics will depend on many variables, including the kind of materials to which the product will be applied, the environment in which the product is stored or applied, and the equipment used for application. Any change in any of these variables can affect the product's performance. It is the buyer's obligation, prior to using the product, to test the suitability of the product for an intended use under the conditions that will exist at the time of the intended use. Bostik does not warrant the product's suitability for any particular application. The product is sold pursuant to Bostik's Terms and Conditions of Sale that accompanies the product at the time of sale. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

### SMART HELP

Please contact your local representative

