



BOSTIK ROLL RF50-RF100

Contact Dry Adhesives



KEY BENEFITS

- Subsequent easy removal.
- Immediate installation without waiting time.
- Micro-perforated mesh, to prevent adhesive lumps from forming.
- Quick, easy and clean installation.
- Repositional if needed.
- Can accept foot traffic immediately.
- Immediate seam welding possible.
- PVC softflooring material not affected.
- Non flammable.
- Solvent-free, phthalate-free.
- Compatible with central heating pipes.
- Comply with LEED & BREEAM requirements .

DESCRIPTION

Removable adhesive strip specially designed for use with flexible floor coverings in renovation projects. Ensures a strong bond around the edges of the room (BOSTIK ROLL RF50), as well as the seams (BOSTIK ROLL RF100). Mainly designed for semi-permanent installation of homogeneous PVC, heterogeneous PVC and expanded vinyl floor covering strips.

On subfloors :

- Concrete¹ slabs.
- Cement screeds¹.
- Calcium sulphate screeds¹.
- Selfleveling compounds.
- Chipboard, plywood¹, OSB¹.
- Metal or non porous substrates.
- Compatible with under-floor heating (low temperature)

¹In case of porous surface, systematically used the dedicated primer Bostik. If the substrate is non-smooth, a

Bostik Ltd.
Stafford, UK
Phone : +44 (0) 1785 27 27 27
Fax : +44 (0) 1785 22 26 65
www.bostik.co.uk

Bostik S.A.
La Plaine Saint-Denis, France
Phone : +33 (0)155 99 90 00
Fax : +33 (0)155 99 90 01
www.bostik.fr

Bostik GmbH
Borgholzhausen, Germany
Phone : +49 (0)54 25/801-0
Fax : +49 (0)54 25/801140
www.bostik.de

Bostik B.V.
's-Hertogenbosch, The Netherlands
Phone : +31 (0)7 36 244 244
Fax : +31 (0)7 36 244 344
www.bostik.nl

TECHNICAL DATA

CHARACTERISTIC	
Adhesive type	Pre-coating based on synthetic resins and reinforced weft
Colour	Colourless glue on white mesh
Waiting time	Without, immediate use
Working time	unlimited
Application temperature	+10°C to +30°C & HR< 70%
Temperature resistance	-40°C to +120°C
Set to traffic	Immediately after installation
Consumption	1 reel = 25 meters long

Bostik selfleveling compound is used to correct it.

On existing bonded floor coverings (refurbishing)

-Compact PVC, semi-flexible vinyle tiles with or without asbestos fiber content.

Others, please contact us.

PREPARATION

Ensure the subfloor is clean, sound, dry, and of adequate tensile and compression strength, free from laitance, cracks and structural defects. It needs to be conformed to the regulation. Any contaminants that may hinder adhesion, such as grease, dust, some curing compounds and moisture sensitive adhesive residues must be completely removed. If the subfloor is not smooth, apply a Bostik self leveling compound to correct the surface.

Make sure existing floor covering is soundly bonded onto the surface below. Clean the whole of the area to be covered using a caustic soda preparation, then rinse with water. Repair any surface defects.

New surfaces must be prepared in accordance with the applicable professional guidelines.

Surfaces should be thoroughly vacuumed.

APPLICATION

On existing floor coverings, insure adhesion and solidity are right everywhere with the original subfloor. Carry out an initial test to make sure BOSTIK Roll RF50/RF100 bonds correctly onto the surface in question.

Flooring installation must be realized according flooring manufacturer instructions. BOSTIK ROLL reels and softfloor coverings are stored together in the same room.

Peripheral holding installation :

Unroll and apply the tape BOSTIK ROLL RF50 on the peripheral subfloor room. The protective paper is left in position. Place and set the softflooring strips. Lift up the strips and remove the protective paper from tapes. Then apply the softfloor covering in its definitive location. Rub down and cut along .

Junction between two strips :

Unroll and apply the tape BOSTIK ROLL RF100 below the two strips to join, the tape's center line remains aligned with the edges. Lift up the strips and remove the protective paper from tapes. Then apply the 2 strips in their definitive location and rub down to insure the bonding in every points .

SEAM WELDS

Seams can be welded immediately after the lengths of covering have been smoothed down.

REMOVAL OF FLOOR COVERING

Removal is quick and easy even after several years. This means a new floor covering can be laid directly on the stripped surface, once cleaned.

STORAGE STABILITY

18 months in original package not opened between +10°C and +30°C.

Reels should be stored in a dry location not subject to extreme heat or cold, and not exposed to direct sunlight.

PRECAUTIONS

Protect reels from dust and moisture.

Article	Gencod	Reel size	PCB
30607860	3549212475598	48mm x 25m	6
30607861	3549212475611	96mm x 25m	3

FURTHER INFORMATION

The following publication is available on request:

- Material Safety Data Sheets (MSDS)

The information given and recommendations made herein are based on Bostik's research only and are not guaranteed to be accurate. The performance of the product, its shelf life, and application characteristics will depend on many variables, including the kind of materials to which the product will be applied, the environment in which the product is stored or applied, and the equipment used for application. Any change in any of these variables can affect the product's performance. It is the buyer's obligation, prior to using the product, to test the suitability of the product for an intended use under the conditions that will exist at the time of the intended use. Bostik does not warrant the product's suitability for any particular application. The product is sold pursuant to Bostik's Terms and Conditions of Sale that accompanies the product at the time of sale. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

SMART HELP

Please contact your local representative

