

# STIX A330 LINO PROJECT

DISPERSION ADHESIVE WITH HIGH INITIAL FORCE

## KEY BENEFITS

- Strong adhesion
- Odour free
- High retention



## APPLICATIONS

### DESTINATIONS

STIX A330 LINO PROJECT is a dispersion adhesive with high initial adhesive strength.

#### Associated floor coverings :

- Bonding linoleum
- Cork linoleum
- Cork on absorbent surfaces

## PRODUCT CHARACTERISTICS

<b>Composition/ colour</b>	Synthetic resin dispersion / Beige white
<b>Waiting time*</b>	5 min
<b>Open time*</b>	10-15 min
<b>Walk on time*</b>	24 hours
<b>Curing time* / Floor installation</b>	After 24 hours
<b>Coverage</b>	400 g/m <sup>2</sup>
<b>Application temperature</b>	air 18°C to 23°C Not above 75 % relative humidity.

\* these times are determined at + 23° C and 50 % relative humidity on normally absorbent substrates

## SUBFLOOR PREPARATION

### CLEANING PREPARATION

The subfloor must be level, permanently dry, clean, free of cracks, tensile and compressive strength in accordance with the requirements of DIN 18365 "Floor covering work" and, if necessary, be professionally prepared for installation. For this purpose, use suitable primers and smoothing compounds from our range. Mastic asphalt screeds and other non-absorbent surfaces should always be levelled out to a minimum layer thickness of 2 mm.

### METHOD OF USE

STIX A330 LINO PROJECT is evenly applied to the substrate with a spatula with suitable TKB serration. Then slowly push or roll the linoleum web into the adhesive bed without air inclusion and rub/roll it in (50 kg articulated roller). Lay the other half of the room in the same way. After approx. 30 minutes, rub/roll the floor covering once again and check for cavities. Heat-seal the joints at an early stage after 24 hours. Observe the instructions of the flooring manufacturer, especially with regard to the air-conditioning of the flooring.

### OCCUPATIONAL SAFETY AND ENVIRONMENTAL PROTECTION

Please refer to the current product safety data sheet for information on occupational safety and environmental protection.

## COVERAGE

400 g/m<sup>2</sup>

## STORAGE STABILITY

Keep container tightly closed. Store in a cool and dry place.  
Protect from frost! Shelf life 12 months.

Code	UC	PCB	GENCOD
30615759	14 kg	1	4008373130511

### SAFETY

For more details, consult the safety data sheet on <https://bostikdsd.thewerccs.com/default.aspx>

*The information given and recommendations made herein are based on Bostik's research only and are not guaranteed to be accurate. The performance of the product, its shelf life, and application characteristics will depend on many variables, including the kind of materials to which the product will be applied, the environment in which the product is stored or applied, and the equipment used for application. Any change in any of these variables can affect the product's performance. It is the buyer's obligation, prior to using the product, to test the suitability of the product for an intended use under the conditions that will exist at the time of the intended use. Bostik does not warrant the product's suitability for any particular application. The product is sold pursuant to Bostik's Terms and Conditions of Sale that accompanies the product at the time of sale. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the pat*

### BOSTIK TECHNICAL ASSISTANCE

Smart Help +XX XX XXX XXX

