



H975

PANELTACK HM HIGHLY ELASTIC CLADDING PANEL ADHESIVE

TECHNICAL DATA SHEET

BENEFITS

- Suitable for all sort of cladding panels like fibre cement boards and aluminium composite panels
- Strong, high modulus
- KOMO certified

PRODUCT DESCRIPTION

Bostik H975 Paneltack HM (High Modulus) is a moisture-curing, elastic adhesive with high modulus based on SMP, specially developed for bonding fibre-cement boards, natural stone, thin ceramic tiles with fibre mesh backing & aluminum composite cladding panels.

APPLICATIONS

Bonding of cladding panels for façade cladding, fascias, soffits, canopies and parapets.

FEATURES

- Solvent- and isocyanate-free.
- Long-lasting high elasticity with optimum distribution of strain.
- Excellent mechanical strength.
- Good moisture- and weather-resistance.
- Simple and fast fixation.

DIRECTIONS OF USE

Please refer to the installation instructions for the specific wall cladding panels.

A wide variety of wall cladding panel systems are available on the market, each with their own individual characteristics. Bostik therefore works closely with major wall cladding panel manufacturers to match the adhesive system to the specific cladding panels. A detailed installation instruction is available for a number of cladding panels, with specific information for the cladding panel concerned.



TECHNICAL DATA

Base	SMP (Silyl Modified Polymer)
Component	1
Type	Elastic
Consistency	Smooth, homogeneous paste
Density	Approx. 1.5 g/ml
Flow resistance 25mm	0mm (at +20°C)
Skin formation (start)	15 min. (at +20°C/RV 50%)
Temperature resistance	-40°C to +90°C
Application temperature	+5°C to +30°C
Tensile strength	2.6 N/mm ² (ISO 37)
Shear strength	2.5 N/mm ² (ISO 37)
Max. allowable movement	3mm

These values are typical properties and may vary +/-3%

CLEANING

Uncured material and tools can be cleaned by using **Bostik T100 UNIVERSAL CLEANER**. Cured material can only be mechanically removed. Hands can be cleaned with **Bostik T150 CLEANING WIPES**.

COLOUR(S)

- Black

PACKAGING

- 290 ml cartridges, 12 per box
- 600ml sausages, 12 per box

SHELF LIFE

In unopened original packaging between + 5°C and +25°C, shelf life is up to 12 months from production date, stored in a dry place.

CERTIFICATIONS

- KOMO
- Fire tests according to EN 13501-1
- Emicode EC1Plus

HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available via [Wercs](#).

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce

Bostik Benelux BV
Denariusstraat 11 • NL-4903 RC Oosterhout
Tel.: +31 (0)162 491 000
www.bostik.com

BOSTIK SMART SUPPORT

Smart help digital
Bostik.com/

Smart help
+31 (0)162 491 000

