

S970

PANELTACK S HIGHLY ELASTIC CLADDING PANEL ADHESIVE

TECHNICAL DATA SHEET

BENEFITS

- MEKO-free
- Quick and easy application
- Excellent moisture- and weather-resistance

PRODUCT DESCRIPTION

Bostik S970 Paneltack S is a moisture-curing, highly elastic adhesive based on silicone, specially developed for bonding of pressed mineral wool panels (ROCKPANEL).

APPLICATIONS

The product is suitable for bonding panels based on pressed mineral wool (ROCKPANEL) in applications such as façade cladding, fascias, soffits and canopies.

APPLICATIONS

- Solvent- and isocyanate-free
- MEKO-free formulation
- Long-term high elasticity with optimum stress
- distribution
- Excellent mechanical strength
- Good moisture- and weather-resistance
- Simple and fast fixation

DIRECTIONS OF USE

Please refer to the installation instructions for the specific wall cladding panels.

A wide variety of wall cladding panel systems are available on the market, each with their own individual characteristics. Bostik therefore works closely with major wall cladding panel manufacturers to match the adhesive system to the specific cladding panels. A detailed installation instruction is available for a number of cladding panels, with specific information for the cladding panel concerned.



TECHNICAL DATA	
Base	2-Pentanone Oxime
Component	1
Туре	Elastic
Consistency	Smooth, homogeneous
	paste
Density	1.26 g/ml (ISO 1183-1)
Modulus 100%	0.79 N/mm2 (DIN 53504 S2)
Tensile strength	2.1 N/mm2 (DIN 53504 S2)
Elongation at break	540% (DIN 53504 S2)
Skin formation (start)	10 min. (at +23°C/50% RH)
Shore A	35 (DIN 53505 3 sec)
Flow	< 2 mm (ISO 7390)
Application temperature	+5°C to +40°C
Curing time	2-3 mm/24 hours (@ +23 °
	C/50% RH)
Temperature resistance	-40°C to +120°C
Application temperature	+5°C to +40°C
Frost resistance during	up to -15°C
transportation	

These values are typical properties and may vary +/-3%

CLEANING

Uncured material and tools can be cleaned by using **Bostik T100 UNIVERSAL CLEANER.** Cured material can only be mechanically removed. Hands can be cleaned with **Bostik T150 CLEANING WIPES.**

COLOUR(S)

White

PACKAGING

- 310 ml cartridges, 12 per box
- 600ml sausages, 12 per box

SHELF LIFE

In unopened original packaging between +5°C and +25°C, shelf life up to 12 months from production date, stored in a dry place.

CERTIFICATIONS

Emicode EC1Plus

HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available via <u>Wercs</u>.

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to devents occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce



Bostik Benelux BV

Denariusstraat 11 • NL-4903 RC Oosterhout Tel.: +31 (0)162 491 000 www.bostik.com