



P925

FOAM'N'FIX TURBO MULTI-USE FAST TACK AND QUICK SETTING UNIVERSAL FOAM ADHESIVE

TECHNICAL DATA SHEET

BENEFITS

- Fast curing and quick setting foam adhesive
- Maximum open time of 2.5 minutes
- Saves time & money
- High shear and tensile strength
- All seasons formulation, -10°C to +40°C
- For bonding and filling purposes
- Provides added thermal insulation

PRODUCT DESCRIPTION

Bostik P925 FOAM'N'FIX TURBO MULTI-USE is a money and time saving multipurpose fast curing and fast setting foam adhesive and is recommended for installing window frames and doors, to fill gaps, bonding stony and concrete type of products as well dry wall panels and decorative elements.

APPLICATIONS

Bostik P925 FOAM'N'FIX TURBO MULTI-USE is a multipurpose construction adhesive providing an excellent adhesion to a wide range of substrates, such as dry walls but also stony and concrete type of surfaces and decorative elements. **Bostik P925 FOAM'N'FIX TURBO MULTI-USE** can also be used for insulating and gap filling purposes in joints around door and window frames and in walls. **Bostik P925 FOAM'N'FIX TURBO MULTI-USE** is created to optimize the installation time: 60 seconds for foam application and 60 seconds for bonding.

METHOD OF APPLICATION

APPLICATION

- **STEP 1:** Shake the can vigorously for 20 times before each application.
- **STEP 2:** Turn the tube over with the valve down, apply the foam within 1 minute. Wait for the film to form (~60-90 seconds depending on the product), from the humidity in the air & then glue. Keep for 1 minute in position to get a strong initial adhesion. Final bonding between 50-70 minutes.



TECHNICAL DATA

Application temperature		-10°C to +40°C
Base		Polyurethane
Curing time		50-70 minutes
Density		15-20 kg/m ³
Dimensional stability	EN 17333-2	-5% < DS < 0%
Fire behaviour	DIN 4102	B3
Tack free time	EN 17333-3	90-150 seconds
Temperature resistance		-40°C to +90°C
Thermal conductivity		30-35 mW/m.K
Tensile strength		90-95 kPa
Shear strength		45-50 kPa
Yield		30-40 litre

These values are typical properties and may vary +/-3%

USE ON DIFFERENT SUBSTRATES

ASSEMBLY AND FILLING THE GAPS:

For application with the adapter we recommend filling the joint/gap approximately 50% and 80% for application with the gun, spray water on the surface and on the foam raw. Wait 15 minutes before cutting, if it is necessary. No contraction after strengthening complete (60 minutes). If the joint is larger than 4 cm, foam should be applied in successive cords, with a waiting time between applications of 6-10 minutes, spray the water after every application.

GLUING PANELS (EPS/XPS/Plasterboard/Wooden Board):

Apply foam to the previously prepared substrate. Apply around the entire circumference. Apply approx. 5 cm from the edge, and in vertical strips 3 cm thick, spaced every 30 cm, on the entire surface of the glued element. Do not spray with water. Within a time not longer than 180 seconds from the beginning of application, but not less than 90 seconds, the element should be pressed to the substrate and secured against displacement between 60 seconds to 120 seconds depending on light to heavy elements. The total curing time is 50 – 70 minutes. Support is required.

- Do not use the water when you use adhesive.
- The use of adhesive does not eliminate mechanical fixing with dowels.

LIMITATIONS

- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene.
- Bituminous surfaces have to be sanded prior to application.
- Not suitable for permanent water load.
- Not suitable for use filling cavities with insufficient moisture.

SURFACE PREPARATIONS AND FINISHING

Substrates must be clean and free of dust, oil and grease. It is important to moisten substrates slightly before use as this improves adhesion and finished cell structure of the foam.

PAINTABILITY

Bostik P925 FOAM'N'FIX TURBO MULTI-USE can be painted or covered with sealant/plaster when fully cured.

CLEANING

Fresh foam can be removed immediately with **Bostik P100 FOAM'N'CLEAN POWER**. After curing surplus foam can be removed with a knife or spatula and the foam surface can be finished.

COLOUR(S)

- Yellow

PACKAGING

- 750 ml cans, 12 per box

SHELF LIFE

In unopened original packaging between + 5°C and + 25°C, shelf life is up to 12 months from production date, stored in a dry place.

CERTIFICATIONS

- EC1 Plus
- A+ French VOC Regulation

HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and via the websites.

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce

Bostik Benelux BV

Denariusstraat 11 • NL-4903 RC Oosterhout
Tel.: +31 (0)162 491 000
www.bostik.com

BOSTIK SMART SUPPORT

Smart help digital
denbraven.com/

Smart help
+31 (0)162 491 000

