

GRIP B501 BITUMEN

Bitumen primer

WATERPROOFING SOLUTIONS

UNIVERSAL

- High quality adhesion promoter
- Solvent-free
- For bitumen bands and membranes

DESCRIPTION

GRIP B501 BITUMEN is a special, solvent-free bitumen adhesive for bitumen screens, coatings and seals. It is particularly suitable for use with the products **BLOCK B515 TERRA 1K** and **BLOCK B525 TERRA 2K**.

GRIP B501 BITUMEN is a liquid bitumen coating with a very high penetration capacity in absorbent substrates.

AREAS OF APPLICATION

Suitable for all common materials such as concrete, porous concrete, mortar, tiles, lime-sandstone, light and hollow concrete blocks, lime and lime cement, etc.

APPLICATION

In the transition zones between horizontal and vertical surfaces, create valleys with **BLOCK C514 TERRA 1K FLEX**. Mix **GRIP B501 BITUMEN** well and apply on the whole surface with a stiff brush, roller or a suitable spray gun. **GRIP B501 BITUMEN** must have dried completely before applying **BLOCK B515 TERRA 1K** or other subsequent treatments. Drying time may vary depending on substrate characteristics, temperature and atmospheric agents.



250-300ml /m²



TECHNICAL DATA

Color	Brown
Composition	Bitumen emulsion
Drying Time	1st coat : 2 hours 2nd coat : 12 hours
Application Temperature	+5°C to +25°C.
Cleaning	Tools can be cleaned using a solvent-based cleaner (white spirit).
Consumption	250-300ml/m ² per layer according to absorbency of the substrate
Shelf life	24 months

PREPARATION OF THE SUBSTRATE

The substrate must be smooth, durable and in good condition, i.e., free of dust, tar, pitch, form oil, contamination, old coatings or layers that may affect adhesion.

To check, run your hand over the surface. There should be no loose parts and the hand should not be too dirty.

Perform a scratch test and check that the substrate is in good condition, free of defects and voids.

Repair the areas of the wall and joints where parts have come loose, as well as cracks, dents and defects, with **RENO X588 FILL 2K ALLROUND**, **BLOCK C514 TERRA 1K FLEX**.

Allow to set before further processing.

The substrate must be free of edges and angular irregularities.

Remove sharp edges and corners. The substrate must be dry.



250-300ml /m²



PACKAGING

CODE	UC	PCB	GENCOD
30622818	4008373137862	5l	96 PC
30622819	4008373137886	10l	60 PC

STORAGE / SHELF LIFE

At least 24 months in original packaging. Protect from frost and direct sunlight. Do not store below 5° C before use.

SAFETY

For more details, consult the safety data sheet on :

<https://bostiksdsthevercs.com/default.aspx>

The information given and recommendations made herein are based on Bostik's research only and are not guaranteed to be accurate. The performance of the products, its shelf life, and application characteristics will depend on many variables, including the kind of materials to which the product will be applied, the environment in which the product is stored or applied, and the equipment used for application. Any change in any of these variables can affect the product's performance. It is the buyer's obligation, prior to using the product, to test the suitability of the product for an intended use. Bostik does not warrant the products suitability for any application. The product is sold pursuant to Bostik's Terms and Conditions of Sale that accompanies the product at the time of sale.

Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the past.

This data sheet supersedes all previous issues

Issued: 02.23

Bostik GmbH

Add your address
Add your telephone number and FAX
Add your email address

SMART CONTACT

+XX (X) XXX X XXX XXX