

# BLOCK B747 TOP TAPE - LEAD

## Self adhesive waterproofing band-lead

### WATERPROOFING SOLUTIONS

### ROOFING & FACADE

- High adhesion
- Very good deformability
- Resistant to rain and UV rays



#### DESCRIPTION

**BLOCK B738 TOP TAPE- LEAD** is a self-adhesive sealing tape coated with lead, aluminum or copper available in several sizes.

The product is designed using modified rubber bitumen formed into a robust bitumen sealing tape with a thickness of approx. 1.5 mm coated with lead. The tape is foldable and is therefore particularly suitable for difficult substrates.

In addition, the sheet has a UV-resistant coating.

#### AREAS OF APPLICATION

**BLOCK B738 TOP TAPE- LEAD** is suitable for safe sealing and gluing joints, gutters, downspouts, roof coverings, roof cuts, etc. It is exceptionally suitable for steel struts as well as conservatory and greenhouse roofs.

#### PRODUCT CHARACTERISTICS

Color	Black with silver, copper or lead surface
Composition	Bitumen sealing tape modified with rubber
Drying Time	-
Application Temperature	+5°C and +45°C. Never apply this product if it freezes.
Cleaning	Clean tools with white spirit.
Consumption	1mc/mc depending on the material for corners and edges and depending on the overlap
Shelf life	60 months

APPLICATION

When unrolling the tape, remove the protective film and place the tape simultaneously to prevent wrinkles from forming.

For small defects, cut out the desired length of tape, completely remove the protective film and press into place.

Then, press down with a cloth or roller and remove the air bubbles by pushing them out to the edges. In connecting areas, allow to overlap by approx. 2.5 cm.

PREPARATION OF THE SUBSTRATE

The substrate must be smooth, strong, dry and in good condition, i.e. free of dust, tar, pitch, formwork oil, contamination, old coatings or layers that can affect adhesion. If necessary, metal substrates should be degreased.

For better adhesion, apply **GRIP B501 BITUMEN** beforehand

**ATTENTION:**  
**BLOCK B738 TOP TAPE- LEAD sticks immediately. Adjustments may no longer be possible.**

STORAGE/ SHELF LIFE

**BLOCK B738 TOP TAPE- LEAD** should be kept dry and protected from frost. Keep unused product in the original closed packaging.

The product can be stored for at least 60 months in its original packaging closed and stored properly.

DELIVERY FORM

CODE	UC	SIZE	GEN COD
30623225	4008373137961	10m x 5cm	432 PC
30623192	4008373137664	10m x 7.5cm	384 PC
30623455	4008373137640	10m x 10cm	288 PC
30623223	4008373137985	10m x 15cm	192 PC
30623228	4008373138005	10m x 30cm	72 PC



SAFETY

For more details, consult the safety data sheet on :

<https://bostiksd.thevercs.com/default.aspx>

*The information given and recommendations made herein are based on Bostik's research only and are not guaranteed to be accurate. The performance of the products, its shelf life, and application characteristics will depend on many variables, including the kind of materials to which the product will be applied, the environment in which the product is stored or applied, and the equipment used for application. Any change in any of these variables can affect the product's performance. It is the buyer's obligation, prior to using the product, to test the suitability of the product for an intended use. Bostik does not warrant the products suitability for any application. The product is sold pursuant to Bostik's Terms and Conditions of Sale that accompanies the product at the time of sale.*

*Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the past.*

This data sheet supersedes all previous issues

Issued: 02.23

Bostik GmbH

Add your address

Add your telephone number and Fax

Add your email

SMART CONTACT

+XX (X) XXX X XXX XXX

