

STIX A930 MULTI FASER

FIBRE-BASED MULTI ADHESIVE

KEY BENEFITS

- Good initial adhesion
- Short waiting time
- Hard adhesive rib



APPLICATIONS

DESTINATION

Multi-functional fibre-containing dispersion adhesive.

Associated floor coverings :

- PVC coverings in sheets and tiles
- LVT design coverings
- CV coverings
- Lonuleum
- Rubber coverings with smooth upper side
- Carpets with different backings as well as coconut and sisal coverings

For carpet coverings with high residual stress, such as stubborn needlefelt coverings, we recommend POWER TEX.

PRODUCT CHARACTERISTICS

| | |
|--|--|
| Composition/ colour | Acrylic water based / Beige white |
| Waiting time* | 5min |
| Open time* | 20min |
| Walk on time* | 24h |
| Curing time* / Floor installation | After 24h |
| Coverage | A2 approx : 300 g/m ² B1 approx. : 360 g/m ² B2 approx. : 600 g/m ² |
| Application temperature | +18°C to 23°C |

*these times are determined at + 23° C and 50 % relative humidity on normally absorbent substrates

SUBFLOOR PREPARATION

CLEANING PREPARATION

The substrate must be level, permanently dry, clean, free from cracks, tensile and compressive strength in accordance with the requirements of DIN 18365 and, if necessary, professionally prepared for installation. Use suitable primers and smoothing compounds for this purpose. As a general rule, smooth over mastic asphalt screeds and other non-absorbent substrates to a minimum layer thickness of 2 mm.

METHOD OF USE

STIX 930 MULTI FASER is evenly applied to the substrate with a serrated trowel. Depending on the floor covering, a short flash-off time may be necessary. Place the floor covering in the semi-wet adhesive bed and rub in thoroughly. After 30-40 minutes, rub the floor covering again. Thermal sealing of the joints should be carried out after 24 hours at the earliest.

Observe the instructions of the flooring manufacturer, especially with regard to the air-conditioning of the flooring.

NOTE : LVT design floor coverings must be laid in the semi-wet (finger test) adhesive bed to avoid residual pressure. The adhesive rib is completely and constantly crushed, so that a closed and even adhesive film is created.

Special notes:

For rubber coverings from 3 mm thickness, the TKB spatula B1 must be used.

When laying thinner coverings and if the laying time is exceeded, the trowel notch can be marked on the top side. We expressly exclude claims arising from this.

In case of increased thermal load we recommend the use of STIX H995 ELASTIC XTREM.

Observe the instructions of the flooring manufacturer.

COVERAGE

A2 approx : 300 g/m²

B1 approx. : 360 g/m²

B2 approx. : 600 g/m²

STORAGE STABILITY

Keep container tightly closed. Store in a cool and dry place. Storable for 12 months.

| Code | UC | PCB | GENCOD |
|----------|-------|-----|---------------|
| 30615779 | 13 kg | 1 | 4008373130627 |

SAFETY

For more details, consult the safety data sheet on <https://bostiksd.thevercs.com/default.aspx>

The information given and recommendations made herein are based on Bostik's research only and are not guaranteed to be accurate. The performance of the product, its shelf life, and application characteristics will depend on many variables, including the kind of materials to which the product will be applied, the environment in which the product is stored or applied, and the equipment used for application. Any change in any of these variables can affect the product's performance. It is the buyer's obligation, prior to using the product, to test the suitability of the product for an intended use under the conditions that will exist at the time of the intended use. Bostik does not warrant the product's suitability for any particular application. The product is sold pursuant to Bostik's Terms and Conditions of Sale that accompanies the product at the time of sale. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the pat

BOSTIK TECHNICAL ASSISTANCE

Smart Help +XX XX XXX XXX

