

**BOSTIKLOW VISCOUS EPOXY GROUT** 

Version 1

Revision Date 21-Jun-2016
Supersedes Date: No information available

# Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product Identifier

Product Name BOSTIKLOW VISCOUS EPOXY GROUT

Pure substance/mixture mixture

#### 1.2. Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Recommended use Adhesives, sealants.
Uses Advised Against No information available.

### 1.3. Details of the Supplier of the Safety Data Sheet

**Company Name** 

Bostik (Shanghai) Management Co., Ltd

Building 1, No.968 Guanghua Road, Minhang District

Shanghai, China Tel: 021-60763101 Fax: 021-60763133 **Manufacturer** 

Bostik India Private Ltd 124/1 & 124/2A

Kachanayakanahalli

Behind Bommasandra Indl.Area Off Hosur Road, Hennagara Post,

Anekal Taluk

Bangalore - 562106, Karnataka,

INDĬA

Tel: 0091-80-27833520 Fax: 00 91-80-27831324

Email: Bostikinfo.India@bostik.com

Please refer to Section 16 for local affiliate addresses.

1.4. Emergency Telephone Number

Emergency Telephone 0532-8388 9090 (China only)

E-mail address SDS.AP@Bostik.com

## Section 2: HAZARD IDENTIFICATION

## 2.1. Classification of the Substance or Mixture

Acute toxicity - Dermal	Category 4 (6.1D)
Skin Corrosion/Irritation	Category 1 Sub-category B (8.2B)
Serious Eye Damage/Eye Irritation	Category 1 (8.3A)
Skin sensitization	Category 1 (6.5B)
Germ Cell Mutagenicity	Category 2 (6.6B)
Carcinogenicity	Category 2 (6.7B)
Acute aquatic toxicity	Category 2 (9.1D)
Chronic aquatic toxicity	Category 2 (9.1B)

Classification in parenthesis is applicable for New Zealand Hazard Classification

ERMA Group No information available

#### 2.2. Label Elements



Revision Date 21-Jun-2016

#### **BOSTIKLOW VISCOUS EPOXY GROUT**

Version 1 Supersedes Date: No information available

#### **Hazard statements**

H312 - Harmful in contact with skin

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H341 - Suspected of causing genetic defects

H351 - Suspected of causing cancer

H411 - Toxic to aquatic life with long lasting effects

#### **Precautionary Statements - Prevention**

P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P281 - Use personal protective equipment as required

P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P264 - Wash face, hands and any exposed skin thoroughly after handling

P272 - Contaminated work clothing should not be allowed out of the workplace

P280 - Wear protective gloves

P273 - Avoid release to the environment

#### **Precautionary Statements - Response**

P321 - Specific treatment (see supplemental first aid instructions on this label)

#### Inhalation

P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P310 - Immediately call a POISON CENTER or doctor/physician

#### Skin

P312 - Call a POISON CENTER or doctor if you feel unwell

P363 - Wash contaminated clothing before reuse

P303 + P361 + P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention

#### Eyes

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

#### Ingestion

P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting

#### Spill

P391 - Collect spillage

### **Precautionary Statements - Storage**

P405 - Store locked up

## Precautionary Statements - Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

#### 2.3. Other Hazards

May be harmful if swallowed

## Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substances

This product is a mixture. Health hazard information is based on its components.

#### 3.2 Mixtures

Chemical Name	CAS No	Weight-%
Bisphenol-A-Epichlorhydrin Epoxy resin	25068-38-6	60 - 70
Isophorone diamine	2855-13-2	10 - 20
n-Butyl glycidyl ether	2426-08-6	5 - 10
2,4,6-Tri(dimethylaminomethyl)phenol	90-72-2	1 - 5

<sup>\*\*\*</sup> Any remaining ingredients are not hazardous

## **Section 4: FIRST AID MEASURES**

## 4.1. Description of First Aid Measures

#### **BOSTIKLOW VISCOUS EPOXY GROUT**

Version 1 Supersedes Date: No information available

**General Advice** Immediate medical attention is required.

Remove to fresh air. Call a physician or poison control center immediately. If not Inhalation

breathing, give artificial respiration. If breathing is difficult, give oxygen.

Immediate medical attention is required. Wash off immediately with soap and plenty of **Skin Contact** 

water while removing all contaminated clothes and shoes. Wash off immediately with

Revision Date 21-Jun-2016

soap and plenty of water.

Immediate medical attention is required. Rinse immediately with plenty of water, also Eye contact

under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub

affected area.

Do NOT induce vomiting. Drink plenty of water. Never give anything by mouth to an Ingestion

> unconscious person. Immediate medical attention is required. Remove from exposure, lie down. Clean mouth with water and drink afterwards plenty of water. Call a physician

or poison control center immediately.

Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Self-protection of the First Aider

4.2. Most Important Symptoms and Effects, Both Acute and Delayed

**Symptoms** None known.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Note to physicians

Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. Treat

symptomatically.

4.4. Reference to Other Sections

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION. Section 11: **Reference to Other Sections** 

TOXICOLOGY INFORMATION.

## Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

**Unsuitable Extinguishing Media** No information available.

5.2. Special Hazards Arising from the Substance or Mixture

Chemical

Specific Hazards Arising from the The product causes burns of eyes, skin and mucous membranes. Thermal

decomposition can lead to release of irritating and toxic gases and vapors. In the event

of fire and/or explosion do not breathe fumes.

5.3. Advice for Firefighters

Special Protective Equipment for Wear self-contained breathing apparatus and protective suit.

Fire-fighters

### Section 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**Personal Precautions** Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

**BOSTIKLOW VISCOUS EPOXY GROUT** 

Version 1 Supersedes Date: No information available

6.2. Environmental Precautions

**Environmental Precautions**Do not allow into any sewer, on the ground or into any body of water. Should not be

released into the environment. Do not flush into surface water or sanitary sewer system. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Revision Date 21-Jun-2016

See Section 12 for additional Ecological Information.

6.3. Methods and Material for Containment and Cleaning up

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

Methods for Cleaning up

Take up mechanically, placing in appropriate containers for disposal. Soak up with inert

absorbent material. Clean contaminated surface thoroughly. Dike far ahead of liquid spill for later disposal. Prevent product from entering drains. Dam up. After cleaning, flush

away traces with water.

6.4. Reference to other sections

Reference to Other Sections Section 7: HANDLING AND STORAGE

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Section 13: DISPOSAL CONSIDERATIONS

## Section 7: HANDLING AND STORAGE

#### 7.1. Precautions for Safe Handling

Advice on Safe Handling Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Ensure adequate ventilation, especially in confined areas. In case of insufficient ventilation, wear suitable respiratory equipment. Use only with adequate ventilation and

in closed systems.

7.2. Conditions for Safe Storage, including any Incompatibilities

General Hygiene Considerations When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Keep

away from food, drink and animal feeding stuffs. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Avoid contact with skin, eyes or clothing. Take off all contaminated clothing and wash it before reuse. Wear suitable gloves and eye/face protection.

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of

children. Keep containers tightly closed in a cool, well-ventilated place. Keep containers

tightly closed in a dry, cool and well-ventilated place. Keep in properly labeled

containers.

Incompatible Materials Incompatible with strong acids and bases Incompatible with oxidizing agents

7.3. Specific End Use(s)

Other Information No information available.

7.4. References to Other Sections

Reference to Other Sections Section 13: DISPOSAL CONSIDERATIONS. Section 10: STABILITY AND REACTIVITY.

### Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control Parameters

#### **Exposure Limits**

Chemical Name	ACGIH TLV	NIOSH IDLH	OSHA PEL	European Union
n-Butyl glycidyl ether	TWA: 3 ppm	IDLH: 250 ppm	TWA: 50 ppm	=
2426-08-6	S*	Ceiling: 5.6 ppm 15 min	TWA: 270 mg/m <sup>3</sup>	
		Ceiling: 30 mg/m <sup>3</sup> 15 min	_	

### **BOSTIKLOW VISCOUS EPOXY GROUT**

Version 1 Supersedes Date: No information available

Chemical Name	Australia	China	Japan	Korea	New Zealand
n-Butyl glycidyl ether 2426-08-6	25 ppm 133 mg/m³	TWA: 60 mg/m <sup>3</sup> STEL: 120 mg/m <sup>3</sup>	-	Skin TWA: 10 ppm TWA: 53 mg/m³	TWA: 25 ppm TWA: 133 mg/m <sup>3</sup>

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration No information available

(PNEC)

**Other Information** No information available

8.2. Exposure Controls

Ensure adequate ventilation, especially in confined areas. **Engineering Controls** 

**Personal Protective Equipment (PPE)** 

**Eye/Face Protection** Wear safety glasses with side shields (or goggles).

**Skin and Body Protection** Wear suitable protective clothing. No special technical protective measures are

necessary under normal conditions.

Hand Protection Wear suitable chemical resistant gloves. The selection of suitable gloves does not only

depend on the material, but also on further marks of quality and various manufacturers. No protective equipment is needed under normal use conditions. Respiratory protection

Revision Date 21-Jun-2016

**Respiratory Protection** required in insufficiently ventilated working areas and during spraying. An air-fed mask,

or for short periods of work, a combination of professional filter is recommended. Do not eat, drink or smoke when using this product. Wash hands thoroughly after **General Hygiene** Considerations handling. Avoid contact with skin, eyes or clothing. Take off contaminated clothing and

wash before reuse.

Environmental Exposure Controls Local authorities should be advised if significant spillages cannot be contained. Do not

allow into any sewer, on the ground or into any body of water. Prevent product from

entering drains.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

## 9.1. Information on Basic Physical and Chemical Properties

Solid **Appearance** 

No information available Color Odor No information available **Odor Threshold** No information available

Property Values Remarks • Method

No information available

No information available **Melting Point/Freezing Point** No information available **Boiling Point** No information available No information available **Flash Point Evaporation Rate** No information available Flammability (solid, gas) No information available

Flammability Limit in Air

**Upper Flammability Limit** No information available No information available **Lower Flammability Limit Vapor Pressure** No information available Vapor Density No information available

**Specific Gravity** No information available Water Solubility Solubility in Other Solvents No information available **Partition Coefficient** No information available **Autoignition Temperature** No information available **Decomposition Temperature** No information available **Kinematic Viscosity** 

No information available **Dynamic Viscosity** No information available **Explosive Properties** No information available

#### **BOSTIKLOW VISCOUS EPOXY GROUT**

Version 1 Supersedes Date: No information available

Revision Date 21-Jun-2016

Oxidizing Properties No information available

9.2. Other Information

Softening Point
Molecular Weight
Solvent Content (%)
Solid Content (%)
Density
No information available

VOC

## Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

**Reactivity** None under normal use conditions.

10.2. Chemical Stability

10.3. Possibility of Hazardous Reactions

Possibility of Hazardous Reactions None under normal processing.

**Hazardous Polymerization** None under normal processing.

10.4. Conditions to Avoid

**Conditions to Avoid** Exposure to air or moisture over prolonged periods.

10.5. Incompatible Materials

Incompatible Materials Incompatible with strong acids and bases. Incompatible with oxidizing agents.

10.6. Hazardous Decomposition Products

Hazardous Decomposition

**Products** 

Thermal decomposition can lead to release of irritating and toxic gases and vapors.

### Section 11: TOXICOLOGY INFORMATION

## 11.1. Information on Toxicological Effects

**Acute Toxicity** 

Product Information Product does not present an acute toxicity hazard based on known or supplied

information.

InhalationNo Data Available.Eye contactNo Data Available.Skin ContactNo Data Available.IngestionNo Data Available.

## Numerical measures of toxicity

## **Unknown acute toxicity**

7.875 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

75.375 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

87.25 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

87.25 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

12.625 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Bisphenol-A-Epichlorhydrin Epoxy	= 11400 mg/kg (Rat)	-	-
resin			
25068-38-6			
Isophorone diamine	= 1040 mg/kg (Rat)	-	-

Revision Date 21-Jun-2016

#### **BOSTIKLOW VISCOUS EPOXY GROUT**

Version 1 Supersedes Date: No information available

2855-13-2			
n-Butyl glycidyl ether	= 2050 mg/kg (Rat) = 1660	$> 2150 \text{ mg/kg} (\text{Rat}) = 2520 \mu \text{L/kg}$	= 2590 ppm (Rat) 4 h
2426-08-6	mg/kg (Rat)	( Rabbit ) = 788 mg/kg ( Rabbit )	
2,4,6-Tri(dimethylaminomethyl)phe	= 2169 mg/kg (Rat)	> 1000 mg/kg (Rat)	-
nol			
90-72-2			

### Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

Skin Corrosion/Irritation
Serious Eye Damage/Eye Irritation
Sensitization
Germ Cell Mutagenicity
Reproductive Toxicity
STOT - Single Exposure
STOT - Repeated Exposure
No information available.
No information available.
No information available.
No information available.

**Target Organ Effects** Blood, Central nervous system, Eyes, Respiratory system, Skin.

Aspiration Hazard No information available. Carcinogenicity No information available.

## Section 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

#### **Ecotoxicity**

#### **Product Information**

Toxic to aquatic life with long lasting effects.

## **Component Information**

Data obtained on the component(s) include

Chemical Name	Algae/Aquatic Plants	Fish	Crustacea
Bisphenol-A-Epichlorhydrin Epoxy	-	1.2 mg/l 96Hr (Oncorhynchus	2.7 mg/l 48hr Daphia Magna
resin		mykiss)	
25068-38-6			
Isophorone diamine	EC50 72 h = 37 mg/L	LC50 96 h = 110 mg/L (Leuciscus	EC50 24 h = 42 mg/L (Daphnia
2855-13-2	(Desmodesmus subspicatus)	idus semi-static)	magna ) EC50 48 h 14.6 - 21.5
			mg/L (Daphnia magna semi-static)
2,4,6-Tri(dimethylaminomethyl)phe	-	CL50 (96h) =175 mg/L Fish	-
nol		(Cyprinus carpio)	
90-72-2			

### 12.2. Persistence and Degradability

No information available.

## 12.3. Bioaccumulative Potential

No information available.

#### 12.4. Mobility in Soil

No information available.

#### 12.5. Results of PBT and vPvB Assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

#### 12.6. Other Adverse Effects

No information available.

i to il il officiation a valiable.			
Chemical Name	EU - Endocrine Disrupters	EU - Endocrine Disruptors -	Endocrine disrupting potential
	Candidate List	Evaluated Substances	

#### **BOSTIKLOW VISCOUS EPOXY GROUT**

Revision Date 21-Jun-2016 Version 1 Supersedes Date: No information available

Bisphenol-A-Epichlorhydrin Epoxy Group III Chemical resin

### Section 13: DISPOSAL CONSIDERATIONS

#### 13.1. Waste Treatment Methods

Waste from Residues/Unused

Disposal should be in accordance with applicable regional, national and local laws and

regulations.

**Contaminated Packaging** 

Do not reuse container.

## Section 14: TRANSPORTATION INFORMATION

**IMDG** 

**Products** 

UN/ID No UN3082

**Proper Shipping Name** Environmentally hazardous substance, liquid, n.o.s. (Epoxide Derivatives, Isophorone

diamine), Marine Pollutant

**Hazard Class** Ш **Packing Group** F-A, S-F EmS-No **Special Provisions** 274, 335, 969

Limited Quantity (LQ)

UN3082, Environmentally hazardous substance, liquid, n.o.s. (Epoxide Derivatives, Description

Isophorone diamine), 9, III, Marine Pollutant

**IATA** 

UN/ID No UN3082

Environmentally hazardous substance, liquid, n.o.s. (Epoxide Derivatives, Isophorone **Proper Shipping Name** 

diamine)

9 **Hazard Class Packing Group** Ш **ERG Code** 9L **Limited Quantity (LQ)** 30 kg G

**Special Provisions** A97, A158, A197

Description UN3082, Environmentally hazardous substance, liquid, n.o.s. (Epoxide Derivatives,

Isophorone diamine), 9, III

**ADR** 

UN/ID No UN3082

**Proper Shipping Name** Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-A-Epichlorhydrin Epoxy

resin, Isophorone diamine)

**Hazard Class** 9 9 **Hazard Labels Packing Group** Ш

Description UN3082, Environmentally hazardous substance, liquid, n.o.s.

(Bisphenol-A-Epichlorhydrin Epoxy resin, Isophorone diamine), 9, III

**Environmental Hazard** ves Limited Quantity (LQ) 5 L

**Special Provisions** 274, 335, 601, 375

Classification Code M6 **Tunnel Restriction Code** Ε

## Section 15: REGULATORY INFORMATION

## **National Regulations**

#### China

This product contains the following substance(s)

Chemical Name	Weight-%	China - Catalog of Hazardous Chemicals - Hazardous Chemicals
Isophorone diamine	10 - 20	X

## **BOSTIKLOW VISCOUS EPOXY GROUT**

Version 1

Revision Date 21-Jun-2016 Supersedes Date: No information available

2855-13-2
-----------

#### **Japan**

Chemical Name	Weight-%	Japan - Pollutant Release Transfer Register (PRTR) - Class 1 Substances
n-Butyl glycidyl ether 2426-08-6	5 - 10	Х

#### Korea

#### K-REACH/chemical control act(CCA)

This product contains the following substance(s)

Chemical Name	Weight-%	Korea - MOE - K-REACH/CCA - Toxic Substances	Korea - MOE - K-REACH/CCA - Prohibited Substances	Korea - MOE - K-REACH/CCA - Restricted Substances	Korea - MOE - Chemicals Control Act (CCA) - Accident Precaution Chemicals	Korea - MOE - K-REACH - Existing Substances Subject to Registration
Bisphenol-A-Epichlorhydri n Epoxy resin 25068-38-6	60 - 70					0
n-Butyl glycidyl ether 2426-08-6	5 - 10					0

## **International Regulations**

## **Europe**

## Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU

This product does not contain Lead (7439-92-1), Cadmium (7440-43-9), Mercury (7439-97-6), Hexavalent chromium (7440-47-3), Polybrominated biphenyls (PBB), and Polybrominated diphenyl ethers (PBDE) above the regulated limit mentioned in this regulation.

## EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## Section 16: OTHER INFORMATION

#### **Local Contacts**

Bostik Korea, Ltd. Bostik-Nitta Co, Ltd Bostik India Private Ltd 6F, 21 2-22,Futamata 124/1 & 124/2A Yao, Osaka Yao, Osaka Kachanayakanahalli

Seoul, 07236 Japan Behind Bommasandra Indl.Area
Korea Tel: 81-72-948-8286 Off Hosur Road, Hennagara Post,

Tel: +82-02-3703-6870 Fax: 81-72-948-8273 Anekal Taluk Fax: +82-02-3703-6850 Fax: 81-72-948-8273 Anekal Taluk Bangalore - 562106, Karnataka,

INDIA Tel: 0091-80-27833520

Fax: 00 91-80-2783324 Email: Bostikinfo.India@bostik.com

#### **BOSTIKLOW VISCOUS EPOXY GROUT**

Version 1 Supersedes Date: No information available

Bostik Findley (Malaysia) Sdn. Bhd

Lot 112 & 113,

Kawasan Perindustrian senawang, seremban, negeri sembilian, Malaysia

Tel: 606-6789788 Fax: 606-6789766

Bostik Phillippines, Inc. 35/F Raffles Corporate Center,

F. Ortigas Jr. Road Ortigas Business Center, Pasig city, Phillippines Tel: 632-900-5656 Fax: 632-900-5622 Bostik Australia Pty Ltd 51-71 High street,

Thomastown Victoria, Australia

Tel: 613 9279-9333 Fax: 613 9279-9342

24-hr Emergency: 1800 033 111 Bostik New Zealand Limited 19 Eastern Hutt Road Wingate, Lower Hutt, New Zealand

Tel: 04-567 5119 Fax: 04-567 5412

24-hr Emergency: 0800 243 622

Bostik Findley (Malaysia) S/B

(Singapore Branch)
2 Jurong East
Street 21 #02-184
IMM Building
Singapore 609601
Tel: 65-6863-4088
Fax: 65-6863-4077
Bostik Indonesia

Setiabudi Atrium Building, Level 2, Suite 203 A Jl. HR Rasuna Said Jakarta Indonesia 12920 Tel: 62 21 521 0404

Fax: 62 21 521 0554

Jiangsu Bositk Adhesive Co.,Ltd No.15-9, Xinggang Road, Changshu Enconomic Development Zone Jiangsu Province 215536

Tel: 0086-512-52266000 Fax: 0086-512-52266020 Bostik (Thailand) Co., Ltd 1/32 Bang-na Thani Tower 16th A Foolr. Soi Bangna-Trad 34, Bangna-Trad rd. Bang-na, Bangkok Tel: 02-361 6460-7 Fax: 02-361 6469

Bostik Vietnam Company Limited

Revision Date 21-Jun-2016

10 Doc Lap Avenue, VSIP 1. Thuan An District, BinhDuong Province. Viet Nam.

Tel: 84 650 3765105 Fax: 84 650 3765109

Bostik Findley (China) Adhesive Ltd No.75, Xin Zhuang 2 Road, Yong He

District, GETDD

Guangzhou, China 511356 Tel: 020-8297 5266 Fax: 020-8297 5277

### Key or Legend to Abbreviations and Acronyms Used in the Safety Data Sheet

No information available

#### **Key Literature References and Sources for Data**

No information available

Prepared By Product Safety & Regulatory Affairs

Revision Date 21-Jun-2016

Revision Note Not applicable.

Training Advice No information available

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**