

PROCOAT PU OFF WHITE
Version 1.01

Revision Date 15-Mar-2017
Supersedes Date: 12-Aug-2016

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Product Name PROCOAT PU OFF WHITE
Pure substance/mixture mixture

1.2. Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Recommended use Adhesives.
Uses Advised Against No information available.

1.3. Details of the Supplier of the Safety Data Sheet

Company Name

Bostik (Shanghai) Management Co., Ltd
 Building 1, No.968 Guanghai Road, Minhang District
 Shanghai, China
 Tel: 021-60763101
 Fax: 021-60763133

Manufacturer

Bostik India Private Ltd
 124/1 & 124/2A
 Kachanayakanahalli
 Behind Bommasandra Indl.Area
 Off Hosur Road, Hennagara Post,
 Anekal Taluk
 Bangalore - 562106, Karnataka,
 INDIA
 Tel: 0091-80-27833520
 Fax: 00 91-80-27831324
 Email: Bostikinfo.India@bostik.com

Please refer to Section 16 for local affiliate addresses.

1.4. Emergency Telephone Number

Emergency Telephone 0532-8388 9090 (China only)

E-mail address SDS.AP@Bostik.com

Section 2: HAZARD IDENTIFICATION

2.1. Classification of the Substance or Mixture

Skin Corrosion/Irritation	Category 2 (6.3A)
Serious Eye Damage/Eye Irritation	Category 2 (6.4)
Carcinogenicity	Category 2 (6.7B)
Reproductive toxicity	Category 1B (6.8A)
Specific target organ toxicity (repeated exposure)	Category 2 (6.9B)
Acute aquatic toxicity	Category 1 (9.1A)
Chronic aquatic toxicity	Category 1 (9.1A)

Classification in parenthesis is applicable for New Zealand Hazard Classification

ERMA Group No information available

2.2. Label Elements



Signal Word

DANGER

Safety Data Sheet

PROCOAT PU OFF WHITE
Version 1.01

Revision Date 15-Mar-2017
Supersedes Date: 12-Aug-2016

Hazard statements

H315 - Causes skin irritation
H319 - Causes serious eye irritation
H351 - Suspected of causing cancer
H360 - May damage fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure
H410 - Very toxic to aquatic life with long lasting effects

Precautionary Statements - Prevention

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P281 - Use personal protective equipment as required
P264 - Wash face, hands and any exposed skin thoroughly after handling
P260 - Do not breathe dust/fume/gas/mist/vapors/spray
P273 - Avoid release to the environment

Precautionary Statements - Response

P321 - Specific treatment (see supplemental first aid instructions on this label)

Skin

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
P332 + P313 - If skin irritation occurs: Get medical advice/attention
P362 - Take off contaminated clothing and wash before reuse

EYES

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P337 + P313 - If eye irritation persists: Get medical advice/attention

Spill

P391 - Collect spillage

Precautionary Statements - Storage

P405 - Store locked up

Precautionary Statements - Disposal

P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other Hazards

- May be fatal if swallowed and enters airways

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Mixture

3.2 Mixtures

Chemical Name	CAS No.	Weight-%
n-Butyl acetate	123-86-4	20 - 30
Xylenes (o-, m-, p- isomers)	1330-20-7	10 - 20
2-Ethoxyethanol	110-80-5	1 - 5
Ethylbenzene	100-41-4	1 - 5

*** Any remaining ingredients are not hazardous

Section 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

General Advice

Immediate medical attention is required.

Inhalation

Immediate medical attention is required. Remove to fresh air. If not breathing, give artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

Skin Contact

Immediate medical attention is required. Wash off immediately with soap and plenty of

Safety Data Sheet

PROCOAT PU OFF WHITE
Version 1.01

Revision Date 15-Mar-2017
Supersedes Date: 12-Aug-2016

water while removing all contaminated clothes and shoes.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. Call a physician immediately.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Drink plenty of water.

Self-protection of the First Aider Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

4.2. Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms None known.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

Note to physicians Treat symptomatically.

4.4. Reference to Other Sections

Reference to Other Sections Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION. Section 11: TOXICOLOGY INFORMATION.

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media No information available.

5.2. Special Hazards Arising from the Substance or Mixture

Specific Hazards Arising from the Chemical Keep product and empty container away from heat and sources of ignition.

5.3. Advice for Firefighters

Special Protective Equipment for Fire-fighters Wear self-contained breathing apparatus and protective suit.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions Use personal protective equipment as required. Keep people away from and upwind of spill/leak.

6.2. Environmental Precautions

Environmental Precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. See Section 12 for additional Ecological Information.

6.3. Methods and Material for Containment and Cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Cover powder spill with plastic sheet or tarp to minimize spreading. Dike far ahead of liquid spill for later disposal.

Methods for Cleaning up Cover liquid spill with sand, earth or other non-combustible absorbent material. Use personal protective equipment as required. Dam up. Take up mechanically, placing in appropriate containers for disposal. Clean contaminated surface thoroughly.

Safety Data Sheet

PROCOAT PU OFF WHITE
Version 1.01

Revision Date 15-Mar-2017
Supersedes Date: 12-Aug-2016

6.4. Reference to other sections

Reference to Other Sections Section 7: HANDLING AND STORAGE
Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION
Section 13: DISPOSAL CONSIDERATIONS

Section 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Advice on Safe Handling Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wash contaminated clothing before reuse. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product.

7.2. Conditions for Safe Storage, including any Incompatibilities

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended. Avoid contact with skin, eyes or clothing. Wash hands thoroughly after handling. Keep away from food, drink and animal feeding stuffs.

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible Materials No information available

7.3. Specific End Use(s)

Other Information No information available.

7.4. References to Other Sections

Reference to Other Sections Section 13: DISPOSAL CONSIDERATIONS. Section 10: STABILITY AND REACTIVITY.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

Exposure Limits

Chemical Name	China	Japan	Korea	New Zealand	Australia
n-Butyl acetate 123-86-4	TWA: 200 mg/m ³ STEL: 300 mg/m ³	TWA: 100 ppm TWA: 475 mg/m ³ ISHL/ACL: 150 ppm	STEL: 200 ppm STEL: 950 mg/m ³ TWA: 150 ppm TWA: 710 mg/m ³	TWA: 150 ppm TWA: 713 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³	150 ppm 713 mg/m ³ 200 ppm STEL 950 mg/m ³ STEL
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 50 mg/m ³ STEL: 100 mg/m ³	TWA: 50 ppm TWA: 217 mg/m ³ ISHL/ACL: 50 ppm	STEL: 150 ppm STEL: 655 mg/m ³ TWA: 100 ppm TWA: 435 mg/m ³	TWA: 50 ppm TWA: 217 mg/m ³	80 ppm 350 mg/m ³ 150 ppm STEL 655 mg/m ³ STEL
2-Ethoxyethanol 110-80-5	TWA: 18 mg/m ³ STEL: 36 mg/m ³ Skin	TWA: 5 ppm TWA: 18 mg/m ³ Skin ISHL/ACL: 5 ppm	Skin TWA: 5 ppm TWA: 19 mg/m ³	TWA: 5 ppm TWA: 18 mg/m ³ Skin	5 ppm 18 mg/m ³
Ethylbenzene 100-41-4	TWA: 100 mg/m ³ STEL: 150 mg/m ³	TWA: 50 ppm TWA: 217 mg/m ³ ISHL/ACL: 20 ppm	STEL: 125 ppm STEL: 545 mg/m ³ TWA: 100 ppm TWA: 435 mg/m ³	TWA: 100 ppm TWA: 434 mg/m ³ STEL: 125 ppm STEL: 543 mg/m ³	100 ppm 434 mg/m ³ 125 ppm STEL 543 mg/m ³ STEL

Chemical Name	European Union	ACGIH TLV	NIOSH IDLH	OSHA PEL
n-Butyl acetate 123-86-4	-	STEL: 150 ppm TWA: 50 ppm	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³	TWA: 150 ppm TWA: 710 mg/m ³
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 50 ppm TWA: 221 mg/m ³	STEL: 150 ppm TWA: 100 ppm	-	TWA: 100 ppm TWA: 435 mg/m ³

Safety Data Sheet

PROCOAT PU OFF WHITE
Version 1.01

Revision Date 15-Mar-2017
Supersedes Date: 12-Aug-2016

	STEL: 100 ppm STEL: 442 mg/m ³ S*			
2-Ethoxyethanol 110-80-5	TWA: 2ppm TWA: 8mg/m ³ S*	TWA: 5 ppm S*	IDLH: 500 ppm TWA: 0.5 ppm TWA: 1.8 mg/m ³	TWA: 200 ppm TWA: 740 mg/m ³ S*
Ethylbenzene 100-41-4	TWA: 100 ppm TWA: 442 mg/m ³ STEL: 200 ppm STEL: 884 mg/m ³ S*	TWA: 20 ppm	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³	TWA: 100 ppm TWA: 435 mg/m ³

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration (PNEC) No information available

Other Information No information available

8.2. Exposure Controls

Engineering Controls Ensure adequate ventilation, especially in confined areas.

PPE - Personal Protection Equipment

Eye/Face Protection	Wear safety glasses with side shields (or goggles).
Skin and Body Protection	Wear suitable protective clothing. No special technical protective measures are necessary under normal conditions.
Hand Protection	Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.
Respiratory Protection	No protective equipment is needed under normal use conditions. Respiratory protection required in insufficiently ventilated working areas and during spraying. An air-fed mask, or for short periods of work, a combination of professional filter is recommended.
General Hygiene Considerations	Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Avoid contact with skin, eyes or clothing. Take off contaminated clothing and wash before reuse.

Environmental Exposure Controls No information available.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Appearance	Very viscous
Color	White
Odor	Solvent
Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting Point/Freezing Point	No information available	
Boiling Point	No information available	
Flash Point	= 196 °C / 384.8 °F	
Evaporation Rate	No information available	
Flammability (solid, gas)	No information available	Not applicable for liquids
Flammability Limit in Air		
Upper Flammability Limit	No information available	
Lower Flammability Limit	No information available	
Vapor Pressure	No information available	
Vapor Density	No information available	
Relative Density	No information available	
Water Solubility	No information available	
Solubility in Other Solvents	No information available	
Partition Coefficient	No information available	

Safety Data Sheet

PROCOAT PU OFF WHITE
Version 1.01

Revision Date 15-Mar-2017
Supersedes Date: 12-Aug-2016

Autoignition Temperature	No information available
Decomposition Temperature	No information available
Kinematic Viscosity	No information available
Dynamic Viscosity	No information available
Explosive Properties	No information available
Oxidizing Properties	No information available

9.2. Other Information

Softening Point	No information available
Molecular Weight	No information available
Solvent Content (%)	No information available
Solid Content (%)	No information available
Density	1.23 g/cm ³
Bulk Density	No information available
VOC	

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity None under normal use conditions.

10.2. Chemical Stability

10.3. Possibility of Hazardous Reactions

Possibility of Hazardous Reactions None under normal processing.

Hazardous Polymerization None under normal processing.

10.4. Conditions to Avoid

Conditions to Avoid Heat, flames and sparks.

10.5. Incompatible Materials

Incompatible Materials No information available.

10.6. Hazardous Decomposition Products

Hazardous Decomposition Products None under normal use conditions.

Section 11: TOXICOLOGY INFORMATION

11.1. Information on Toxicological Effects

Acute Toxicity

Product Information	Product does not present an acute toxicity hazard based on known or supplied information.
Inhalation	No Data Available.
Eye contact	No Data Available.
Skin Contact	No Data Available.
Ingestion	No Data Available.

Numerical measures of toxicity

Unknown acute toxicity

- 19.4864 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
- 19.4864 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
- 63.3585 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

Safety Data Sheet

PROCOAT PU OFF WHITE
Version 1.01

Revision Date 15-Mar-2017
Supersedes Date: 12-Aug-2016

48.5631 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
43.2631 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
n-Butyl acetate 123-86-4	>10650 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat) 4 h
Xylenes (o-, m-, p- isomers) 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit) > 1700 mg/kg (Rabbit)	= >47635 mg/L (Rat) 4 h = >5000 ppm (Rat) 4 h
2-Ethoxyethanol 110-80-5	= 2800 mg/kg (Rat)	= 3300 mg/kg (Rabbit)	= 4267 ppm (Rat) 4 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 1432 mg/L (Rat) 4 h

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

Skin Corrosion/Irritation	No information available.
Serious Eye Damage/Eye Irritation	No information available.
Sensitization	No information available.
Germ Cell Mutagenicity	No information available.
Reproductive Toxicity	No information available.
STOT - Single Exposure	No information available.
STOT - Repeated Exposure	No information available.
Target Organ Effects	Blood, Central nervous system, Central Vascular System (CVS), Eyes, hematopoietic system, Kidney, Liver, Lungs, Reproductive System, Respiratory system, Skin.
Aspiration Hazard	No information available.
Carcinogenicity	No information available.

Chemical Name	IARC	China	Japan
Xylenes (o-, m-, p- isomers)	Group 3	-	-
Ethylbenzene	Group 2B	-	Group 2B

IARC (International Agency for Research on Cancer) Group 2B - Possibly Carcinogenic to Humans Group 3 - Not Classifiable as to Carcinogenicity in Humans

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity

Product Information

Very toxic to aquatic life with long lasting effects.

Component Information

Data obtained on the component(s) include

Chemical Name	Algae/Aquatic Plants	Fish	Crustacea
n-Butyl acetate 123-86-4	EC50 72 h = 674.7 mg/L (Desmodesmus subspicatus)	LC50 96 h 17 - 19 mg/L (Pimephales promelas flow-through)	EC50 48 h = 44 mg/L (Daphnia magna)
Xylenes (o-, m-, p- isomers) 1330-20-7	-	LC50 96 h 13.5 - 17.3 mg/L (Oncorhynchus mykiss)	EC50 48 h = 3.4 mg/L (water flea)
2-Ethoxyethanol 110-80-5	EC50 72 h > 1000 mg/L (Desmodesmus subspicatus)	LC50 96 h > 10000 mg/L (Lepomis macrochirus static) LC50 96 h > 0.1 mg/L (Pimephales promelas static)	EC50 48 h > 10000 mg/L (Daphnia magna)
Ethylbenzene 100-41-4	EC50 72 h 2.6 - 11.3 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h = 4.2 mg/L (Oncorhynchus mykiss semi-static)	EC50 48 h 1.8 - 2.4 mg/L (Daphnia magna)

12.2. Persistence and Degradability

No information available.

12.3. Bioaccumulative Potential

No information available.

Safety Data Sheet

PROCOAT PU OFF WHITE
Version 1.01

Revision Date 15-Mar-2017
Supersedes Date: 12-Aug-2016

12.4. Mobility in Soil

No information available.

12.5. Results of PBT and vPvB Assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other Adverse Effects

No information available.

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste Treatment Methods

Waste from Residues/Unused Products	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated Packaging	Disposal should be in accordance with applicable regional, national and local laws and regulations.

Section 14: TRANSPORTATION INFORMATION

IMDG

UN/ID No	UN3082
Proper Shipping Name	Environmentally hazardous substance, liquid, n.o.s. (Dibutyltin dilaurate)
Hazard Class	9
Packing Group	III
Marine Pollutant	Np
EmS-No	F-A, S-F
Special Provisions	274, 335, 969
Limited Quantity (LQ)	5 L
Description	UN3082, Environmentally hazardous substance, liquid, n.o.s. (Dibutyltin dilaurate), 9, III

IATA

UN/ID No	UN3082
Proper Shipping Name	Environmentally hazardous substance, liquid, n.o.s. (Dibutyltin dilaurate)
Hazard Class	9
Packing Group	III
ERG Code	9L
Limited Quantity (LQ)	30 kg G
Special Provisions	A97, A158, A197
Description	UN3082, Environmentally hazardous substance, liquid, n.o.s. (Dibutyltin dilaurate), 9, III

ADR

UN/ID No	UN3082
Proper Shipping Name	Environmentally hazardous substance, liquid, n.o.s. (Dibutyltin dilaurate)
Hazard Class	9
Hazard Labels	9
Packing Group	III
Description	UN3082, Environmentally hazardous substance, liquid, n.o.s. (Dibutyltin dilaurate), 9, III
Environmental Hazard	yes
Limited Quantity (LQ)	5 L
Special Provisions	274, 335, 601, 375
Classification Code	M6
Tunnel Restriction Code	E

Section 15: REGULATORY INFORMATION

Safety Data Sheet

PROCOAT PU OFF WHITE
Version 1.01

Revision Date 15-Mar-2017
Supersedes Date: 12-Aug-2016

National Regulations

China

This product contains the following substance(s)

Chemical Name	Weight-%	China - Catalog of Hazardous Chemicals - Hazardous Chemicals
n-Butyl acetate 123-86-4	20 - 30	X
Xylenes (o-, m-, p- isomers) 1330-20-7	10 - 20	X
2-Ethoxyethanol 110-80-5	1 - 5	X
Ethylbenzene 100-41-4	1 - 5	X

Japan

This product contains the following Class 1 and Class 2 Designated Chemical Substances per Japan PRTR Law.

Chemical Name	Weight-%	Japan - Pollutant Release Transfer Register (PRTR) - Class 1 Substances
Xylenes (o-, m-, p- isomers) 1330-20-7	10 - 20	X
2-Ethoxyethanol 110-80-5	1 - 5	X
Ethylbenzene 100-41-4	1 - 5	X

Korea

K-REACH/chemical control act(CCA)

This product contains the following substance(s)

Chemical Name	Weight-%	Korea - MOE - K-REACH/CCA - Toxic Substances	Korea - MOE - K-REACH/CCA - Prohibited Substances	Korea - MOE - K-REACH/CCA - Restricted Substances	Korea - MOE - Chemicals Control Act (CCA) - Accident Precaution Chemicals	Korea - MOE - K-REACH - Existing Substances Subject to Registration
Xylenes (o-, m-, p- isomers) 1330-20-7	10 - 20	O				O
2-Ethoxyethanol 110-80-5	1 - 5	O				O

International Regulations

Europe

Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU

This product does not contain Lead (7439-92-1), Cadmium (7440-43-9), Mercury (7439-97-6), Hexavalent chromium (7440-47-3), Polybrominated biphenyls (PBB), and Polybrominated diphenyl ethers (PBDE) above the regulated limit mentioned in this regulation.

EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59

This product contains one or more candidate substance(s) of very high concern (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Safety Data Sheet

PROCOAT PU OFF WHITE
Version 1.01

Revision Date 15-Mar-2017
Supersedes Date: 12-Aug-2016

Chemical Name	CAS No.
2-Ethoxyethanol	110-80-5

Section 16: OTHER INFORMATION

Local Contacts

Bostik Korea, Ltd.
6F, 21
Gukhoe-daero 62-gil Yeongdeungpo-gu
Seoul, 07236
Korea
Tel: +82-02-3703-6870
Fax: +82-02-3703-6850

Bostik-Nitta Co, Ltd
2-22,Futamata
Yao, Osaka
Japan
Tel: 81-72-948-8286
Fax: 81-72-948-8273

Bostik India Private Ltd
124/1 & 124/2A
Kachanayakanahalli
Behind Bommasandra Indl.Area
Off Hosur Road, Hennagara Post,
Anekal Taluk
Bangalore - 562106, Karnataka,
INDIA
Tel: 0091-80-27833520
Fax: 00 91-80-27831324
Email: Bostikinfo.India@bostik.com

Bostik Findley (Malaysia) Sdn. Bhd
Lot 112 & 113,
Kawasan Perindustrian senawang,
seremban, negeri sembilan, Malaysia
Tel: 606-6789788
Fax: 606-6789766

Bostik Findley (Malaysia) S/B
(Singapore Branch)
2 Jurong East
Street 21 #02-184
IMM Building
Singapore 609601
Tel: 65-6863-4088
Fax: 65-6863-4077

Bostik (Thailand) Co., Ltd
1/32 Bang-na Thani
Tower 16th A Foolr.
Soi Bangna-Trad 34,
Bangna-Trad rd.
Bang-na, Bangkok
Tel: 02-361 6460-7
Fax: 02-361 6469
Bostik Vietnam Company Limited
10 Doc Lap Avenue,
VSIP 1. Thuan An District,
BinhDuong Province. Viet Nam.
Tel: 84 650 3765105
Fax: 84 650 3765109

Bostik Phillippines, Inc.
35/F Raffles Corporate Center,
F. Ortigas Jr. Road
Ortigas Business Center,
Pasig city, Phillippines
Tel: 632-900-5656
Fax: 632-900-5622
Bostik Australia Pty Ltd
51-71 High street,
Thomastown Victoria
Australia
Tel: 613 9279-9333
Fax: 613 9279-9342
24-hr Emergency: 1800 033 111
Bostik New Zealand Limited
19 Eastern Hutt Road Wingate,
Lower Hutt, New Zealand
Tel: 04-567 5119
Fax: 04-567 5412

Bostik Indonesia
Setiabudi Atrium Building,
Level 2, Suite 203 A
Jl. HR Rasuna Said
Jakarta Indonesia 12920
Tel: 62 21 521 0404
Fax: 62 21 521 0554
Jiangsu Bositk Adhesive Co.,Ltd
No.15-9, Xinggang Road, Changshu
Enconomic Development Zone
Jiangsu Province 215536
Tel: 0086-512-52266000
Fax: 0086-512-52266020

Bostik Findley (China) Adhesive Ltd
No.75, Xin Zhuang 2 Road, Yong He
District, GETDD
Guangzhou, China 511356
Tel: 020-8297 5266
Fax: 020-8297 5277

Key or Legend to Abbreviations and Acronyms Used in the Safety Data Sheet
No information available

Key Literature References and Sources for Data
No information available

Prepared By	Product Safety & Regulatory Affairs
Revision Date	15-Mar-2017
Revision Note	Not applicable.
Training Advice	No information available
Disclaimer	

Safety Data Sheet

PROCOAT PU OFF WHITE
Version 1.01

Revision Date 15-Mar-2017
Supersedes Date: 12-Aug-2016

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet