

# **S766**

# KITCHEN & BATHROOM SILICONE PREMIUM GRADE NEUTRAL SILICONE SEALANT

## **TECHNICAL DATA SHEET**

## **BENEFITS**

- 100% Pure neutral curing, almost odourless
- Perfect adhesion to most common building substrates
- Excellent resistance to UV, water and weather
- Highly mold resistant
- Non corrosive towards metals
- Wide adhesion spectrum
- Wide colour availability

# **PRODUCT DESCRIPTION**

**Bostik S766 KITCHEN & BATHROOM SILICONE PREMIUM** is a versatile neutral silicone sealant for sanitary joints, which cures under influence of humidity to form a durable elastic rubber.

#### **APPLICATIONS**

**Bostik S766 KITCHEN & BATHROOM SILICONE PREMIUM** is specially developed for durable elastic sealing of sanitary joints in kitchens, bathrooms, showers and industrial applications.

#### **DIRECTIONS OF USE**

A joint with the correct dimensions is able to absorb movements between building materials.

The joint depth should always be in the correct relationship of the joint width. A general rule is the ratio of joint depth to the width of the joint with a joint width up to 10 mm is 1:1, with a minimum of 5 mm in width and depth. For joints wider than 10 mm, the depth is the width divided by 3 plus 6 mm.



TECHNICAL DATA		
100% modulus	DIN 53504 S2	0,48 N/mm <sup>2</sup>
Application		+5°C to +40°C
temperature		
Base		Neutral Oxime
Curing time	@+23°C/50%RH	2 mm/24 hours
Density	ISO 1183-1	1,02 g/ml
Elongation at break	ASTM D412	497%
Sag Resistance	ASTM C639	0 mm
Shore A hardness	ASTM C661	26
Tack free time		5 mins @
		+23°C/50% RH
Temperature		-50°C to +150°C
resistance		
Tensile strength	DIN 53504 S2	1,69 N/mm <sup>2</sup>

These values are typical properties and may vary +/-3%

#### **LIMITATIONS**

- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates
- Discoloration can occur in dark places and by contact with chemicals

#### SURFACE PREPARATIONS AND FINISHING

Application temperature + 5°C to + 40°C (applies to environment and substrates). All substrates must be solid, clean and free of grease and dust. Clean substrates with Bostik T100 UNIVERSAL CLEANER. Bostik S766 KITCHEN & BATHROOM SILICONE PREMIUM adheres perfectly without the use of primer to most non-porous substrates. Porous substrates to be pre- treated with Bostik T300 UNIVERSAL PRIMER. Always test adhesion prior to application. Use Bostik T500 FINISHING SOAP to smooth the joint.

#### **PAINTABILITY**

Bostik S766 KITCHEN & BATHROOM SILICONE **PREMIUM** is not paintable. We recommend covering the edges of the joint with masking tape to prevent surfaces that need to be painted from being contaminated by silicone.

#### **CLEANING**

Tools should be cleaned after use with water. Hands can be cleaned with Bostik T150 CLEANING WIPES and/or water and soap. Cured material can only be mechanically removed.

#### COLOUR(S)

- Clear
- White
- Black

#### **PACKAGING**

260 ml Cartridge, 25 per box

For product specifications, please refer to the Online Product Detail Page

#### SHELF LIFE AND STORAGE

In unopened original packaging between + 5°C and + 25°C, shelf life is up to 12months from production date, stored in a dry place.

#### **HEALTH & SAFETY**

Product Safety Data Sheet must be read and understood before use. These are available on request and via the websites.

of the product are given in good faith and based on tests which we believe to be reliable. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. However, no warranty in respect of merchantability or fitness for a particular purpose, nor any liability arising out of any legal relationship, whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advise offered. No guarantee of their accuracy can be made because of the great range of field conditions and variation encountered in raw materials, manufacturing equipment and methods. Thus, the products are sold with limited warranty only, and on condition that purchasers will make their own tests to determine the suitability of the product for their particular purposes. Under no circumstances will Bostik be liable to anyone except for replacement of the products or refund of the purchase price.

# **Bostik**

8 Bonding & Bonding Technical Data Sheet S766 KITCHEN & BATHROOM SILICONE PREMIUM JUN\_2021 The information and recommendations relating to the application and end-use **BOSTIK SMART SUPPORT** Smart help digital bostik.com/ Smart help +606 678 9788