

Bostik Instant Paintable Caulk.

Date: 03 May 2016

Fact Sheet No.: TDSBM 1

YOUR SMART ADVANTAGES

- Paintable immediately after application.
- Excellent adhesion without the use of a primer.
- Reduces cracking and discolouration of the paint.
- Easy to apply & Clean.

USES

Bostik Instant Paintable Caulk is a high quality acrylic sealant specifically developed to be overpainted with water based and synthetic paints immediately after application.

This product is for interior use and adheres to most surfaces. Bostik Instant Paintable Caulk has a low odour easy to apply and is not corrosive to metals. For sealing and filling gaps where movement can occur, such as those between plasterwork, window&door frames, skirting boards and architraves.

PRODUCT CHARACTERISTICS

| | |
|--------------------|--|
| Colour | White |
| Form | Paste |
| Specific Gravity | 1.5 approx. |
| Composition | Acryl Dispersion |
| Product Code | 30606785 310ml x12 |
| Storage/Shelf Life | Store for up to 12 months from date of manufacture in original, unopened packaging under cool, dry, conditions within the temperature range of +5°C to +30°C and out of direct sunlight. Protect from frost. |

TYPICAL PERFORMANCE DATA (Approx.)

| | |
|-------------------------|---------------|
| Application Temperature | +5°C to +40°C |
|-------------------------|---------------|

| | |
|-------------------------|--|
| Service Temperature | -20°C to +75°C |
| Coverage | 15 metres of 5mm diameter bead per C20 cartridge |
| Drying Times | Approx. 15 minutes. However, full bond strength will be achieved after 24 hours. |
| Solvent for Cleaning Up | White Spirit |

DIRECTIONS FOR USE

IMPORTANT: Before using EVO-STIK Sticks Like Sh*t Turbo refer to the relevant Health & Safety Data Sheet, available at www.bostik.co.uk.

PREPARATION

1. Surfaces must be sound, clean and free from contaminants such as dust, oil, grease and any loose material.
2. Cut off the dome at the top of the cartridge taking care not to damage the thread. Cut the nozzle at a 45° angle to the required diameter and screw onto the cartridge.
3. Insert the cartridge into a cartridge gun and repeatedly squeeze the trigger until the adhesive appears.

APPLICATION

4. Always tool using a spatula of stick wetted with water within 5 mins of application.
5. Beads 5mm in diameter are generally sufficient.

CLEANING

6. Uncured product can be removed with water

PRECAUTIONS IN USE

For any application not covered please contact Technical Services on +353 1 8624998.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

BOSTIK HOTLINE

Smart help +353 1 8624998



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.