

Date: 09 August 2013

Information Sheet No.: TDS00444

## CEMENTONE WATERSEAL A WATER REPELLENT SOLUTION

Cementone Waterseal is a long lasting, deeply penetrating, water repellent solution for porous external walls and fascias. It deposits a waterproof resin in the capillaries of the substrate which expands on reaction with residual moisture and almost completely reduces rainwater penetration, whilst still allowing the substrate to breathe. This reduction of the movement of water through the structure improves insulation, reduces dirt retention, mould and algae growth. It also reduces the incidence of efflorescence. Cementone Waterseal is completely colourless although it may enhance the colour of treated surfaces in rare cases. Before using this product refer to the relevant Health & Safety Sheet.

### Uses

- Cementone Waterseal is a highly efficient water repellent liquid for ABOVE GROUND dry, porous substrates:
- Brickwork, cement renderings, asbestos cement, cast concrete, roughcast
- All stonework & limestone
- Wood

### Product Characteristics

<b>Colour</b>	Clear	
<b>Form</b>	Solvent based liquid	
<b>Specific Gravity</b>	0.8 approximately	
<b>Composition</b>	Polyoxo aluminium stearate based	
<b>Product Code</b>	<b>222175</b>	5 Litres x 4
	<b>366442</b>	25 Litres

**Shelf life/storage** Two years from date of manufacture when stored in original unopened containers in a cool, dry place within the temperature range +5°C to +25°C and out of direct sunlight. PROTECT FROM FROST

### Typical Performance Data (approx.)

**Coverage** 2 - 5 m<sup>2</sup> per litre per coat

### Directions for use

#### IMPORTANT

Before using Cementone Waterseal refer to the relevant Health & Safety Data Sheet. Available at [www.bostik.co.uk](http://www.bostik.co.uk) named as the code above.

#### Application

1. Surfaces must be clean, dry, porous and free of any contamination. Bitumen must be totally removed, as it will run.
2. Any structural defects, particularly mortar joints, must be made good and allowed to cure before application. Note: Cementone Waterseal will not seal and reduce penetration of water into open textured concrete blocks.
3. Apply one or two coats of Cementone Waterseal to the prepared surface using a large brush or low pressure spray equipment, care being taken to ensure no excessive over-spray or inhalation by the operative.
4. In exceptional circumstances further coats may be necessary.
5. Allow at least 2 hours between coats and do not apply to surfaces affected by rain or frost.
6. Take precautions to ensure Cementone Waterseal does not come into contact with glass window panes and decorative coatings, as it will be very difficult to remove once dry.

#### Cleaning

7. Clean tools immediately after use with white spirit.
8. Any over-spray MUST be removed with paint thinner or white spirit whilst wet.

Date: 09 August 2013

Information Sheet No.: TDS00444

## Precautions in Use

Cementone Waterseal is not intended as a damp-proof membrane or in below ground waterproofing applications. It is not designed for use indoors or in enclosed areas, due to its solvent content.

This product should not be used for waterproofing ponds or pools. Also take care to prevent run-off getting into nearby pools or ponds.

It is not designed as a dustproofer for walls or floors.

The product works by lining the capillaries of the substrate. To be able to allow this the substrate **MUST** be both dry and porous. If it is applied to wet or non-porous surfaces either by design or accidentally it will dry to leave a white deposit, which is very difficult to remove.

If used indoors or in confined spaces the solvent will take much longer to evaporate. In some cases the odour of solvent may be present for many weeks.

If paint is to be applied the product must be completely dry and the surface weathered for at least six months. Always test a small area for paint suitability.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data Sheet for Cementone Waterseal.

Date: 09 August 2013

Information Sheet No.: TDS00444

Sales & Technical contacts at Bostik	Telephone	Facsimile	Email addresses
Sales	0844 371 1192	01785 241818	<a href="mailto:customer.service@bostik.com">customer.service@bostik.com</a>
Technical advice	0844 371 1197	01785 272867	<a href="mailto:technical.service@bostik.com">technical.service@bostik.com</a>
Technical Data & COSHH (MSDS) sheets	01785 272625	01785 212962	<a href="mailto:stafford.gatehouse@bostik.com">stafford.gatehouse@bostik.com</a>

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.