



Rito Silvershield

Solar reflecting Paint for Roofs.

Date: 09 April 2018

Fact Sheet No.: Bos Rito

YOUR SMART ADVANTAGES

- Light & Heat reflective finish reduces temp gain.
- Waterproof protective coating
- Tough flexible membrane to accommodate normal roof movement.
- Helps prevent cracking & crazing.

USES

Bostik Rito silvershield is a high quality aluminium pigmented bituminous coating for use on metal surfaces and all matured bituminous roofing surfaces such as roofing felt, asphalt and cold applied bituminous systems. Ideal to protect Felt, Slate, corrugated zinc, Lead and concrete surfaces.

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	+5°C to +30°C / optimum +20°C
Drying Times	1-2 Hours dependant on Temperature and Humidity
Coverage	8 -10m ² /litre on rough surfaces. 10-15m ² /Litre on Smooth surfaces.
Fire resistance	Wet: Flammable Dry: will burn slowly.

PRODUCT CHARACTERISTICS

Colour	Silver
Form	Liquid solvent
Product Code	30810521 – Bostik Rito Silvershield 5ltr 30810522–Bostik Rito Silvershield 25ltr.
Storage/Shelf Life	30 days or 50m ² per 10 cool, dry conditions between +5C and 25C. 12 months. Store Valve up & upright position.

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Rito Silvershield refer to the relevant Health & Safety Data Sheet at www.Bostik.IE

PREPARATION

1. It is strongly recommended to wear safety Gloves and Safety Goggles when using this product.
2. Stir can before application. Stir frequently during use.
3. Substrates must be matured, sound clean and dry.

APPLICATION

4. Stir well ensuring any settlement is incorporated.
5. Apply using a soft sweeping brush, Paintbrush, Paint rollers are the most economical in labour and consumption of product.
6. Avoid excessive working of Bostik Rito Silvershield as this can reduce the brilliance of the finish.



FM 01696
BS EN ISO 9001:2008

Bostik Industries Ltd. Newtown, Swords, Co. Dublin, Ireland. Tel: +353 1 8624900 www.bostik.ie

7. Apply 2 Coats: The second coat is applied as soon as the first coat is dry.
8. Allow 24 hours before foot traffic.

PRECAUTIONS IN USE

Do Not apply when rain, frost or overnight dew is expected before the coating is completely dry, as bronzing of the surface may result.

For any application not covered please contact Technical Services on +353 1 8624998 or visit www.bostik.ie for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Rito Silvershield, available at www.bostik.ie.

BOSTIK HOTLINE

Smart help +353 1 8624998



FM 01696
BS EN ISO 9001:2008

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 01 8624999	Fax: 01 8402186	orders.bostik-irl@bostik.com
Technical Advice	Tel: 01 8624998	Fax: 01 8402186	
Technical Data & COSHH (MSDS) Data Sheets	Tel: 01 8624900	Fax: 01 8402186	



FM 01696
BS EN ISO 9001:2008