

Bostik SHP Primer. Solvent free Acrylic.

Date: 19 July 2016 Fact Sheet No.:

YOUR SMART ADVANTAGES

- Ready to use one part sanded acrylic primer.
- Suitable for floors & walls(easily applied by Roller)
- Provides optimum adhesion.

USES

Bostik SHP is suitable as a primer prior to levelling and Tiling work on: Smooth &sound substrates such as ceramic tiles, Terrazzo Natural stone coverings. Especially suitable for laying over old vinyl, Linoleum and old adhesive residues.

PRODUCT CHARACTERISTICS	
Colour	Blue
Form	Liquid
Product codes	1kg 30605378 5kg 30810659
Composition	Special Acrylate
Storage/Shelf Life	Always store upright in cool, dry conditions. Do not expose to temperatures above +50C. 12 months.
TYPICAL PERFORMANCE DATA (Approx.)	
Application Temperature	+5°C to +30°C
Coverage	8/10m2 per 1kg
Density	1.3kg/litre
Drying Times	1 to 3 hours

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik SHP refer to the relevant Health & Safety Data Sheet, available at www.bostik.ie

PREPARATION

- Surfaces must be sound, stable and should have a effective damp proof membrane.
- 2. Poorly attached floor coverings should be grinded.

APPLICATION

- 3. Stir well.
- 4. Apply by roller paintbrush or applicator pads.

CLEANING

5. Clean tools after use in water.

PRECAUTIONS IN USE

For any application not covered please contact Technical Services on +353 1 8624998 or visit www.bostik.ie for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik SHP, available at www.bostik.ie.

BOSTIK HOTLINE

Smart help +353 18624998







This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales Tel: 01 8624999 Fax: 018402186 orders.bostik-irl@bostik.com

Technical Advice Tel: 01 8624998 Fax: 01 8402186
Technical Data & COSHH (MSDS) Data Sheets Tel: 01 8624900 Fax: 01 8402186

