



# BOSTIK RENDER WP

## WATERPROOF CEMENT BASED PLASTER

### KEY FEATURES

- Premixed to ensure high consistent quality delivered to site
- High convenience in handling the prepacked plaster
- Just adding the required water to achieve consistency in workability
- Mixing and application is easy
- Excellent bond strength
- High durability and good weather resistance
- No wastages on sand and cement in opened bag
- Cleaning limited to just disposing the used paper bag

### DESCRIPTION

Bostik Render WP is a premixed cement based plaster with waterproof properties. It provides an excellent workability that is easy to use by just adding water.

Bostik Render WP consists of cement, graded sand and waterproof additives that provide a bond to concrete and brick substrates. It is meant for internal and external plastering that will surpass the specifiers' stringent requirement.

### RECOMMENDED USES

Bostik Render WP can be used for bedding brickwork, blockwork and as backing and bedding for tiles.

Bostik Render WP is highly recommended for all types of concrete substrates, lightweight autoclaved aerated blocks, brick walls and block walls.

### SUBSTRATE PREPARATION

All substrates shall be sound, clean, free of dust, oil, grease and other contaminants. Site practices like washing of the substrate a day before plastering is highly encouraged. Dampen dry concrete surface before application.

### APPLICATION INSTRUCTION

#### MIXING

Add approximately 5.6 to 6.5 litres of water to every 40

### PERFORMANCE PROPERTIES

Appearance	Grey Powder
Water required	5.6 to 6.5 Litres of water per 40kg bag
Consistency	Homogeneous mortar paste
Binder	Cement
Filler	Graded sand
Additives	Polymer for workability, water retention and adhesion
Water Retentivity	≥ 95% (BS 4551: part 1: 1998)
Pot Life	60 minutes
Compressive Strength	12 to 20N/mm <sup>2</sup>
Shrinkage	< 0.1%

kg bag of Bostik Render WP.

Add Bostik Render WP gradually into measured clean water while stirring with electric paddle mixer. Mix for approximately 3 to 5 minutes.

Bostik Render WP is ready for use after achieving a consistent homogeneous paste.

### PLACING

Bostik Render WP can be applied by using a steel trowel or by spraying. Bostik Render WP will remain workable up to 45 minutes after mixing. Any hydration through the addition of water will degrade the performance of the mortar mix.

### COVERAGE

25 to 30m<sup>2</sup>/mm per 40kg bag.

### PACKAGING

40 kg bag.

### STORAGE AND SHELF LIFE

Store all materials in a cool dry place, in an elevated condition.

The shelf life of Bostik Render WP is 12 months from date of manufacturing in original, unopened bag.

## HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent SDS - Safety Data Sheet (available upon request) containing physical, ecological, toxicological and other safety related data.

The information and recommendations relating to the application and end-use of the product are given in good faith and based on tests which we believe to be reliable. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. However, no warranty in respect of merchantability or fitness for a particular purpose, nor any liability arising out of any legal relationship, whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. No guarantee of their accuracy can be made because of the great range of field conditions and variation encountered in raw materials, manufacturing equipment and methods. Thus, the products are sold with limited warranty only, and on condition that purchasers will make their own tests to determine the suitability of the product for their particular purposes. Under no circumstances will Bostik be liable to anyone except for replacement of the products or refund of the purchase price.

**BOSTIK HOTLINE**

**Smart help**  
**+606 678 9788**



**Bostik Findley (Malaysia) Sdn. Bhd.** 1994010000474 (286152-V)

Lot 112 & 113, Kawasan Perindustrian Senawang,  
70450 Seremban, Negeri Sembilan,  
Malaysia

Tel : +606 678 9788 Fax : +606 678 9766

**www.bostik.com**  
**an Arkema company**