

BOSTIK BUTYL MASTIC SEALANTS BPIR DECLARATION

Version 1.0 July 2024



DESIGNATED BUILDING PRODUCT: Class 1

DECLARATION

Bostik New Zealand Ltd (Bostik) has provided this declaration to satisfy the provisions of the **Building (Building Product Information Requirements) Regulations 2022**.

COMPANY DETAILS

Name	Bostik New Zealand Ltd
Role	Manufacturer
NZBN	9429039292674
Address	19 Eastern Hutt Rd, Wingate, Lower Hutt
Website	www.bostik.com/newzealand/en_NZ/
Email	nzsales@bostik.com
Phone	0508 222 777

DESCRIPTION OF BUILDING PRODUCT

Bostik manufactures and supplies butyl mastic sealants.

Butyl mastic sealants are formulated from a blend of butyl rubber and polyisobutylene. This group of sealants bonds to common materials such as metal, glass, wood, concrete and masonry, and cures to form a permanently plastic seal that is weather resistant. Priming is not required prior to application and it may be painted. It can accommodate joint movement of $\pm 5\%$.

Bostik butyl mastic sealants are manufactured to the applicable standards and are third-party tested where relevant. Bostik has an active in-house testing regime for all their products.

For a complete list of Bostik butyl mastic sealants and their use, refer to Appendix 1.

Bostik has a lengthy history in speciality adhesives. It originated in Massachusetts, America in 1889 and was known as the Boston Blacking Company. The name Bostik was adopted in 1960. In 2015 it became part of the Arkema group. Bostik has a strong focus on **sustainability**; products and how they operated the business.

CONTRIBUTION TO BUILDING WORK CODE OBLIGATIONS

Bostik butyl mastic sealants do not have building code obligations. Building code obligations arise when used in building work. Bostik relies on their in-house testing, third-party testing, and compliance with standards, as applicable, to make the following claims.

When used in building work, Bostik butyl mastic sealants *may* contribute to compliance with the applicable performance criteria in respect of:

- B1 (Structure)
- B2 (Durability)
- E2 (External Moisture)
- E3 (Internal Moisture)
- F2 (Hazardous Building Materials): F2.3.1.

FOR FURTHER INFORMATION

Bostik butyl mastic sealants must be used and stored in accordance with all information supplied by Bostik.

For supporting information refer to **Bostik**.

RESPONSIBLE PERSON

In accordance with Regulation 8, as the responsible person I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm Bostik butyl mastic sealants, as referred to in this statement, are not subject to a warning or ban under **s26 of the Building Act**.

Signed for and on behalf of Bostik New Zealand Ltd:

Tim Lewis

Tim Lewis
MANAGING DIRECTOR

July 2024



BOSTIK BUTYL MASTIC SEALANTS

APPENDIX 1

Version 1.0 July 2024

Bostik supplies Butyl Mastic sealants, for exterior and interior applications.

BOSTIK 5612

Bostik Non Skinning Mastic (5612) is a bedding or gasket style sealant.

It retains its soft plastic state providing a dust proof, weather resistant, flexible seal.

It adheres to a large variety of surfaces and is therefore suitable for use as a sealant for cool room walls, sealing of air conditioning flange joints, as a glazing sealant and in the bedding or internal sealing of windows and flashings.

Click here for more [information](#).