# BPIR DECLARATION



Version 1.0 July 2024

#### **DESIGNATED BUILDING PRODUCT:** Class 1

#### **DECLARATION**

Bostik New Zealand Ltd (Bostik) has provided this declaration to satisfy the provisions of the **Building** (Building Product Information Requirements) Regulations 2022.

## **COMPANY DETAILS**

Name	Bostik New Zealand Ltd	
Role	Manufacturer	
NZBN	9429039292674	
Address	19 Eastern Hutt Rd, Wingate, Lower Hutt	
Website	www.bostik.com/newzealand/en_NZ/	
Email	nzsales@bostik.com	
Phone	0508 222 777	

#### **DESCRIPTION OF BUILDING PRODUCT**

Bostik manufactures and supplies putty for plumbing and glazing.

Glazing putty is used to hold and seal glazing into joinery. That is, it holds the glazing in place and seals it to avoid moisture ingress. The base components of glazing putty are a mixture of linseed oil and whiting (calcium carbonate). Additional components are added to improve the putty's performance.

Exterior grade putty is more UV and moisture resistant, but all putty retains a flexibility throughout its serviceable life. This flexibility cushions glazing from the effects of building movement that will arise during normal environmental conditions. Glazing putty is paintable once cured.

Plumbing putty is a malleable, clay-like compound that creates a watertight seal by filling in spaces under flanges associated with the installation of taps, sinks and drains. The putty prevents water seepage.

For a complete list of Bostik's glazing putty and their use refer to Appendix 1.

Bostik has a lengthy history in speciality adhesives. It originated in Massachusetts, America in 1889 and was known as the Boston Blacking Company. The name Bostik was adopted in 1960. In 2015 it became part of the Arkema group. Bostik has a strong focus on **sustainability**; products and how they operated the business.



#### CONTRIBUTION TO BUILDING WORK CODE OBLIGATIONS

Putty does not have building code obligation. Building code obligations arise when used in building work. Bostik relies on their in-house testing, third-party testing, and compliance with standards, as applicable, to make the following claims. When used in building work Bostik glazing putty will contribute to compliance:

- E2 (external moisture).
- G12 (water supplies).
- G13 (foul water).

#### FOR FURTHER INFORMATION

Bostik putty must be used and stored in accordance with all information supplied by Bostik.

For supporting information refer to **Bostik**.

### **RESPONSIBLE PERSON**

In accordance with Regulation 8, as the responsible person I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm Bostik putty, as referred to in this statement, are not subject to a warning or ban unders26 of the Building Act.

## Signed for and on behalf of Bostik New Zealand Ltd:

Tim Lewis

Tim Lewis
MANAGING DIRECTOR
July 2024



# BOSTIK PUTTY APPENDIX 1



Version 1.0 July 2024

Bostik supplies putty for glazing and plumbing applications.

### KwikPaint Glazing Putty

Kwikpaint Glazing Putty is a NZ-made, white, exterior grade putty. It is suitable for use with timber, steel and aluminium joinery and most glass types.

The putty is quick drying, allowing same day painting. The formulation is non-oily and can be painted with water and oil-based paints.

When applied correctly it will not shrink or crack and dries to a wrinkle-free finish.

Steel and timber joinery must be primed prior to the application of the putty. The putty should not be used in conjunction with other sealants.

Click here for more information.

# Plumbers Putty

Bostik's Plumbers Putty is an odourless, white, non-staining putty designed specifically for use in plumbing installations.

It must not be subjected to sunlight or direct weathering and is not paintable.

Steel and timber joinery must be primed prior to the application of the putty. The putty should not be used in conjunction with other sealants.

It remains permanently flexible, is non-taky and water resistant.

Click here for more information.