

BOSTIK SOLVENT-BASED SEALANTS BPIR DECLARATION

Version 1.0 July 2024



DESIGNATED BUILDING PRODUCT: Class 1

DECLARATION

Bostik New Zealand Ltd (Bostik) has provided this declaration to satisfy the provisions of the **Building (Building Product Information Requirements) Regulations 2022**.

COMPANY DETAILS

Name	Bostik New Zealand Ltd
Role	Manufacturer
NZBN	9429039292674
Address	19 Eastern Hutt Rd, Wingate, Lower Hutt
Website	www.bostik.com/newzealand/en_NZ/
Email	nzsales@bostik.com
Phone	0508 222 777

DESCRIPTION OF BUILDING PRODUCT

Bostik manufactures and supplies solvent-based sealants.

Solvent-based sealants are high in volatile organic compounds, referred to as VOCs. This means that they have a strong odour, and as a result are more suited for exterior use or where there is an opportunity for the odour to flash off. They,

- are hard wearing,
- provide a high-gloss finish,
- are fast drying,
- remain fully flexible,
- perform over a wide range of temperatures, and
- adhere to many surfaces.

These types of sealants are used in other industries as well as the construction industry, including the automotive industry.

For a complete list of Bostik solvent-based sealants and their use, refer to Appendix 1.

Bostik has a lengthy history in speciality adhesives. It originated in Massachusetts, America in 1889 and was known as the Boston Blacking Company. The name Bostik was adopted in 1960. In 2015 it became part of the Arkema group. Bostik has a strong focus on **sustainability**, products and how they operated the business.

CONTRIBUTION TO BUILDING WORK CODE OBLIGATIONS

Bostik solvent-based sealants do not have building code obligations. Building code obligations arise when used in building work. Bostik relies on their in-house testing, third-party testing, and compliance with standards, as applicable, to make the following claims.

When used in building work, Bostik solvent-based sealants *may* contribute to compliance with the applicable performance criteria in respect of:

- B1 (Structure)
- B2 (Durability)
- E2 (External Moisture)
- G4 (Ventilation)
- F2 (Hazardous Building Materials): F2.3.1.

FOR FURTHER INFORMATION

Bostik solvent-based sealants must be used and stored in accordance with all information supplied by Bostik.

For supporting information, refer to **Bostik**.

RESPONSIBLE PERSON

In accordance with Regulation 8, as the responsible person I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm Bostik solvent-based sealants, as referred to in this statement, are not subject to a warning or ban under **s26 of the Building Act**.

Signed for and on behalf of Bostik New Zealand Ltd:

Tim Lewis

Tim Lewis
MANAGING DIRECTOR

July 2024

BOSTIK SOLVENT-BASED SEALANTS

APPENDIX 1



Version 1.0 July 2024

Bostik supplies solvent-based sealants for the construction and automotive sectors.

Duct Sealer

Duct sealer is a grey, non-slump, fast drying (30 – 60 minutes) sealer. It is recommended for use in sealing lap joints (up to 5 mm) in heating and air conditioning ducting as well as in automotive applications. It bonds well to many substrates including wood, concrete, galvanised and other metals, and is water and oil resistant.

Duct sealer is not suitable for use with polystyrene, polyethylene or Teflon.

Once dry, Duct sealer remains fully flexible

Click here for more [information](#).