BOSTIK WET AREA MEMBRANES

BPIR DECLARATION

Version 1.0 October 2024

DESIGNATED BUILDING PRODUCT: Class 1

DECLARATION

Bostik New Zealand Ltd (Bostik) has provided this declaration to satisfy the provisions of the Building (Building Product Information Requirements) Regulations 2022.

COMPANY DETAILS

Name	Bostik New Zealand Ltd
Role	Manufacturer
NZBN	9429039292674
Address	19 Eastern Hutt Rd, Wingate, Lower Hutt
Website	www.bostik.com/newzealand/en_NZ/
Email	nzsales@bostik.com
Phone	0508 222 777

DESCRIPTION OF BUILDING PRODUCT

Bostik supplies membranes for use in wet areas in interior and exterior applications.

The membranes are manufactured from different materials (which determine their scope of use) and include polyurethane, butyl rubber and epoxy systems.

Bostik have BRANZ appraisals for the Dampfix® range of systems.

For the complete list of Bostik wet area membranes and their use, refer to Appendix 1.

Bostik has a lengthy history in speciality adhesives and associated products. It originated in Massachusetts, America in 1889 and was known as the Boston Blacking Company. The name Bostik was adopted in 1960. In 2015 it became part of the Arkema group. Bostik has a strong focus on sustainability; products and how they operated the business.

CONTRIBUTION TO BUILDING WORK CODE OBLIGATIONS

Bostik relies on their in-house testing, third-party testing, and compliance with standards, as applicable, to make the following claims.

Bostik wet area membranes comply with or *may* contribute to compliance with the applicable performance criteria in respect of:

- B1 (Structure): B1.3.1, B1.3.2, B1.3.3 (b, e, j, m, q)
- B2 (Durability): B2.3.1 (b)
- E2 (External Moisture): E2.3.1, E3.2.2, E2.3.7
- E3 (Internal Moisture): E3.3.6
- F2 (Hazardous Building Materials): F2.3.1.

FOR FURTHER INFORMATION

Bostik wet area membranes must be used and stored in accordance with all information supplied by Bostik.

For supporting information, refer to Bostik.

RESPONSIBLE PERSON

In accordance with Regulation 8, as the responsible person I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm Bostik wet area membranes, as referred to in this statement, are not subject to a warning or ban under s26 of the Building Act.

Signed for and on behalf of Bostik New Zealand Ltd:

Tim Lewis

Tim Lewis
MANAGING DIRECTOR

October 2024

BOSTIK WATER-BASED TILE ADHESIVES

APPENDIX 1

Version 1.0 October 2024

Bostik supplies a full range of adhesives for exterior and interior application.

MOISTURE SEAL PART A & B

Moisture seal is a class 2, two-part water-based epoxy coating.

It is intended for use as a moisture and vapour barrier for concrete or masonry surfaces. Where used on floors it is part of the surface preparation for installing floor coverings of any type. It may be used in interior, exterior and below ground applications.

It is low odour and does not emit VOCs.

Go to our website for more information.

DAMPFIX 3

Dampfix® 3 is a two-part cementitious and acrylic waterproofing membrane. It is suitable for use in interior and exterior applications including immersed applications such as pools.

It is fibre-reinforced for added strength and dries quickly – recoating is possible after 1 – 2 hours and in most conditions, tiling can be carried out the same day.

Dampfix® is BRANZ appraised.

Go to our website for more information.

DAMPFIX GOLD

Dampfix® gold is a one-component, highly elastic, class 3, water-based polyurethane waterproofing membrane. Two coats must be applied, with the second coat able to be applied within 2 hours. It may be flood tested after 72 hours.

It suitable for use in interior and exterior applications and is specifically formulated for application on graded substrates that provide positive falls to drainage outlets.

The performance of Dampfix® Gold is assured through a BRANZ appraisal where used in interior applications.

It may not be left exposed and is not recommended for use in immersed applications such as pools.

Go to our website for more information.

DAMPFIX PEEL N STICK WATPROOFING SYSTEM

Dampfix® Peel N Stick (PS) waterproofing system is a BRANZ appraised system.

Got to our website for more information on the products that comprise this system.

Dampfix® PS Waterproofing Sheet Membrane,

Dampfix® PS Foil Tape,

Dampfix® PS External Preformed Corner,

Dampfix® PS Internal Preformed Corner,

Dampfix® PS Foil Wall Piping Collar,

Dampfix® PS Foil Floor Piping Collar.

The system is based on a Class 2 sealing membrane coated with a butyl rubber adhesive.

It is supplied for use as a complete wet room sealing system suitable for use on floors and walls in conjunction with substrates of cement rendered masonry, concrete, FC sheeting, structural plywood and water resistant plywood.