



Primer MSP

Product

Simson Primer MSP is a liquid primer for adhesion improvement of sealants and adhesives on porous surfaces.

Applications

Pre-treatment of mineral surfaces, such as brick, concrete and cellular concrete.

Features

Essential product to obtain a durable adhesion.

Method of use

Surface: The surfaces should have a firm and solid structure and must be clean, dry and dust- and grease free.

Preparation: Keep the packaging well closed until the moment of use. Do not use primers straight from the original packing. Pour as much primer in a clean glass, tin or paint tray, as can be used within 30 minutes. Do not use any left primer residues. Immediately close the original tin.

The best adhesion results are obtained when the bonding or sealing will be realised within 6 hours after the primer has dried. Therefore do not apply more primer than can be sealed or bonded within 6 hours. Avoid contact of the cleaned and primed surfaces, because greasy fingers will be of a negative influence on the adhesion. Also condensation can negatively influence the adhesion. It is not recommendable to apply the primer during very high air humidity, for example during dense fog.

Application: Apply the primer always with a clean brush or clean velvet brush roller. Apply primer on the adhesion surfaces in a closed coat. Although the primer is transparent and will not discolour, a primer coat can yet be visible. If this is unacceptable a masking tape can be used to cover the surface parts, where no primer is required. On very porous surfaces a second primer coat may be necessary after the first coat has dried for 60 - 90 minutes.

Application temperature: From +5°C till +30°C.

Drying time: Minimal drying time 60 minutes.

Usage: Depending on the porosity of the surface between 2 - 4 m² per litre.



Primer MSP

Technical data

Dry contents	40%		
Specific gravity	0.95 g/ml		
Flash point	< 21°C		
Minimum drying time	60 minutes	(at 20°C/RV 50%)	

Colour
transparent

Packaging
tin 500 ml

Article code
022080

Storage stability

Store cool, dry and frost-free in unopened original packaging. Can be stored for 6 months, opened packaging has limited shelf life.

Further information

The following publication is available on request:

- Material Safety Data Sheets (MSDS)

Bostik B.V.

Postbus 303
5201 AH 's-Hertogenbosch
Tel: +31 (0)73 6 244 244
Fax: +31 (0)73 6 244 344
E-mail: infonl@bostik.com
Internet: www.bostik.nl

Bostik Belux SA-NV

Meulestedekaai 86
B-9000 Gent
Tel: +32 (0)9 255 17 00
Fax: +32 (0)9 255 17 01
E-mail: info@bostik.be
Internet: www.bostik.be