



ULTRAGRIP

PLASTERBOARD STUD ADHESIVE

24 October 2014

YOUR SMART ADVANTAGES

- Non slump
- Economical
- Easy to apply
- Water based
- NZ made
- Suitable for vertical, horizontal and overhead applications
- High bond strength

USES

- To fix plasterboard to steel or timber studs and frames (in conjunction with nails and screws)
- Filling irregular gaps between plasterboard and frame
- Bonding chipboard, plywood, Masonite and Hardie-Flex sheeting to studs or solid walls.

PRODUCT CHARACTERISTICS

Colour	Blue
Viscosity	Non slump paste
Composition	Water based
Application temperature	10 to 30°C
Open Time	15 to 20 minutes
Coverage	Approximatley 40m ² of plasterboard per litre
Product codes	
600mL sausage/20 per carton	30804611
4L Pail	30804597

TYPICAL PERFORMANCE DATA (approx.)

Specification	Conforms to AS 2329 Mastic adhesives for fixing wallboards
---------------	--

DIRECTIONS FOR USE

Read and understand the Material Safety Data Sheet before using this product.

SURFACE PREPARATION

Ensure all surfaces are clean, dry and free from dirt, grease or loose material. All framing dimensions must comply with NZS 3604:1999. All surfaces must be at least 10°C.

APPLICATION

Walls: Apply Ultragrip Stud Adhesive in daubs of about 35mm wide by 15 to 25mm high at 300mm centres to intermediate studs. Immediately fix sheet in place. The perimeter must be mechanically fixed.

Ceilings: Work one sheet at a time. Apply Ultragrip Stud Adhesive in daubs of about 35mm wide by 15 to 25mm high at 200mm centres except for the perimeter and centre line, which must be screwed. Immediately fix sheet in place.

Note: Ensure full contact between the sheets and Ultragrip Stud Adhesive until adhesive sets. The use of temporary direct fix screws through blocks are recommended. Ultragrip Stud Adhesive will dry and full strength in 24 hours to 48 hours.

LIMITATIONS

- Ultragrip Stud Adhesive must be used in conjunction with nails or screws.
- Do not apply adhesive around sheet edges, or under fasteners.
- Do not nail or screw through the adhesive.
- Do not fix nails or screws closer than 200mm to adhesive.
- Do not fix more than one sheet at a time to avoid skinning of the adhesive, which may result in adhesion failure.
- One surface must be absorbent to allow the adhesive to dry properly. Two impervious surfaces cannot be bonded using this adhesive.

CLEANING

Clean up with water before adhesive cures.

STORAGE AND SHELF LIFE

Store in a cool dry place below 25°C and out of direct sunlight. Do not freeze. Shelf life is 12 months from the date of manufacture when stored as directed.

ULTRAGIP

DISPOSAL

Empty sausages and pails may be disposed via local landfill. If spilt, absorb with clay, sand or earth. Ensure wash water discharges to sewer only. Do not allow wash water to enter storm water drains. Collect and preferably allow the product to dry before disposal to landfill. Otherwise seal in properly labelled containers or drums for disposal to landfill.

PRECAUTIONS IN USE

Complete details on each of the products mentioned are available on the product Safety Data Sheets. To ensure no harm is caused to persons using Bostik products, it is recommended that all concerned read the appropriate Safety Data Sheets. Visit www.bostik.co.nz for copies. Bostik Ultragrip Stud Adhesive is not classified as Dangerous Goods or as a Hazardous Substance. The product however, should be used in accordance with good occupational, health and safety practices.

For emergency information contact the National Poisons Information Centre, phone 0800 764 766 (0800 POISON) or CHEMICALL, phone 0800 243 622.



This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out of date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Consumer Guarantees Act 1993. Sale of the product by Bostik is subject to the Bostik New Zealand Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit www.bostik.co.nz