



Product Technical Statement

Bostik UL-Screed

Bostik NZ Ltd manufactures adhesives, sealants and other products used in building and construction that are not by themselves within the scope of the New Zealand Building Code (NZBC). The products may be part of, or used with another product, or system that must comply with the NZBC.

Bostik provides technical information to support Provider Statements regarding compliance with NZBC.

Product Description and Use

Bostik UL-Screed is a fast setting high build modified cementitious levelling screed. Specially formulated for quick and easy application to achieve required falls without any shrinkage or cracking.

Recommended applications:

- Externally balconies or in ramp applications
- Wet areas where controlled falls are required.
- Onto concrete and FC (Cement sheet) sheet substrate.
- Residential, commercial or medium industrial applications.
- As a system in conjunction with Bostik/ASA wet area internal waterproofing membranes.

The technical information for Bostik UL-Screed can be found on the Bostik website www.bostik.co.nz.

This information includes:

- Technical Data Sheet
- Safety Data Sheet

New Zealand Building Code (NZBC)

Bostik UL-Screed, if designed, used, installed and maintained in accordance with the information provided by Bostik New Zealand, will contribute to or meet the following provisions of the NZBC:

- **Clause B2 DURABILITY: Clause B2 DURABILITY:** Performance B2.3.1 (c), 5 years.
- **Clause F2 HAZARDOUS BUILDING MATERIALS:** Performance F2.3.1.

Quality Assurance

Bostik has a long history of supply of quality products to the building and construction industries. Products are manufactured and tested under strict quality controlled conditions.

Bostik products of similar formulation to Bostik UL-Screed have been supplied and used in building in New Zealand for over 15 years.

Maintenance Requirements

Interior: yearly inspection and repair of defects as found is required.



Expected product life

It is expected that Bostik UL-Screed will have a life of at least 5 years when applied by a skilled contractor in accordance with specifications and recommended methods of application.

The life expectancy does not take into account failure or breakdown of Bostik UL-Screed partially or wholly due to:

- faulty or unskilled application
- incorrect storage of the product
- use of the product outside of its recommended shelf life
- use other than as recommended
- not inspecting the product regularly and repairing any defects
- factors and conditions outside the control of Bostik, including:
 - movement of the substrate or structural cracking
 - hydrostatic pressure or entrapped moisture
 - maltreatment, such as mechanical damage, at any time of the product
 - faulty design and/or construction of the premises leading to weather – tightness issues.

Differing materials, substrates, environments, site conditions, product storage, handling and application may affect results.

Warranty

Bostik is not liable for representations made by users, suppliers, or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless or negligent use or storage of the product, including out of date product. To the maximum extent permitted by law Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Consumer Guarantees Act 1993. Any liability arising from use of the product is limited to the replacement or purchase price of the product.

Contact

For more information on Bostik, products and conditions of use and sale contact:

Bostik New Zealand Ltd

0508 222 272

e-mail: nzsales@bostik.com

www.bostik.co.nz