

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

BOSTIK 1010 THICK FLOW

Supercedes Date: 16-Sep-2021

Revision date 16-Sep-2021 Revision Number 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name Pure substance/mixture BOSTIK 1010 THICK FLOW Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use	
Uses advised against	

Cement. Building and construction work. None known.

1.3. Details of the supplier of the safety data sheet

Company Name Bostik AB Strandbadsvaegen 22 PO Box 903 25109 Helsingborg, Sweden Tel: +46 42 19 50 00 Fax: +46 42 19 50 20

E-mail address

SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone

No information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 1 - (H318)
Specific target organ toxicity — single exposure	Category 3 H335

2.2. Label elements

Contains Cement, portland, chemicals (Chromium VI reduced)



Signal word Danger

Hazard statements H315 - Causes skin irritation.

BOSTIK 1010 THICK FLOW

Supercedes Date: 16-Sep-2021

H318 - Causes serious eye damage.

H335 - May cause respiratory irritation.

Precautionary Statements - EU (§28, 1272/2008)

P102 - Keep out of reach of children

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P284 - Wear respiratory protection

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Additional information

Cement product for which the amount of chromium VI was decreased to < 0,0002 % by a reduction agent (related to the total dry weight).

2.3. Other hazards

Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease. Product dust may be irritating to eyes, skin and respiratory system. Repeated exposure may cause skin dryness or cracking. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Quartz	238-878-4	14808-60-7	40 - <80	^		[4]
Cement, portland, chemicals (Chromium VI reduced)	266-043-4	65997-15-1	1 - 10	STOT SE 3 (H335) Skin Irrit. 2 (H315) Eye Dam. 1 (H318)		Exempt

NOTE [4] - This substance is exempted from registration according to the provisions of Article 2(7)(a) and Annex IV of REACH

NOTE [5] - This substance is exempted from registration according to the provisions of Article 2(7)(a) and Annex V of REACH

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

BOSTIK 1010 THICK FLOW Supercedes Date: 16-Sep-2021

SECTION 4: First aid measu	res	
4.1. Description of first aid measures		
General advice	If medical advice is needed, have product container or label at hand.	
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.	
Eye contact	Do not rub affected area. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.	
Skin contact	Brush off loose particles from skin. Remove material from skin immediately. Take off contaminated clothing and wash it before reuse.	
Ingestion	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.	
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).	
4.2. Most important symptoms and	effects, both acute and delayed	
Symptoms	Burning sensation. Causes serious eye damage. Irritating to skin. Inhalation of dust in high concentration may cause irritation of respiratory system. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers.	
4.3. Indication of any immediate m	edical attention and special treatment needed	
Note to doctors	Treat symptomatically.	
SECTION 5: Firefighting me	asures	
5.1. Extinguishing media		
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.	
Unsuitable extinguishing media	Full water jet. Do not scatter spilled material with high pressure water streams.	
5.2. Special hazards arising from t	he substance or mixture	
Specific hazards arising from the chemical	No information available.	
Hazardous combustion products	Carbon dioxide (CO2). Sulphur oxides. Silicon dioxide.	
5.3. Advice for firefighters		
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.	
SECTION 6: Accidental release measures		

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

Avoid generation of dust. Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required.

BOSTIK 1010 THICK FLOW

Supercedes Date: 16-Sep-2021

Other information	Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.
6.2. Environmental precautions	
Environmental precautions	Prevent product from entering drains. Do not allow to enter into soil/subsoil.
6.3. Methods and material for conta	ainment and cleaning up
Methods for containment	Cover powder spill with plastic sheet or tarp to minimise spreading and keep powder dry. Prevent dust cloud.
Methods for cleaning up	Do not dry sweep dust. Wet dust with water before sweeping or use a vacuum to collect dust. Use appropriate personal protective equipment (PPE). Carefully shovel or sweep up spilled material and place in suitable container. Avoid generating dust.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.
6.4. Reference to other sections	
Reference to other sections	See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling	Ensure adequate ventilation. Avoid generation of dust. Avoid contact with skin, eyes or clothing. Use personal protection equipment. Take off contaminated clothing and wash it before reuse.
General hygiene considerations	Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.
7.2. Conditions for safe storage, inc	cluding any incompatibilities
Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Keep the packing dry and well sealed to prevent contamination and absorption of humidity.

7.3. Specific end use(s)

Specific use(s)

Cement. Building and construction work.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union
Quartz	TWA: 0.1 mg/m ³
14808-60-7	

BOSTIK 1010 THICK FLOW Supercedes Date: 16-Sep-2021

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration No information available. (PNEC)

8.2. Exposure controls

Engineering controls

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection
Hand protectionWear safety glasses with side shields (or goggles).For operations where prolonged or repeated skin contact may occur, impervious gloves
should be worn. Gloves made of plastic or rubber. Gloves should be replaced regularly
and if there is any sign of damage to the glove material.Skin and body protectionAvoid contact with skin, eyes or clothing. Wear appropriate personal protective clothing
to prevent skin contact.Respiratory protectionNo protective equipment is needed under normal use conditions. If exposure limits are
exceeded or irritation is experienced, ventilation and evacuation may be required. Avoid
generation of dust. Possible nuisance dust.Recommended filter type:Wear a respirator conforming to EN 140 with Type P2/P3 filter or better.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Appearance Colour Odour Odour threshold	Solid Powder Grey Characteristic No information available		
Property	Values	Remarks	Method
рН	No data available		
pH (as aqueous solution)	11 - 11.5		
Melting point / freezing point	Not applicable °C		
Initial boiling point and boiling range	Not applicable . °C		
Flash point	Not applicable . °C		
Evaporation rate	Not applicable .		
Flammability	No data available		
Flammability Limit in Air			
Upper flammability or explosive limits	No data available		
Lower flammability or explosive limits	No data available		
Vapour pressure	No data available		
Relative vapour density	No data available		
Relative density	No data available		
Water solubility	Cement based products react and		
	solidify in contact with water		
Solubility(ies)	No data available		
Partition coefficient	No data available		
Autoignition temperature	No data available		
Decomposition temperature	No data available		
Kinematic viscosity	Not applicable .		
Dynamic viscosity	Not applicable .		

BOSTIK 1010 THICK FLOW Supercedes Date: 16-Sep-2021 Revision date 16-Sep-2021 Revision Number 1

Explosive properties Oxidising properties	No data available No data available
9.2. Other information Solid content (%) Softening Point VOC Content (%) Density	100 Not relevant No data available
SECTION 10: Stability and re	eactivity
10.1. Reactivity	
Reactivity	Stable under recommended storage conditions.
10.2. Chemical stability	
Stability	Keep away from Incompatible materials. Stable under recommended storage conditions.
Explosion data	
Sensitivity to mechanical impact	None.
_ · · · · · · · · · ·	None.
10.3. Possibility of hazardous reac	tions
Possibility of hazardous reactions	None under normal processing.
10.4. Conditions to avoid	
Conditions to avoid	Product cures with moisture.
10.5. Incompatible materials	
Incompatible materials	Strong acids. Strong bases. Strong oxidising agents. Acids. Aluminium.
10.6. Hazardous decomposition pro	oducts
Hazardous decomposition products	None under normal use conditions. Stable under recommended storage conditions.
SECTION 11: Toxicological i	nformation
11.1. Information on toxicological e	effects
Information on likely routes of exp	osure
Product Information	
Inhalation	May cause irritation of respiratory tract.
Eye contact	Causes serious eye damage.
Skin contact	Causes skin irritation. (based on components).
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.
Symptoms related to the physical,	chemical and toxicological characteristics

BOSTIK 1010 THICK FLOW

Symptoms

Redness. Burning. May cause blindness. May cause redness and tearing of the eyes.

Numerical measures of toxicity

No information available

Acute toxicity The following values are calculated based on chapter 3.1 of the GHS document ATEmix (dermal) 11,772.00 mg/kg ATEmix (inhalation-dust/mist) 46.60 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Quartz 14808-60-7	>2000 mg/kg (Rattus)		
Cement, portland, chemicals (Chromium VI reduced) 65997-15-1		>2000 Kg/mg (Lapin)	>5 g/m³ (Rattus)
Delayed and immediate effect	s as well as chronic effects fr	om short and long-term expos	sure
Skin corrosion/irritation	Irritating to skin.		
Serious eye damage/eye irrita	tion Risk of serious damage to	o eyes.	
Respiratory or skin sensitisati	on Based on available data,	the classification criteria are not	met.
Germ cell mutagenicity	Based on available data,	the classification criteria are not	met.
Carcinogenicity	Based on available data,	the classification criteria are not	met.
Reproductive toxicity	Based on available data,	the classification criteria are not	met.
STOT - single exposure	May cause respiratory irri	itation.	
STOT - repeated exposure	Based on available data,	the classification criteria are not	met.
Aspiration hazard	Based on available data,	the classification criteria are not	met.
11.2. Information on other	hazards		
11.2.1. Endocrine disrupting properties			
Endocrine disrupting properti	es No information available.		
11.2.2. Other information			
Other adverse effects	No information available.		

BOSTIK 1010 THICK FLOW Supercedes Date: 16-Sep-2021

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation

No information available.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Quartz	-	0
14808-60-7		

12.4. Mobility in soil

Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

- 12.6. Other adverse effects
- Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Do not reuse empty containers.
European Waste Catalogue	10 13 14 waste concrete and concrete sludge 17 09 04 mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)14.1 UN number or ID number14.2 Proper Shipping NameNot regulated

BOSTIK 1010 THICK FLOW Supercedes Date: 16-Sep-2021

14.3 Transport hazard class(es) 14.4 Packing group 14.5 Environmental hazards 14.6 Special Provisions	Not regulated Not regulated Not applicable None	
IMDG		
14.1 UN number or ID number	Not regulated	
14.2 Proper Shipping Name	Not regulated	
14.3 Transport hazard class(es)	Not regulated	
14.4 Packing group	Not regulated	
14.5 Marine pollutant	NP	
14.6 Special Provisions	None	
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code		Not applicable

Air transport (ICAO-TI / IATA-DGR)		
	UN number or ID number	Not regulated
14.2	Proper Shipping Name	Not regulated
14.3	Transport hazard class(es)	Not regulated
14.4	Packing group	Not regulated
14.5	Environmental hazards	Not applicable
14.6	Special Provisions	None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Cement, portland, chemicals (Chromium VI reduced)	65997-15-1	item 47

47 where product supplied with reducing agent the packaging must be marked with the storage conditions and storage period appropriate to maintaining the activity of the reducing agent to keep the content of soluble chromium VI below 2mg/Kg

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

BOSTIK 1010 THICK FLOW

Supercedes Date: 16-Sep-2021

Not applicable

National regulations

France

Occupational Illnesses (R-463-3, France)

Chemical name	French RG number
Quartz	RG 25
14808-60-7	
Cement, portland, chemicals (Chromium VI reduced)	RG 8,RG 10
65997-15-1	RG 8

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) slightly hazardous to water (WGK 1)

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Chemical name	Netherlands - List of Carcinogens
Quartz	Present (respirable dust, crystalline)
14808-60-7	

Sweden

Swedish Work Environment Authority's Statute (AFS 2015:2) QUARTZ AFS 2015:2

Occupational exposure limits AFS 2018:1

Special care should be applied for employees under the age of 18. Young people under the age of 18 may not carry out any work causing harmful exposure to this product. AFS 2012:3

<u>Denmark</u>	
Registration number(s) (P-no.)	2499694
MAL-Code	00-4
Norway	
Registration number(s) (PRN-no.)	86024

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H315 - Causes skin irritation

H318 - Causes serious eye damage

H335 - May cause respiratory irritation

Legend

TWA	
STEL	

TWA (time-weighted average) STEL (Short Term Exposure Limit)

BOSTIK 1010 THICK FLOW Supercedes Date: 16-Sep-2021 Revision date 16-Sep-2021 Revision Number 1

Ceiling * SVHC PBT vPvB STOT RE STOT SE EWC	Ceiling Limit Value Skin designation Substance(s) of Very High Concern Persistent, Bioaccumulative, and Toxic (PBT) Chemicals Very Persistent and very Bioaccumulative (vPvB) Chemicals Specific target organ toxicity - Repeated exposure Specific target organ toxicity - Single exposure European Waste Catalogue	
Key literature references and sources for data No information available		
Prepared By	Product Safety & Regulatory Affairs	
Revision date	16-Sep-2021	
Indication of changes		
Revision note	Not applicable.	
Training Advice	No information available	
Further information	No information available	

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet