

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008
This SDS is for generic information purposes and does not reflect required country specific
information for OEL

BUTYL 1590 BLACK Supercedes Date: 30-Nov-2016 Revision date 09-Apr-2021 Revision Number 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BUTYL 1590 BLACK

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant.
Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik AB Strandbadsvaegen 22 PO Box 903 25109 Helsingborg, Sweden

Tel: +46 42 19 50 00 Fax: +46 42 19 50 20

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Specific target organ toxicity — single exposure	Category 3 - (H336)
Chronic aquatic toxicity	Category 3 - (H412)
Flammable liquids	Category 3 - (H226)

2.2. Label elements

Contains Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics



Signal word Warning

Hazard statements

H336 - May cause drowsiness or dizziness.

H412 - Harmful to aquatic life with long lasting effects.

Europe - EN Page 1/12

Revision date 09-Apr-2021

Revision Number 2

BUTYL 1590 BLACK
Supercedes Date: 30-Nov-2016

H226 - Flammable liquid and vapour.

EU Specific Hazard Statements

EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280 - Wear protective gloves and eye/face protection

P271 - Use only outdoors or in a well-ventilated area

P405 - Store locked up

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

Harmful to aquatic life. In use, may form flammable/explosive vapour-air mixture.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	919-857-5	64742-48-9	20 - 25	STOT SE 3 (H336) Asp. Tox. 1 (H304) (EUH066) Flam. Liq. 3 (H226)		01-2119463258- 33
4-(1,1,3,3-tetramethylbut yl)phenol, (4-tert-Octylphenol)	205-426-2	140-66-9	0.01 - <0.05	Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)		01-2119541687- 29-XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Europe - EN Page 2/12

Supercedes Date: 30-Nov-2016 **Revision Number** 2

SECTION 4: First aid measures

BUTYL 1590 BLACK

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance.

Inhalation Remove to fresh air. IF exposed or concerned: Get medical advice/attention.

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Eye contact

Keep eye wide open while rinsing. Do not rub affected area. Get medical attention

Revision date 09-Apr-2021

immediately if symptoms occur.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. Get medical attention if symptoms occur.

Ingestion Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious

person. Call a doctor.

Remove all sources of ignition. Ensure that medical personnel are aware of the Self-protection of the first aider

> material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more

information.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Inhalation of high vapour concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam. **Suitable Extinguishing Media**

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated

fire extinguishing water must be disposed of in accordance with local regulations.

Hazardous combustion products Carbon dioxide (CO2).

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak, ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention

Europe - EN Page 3 / 12

Supercedes Date: 30-Nov-2016 Revision Number 2

to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled

Revision date 09-Apr-2021

material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

BUTYL 1590 BLACK

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or

spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A

vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later

disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. In case of insufficient

ventilation, wear suitable respiratory equipment.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should

not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the

product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the

particular national regulations. Store in accordance with local regulations.

Recommended storage

temperature

Keep at temperatures between 5 and 25 °C.

7.3. Specific end use(s)

Specific use(s)

Sealant.

Europe - EN Page 4/12

Supercedes Date: 30-Nov-2016 Revision Number 2

Revision date 09-Apr-2021

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

BUTYL 1590 BLACK

Exposure Limits

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)					
Hydrocarbons, C9-C11, n-alkanes	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)				
Туре		Derived No Effect Level (DNEL)	Safety factor		
Long term Systemic health effects	Dermal	300 mg/kg bw/d			
Long term Systemic health effects	Inhalation	1500 mg/m ³			

Predicted No Effect Concentration No information available. (PNEC)

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be

exhausted directly at the point of origin.

Personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Wear protective gloves. The breakthrough time of the gloves depends on the material

and the thickness as well as the temperature.

Skin and body protection Suitable protective clothing.

Respiratory protection In case of inadequate ventilation wear respiratory protection. In case of mist, spray or

aerosol exposure wear suitable personal respiratory protection and protective suit.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid
Appearance Paste
Colour Black
Odour Characteristic

Odour threshold No information available

Property Values Remarks • Method

pH No data available Not applicable Insoluble in water

pH (as aqueous solution)

Melting point / freezing point

Initial boiling point and boiling

No data available

No data available

154 - 193 °C

Europe - EN Page 5/12

BUTYL 1590 BLACK
Supercedes Date: 30-Nov-2016
Revision date 09-Apr-2021
Revision Number 2

range

Flash point 41 °C

Evaporation rate No data available Flammability Not applicable for liquids

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapour pressure 3 hPa

Relative vapour density
Relative density
Water solubility
Solubility(ies)
Partition coefficient
Autoignition temperature
Decomposition temperature
No data available
No data available
No data available
No data available

Kinematic viscosity > 25

Dynamic viscosityNo data availableExplosive propertiesNo data availableOxidising propertiesNo data available

9.2. Other information

Solid content (%) 78.7

VOC Content (%)

Density 1.28 g/cm³

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

10.5. Incompatible materials

Incompatible materialsNone known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

@ 40°C

Europe - EN Page 6/12

BUTYL 1590 BLACK
Supercedes Date: 30-Nov-2016
Revision date 09-Apr-2021
Revision Number 2

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation May cause drowsiness or dizziness.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Inhalation of high vapour concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	>6000 mg/kg (Rattus)	> 3160 mg/kg (Oryctolagus cuniculus)	LC50 Vapour (4h) >5020 mg/m³ (Rattus)
4-(1,1,3,3-tetramethylbutyl)phe nol, (4-tert-Octylphenol) 140-66-9	=4600 mg/kg (Rattus)	= 1880 mg/kg (Oryctolagus cuniculus)	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationBased on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as mutagenic.

Chemical name	European Union
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2%	Muta. 1B
aromatics	
64742-48-9	

Carcinogenicity Based on available data, the classification criteria are not met.

Europe - EN Page 7/12

Revision date 09-Apr-2021

Supercedes Date: 30-Nov-2016 Revision Number 2

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties

11.2.2. Other information

BUTYL 1590 BLACK

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		microorganisms			(long-term)
Hydrocarbons, C9-C11,	EL50 (72h) >	LC50:	-	LL50 (48h) >		
n-alkanes, isoalkanes,	1000 mg/l	=2200mg/L		1000 mg/l		
cyclics, <2% aromatics	(Pseudokirchner	(96h,		(Daphnia		
64742-48-9	iella	Pimephales		magna)		
	subcapitata)	promelas)		OECD 202		
	OECD 201					
4-(1,1,3,3-tetramethylb	EC50: =1.9mg/L	LC50:	-	EC50: 0.07 -	10	10
utyl)phenol,	(96h,	=0.25mg/L (96h,		0.12mg/L (48h,		
(4-tert-Octylphenol)	Pseudokirchneri	Pimephales		Daphnia magna)		
140-66-9	ella subcapitata)	promelas) LC50:				
	EC50: =1.1mg/L	1.5 - 2.2mg/L				
	(72h,	(96h, Leuciscus				
	Desmodesmus	idus)				
	subspicatus)					

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
4-(1,1,3,3-tetramethylbutyl)phenol,	4.12	-
(4-tert-Octylphenol)		
140-66-9		

Europe - EN Page 8/12

BUTYL 1590 BLACK
Supercedes Date: 30-Nov-2016
Revision date 09-Apr-2021
Revision Number 2

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

Chemical name	PBT and vPvB assessment
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	The substance is not PBT / vPvB
4-(1,1,3,3-tetramethylbutyl)phenol, (4-tert-Octylphenol) 140-66-9	The substance is not PBT / vPvB

12.6. Other adverse effects

Other adverse effects No information available.

Endocrine Disruptor Information

Chemical name	EU - Endocrine Disrupters Candidate List	EU - Endocrine Disruptors - Evaluated Substances
4-(1,1,3,3-tetramethylbutyl)phenol, (4-tert-Octylphenol)	Group II Chemical	Medium Exposure Concern

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging

Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or

weld containers.

European Waste Catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous

substances

15 01 10*: Packaging containing residues of or contaminated by dangerous substances

Other information

Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number14.2 Proper Shipping NameUN1133Adhesives

14.3 Transport hazard class(es) 3 Labels 3 14.4 Packing group

Description UN1133, Adhesives, 3, III, (D/E)

14.5 Environmental hazards Not applicable

14.6 Special Provisions None
Classification code F1
Tunnel restriction code
Limited Quantity (LQ) 5 L
ADR Hazard Id (Kemmler 30

Number)

<u>IMDG</u>

Europe - EN Page 9/12

BUTYL 1590 BLACK
Supercedes Date: 30-Nov-2016
Revision date 09-Apr-2021
Revision Number 2

14.1 UN number or ID number14.2 Proper Shipping NameUN1133Adhesives

14.3 Transport hazard class(es) 3 14.4 Packing group

Description UN1133, Adhesives, 3, III, (47°C c.c.)

 14.5 Marine pollutant
 NP

 14.6 Special Provisions
 223, 955

 Limited Quantity (LQ)
 5 L

 EmS-No
 F-E, S-D

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID numberUN113314.2 Proper Shipping NameAdhesives14.3 Transport hazard class(es)3

14.4 Packing group

Description UN1133, Adhesives, 3, III

14.5 Environmental hazards Not applicable

14.6 Special Provisions A3 Limited Quantity (LQ) 10 L ERG Code 3L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS P5b - FLAMMABLE LIQUIDS P5c - FLAMMABLE LIQUIDS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Europe - EN Page 10/12

Revision date 09-Apr-2021

Revision Number 2

BUTYL 1590 BLACK

·

Persistent Organic Pollutants

Supercedes Date: 30-Nov-2016

Not applicable

National regulations

France

Occupational Illnesses (R-463-3, France)

Chemical name	French RG number
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	RG 84
64742-48-9	

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

Flammable liquid (R10), EEC: refer to Annex III No. 1 (fire and explosion hazards) and § 7 paragraph 3

Water hazard class (WGK) obviously hazardous to water (WGK 2)

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Sweden

Occupational exposure limits AFS 2018:1

Denmark

Registration number(s) (P-no.) 336752 MAL-Code 1-1

Norway

Registration number(s) (PRN-no.) 8021

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking

H226 - Flammable liquid and vapour

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H318 - Causes serious eye damage

H336 - May cause drowsiness or dizziness

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value
* Skin designation

Europe - EN Page 11/12

Supercedes Date: 30-Nov-2016 Revision Number 2

Revision date 09-Apr-2021

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

Key literature references and sources for data

No information available

BUTYL 1590 BLACK

Prepared By Product Safety & Regulatory Affairs

Revision date 09-Apr-2021

Indication of changes

Revision note Not applicable.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Europe - EN Page 12/12