



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008
This SDS is for generic information purposes and does not reflect required country specific information for OEL

BOSTIK CONTACT 1782
Supersedes date 19-May-2020

Revision date 15-Aug-2024
Revision Number 1.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK CONTACT 1782

Other means of identification

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik SA
420 rue d'Estienne d'Orves
92700 Colombes
FRANCE
Tel: +33 (0)1 49 00 90 00

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to
Regulation (EC) No. 1272/2008
[CLP]

Serious eye damage/eye irritation	Category 2 - (H319)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Category 3 Narcotic effects	
Chronic aquatic toxicity	Category 3 - (H412)
Flammable liquids	Category 2 - (H225)

2.2. Label elements

Contains Acetone; Methyl ethyl ketone

SAFETY DATA SHEET

BOSTIK CONTACT 1782
Supersedes date 19-May-2020

Revision date 15-Aug-2024
Revision Number 1.01



Signal word
Danger

Hazard statements

H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H412 - Harmful to aquatic life with long lasting effects
H225 - Highly flammable liquid and vapour

EU Specific Hazard Statements

EUH066 - Repeated exposure may cause skin dryness or cracking
EUH208 - Contains 1,4-Benzenediol, 2,5-bis(1,1-dimethylpropyl)-. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P261 - Avoid breathing mist/vapours/spray
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves and eye/face protection
P312 - Call a POISON CENTER or doctor if you feel unwell
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
P405 - Store locked up
P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

PBT & vPvB

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No..	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Acetone 40 - <80 %	200-662-2 (606-001-00-8)	67-64-1	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225)	-	-	-	01-2119471330-49-XXXX

SAFETY DATA SHEET

BOSTIK CONTACT 1782
Supersedes date 19-May-2020

Revision date 15-Aug-2024
Revision Number 1.01

(EUH066)							
Methyl ethyl ketone 10 - <20 %	201-159-0 (606-002-00-3)	78-93-3	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)	-	-	-	01-2119457290-43-XXXX
1,4-Benzenediol, 2,5-bis(1,1-dimethylpropyl)- 0.05 - <0.1 %	201-222-2	79-74-3	Acute Tox. 4 (H302) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	-	-	10	01-2119539460-43-XXXX

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATE_{mix}) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Acetone	200-662-2 (606-001-00-8)	67-64-1	5800	-	-	-	-
Methyl ethyl ketone	201-159-0 (606-002-00-3)	78-93-3	-	-	-	-	-
1,4-Benzenediol, 2,5-bis(1,1-dimethylpropyl)-	201-222-2	79-74-3	1900	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a doctor.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

SAFETY DATA SHEET

BOSTIK CONTACT 1782
Supersedes date 19-May-2020

Revision date 15-Aug-2024
Revision Number 1.01

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
Effects of Exposure	No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Treat symptomatically.
------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO ₂). Water spray. Alcohol resistant foam.
Unsuitable extinguishing media	No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Hazardous combustion products	Carbon oxides.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.
---	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for containment	Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later
--------------------------------	--

SAFETY DATA SHEET

BOSTIK CONTACT 1782
Supersedes date 19-May-2020

Revision date 15-Aug-2024
Revision Number 1.01

disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Eliminate all ignition sources if safe to do so.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

Recommended storage temperature Keep at temperatures between 5 and 25 °C.

7.3. Specific end use(s)

Specific use(s)
Adhesives.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union
Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³

SAFETY DATA SHEET

BOSTIK CONTACT 1782
Supersedes date 19-May-2020

Revision date 15-Aug-2024
Revision Number 1.01

Methyl ethyl ketone 78-93-3	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³
--------------------------------	--

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)

Acetone (67-64-1)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	186 mg/kg bw/d	
Short term Local health effects worker	Inhalation	2420 mg/m ³	
Long term Systemic health effects worker	Inhalation	1210 mg/m ³	

Methyl ethyl ketone (78-93-3)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	1161 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	600 mg/m ³	

Derived No Effect Level (DNEL)

Acetone (67-64-1)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	200 mg/m ³	
Consumer Long term Systemic health effects	Dermal	62 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	62 mg/kg bw/d	

Methyl ethyl ketone (78-93-3)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	412 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	106 mg/m ³	
Consumer Local health effects Systemic health effects	Oral	31 mg/kg bw/d	

Predicted No Effect Concentration

SAFETY DATA SHEET

BOSTIK CONTACT 1782
Supersedes date 19-May-2020

Revision date 15-Aug-2024
Revision Number 1.01

(PNEC)

Predicted No Effect Concentration (PNEC)	
Acetone (67-64-1)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10.6 mg/l
Freshwater - intermittent	21 mg/l
Marine water	1.06 mg/l
Microorganisms in sewage treatment	100 mg/l
Freshwater sediment	30.4 mg/kg dry weight
Marine water	3.04 mg/kg dry weight
Soil	29.5 mg/kg dry weight

Methyl ethyl ketone (78-93-3)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	55.8 mg/l
Marine water	55.8 mg/l
Freshwater sediment	287.74 mg/l
Marine sediment	287.7 mg/l
Soil	22.5 mg/l

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

Personal protective equipment

Eye/face protection Tight sealing safety goggles. Face protection shield.
Hand protection Wear protective gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature.
Skin and body protection Antistatic footwear. Wear fire/flame resistant/retardant clothing. Suitable protective clothing.
Respiratory protection In case of inadequate ventilation wear respiratory protection. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
Recommended filter type: Organic gases and vapours filter conforming to EN 14387.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid
Appearance Viscous
Colour Colourless
Odour Ketones and their derivatives.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	
Initial boiling point and boiling range	= 56 °C	
Flammability	No data available	Flammable liquid
Flammability Limit in Air		None known
Upper flammability or explosive limits	13.3	
Lower flammability or explosive limits	2	
Flash point	= -20 °C	
Autoignition temperature	404 °C	None known
Decomposition temperature		None known
pH	No data available	Not applicable. Insoluble in water.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	3800 mm ² /s	

SAFETY DATA SHEET

BOSTIK CONTACT 1782
Supersedes date 19-May-2020

Revision date 15-Aug-2024
Revision Number 1.01

Dynamic viscosity	No data available	
Water solubility	Insoluble in water.	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	<110 kPa	None known
Relative density	0.86	
Bulk density	No data available	
Liquid Density	No data available	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

Solid content (%)	approx 25	
VOC content		No data available

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

SAFETY DATA SHEET

BOSTIK CONTACT 1782
Supersedes date 19-May-2020

Revision date 15-Aug-2024
Revision Number 1.01

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness or dizziness.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	Specific test data for the substance or mixture is not available. May cause irritation. Prolonged contact may cause redness and irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms May cause redness and tearing of the eyes. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	>2000 mg/kg
ATEmix (dermal)	>2000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapour)	>20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone	=5800 mg/kg (Rattus) 3000 mg/Kg (mouse)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
Methyl ethyl ketone	=2483 mg/kg (Rattus)	= 5000 mg/kg (Oryctolagus cuniculus)	=11700 ppm (Rattus) 4 h
1,4-Benzenediol, 2,5-bis(1,1-dimethylpropyl)-	=2 g/kg (Rattus)	> 3160 mg/kg (Rabbit)	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Acetone (67-64-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			irritant

Methyl ethyl ketone (78-93-3)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			irritant

SAFETY DATA SHEET

BOSTIK CONTACT 1782
Supersedes date 19-May-2020

Revision date 15-Aug-2024
Revision Number 1.01

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)		
Methyl ethyl ketone 78-93-3	EC50=1972 mg/l (Pseudokirchneriella subcapitata)	LC50: 3130 - 3320mg/L (96h, Pimephales promelas)	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50 48 h > 308 mg/L (Daphnia magna)		
1,4-Benzenediol, 2,5-bis(1,1-dimethylpropyl)- 79-74-3	CE50 (72h) 1.2 - 1.7 mg/L Algae	CL50 (96h) 0.013 mg/L (Lepomis macrochirus)	-	CE50 (48h) 0.91 Daphnia (Daphnia Magna)		10

12.2. Persistence and degradability

Persistence and degradability No information available.

Acetone (67-64-1)

SAFETY DATA SHEET

BOSTIK CONTACT 1782
Supersedes date 19-May-2020

Revision date 15-Aug-2024
Revision Number 1.01

Method	Exposure time	Value	Results
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)	28 days	biodegradation	91 % Readily biodegradable

Methyl ethyl ketone (78-93-3)

Method	Exposure time	Value	Results
OECD Test No. 301D: Ready Biodegradability: Closed Bottle Test (TG 301 D)	28 days	biodegradation	98 % Readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Acetone	-0.24
Methyl ethyl ketone	0.3
1,4-Benzenediol, 2,5-bis(1,1-dimethylpropyl)-	2.1

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Acetone	The substance is not PBT / vPvB
Methyl ethyl ketone	The substance is not PBT / vPvB
1,4-Benzenediol, 2,5-bis(1,1-dimethylpropyl)-	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

European Waste Catalogue 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
15 01 10*: Packaging containing residues of or contaminated by dangerous substances

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SAFETY DATA SHEET

BOSTIK CONTACT 1782
Supersedes date 19-May-2020

Revision date 15-Aug-2024
Revision Number 1.01

SECTION 14: Transport information

Note: The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

Land transport (ADR/RID)

14.1 UN number or ID number	UN1133
14.2 UN proper shipping name	Adhesives
14.3 Transport hazard class(es)	3
Labels	3
14.4 Packing group	II
Description	UN1133, Adhesives, 3, II, (D/E)
14.5 Environmental hazards	No
14.6 Special precautions for user	
Special Provisions	640D
Classification code	F1
Tunnel restriction code	(D/E)
Limited quantity (LQ)	5 L
ADR Hazard Id (Kemmler Number)	33

IMDG

14.1 UN number or ID number	UN1133
14.2 UN proper shipping name	Adhesives
14.3 Transport hazard class(es)	3
14.4 Packing group	II
Description	UN1133, Adhesives, 3, II, (-20°C c.c.)
14.5 Marine pollutant	NP
14.6 Special precautions for user	
Special Provisions	None
Limited Quantity (LQ)	5 L
EmS-No.	F-E, S-D
14.7 Maritime transport in bulk according to IMO instruments	
Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	UN1133
14.2 UN proper shipping name	Adhesives
14.3 Transport hazard class(es)	3
14.4 Packing group	II
Description	UN1133, Adhesives, 3, II
14.5 Environmental hazards	No
14.6 Special precautions for user	
Special Provisions	A3
Limited quantity (LQ)	1 L
ERG Code	3L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

SAFETY DATA SHEET

BOSTIK CONTACT 1782
Supersedes date 19-May-2020

Revision date 15-Aug-2024
Revision Number 1.01

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS
P5b - FLAMMABLE LIQUIDS
P5c - FLAMMABLE LIQUIDS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. This product contains:

Chemical name	Reporting of suspicious transactions, disappearances and thefts	Restricted	Registration
Acetone - 67-64-1	Regulated		

National regulations

France

Occupational Illnesses (R-463-3, France)

Chemical name	French RG number
Acetone 67-64-1	RG 84
Methyl ethyl ketone	RG 84

SAFETY DATA SHEET

BOSTIK CONTACT 1782
Supersedes date 19-May-2020

Revision date 15-Aug-2024
Revision Number 1.01

78-93-3

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

Flammable liquid (R11), EEC: refer to Annex III No. 1 (fire and explosion hazards) and § 7 paragraph 4

Water hazard class (WGK) obviously hazardous to water (WGK 2)

TRGS - 510 Storage Class Storage Class 3 : Flammable liquids

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Not Listed

Sweden

Occupational exposure limits AFS 2018:1

Denmark

Registration number(s) (P-no.) 534302

MAL-Code 4-1

AT-Guide C.0.1 August 2007: Limit values for substances and materials

Norway

Registration number(s) (PRN-no.) 8022

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H225 - Highly flammable liquid and vapour
H302 - Harmful if swallowed
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances

vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT RE: Specific target organ toxicity - Repeated exposure

STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA TWA (time-weighted average)

STEL

STEL (Short Term Exposure Limit)

AGW Occupational exposure limit value

BGW

Biological limit value

SAFETY DATA SHEET

BOSTIK CONTACT 1782
Supersedes date 19-May-2020

Revision date 15-Aug-2024
Revision Number 1.01

Ceiling Maximum limit value Sk* Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)
European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)
European Chemicals Agency (ECHA) (ECHA_API)
Environmental Protection Agency
Acute Exposure Guideline Level(s) (AEGl(s))
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
NIOSH (National Institute for Occupational Safety and Health)
Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications
Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme
Organisation for Economic Co-operation and Development Screening Information Data Set

Prepared By Product Safety & Regulatory Affairs
Revision date 15-Aug-2024
Revision note SDS sections updated 6 8
Training Advice Provide adequate information, instruction, and training for operator
Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878, and Regulation (EC) No. 1272/2008

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet