



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008  
This SDS is for generic information purposes and does not reflect required country specific information for OEL

**BOSTIK EPOXY EXTRA STRONG - RESIN**  
Supersedes Date: 21-Feb-2023

Revision date 21-Feb-2023  
Revision Number 1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product Name BOSTIK EPOXY EXTRA STRONG - RESIN

### Other means of identification

Pure substance/mixture Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesive

Uses advised against Consumer use.

### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Bostik AB  
Strandbadsvaegen 22  
PO Box 903  
25109 Helsingborg, Sweden  
Tel: +46 42 19 50 00  
Fax: +46 42 19 50 20

E-mail address SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

Emergency Telephone

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitisation	Category 1 - (H317)
Chronic aquatic toxicity	Category 2 - (H411)

### 2.2. Label elements

Contains Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

# SAFETY DATA SHEET

**BOSTIK EPOXY EXTRA STRONG - RESIN**  
Supersedes Date: 21-Feb-2023

Revision date 21-Feb-2023  
Revision Number 1



**Signal word**  
Warning

#### Hazard statements

H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation  
H411 - Toxic to aquatic life with long lasting effects

#### EU Specific Hazard Statements

EUH205 - Contains epoxy constituents. May produce an allergic reaction

#### Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand  
P102 - Keep out of reach of children  
P261 - Avoid breathing vapours  
P280 - Wear protective gloves  
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P501 - Dispose of contents/ container to an approved waste disposal plant

#### Additional information

This product is part of a kit. Please also refer to the SDS for the other component(s) of the kit.

#### 2.3. Other hazards

Harmful to aquatic life.

#### PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No.	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 80 - 100 %	500-033-5	25068-38-6	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Aquatic Chronic 2 (H411)	Eye Irrit. 2 :: C>=5% Skin Irrit. 2 :: C>=5%	-	-	01-2119456619-26-xxxx
Formaldehyde,	500-006-8	9003-36-5	Skin Irrit. 2 (H315)	-	-	-	01-2119454392-

# SAFETY DATA SHEET

**BOSTIK EPOXY EXTRA STRONG - RESIN**  
Supersedes Date: 21-Feb-2023

Revision date 21-Feb-2023  
Revision Number 1

oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol 5 - <10 %			Skin Sens. 1 (H317) Aquatic Chronic 2 (H411)				40-XXXX
----------------------------------------------------------------------------------	--	--	-------------------------------------------------	--	--	--	---------

**Full text of H- and EUH-phrases: see section 16**

## Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	500-033-5	25068-38-6	-	-	-	-	-
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	500-006-8	9003-36-5	-	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	Show this safety data sheet to the doctor in attendance.
<b>Inhalation</b>	Remove to fresh air. Get medical attention immediately if symptoms occur.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
<b>Skin contact</b>	May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes.
<b>Ingestion</b>	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.
<b>Self-protection of the first aider</b>	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation.

### 4.3. Indication of any immediate medical attention and special treatment needed

# SAFETY DATA SHEET

BOSTIK EPOXY EXTRA STRONG - RESIN  
Supercedes Date: 21-Feb-2023

Revision date 21-Feb-2023  
Revision Number 1

**Note to doctors** May cause sensitisation in susceptible persons. Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable Extinguishing Media** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media** Full water jet.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards arising from the chemical** Product is or contains a sensitiser. May cause sensitisation by skin contact.

**Hazardous combustion products** No information available.

### 5.3. Advice for firefighters

**Special protective equipment and precautions for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Ensure adequate ventilation. Avoid contact with skin, eyes or clothing.

**Other information** Refer to protective measures listed in Sections 7 and 8.

**For emergency responders** Use personal protection recommended in Section 8.

### 6.2. Environmental precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so.

### 6.3. Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

**Methods for cleaning up** Take up mechanically, placing in appropriate containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

### 6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation. Avoid contact with skin, eyes or clothing. This product is part of a kit. Please also refer to the SDS for the other component(s) of the kit.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.

# SAFETY DATA SHEET

BOSTIK EPOXY EXTRA STRONG - RESIN  
Supersedes Date: 21-Feb-2023

Revision date 21-Feb-2023  
Revision Number 1

## 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place.

## 7.3. Specific end use(s)

**Specific use(s)**  
Adhesive.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure Limits

**Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.**

**Derived No Effect Level (DNEL)** No information available

Derived No Effect Level (DNEL)			
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Short term Systemic health effects	Dermal	8.33 mg/kg bw/d	
worker Long term Systemic health effects	Dermal	8.33 mg/kg bw/d	
worker Short term Systemic health effects	Inhalation	12.25 mg/kg bw/d	

Derived No Effect Level (DNEL)			
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Short term Systemic health effects	Dermal	3.571 mg/kg bw/d	
Consumer Short term Systemic health effects	Oral	0.75 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	3.571 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.75 mg/kg bw/d	

**Predicted No Effect Concentration (PNEC)** No information available.

# SAFETY DATA SHEET

BOSTIK EPOXY EXTRA STRONG - RESIN  
Supersedes Date: 21-Feb-2023

Revision date 21-Feb-2023  
Revision Number 1

Predicted No Effect Concentration (PNEC)	
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.006 mg/l
Marine water	0.0006 mg/l
Freshwater sediment	0.996 mg/l
Marine sediment	0.0996 mg/l
Soil	0.196 mg/l

## 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment

#### Eye/face protection

Wear safety glasses with side shields (or goggles).

#### Hand protection

Recommended Use: Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Unsuitable gloves materials: Disposable gloves. Leather. Gloves must conform to standard EN 374

#### Skin and body protection

Wear suitable protective clothing.

#### Respiratory protection

During spraying wear suitable respiratory equipment. In case of inadequate ventilation wear respiratory protection.

#### Recommended filter type:

Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Organic gases and vapours filter conforming to EN 14387.

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Liquid
Colour	Colourless
Odour	Characteristic.
Odour threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	None known
Flammability	Not applicable for liquids	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	> 150 °C	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	6	Not applicable.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	40000 mPa s	
Water solubility	Immiscible in water.	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known

# SAFETY DATA SHEET

**BOSTIK EPOXY EXTRA STRONG - RESIN**  
Supersedes Date: 21-Feb-2023

Revision date 21-Feb-2023  
Revision Number 1

<b>Bulk Density</b>	No data available	
<b>Density</b>	1.15 g/cm <sup>3</sup>	
<b>Relative vapour density</b>	No data available	None known
<b>Particle characteristics</b>		
<b>Particle Size</b>	No information available	
<b>Particle Size Distribution</b>	No information available	

## 9.2. Other information

<b>Solid content (%)</b>	91	
<b>VOC content</b>		No data available

9.2.1. Information with regards to physical hazard classes  
Not applicable

9.2.2. Other safety characteristics  
No information available

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

**Reactivity** No information available.

### 10.2. Chemical stability

**Stability** Stable under normal conditions.

### Explosion data

<b>Sensitivity to mechanical impact</b>	None.
<b>Sensitivity to static discharge</b>	None.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** None under normal processing.

### 10.4. Conditions to avoid

**Conditions to avoid** None known based on information supplied.

### 10.5. Incompatible materials

**Incompatible materials** None known based on information supplied.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** None under normal use conditions. Stable under recommended storage conditions.

## **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

#### **Product Information**

<b>Inhalation</b>	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
-------------------	--------------------------------------------------------------------------------------------------------------

# SAFETY DATA SHEET

**BOSTIK EPOXY EXTRA STRONG - RESIN**  
Supersedes Date: 21-Feb-2023

Revision date 21-Feb-2023  
Revision Number 1

<b>Eye contact</b>	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
<b>Skin contact</b>	May cause sensitisation by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Causes skin irritation.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

## Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes.

## Acute toxicity

### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

<b>ATEmix (oral)</b>	99,999.00 mg/kg
<b>ATEmix (dermal)</b>	99,999.00 mg/kg
<b>ATEmix (inhalation-gas)</b>	99,999.00 ppm
<b>ATEmix (inhalation-dust/mist)</b>	99,999.00 mg/l
<b>ATEmix (inhalation-vapour)</b>	99,999.00 mg/l

### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	LD50 (Rattus) > 2000 mg/kg OECD 420	>2000 mg/Kg (Rattus)	-
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	>2 g/kg (Rattus)	LD50 > 2000 mg/kg (Rattus) (OECD 402)	-

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Skin corrosion/irritation</b>	Causes skin irritation.
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.
<b>Respiratory or skin sensitisation</b>	May cause an allergic skin reaction.
<b>Germ cell mutagenicity</b>	Based on available data, the classification criteria are not met.
<b>Carcinogenicity</b>	Based on available data, the classification criteria are not met.
<b>Reproductive toxicity</b>	Based on available data, the classification criteria are not met.
<b>STOT - single exposure</b>	Based on available data, the classification criteria are not met.



# SAFETY DATA SHEET

BOSTIK EPOXY EXTRA STRONG - RESIN  
Supersedes Date: 21-Feb-2023

Revision date 21-Feb-2023  
Revision Number 1

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 11.2.2. Other information

**Other adverse effects** No information available.

**Note:** PC-ADH-8 Multi-component adhesives and sealants This product is part of a kit Please also refer to the SDS for the other component(s) of the kit

## **SECTION 12: Ecological information**

### 12.1. Toxicity

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	EC50 (72h) = 9.4 mg/L (Scenedesmus capricornutum) EPA-660/3-75-009	1.2 mg/l 96Hr (Oncorhynchus mykiss)	-	2.7 mg/l 48hr Daphia Magna		

### 12.2. Persistence and degradability

**Persistence and degradability** No information available.

### 12.3. Bioaccumulative potential

#### Bioaccumulation

#### Component Information

Chemical name	Partition coefficient
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	3.26
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	3.6

### 12.4. Mobility in soil

**Mobility in soil** No information available.

### 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	The substance is not PBT / vPvB
Formaldehyde, oligomeric reaction products with	The substance is not PBT / vPvB

# SAFETY DATA SHEET

BOSTIK EPOXY EXTRA STRONG - RESIN  
Supersedes Date: 21-Feb-2023

Revision date 21-Feb-2023  
Revision Number 1

1-chloro-2,3-epoxypropane and phenol

## 12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

## 12.7. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Waste from residues/unused products** Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Do not reuse empty containers.

**European Waste Catalogue** 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous substances

**Other information** Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

### Land transport (ADR/RID)

**14.1 UN number or ID number** UN3082

**14.2 Proper Shipping Name** Environmentally hazardous substances, liquid, n.o.s (Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)

**14.3 Transport hazard class(es)** 9

**Labels** 9

**14.4 Packing group** III

**Description** UN3082, Environmentally hazardous substances, liquid, n.o.s (Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol), 9, III, (-)

**14.5 Environmental hazards** Yes

**14.6 Special Provisions** 274, 335, 601, 375

**Classification code** M6

**Tunnel restriction code** (-)

**Limited quantity (LQ)** 5 L

**ADR Hazard Id (Kemmler Number)** 90

### IMDG

**14.1 UN number or ID number** UN3082

**14.2 Proper Shipping Name** Environmentally hazardous substances, liquid, n.o.s (Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)

**14.3 Transport hazard class(es)** 9

**14.4 Packing group** III

**Description** UN3082, Environmentally hazardous substances, liquid, n.o.s (Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol), 9, III, Marine Pollutant

**14.5 Marine pollutant** P

**14.6 Special Provisions** 274, 335, 969

# SAFETY DATA SHEET

**BOSTIK EPOXY EXTRA STRONG - RESIN**  
Supersedes Date: 21-Feb-2023

Revision date 21-Feb-2023  
Revision Number 1

Limited Quantity (LQ) 5 L  
EmS-No F-A, S-F  
14.7 Maritime transport in bulk according to IMO instruments Not applicable

## Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number UN3082  
14.2 Proper Shipping Name Environmentally hazardous substances, liquid, n.o.s (Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW)  
14.3 Transport hazard class(es) 9  
14.4 Packing group III  
Description UN3082, Environmentally hazardous substances, liquid, n.o.s (Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW), 9, III  
14.5 Environmental hazards Yes  
14.6 Special Provisions A97, A158, A197  
Limited quantity (LQ) 30 kg G  
ERG Code 9L

## **Section 15: REGULATORY INFORMATION**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

#### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

##### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

##### **EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction**

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

##### **Substance subject to authorisation per REACH Annex XIV**

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

##### **Dangerous substance category per Seveso Directive (2012/18/EU)**

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

##### **Ozone-depleting substances (ODS) regulation (EC) 1005/2009**

Not applicable

##### **Persistent Organic Pollutants**

Not applicable

#### National regulations

##### France

Europe - BE

# SAFETY DATA SHEET

**BOSTIK EPOXY EXTRA STRONG - RESIN**  
Supersedes Date: 21-Feb-2023

Revision date 21-Feb-2023  
Revision Number 1

## Germany

**Ordinance on Industrial Safety and Health - Germany - BetrSichV**  
No flammable liquids in accordance with BetrSichV

**Water hazard class (WGK)** obviously hazardous to water (WGK 2)

## Netherlands

**List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)**  
Not Listed

## Sweden

AFS 2011: 19 - Chemical working environment risks (Amended and reprinted in AFS 2014: 43), §§37a-g  
Special care should be applied for employees under the age of 18. Young people under the age of 18 may not carry out any work causing harmful exposure to this product. AFS 2012:3

## Denmark

**Registration number(s) (P-no.)** No information available  
**MAL-Code** 00-5

## Norway

**Registration number(s) (PRN-no.)** 303040

## 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

## **SECTION 16: Other information**

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### **Full text of H-Statements referred to under section 3**

H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation  
H411 - Toxic to aquatic life with long lasting effects

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

vPvB: Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE: Specific target organ toxicity - Repeated exposure

STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

#### **Legend SECTION 8: Exposure controls/personal protection**

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	*	Skin designation

## **Classification procedure**

# SAFETY DATA SHEET

**BOSTIK EPOXY EXTRA STRONG - RESIN**  
Supersedes Date: 21-Feb-2023

Revision date 21-Feb-2023  
Revision Number 1

Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

## Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)  
European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA\_RAC)  
European Chemicals Agency (ECHA) (ECHA\_API)  
EPA (Environmental Protection Agency)  
Acute Exposure Guideline Level(s) (AEGL(s))  
International Uniform Chemical Information Database (IUCLID)  
National Institute of Technology and Evaluation (NITE)  
NIOSH (National Institute for Occupational Safety and Health)  
Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications  
Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme  
Organisation for Economic Co-operation and Development Screening Information Data Set

**Prepared By** Product Safety & Regulatory Affairs

**Revision date** 21-Feb-2023

**Training Advice** No information available

**Further information** No information available

## Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008  
This SDS is for generic information purposes and does not reflect required country specific information for OEL

**BOSTIK EPOXY EXTRA STRONG - Part B**  
Supersedes Date: 12-May-2023

Revision date 12-May-2023  
Revision Number 1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product Name BOSTIK EPOXY EXTRA STRONG - Part B

### Other means of identification

Pure substance/mixture Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives Hardener

Uses advised against None known.

### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Bostik AB  
Strandbadsvaegen 22  
PO Box 903  
25109 Helsingborg, Sweden  
Tel: +46 42 19 50 00  
Fax: +46 42 19 50 20

E-mail address SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

Emergency Telephone

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Serious eye damage/eye irritation	Category 1 - (H318)
Skin sensitisation	Category 1 - (H317)
Chronic aquatic toxicity	Category 2 - (H411)

### 2.2. Label elements

Contains Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine, Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction, Amines, polyethylenepoly-, tetraethylenepentamine fraction



# SAFETY DATA SHEET

**BOSTIK EPOXY EXTRA STRONG - Part B**  
Supersedes Date: 12-May-2023

Revision date 12-May-2023  
Revision Number 1

## Signal word

Danger

## Hazard statements

H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H411 - Toxic to aquatic life with long lasting effects

## Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand  
P102 - Keep out of reach of children  
P280 - Wear face protection  
P302 + P352 - IF ON SKIN: Wash with plenty of water and soap  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P501 - Dispose of contents/ container to an approved waste disposal plant

## Additional information

This product is part of a kit. Please also refer to the SDS for the other component(s) of the kit.

## 2.3. Other hazards

Toxic to aquatic life.

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No.	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine 40 - <80 %	614-339-2	68154-62-1	Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Aquatic Chronic 3 (H412)	-	-	-	[7]
Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction >25 - <40 %	292-588-2	90640-67-8	Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Aquatic Chronic 2 (H411)	-	-	1	01-2119972322-40-XXXX
Amines, polyethylenepoly-,	292-587-7	90640-66-7	Acute Tox. 4 (H312) Skin Corr. 1B (H314)	-	-	-	01-2119487290-37-XXXX

# SAFETY DATA SHEET

**BOSTIK EPOXY EXTRA STRONG - Part B**  
**Supersedes Date:** 12-May-2023

**Revision date** 12-May-2023  
**Revision Number** 1

tetraethylenepentamine fraction 5 - <10 %			Skin Sens. 1 (H317) Acute Tox. 4 (H302) Eye Dam. 1 (H318) Aquatic Chronic 2 (H411)				
----------------------------------------------	--	--	---------------------------------------------------------------------------------------------	--	--	--	--

**Full text of H- and EUH-phrases: see section 16**

*NOTE [7] - No registration number is given for this substance because it is a polymer exempted from registration according to the provisions of Article 2(9) of REACH. All monomers or other substances within the polymer are registered or exempt from registration*

## Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine	614-339-2	68154-62-1	-	-	-	-	-
Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction	292-588-2	90640-67-8	-	-	-	-	-
Amines, polyethylenepoly-, tetraethylenepentamine fraction	292-587-7	90640-66-7	1716	1465	-	-	-

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.
<b>Inhalation</b>	Remove to fresh air. Get medical attention immediately if symptoms occur.
<b>Eye contact</b>	Get immediate medical attention. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water for at least 15 minutes. May cause



# SAFETY DATA SHEET

**BOSTIK EPOXY EXTRA STRONG - Part B**  
Supersedes Date: 12-May-2023

Revision date 12-May-2023  
Revision Number 1

---

	an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor.
<b>Ingestion</b>	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.
<b>Self-protection of the first aider</b>	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

## **4.2. Most important symptoms and effects, both acute and delayed**

**Symptoms** Burning sensation. Itching. Rashes. Hives.

## **4.3. Indication of any immediate medical attention and special treatment needed**

**Note to doctors** May cause sensitisation in susceptible persons. Treat symptomatically.

## **SECTION 5: Firefighting measures**

### **5.1. Extinguishing media**

**Suitable Extinguishing Media** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media** Full water jet.

### **5.2. Special hazards arising from the substance or mixture**

**Specific hazards arising from the chemical** Product is or contains a sensitiser. May cause sensitisation by skin contact.

### **5.3. Advice for firefighters**

**Special protective equipment and precautions for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

**Other information** Refer to protective measures listed in Sections 7 and 8.

**For emergency responders** Use personal protection recommended in Section 8.

### **6.2. Environmental precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

### **6.3. Methods and material for containment and cleaning up**

**Methods for containment** Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

**Methods for cleaning up** Take up mechanically, placing in appropriate containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

# SAFETY DATA SHEET

BOSTIK EPOXY EXTRA STRONG - Part B  
Supersedes Date: 12-May-2023

Revision date 12-May-2023  
Revision Number 1

## 6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Advice on safe handling** This product is part of a kit. Please also refer to the SDS for the other component(s) of the kit. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Take off contaminated clothing and wash it before reuse.

**General hygiene considerations** Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.

### 7.3. Specific end use(s)

**Specific use(s)**  
Adhesives. Hardener.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

**Exposure Limits** This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies

**Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.**

**Derived No Effect Level (DNEL)** No information available

Derived No Effect Level (DNEL)			
Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction (90640-67-8)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	0.952 mg/m <sup>3</sup>	
worker Long term Local health effects	Inhalation	0.952 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	0.272 mg/kg bw/d	

# SAFETY DATA SHEET

BOSTIK EPOXY EXTRA STRONG - Part B  
Supersedes Date: 12-May-2023

Revision date 12-May-2023  
Revision Number 1

Derived No Effect Level (DNEL)			
Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction (90640-67-8)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	0.169 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	97.2 µg/Kg bw/day	
Consumer Long term Systemic health effects	Oral	97.2 µg/Kg bw/day	

## Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction (90640-67-8)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.002 mg/l
Marine water	0 mg/l
Freshwater sediment	243 mg/kg dry weight
Marine sediment	24.3 mg/kg dry weight
Sewage treatment plant	4.21 mg/l

## 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment

- Eye/face protection** Wear safety glasses with side shields (or goggles). Wear chemical splash goggles and face shield when eye and face contact is possible due to splashing or spraying of material.
- Hand protection** Recommended Use: Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 240 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Unsuitable protective clothing. Leather. Disposable gloves. Gloves must conform to standard EN 374
- Skin and body protection** Suitable protective clothing.
- Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment. During spraying wear suitable respiratory equipment.
- Recommended filter type:** Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Organic gases and vapours filter conforming to EN 14387.

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Liquid
Colour	Colourless
Odour	Characteristic.
Odour threshold	No information available

# SAFETY DATA SHEET

BOSTIK EPOXY EXTRA STRONG - Part B  
Supersedes Date: 12-May-2023

Revision date 12-May-2023  
Revision Number 1

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	None known
Flammability	Not applicable for liquids	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	> 150 °C	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	No data available	None known.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	27500 mPa s	
Water solubility	Immiscible in water.	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	0.97 g/cm <sup>3</sup>	None known
Bulk Density	No data available	
Liquid Density	No data available	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

## 9.2. Other information

Solid content (%) No information available  
VOC content No data available

9.2.1. Information with regards to physical hazard classes  
Not applicable

9.2.2. Other safety characteristics  
No information available

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Reactivity No information available.

### 10.2. Chemical stability

Stability Stable under normal conditions.

#### Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

### 10.4. Conditions to avoid

# SAFETY DATA SHEET

BOSTIK EPOXY EXTRA STRONG - Part B  
Supersedes Date: 12-May-2023

Revision date 12-May-2023  
Revision Number 1

**Conditions to avoid** None known based on information supplied.

## 10.5. Incompatible materials

**Incompatible materials** None known based on information supplied.

## 10.6. Hazardous decomposition products

**Hazardous decomposition products** None under normal use conditions. Stable under recommended storage conditions.

## **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

##### Product Information

<b>Inhalation</b>	Specific test data for the substance or mixture is not available.
<b>Eye contact</b>	Specific test data for the substance or mixture is not available. Causes serious eye damage. May cause irreversible damage to eyes.
<b>Skin contact</b>	Specific test data for the substance or mixture is not available. May cause irritation. May cause sensitisation by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components).
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Redness. Burning. May cause blindness. Itching. Rashes. Hives.

#### Acute toxicity

#### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

<b>ATEmix (oral)</b>	8,580.00 mg/kg
<b>ATEmix (dermal)</b>	7,325.00 mg/kg
<b>ATEmix (inhalation-gas)</b>	>20000 ppm
<b>ATEmix (inhalation-dust/mist)</b>	>5 mg/l
<b>ATEmix (inhalation-vapour)</b>	>20 mg/l

#### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction	>2000 mg/Kg (Rattus) (OECD 423)	>2000 mg/Kg (Rattus) (OECD 402)	-
Amines, polyethylenepoly-, tetraethylenepentamine fraction	LD50 = 1716 mg/kg (Rattus) EPA FR Vol.50, No. 188, September 27, 1985	LD50 = 1465 mg/kg (Oryctolagus cuniculus) OECD 402	-

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

# SAFETY DATA SHEET

**BOSTIK EPOXY EXTRA STRONG - Part B**  
Supercedes Date: 12-May-2023

Revision date 12-May-2023  
Revision Number 1

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

**Serious eye damage/eye irritation** Causes serious eye damage.

**Respiratory or skin sensitisation** May cause an allergic skin reaction.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 11.2.2. Other information

**Other adverse effects** No information available.

**Note:** This product is part of a kit Please also refer to the SDS for the other component(s) of the kit PC-ADH-8 Multi-component adhesives and sealants

## **SECTION 12: Ecological information**

### 12.1. Toxicity

**Ecotoxicity** Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine 68154-62-1	-	LC50: =7.07mg/L (96h, Danio rerio)	-	-		
Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and	-	LC50 (96h) = 7.07 mg/L (Danio rerio)	-	-		1

# SAFETY DATA SHEET

**BOSTIK EPOXY EXTRA STRONG - Part B**  
Supersedes Date: 12-May-2023

Revision date 12-May-2023  
Revision Number 1

fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8						
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	EC50 (72h) = 6.8 mg/l (Pseudokirchneriella subcapitata) OECD 201	LC50 96Hr 0.42 g/l (Poecilia reticulata )	-	EC50 48 Hr 24.1 mg/l (Daphnia magna)		

## 12.2. Persistence and degradability

**Persistence and degradability** No information available.

## 12.3. Bioaccumulative potential

### Bioaccumulation

#### Component Information

Chemical name	Partition coefficient
Amines, polyethylenepoly-, tetraethylenepentamine fraction	-3.16

## 12.4. Mobility in soil

**Mobility in soil** No information available.

## 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction	The substance is not PBT / vPvB
Amines, polyethylenepoly-, tetraethylenepentamine fraction	The substance is not PBT / vPvB

## 12.6. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

## 12.7. Other adverse effects

No information available.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

**Waste from residues/unused products** Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Do not reuse empty containers.

**European Waste Catalogue** 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous substances

# SAFETY DATA SHEET

BOSTIK EPOXY EXTRA STRONG - Part B  
Supersedes Date: 12-May-2023

Revision date 12-May-2023  
Revision Number 1

**Other information** Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

### Land transport (ADR/RID)

14.1 UN number or ID number	UN3082
14.2 UN proper shipping name	Environmentally hazardous substances, liquid, n.o.s (Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction, Amines, polyethylenepoly-, tetraethylenepentamine fraction)
14.3 Transport hazard class(es)	9
Labels	9
14.4 Packing group	III
Description	UN3082, Environmentally hazardous substances, liquid, n.o.s (Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction, Amines, polyethylenepoly-, tetraethylenepentamine fraction), 9, III, (-)
14.5 Environmental hazards	Yes
14.6 Special precautions for user	
Special Provisions	274, 335, 601, 375
Classification code	M6
Tunnel restriction code	(-)
Limited quantity (LQ)	5 L
ADR Hazard Id (Kemmler Number)	90

### IMDG

14.1 UN number or ID number	UN3082
14.2 UN proper shipping name	Environmentally hazardous substances, liquid, n.o.s (Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction, Amines, polyethylenepoly-, tetraethylenepentamine fraction)
14.3 Transport hazard class(es)	9
14.4 Packing group	III
Description	UN3082, Environmentally hazardous substances, liquid, n.o.s (Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction, Amines, polyethylenepoly-, tetraethylenepentamine fraction), 9, III, Marine Pollutant
14.5 Marine pollutant	P
14.6 Special precautions for user	
Special Provisions	274, 335, 969
Limited Quantity (LQ)	5 L
EmS-No.	F-A, S-F
14.7 Maritime transport in bulk according to IMO instruments	
Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	UN3082
14.2 UN proper shipping name	Environmentally hazardous substances, liquid, n.o.s (Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction, Amines, polyethylenepoly-, tetraethylenepentamine fraction)
14.3 Transport hazard class(es)	9
14.4 Packing group	III
Description	UN3082, Environmentally hazardous substances, liquid, n.o.s (Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction, Amines, polyethylenepoly-, tetraethylenepentamine fraction), 9, III



# SAFETY DATA SHEET

**BOSTIK EPOXY EXTRA STRONG - Part B**  
Supersedes Date: 12-May-2023

Revision date 12-May-2023  
Revision Number 1

14.5 Environmental hazards Yes  
14.6 Special precautions for user  
Special Provisions A97, A158, A197  
Limited quantity (LQ) 30 kg G  
ERG Code 9L

## Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

#### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

##### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

##### **EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction**

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

##### **Substance subject to authorisation per REACH Annex XIV**

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

##### **Dangerous substance category per Seveso Directive (2012/18/EU)**

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

##### **Ozone-depleting substances (ODS) regulation (EC) 1005/2009**

Not applicable

##### **Persistent Organic Pollutants**

Not applicable

#### National regulations

##### France

##### Germany

##### **Ordinance on Industrial Safety and Health - Germany - BetrSichV**

No flammable liquids in accordance with BetrSichV

**Water hazard class (WGK)** obviously hazardous to water (WGK 2)

##### Netherlands

# SAFETY DATA SHEET

**BOSTIK EPOXY EXTRA STRONG - Part B**  
Supersedes Date: 12-May-2023

Revision date 12-May-2023  
Revision Number 1

## List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Not Listed

### Sweden

Special care should be applied for employees under the age of 18. Young people under the age of 18 may not carry out any work causing harmful exposure to this product. AFS 2012:3

### Denmark

Registration number(s) (P-no.) No information available

MAL-Code 00-5

### Norway

Registration number(s) (PRN-no.) 303032

## 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

## SECTION 16: Other information

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

H302 - Harmful if swallowed

H312 - Harmful in contact with skin

H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H411 - Toxic to aquatic life with long lasting effects

H412 - Harmful to aquatic life with long lasting effects

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

vPvB: Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE: Specific target organ toxicity - Repeated exposure

STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

#### Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	*	Skin designation

#### Classification procedure

Calculation method

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method

# SAFETY DATA SHEET

**BOSTIK EPOXY EXTRA STRONG - Part B**  
**Supersedes Date:** 12-May-2023

**Revision date** 12-May-2023  
**Revision Number** 1

Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	On basis of test data
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

## Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)  
European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA\_RAC)  
European Chemicals Agency (ECHA) (ECHA\_API)  
EPA (Environmental Protection Agency)  
Acute Exposure Guideline Level(s) (AEGl(s))  
International Uniform Chemical Information Database (IUCLID)  
National Institute of Technology and Evaluation (NITE)  
NIOSH (National Institute for Occupational Safety and Health)  
Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications  
Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme  
Organisation for Economic Co-operation and Development Screening Information Data Set

**Prepared By** Product Safety & Regulatory Affairs

**Revision date** 12-May-2023

**Training Advice** No information available

**Further information** No information available

## Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Regulation (EC) No. 1272/2008 and Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**