

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008
This SDS is for generic information purposes and does not reflect required country specific
information for OEL

FLEX'N'PAINT WHITE

Supercedes Date: 17-Feb-2022

Revision date 05-Jan-2023 Revision Number 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name FLEX'N'PAINT WHITE

Other means of identification

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik AB Strandbadsvaegen 22 PO Box 903 25109 Helsingborg, Sweden Tel: +46 42 19 50 00

Tel: +46 42 19 50 00 Fax: +46 42 19 50 20

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

Hazard statements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

EU Specific Hazard Statements

EUH208 - Contains Trimethoxyvinylsilane & N-(3-(trimethoxysilyl)propyl)ethylenediamine. May produce an allergic reaction EUH210 - Safety data sheet available on request

2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

Europe - BE Page 1/15

Revision date 05-Jan-2023

FLEX'N'PAINT WHITE

Supercedes Date: 17-Feb-2022 Revision Number 2

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No.	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-ter m)	REACH registration number
Trimethoxyvinylsilane 1 - <2.5 %	(014-049-00- 0) 220-449-8	2768-02-7	Skin Sens. 1B (H317) Acute Tox. 4 (H332) Flam. Liq. 3 (H226)	-	-	-	01-2119513215- 52-XXXX
Titanium dioxide 0.1- <1 %	(022-006-00- 2) 236-675-5	13463-67-7	[C]	-	-	-	01-2119489379- 17-XXXX
N-(3-(trimethoxysilyl)pro pyl)ethylenediamine 0.1- <1 %	217-164-6	1760-24-3	Eye Dam. 1 (H318) Skin Sens. 1 (H317) Acute Tox. 4 (H332) STOT SE 3 (H335)	-	-	-	01-2119970215- 39-XXXX

Air contaminants formed when using the substance or mixture as intended

Chemical name	EC No (EU	Weight-%	Classification	Specific	M-Factor	M-Factor	REACH
	Index No)		according to	concentration limit		(long-ter	registration
			Regulation (EC) No.	(SCL)		m)	number
			1272/2008 [CLP]				
Methyl alcohol	(603-001-00	1 - <2.5	Acute Tox. 3 (H301)	STOT SE 1 ::	-	-	01-211943330
67-56-1	-X)		Acute Tox. 3 (H311)	C>=10%			7-44-XXXX
	200-659-6		Acute Tox. 3 (H331)	STOT SE 2 ::			
			STOT SE 1 (H370)	3%<=C<10%			
			Flam. Liq. 2 (H225)				

Full text of H- and EUH-phrases: see section 16

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[C] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No	Oral LD50 mg/kg	Dermal LD50 mg/kg	LC50 - 4 hour -	Inhalation LC50 - 4 hour - vapour - mg/L	
Trimethoxyvinylsilane	(014-049-00-0) 220-449-8	2768-02-7	-	-	-	11	-
Titanium dioxide	(022-006-00-2) 236-675-5	13463-67-7	-	-	-	-	-

Europe - BE Page 2/15

FLEX'N'PAINT WHITE

Supercedes Date: 17-Feb-2022

Revision date 05-Jan-2023

Revision Number 2

Chemical name	EC No (EU	CAS No	Oral LD50	Dermal LD50	Inhalation	Inhalation	Inhalation
	Index No)		mg/kg	mg/kg	LC50 - 4 hour -	LC50 - 4 hour -	LC50 - 4 hour -
					dust/mist -	vapour - mg/L	gas - ppm
					mg/L		
N-(3-(trimethoxysilyl)pr opyl)ethylenediamine	217-164-6	1760-24-3	-	-	1.5	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Notes

See section 16 for more information

Chemical name	Notes
Titanium dioxide - 13463-67-7	V,W,10

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. If medical advice is needed,

have product container or label at hand.

Inhalation Remove to fresh air. If symptoms persist, call a doctor.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Skin contact In the case of skin irritation or allergic reactions see a doctor. Wash skin with soap and

water.

Ingestion Call a doctor immediately. Rinse mouth thoroughly with water. Never give anything by

mouth to an unconscious person. Small amounts of toxic methanol are released by

hydrolysis.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon

curing.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the Thermal decomposition can lead to release of irritating gases and vapours.

Europe - BE Page 3/15

FLEX'N'PAINT WHITE Revision date 05-Jan-2023 Supercedes Date: 17-Feb-2022 **Revision Number** 2

chemical

5.3. Advice for firefighters

Special protective equipment and Wear self contained breathing apparatus for fire fighting if necessary.

precautions for fire-fighters

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Ensure adequate ventilation. Do not get

in eyes, on skin, or on clothing.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section

12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Do not scatter spilled material with high pressure water streams. Absorb with earth, sand

or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Use personal protection equipment. Avoid contact with skin,

eyes or clothing.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink

or smoke when using this product. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Protect from moisture. Keep away from food, drink and animal feedingstuffs. **Storage Conditions**

Recommended storage

temperature

Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)

Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

Europe - BE Page 4 / 15

FLEX'N'PAINT WHITE Supercedes Date: 17-Feb-2022

Supercedes Date: 17-Feb-2022 Revision Number 2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

Revision date 05-Jan-2023

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union
Methyl alcohol	TWA: 200 ppm
67-56-1	TWA: 260 mg/m ³
	*

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)					
Trimethoxyvinylsilane (2768	Trimethoxyvinylsilane (2768-02-7)				
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
worker Systemic health effects Long term	Inhalation	27,6 mg/m³			
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d			

Titanium dioxide (13463-67-7)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker	Inhalation	10 mg/m³		
Long term				
Local health effects				

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)					
Туре	Exposure route	Derived No Effect Level	Safety factor		
		(DNEL)			
worker	Inhalation	35.5 mg/m³			
Systemic health effects					
Long term					
worker	Dermal	5 mg/kg bw/d			
Systemic health effects					
Long term					

Derived No Effect Level (DN	Derived No Effect Level (DNEL)				
Trimethoxyvinylsilane (2768	-02-7)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m³			
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d			
Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d			

Europe - BE Page 5/15

FLEX'N'PAINT WHITE

Supercedes Date: 17-Feb-2022

Revision date 05-Jan-2023 Revision Number 2

Titanium dioxide (13463-67-7)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer	Oral	700 mg/kg bw/d			
Long term					
Systemic health effects					

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)					
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer Systemic health effects Long term	Oral	2.5 mg/kg bw/d			
Consumer Systemic health effects Long term	Inhalation	8.7 mg/m ³			
Consumer Systemic health effects Long term	Dermal	2.5 mg/kg bw/d			

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)					
Trimethoxyvinylsilane (2768-02-7)					
Environmental compartment	Predicted No Effect Concentration (PNEC)				
Freshwater	0.34 mg/l				
Marine water	0.034 mg/l				
Microorganisms in sewage treatment	110 mg/l				

Titanium dioxide (13463-67-7)				
Environmental compartment	Predicted No Effect Concentration (PNEC)			
Marine water	0.0184 mg/l			
Freshwater sediment	1000 mg/kg			
Freshwater	0.184 mg/l			
Marine sediment	100 mg/kg			
Soil	100 mg/kg			
Microorganisms in sewage treatment	100 mg/l			
Freshwater - intermittent	0.193 mg/l			

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)				
Environmental compartment	Predicted No Effect Concentration (PNEC)			
Freshwater	0.062 mg/l			
Marine water	0.0062 mg/l			
Sewage treatment plant	25 mg/l			

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Hand protection Wear suitable gloves. Recommended Use:. Neoprene™. Nitrile rubber. Butyl rubber.

Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific

gloves. Gloves must conform to standard EN 374

Skin and body protection None under normal use conditions.

Respiratory protection In case of inadequate ventilation wear respiratory protection. Wear a respirator

Europe - BE Page 6/15

FLEX'N'PAINT WHITE

Supercedes Date: 17-Feb-2022

Revision date 05-Jan-2023

Revision Number 2

conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation,

especially in confined areas.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid
Appearance Paste
Colour White

Odour Characteristic.

Odour threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

Melting point / freezing pointNo data availableNone knownInitial boiling point and boilingNo data availableNone known

range

Flammability No data available None known Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Flash point > 100 °C

Autoignition temperatureNo data availableNone knownDecomposition temperatureNo data availableNone knownpHNo data availableNone known

pH No data available None known.pH (as aqueous solution) No data available None known

Kinematic viscosity > 21 mm²/s Dynamic viscosity No data available

Water solubility No data available. Product cures with

moisture

Solubility(ies)No data availableNone knownPartition coefficientNo data availableNone knownVapour pressureNo data availableNone knownRelative densityNo data availableNone known

Bulk Density
No data available
Liquid Density
1.45 g/cm³

Relative vapour density No data available None known

Particle characteristics

Particle Size No information available Particle Size Distribution No information available

9.2. Other information

Solid content (%) No information available

VOC content No data available

9.2.1. Information with regards to physical hazard classes Not applicable

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

Europe - BE Page 7/15

FLEX'N'PAINT WHITE

Supercedes Date: 17-Feb-2022

Revision date 05-Jan-2023

Revision Number 2

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical

None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture. Do not freeze. Keep away from open

flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released, when the product is exposed to moisture or water. Small amounts of methanol (CAS 67-56-1)

are formed by hydrolysis and released upon curing.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (inhalation-vapour) 657.0784 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50

Europe - BE Page 8/15

FLEX'N'PAINT WHITE

Supercedes Date: 17-Feb-2022

Revision date 05-Jan-2023

Revision Number 2

	-	_		
Trimethoxyvinylsilane LD50 = 7120 -7236 mg/kg		= 3540 mg/kg (Oryctolagus	LC50 (4hr) 16.8 mg/l (Rattus)	
	(Rattus) OECD 401	cuniculus)	OECD TG 403	
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus) 4 h	
N-(3-(trimethoxysilyl)propyl)eth ylenediamine	=2295 mg/kg (Rattus)	>2000 mg/Kg (Rattus)	LC50 4H (Aerosol)1.5 - 2.44 mg/L air	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit	Dermal			Non-irritant
Acute Dermal					
Irritation/Corrosion					

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye		24 hours	Non-irritant
Acute Eye					
Irritation/Corrosion					

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	Eye			Non-irritant
Acute Eye					
Irritation/Corrosion					

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	sensitising
Sensitisation, Buehler test			

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	Not a skin sensitiser
Sensitisation			
OECD Test No. 429: Skin	Mouse	Dermal	Not a skin sensitiser
Sensitisation: Local Lymph Node			
Assay			

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Component Information

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 471: Bacterial Reverse	in vitro	Not mutagenic
Mutation Test		

Europe - BE Page 9/15

FLEX'N'PAINT WHITE

Supercedes Date: 17-Feb-2022

Revision Number 2

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 422: Combined Repeated Dose	Rat	Not Classifiable
Toxicity Study with the		
Reproduction/Developmental Toxicity Screening		
Test		

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413:	Rat	Inhalation vapour		90 days	0.058 NOAEL
Sub-chronic Inhalation					
Toxicity: 90-day Study					

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Trimethoxyvinylsilane	EC 50 (72h) >	LC50 (96h) =	-	EC50(48hr)		(long-term)
2768-02-7	957 mg/l	191 mg/l		168.7mg/l		
	(Desmodesmus subspicatus)	(Oncorhynchus mykiss)		(Daphnia magna)		
	EU Method C.3	mykloo)		magna)		
Titanium dioxide	LC50 (96h)	-	-	-		
13463-67-7	>10000 mg/l					
	(Cyprinodon					
	variegatus)					
	OECD 203					

Europe - BE Page 10/15

FLEX'N'PAINT WHITE

Supercedes Date: 17-Feb-2022

Revision date 05-Jan-2023

Revision Number 2

N-(3-(trimethoxysilyl)pr	-	LC50 (96H)	-	EC50 (48h)	
opyl)ethylenediamine		=597 mg/L		=81mg/L	
1760-24-3		(Danio		Daphnia magna	
		rerio)Semi-static		Static	

12.2. Persistence and degradability

Persistence and degradability No information available.

Trimethoxyvinylsilane (2768-02-7)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready	28 days	BOD	51 % Not readily
Biodegradability: Manometric	·		biodegradable
Respirometry Test (TG 301 F)			-

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient	
Trimethoxyvinylsilane	1.1	
N-(3-(trimethoxysilyl)propyl)ethylenediamine	-0.3	

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

Chemical name	PBT and vPvB assessment		
Trimethoxyvinylsilane	The substance is not PBT / vPvB		
Titanium dioxide	The substance is not PBT / vPvB PBT assessment does		
	not apply		
N-(3-(trimethoxysilyl)propyl)ethylenediamine	The substance is not PBT / vPvB		

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products

Dispose of contents/container in accordance with local, regional, national, and

international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

Europe - BE Page 11/15

FLEX'N'PAINT WHITE

Supercedes Date: 17-Feb-2022 Revision Number 2

Revision date 05-Jan-2023

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable14.6 Special ProvisionsNone

....

14.1UN number or ID numberNot regulated14.2Proper Shipping NameNot regulated14.3Transport hazard class(es)Not regulated14.4Packing groupNot regulated14.5Marine pollutantNP14.6Special ProvisionsNone

14.7 Maritime transport in bulk Not applicable

according to IMO instruments

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable14.6 Special ProvisionsNone

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Europe - BE Page 12/15

FLEX'N'PAINT WHITE

Supercedes Date: 17-Feb-2022 Revision Number 2

Revision date 05-Jan-2023

_

Persistent Organic Pollutants

Not applicable

National regulations

France

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) slightly hazardous to water (WGK 1)

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Not Listed

Sweden

Occupational exposure limits AFS 2018:1

Denmark

Registration number(s) (P-no.) No information available

MAL-Code 0-1

AT-Guide C.0.1 August 2007: Limit values for substances and materials

Norway

Registration number(s) (PRN-no.) No information available

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H332 - Harmful if inhaled

H335 - May cause respiratory irritation

Notes relating to the identification, classification and labelling of substances

Note V: If the substance is to be placed on the market as fibres (with diameter < 3 μm, length > 5 μm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied

Note W: It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung

Notes relating to the classification and labelling of mixtures

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of

Europe - BE Page 13/15

Supercedes Date: 17-Feb-2022 Revision Number 2

Revision date 05-Jan-2023

titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm

SVHC: Substances of Very High Concern for Authorisation:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB: Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE: Specific target organ toxicity - Repeated exposure
STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

FLEX'N'PAINT WHITE

LOW: List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

AGW Occupational exposure limit value BGW Biological limit value Ceiling Maximum limit value * Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	On basis of test data
mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)

European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)

European Chemicals Agency (ECHA) (ECHA_API)

EPA (Environmental Protection Agency)

Acute Exposure Guideline Level(s) (AEGL(s))

International Uniform Chemical Information Database (IUCLID)

National Institute of Technology and Evaluation (NITE)

NIOSH (National Institute for Occupational Safety and Health)

Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme

Organisation for Economic Co-operation and Development Screening Information Data Set

Prepared By Product Safety & Regulatory Affairs

Revision date 05-Jan-2023

Training Advice No information available

Further information No information available

Europe - BE Page 14/15

FLEX'N'PAINT WHITE
Supercedes Date: 17-Feb-2022

Revision date 05-Jan-2023 Revision Number 2

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Europe - BE Page 15/15