

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008
This SDS is for generic information purposes and does not reflect required country specific information for OEL

BOSTIK FLEX RAPID PLUS Supercedes Date: 08-Feb-2021 Revision date 12-May-2023 Revision Number 2

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK FLEX RAPID PLUS

Other means of identification

Unique Formula Identifier (UFI) UFI:YKDG-37VH-AU2V-00Q7

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Cement Building and construction work

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

**Company Name** 

Bostik AB Strandbadsvaegen 22 PO Box 903 25109 Helsingborg, Sweden

Tel: +46 42 19 50 00 Fax: +46 42 19 50 20

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

**Emergency Telephone** 

# **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Serious eye damage/eye irritation Category 1 - (H318)

## 2.2. Label elements

Contains Cement Portland White



**Signal word** Danger

Europe - BE Page 1/12

BOSTIK FLEX RAPID PLUS
Supercedes Date: 08-Feb-2021
Revision Number 2

### **Hazard statements**

H318 - Causes serious eye damage

# Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P280 - Wear protective gloves and eye/face protection

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor

### 2.3. Other hazards

When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease. Product dust may be irritating to eyes, skin and respiratory system. Repeated exposure may cause skin dryness or cracking. Causes mild skin irritation.

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors.

# SECTION 3: Composition/information on ingredients

# 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No (EU	CAS No.	Classification	Specific	M-Factor	M-Factor	REACH
	Index No).		according to	concentration limit		(long-ter	registration
			Regulation (EC) No.	(SCL)		m)	number
			1272/2008 [CLP]				
Cement Portland White	266-043-4	65997-15-1	STOT SE 3 (H335)	-	-	-	[5]
5 - <10 %			Skin Irrit. 2 (H315)				
			Eye Dam. 1 (H318)				

Full text of H- and EUH-phrases: see section 16

NOTE [5] - This substance is exempted from registration according to the provisions of Article 2(7)(a) and Annex V of REACH

# Acute Toxicity Estimate No information available

Chemical name	EC No (EU Index No)	CAS No	Oral LD50 mg/kg	Dermal LD50 mg/kg	LC50 - 4 hour -	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Cement Portland White	266-043-4	65997-15-1	-	-	-	-	-

Europe - BE Page 2/12

BOSTIK FLEX RAPID PLUS
Supercedes Date: 08-Feb-2021
Revision date 12-May-2023
Revision Number 2

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

General advice If medical advice is needed, have product container or label at hand.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur.

Eye contact Do not rub affected area. Immediately flush with plenty of water. After initial flushing,

remove any contact lenses and continue flushing for at least 15 minutes. Consult an

ophthalmologist.

**Skin contact** Brush off loose particles from skin. Remove material from skin immediately. Take off

contaminated clothing and wash it before reuse.

**Ingestion** Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce

vomiting. Call a doctor.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section

8).

## 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** This powder (wet or dry) may cause irritation or potentially irreversible serious damage

upon contact with the eyes. Burning sensation. Causes serious eye damage. Inhalation of dust in high concentration may cause irritation of respiratory system. Irritating to skin. Prolonged contact may cause redness and irritation. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when

kneeling in wet cement even when wearing trousers.

# 4.3. Indication of any immediate medical attention and special treatment needed

# **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

surrounding environment.

Unsuitable extinguishing media Full water jet.

## 5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

No information available.

chemical

Hazardous combustion products Sulphur oxides.

5.3. Advice for firefighters

Europe - BE Page 3/12

**BOSTIK FLEX RAPID PLUS** Revision date 12-May-2023 Supercedes Date: 08-Feb-2021 **Revision Number** 2

precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

# **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid generation of dust. Do not get in eyes, on skin, or on clothing. Use personal

protective equipment as required.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

**Environmental precautions** Prevent product from entering drains. Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

**Methods for containment** Cover powder spill with plastic sheet or tarp to minimise spreading and keep powder dry.

Prevent dust cloud.

Methods for cleaning up Do not dry sweep dust. Wet dust with water before sweeping or use a vacuum to collect

dust. Use appropriate personal protective equipment (PPE). Carefully shovel or sweep

up spilled material and place in suitable container. Avoid generating dust.

Clean contaminated objects and areas thoroughly observing environmental regulations. Prevention of secondary hazards

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Ensure adequate ventilation. Avoid generation of dust. Avoid contact with skin, eyes or Advice on safe handling

clothing. Use personal protection equipment. Take off contaminated clothing and wash it

before reuse.

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. **Storage Conditions** 

Keep out of the reach of children. Keep the packing dry and well sealed to prevent

contamination and absorption of humidity. Protect from moisture.

### 7.3. Specific end use(s)

## Specific use(s)

Building and construction work. Cement.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

# SECTION 8: Exposure controls/personal protection

Europe - BE Page 4 / 12

BOSTIK FLEX RAPID PLUS

Supercedes Date: 08-Feb-2021

Revision date 12-May-2023

Revision Number 2

## 8.1. Control parameters

**Exposure Limits** 

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration (PNEC)

8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Hand protection For operations where prolonged or repeated skin contact may occur, impervious gloves

should be worn. Gloves made of plastic or rubber. Nitrile rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific

gloves.

**Skin and body protection** Avoid contact with skin, eyes or clothing. Wear appropriate personal protective clothing

to prevent skin contact.

**Respiratory protection**None under normal use conditions. Avoid generation of dust. Possible nuisance dust. In

case of insufficient ventilation, wear suitable respiratory equipment. No protective equipment is needed under normal use conditions. If exposure limits are exceeded or

irritation is experienced, ventilation and evacuation may be required.

**Recommended filter type:** Wear a respirator conforming to EN 140 with Type P2/P3 filter or better.

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

## **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Physical state Solid
Appearance Powder
Colour White

Odour No information available.
Odour threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

Melting point / freezing pointNot applicable. °CNone knownInitial boiling point and boilingNot applicable. °CNone known

range

Flammability No data available None known Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Flash point Not applicable . °C None known Autoignition temperature No data available None known

Decomposition temperature None known

pH No data available None known. pH (as aqueous solution) 11 - 11.5 None known

Europe - BE Page 5/12

BOSTIK FLEX RAPID PLUS

Supercedes Date: 08-Feb-2021

Revision date 12-May-2023

Revision Number 2

Kinematic viscosity Not applicable . None known

Dynamic viscosity

Water solubility Miscible in water. Cement based None known

products react and solidify in contact

with water

Solubility(ies)No data availableNone knownPartition coefficientNo data availableNone knownVapour pressureNo data availableNone knownRelative densityNo data availableNone known

Bulk Density 1.35

Liquid Density No data available

Relative vapour density No data available None known

Particle characteristics

Particle Size No information available Particle Size Distribution No information available

9.2. Other information

Solid content (%) 100 Softening Point Not relevant

VOC content No data available

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available Not applicable .

# SECTION 10: Stability and reactivity

10.1. Reactivity

**Reactivity** Product cures with moisture.

10.2. Chemical stability

**Stability** Keep away from Incompatible materials. Stable under recommended storage conditions.

**Explosion data** 

Sensitivity to mechanical

None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents. Acids. Aluminium.

10.6. Hazardous decomposition products

**Hazardous decomposition** None under normal use conditions. Stable under recommended storage conditions. **products** 

# **SECTION 11: Toxicological information**

Europe - BE Page 6/12

BOSTIK FLEX RAPID PLUS

Supercedes Date: 08-Feb-2021

Revision date 12-May-2023

Revision Number 2

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

# Information on likely routes of exposure

### **Product Information**

**Inhalation** Specific test data for the substance or mixture is not available.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

damage. May cause irreversible damage to eyes.

**Skin contact** Specific test data for the substance or mixture is not available. May cause irritation.

Causes mild skin irritation.

**Ingestion** Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhoea.

## Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. Burning. May cause blindness. Prolonged contact may cause redness and

irritation.

# Acute toxicity

### **Numerical measures of toxicity**

# The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 >5000 mg/kg

 ATEmix (dermal)
 >5000 mg/kg

 ATEmix (inhalation-gas)
 >20000 ppm

 ATEmix (inhalation-dust/mist)
 >5 mg/l

 ATEmix (inhalation-vapour)
 >20 mg/l

### **Component Information**

Chemical name	Chemical name Oral LD50		Inhalation LC50	
Cement Portland White	>2000 mg/Kg	>2000 mg/Kg	-	

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation**Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Causes serious eye damage.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

Europe - BE Page 7/12

BOSTIK FLEX RAPID PLUS
Supercedes Date: 08-Feb-2021
Revision date 12-May-2023
Revision Number 2

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure**Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

# **SECTION 12: Ecological information**

12.1. Toxicity

**Ecotoxicity** 

# 12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

**Bioaccumulation** There is no data for this product.

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the

threshold of declaration.

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

# **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

Europe - BE Page 8/12

BOSTIK FLEX RAPID PLUS

Revision date 12-May-2023

Supercedes Date: 08-Feb-2021 Revision Number 2

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

environmental legislation.

Contaminated packaging

Do not reuse empty containers.

**European Waste Catalogue** 

16 03 03\* inorganic wastes containing hazardous substances

15 01 10\*: Packaging containing residues of or contaminated by dangerous substances Cured product can be treated as construction waste. In the management of larger

quantities consult with local authorities and local waste disposal company 17 09 04 mixed construction and demolition wastes other than those mentioned in 17 09

01, 17 09 02 and 17 09 03

Other information

Waste codes should be assigned by the user based on the application for which the

product was used.

# **SECTION 14: Transport information**

## Land transport (ADR/RID)

14.1 UN number or ID number
14.2 UN proper shipping name
14.3 Transport hazard class(es)
14.4 Packing group
14.5 Environmental hazards
Not regulated
Not regulated
Not regulated
Not applicable

14.6 Special precautions for user

Special Provisions None

### **IMDG**

14.1 UN number or ID number
 14.2 UN proper shipping name
 14.3 Transport hazard class(es)
 14.4 Packing group
 Not regulated
 Not regulated
 Not regulated
 Not regulated

14.5 Marine pollutant NP

14.6 Special precautions for user

Special Provisions None

14.7 Maritime transport in bulk

according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number
 14.2 UN proper shipping name
 14.3 Transport hazard class(es)
 14.4 Packing group
 14.5 Environmental hazards
 Not regulated
 Not regulated
 Not regulated
 Not applicable

14.6 Special precautions for user

Special Provisions None

# Section 15: REGULATORY INFORMATION

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# **European Union**

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

# Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

# **SVHC: Substances of Very High Concern for Authorisation:**

Europe - BE Page 9/12

BOSTIK FLEX RAPID PLUS Supercedes Date: 08-Feb-2021 Revision date 12-May-2023 Revision Number 2

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

# EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

## Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

### Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

# **Persistent Organic Pollutants**

Not applicable

### National regulations

### France

# Occupational Illnesses (R-463-3, France)

Chemical name	French RG number		
Cement Portland White	RG 8,RG 10		
65997-15-1	RG 8		

## Germany

### Ordinance on Industrial Safety and Health - Germany - BetrSichV

No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) slightly hazardous to water (WGK 1)

# Netherlands

# List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

# <u>Sweden</u>

Occupational exposure limits AFS 2018:1

### **Denmark**

Registration number(s) (P-no.) No information available

MAL-Code 00-4

AT-Guide C.0.1 August 2007: Limit values for substances and materials

# **Norway**

Registration number(s) (PRN-no.) 643772

## 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No

Europe - BE Page 10/12

BOSTIK FLEX RAPID PLUS
Supercedes Date: 08-Feb-2021
Revision date 12-May-2023
Revision Number 2

Chemical Safety Assessment has been carried out for this mixture.

# **SECTION 16: Other information**

### Key or legend to abbreviations and acronyms used in the safety data sheet

### Full text of H-Statements referred to under section 3

H315 - Causes skin irritation

H318 - Causes serious eye damage H335 - May cause respiratory irritation

SVHC: Substances of Very High Concern for Authorisation:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB: Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE: Specific target organ toxicity - Repeated exposure
STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

LOW: List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

### Legend SECTION 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

AGW Occupational exposure limit value BGW Biological limit value Ceiling Maximum limit value \* Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

### Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)

European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA\_RAC)

European Chemicals Agency (ECHA) (ECHA\_API)

EPA (Environmental Protection Agency)

Acute Exposure Guideline Level(s) (AEGL(s))

International Uniform Chemical Information Database (IUCLID)

National Institute of Technology and Evaluation (NITE)

NIOSH (National Institute for Occupational Safety and Health)

Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications

Europe - BE Page 11/12

BOSTIK FLEX RAPID PLUS
Supercedes Date: 08-Feb-2021
Revision date 12-May-2023
Revision Number 2

Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme Organisation for Economic Co-operation and Development Screening Information Data Set

Prepared By Product Safety & Regulatory Affairs

Revision date 12-May-2023

Training Advice No information available

Further information No information available

## Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Regulation (EC) No. 1272/2008 and Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet** 

Europe - BE Page 12/12