

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

BOSTIK H565 GLASS'N'SEAL MULTI Supercedes Date: 12-Jan-2023

### Revision date 25-Jan-2024 Revision Number 2

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier BOSTIK H565 GLASS'N'SEAL MULTI **Product Name** This substance/ mixture contains nanoforms Form Other means of identification Mixture Pure substance/mixture 1.2. Relevant identified uses of the substance or mixture and uses advised against **Recommended use** Adhesives and/or sealants Not to be used in articles intended for direct or prolonged skin contact. Not to be used in Uses advised against production of toys or childcare articles. Fabrics, textiles and apparel: bedding and clothing. Gloves. Footwear (shoes, boots). Paper products: tissue, towels, disposable dinnerware, nappies, feminine hygiene products, adult incontinence products, writing paper. Reason why uses advised against Restricted substance per REACH Annex XVII 1.3. Details of the supplier of the safety data sheet **Company Name** 

Bostik AB Strandbadsvaegen 22 PO Box 903 25109 Helsingborg, Sweden Tel: +46 42 19 50 00 Fax: +46 42 19 50 20

E-mail address

SDS.box-EU@bostik.com

# 1.4. Emergency telephone number

**Emergency Telephone** 

# **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

# 2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

### Hazard statements

BOSTIK H565 GLASS'N'SEAL MULTI

Supercedes Date: 12-Jan-2023

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

### **EU Specific Hazard Statements**

EUH208 - Contains Trimethoxyvinylsilane. May produce an allergic reaction EUH212 - Warning! Hazardous respirable dust may be formed when used. Do not breathe dust EUH210 - Safety data sheet available on request

### 2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

### PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors.

# **SECTION 3: Composition/information on ingredients**

### 3.1 Substances

Not applicable

# 3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-ter m)	REACH registration number
Titanium dioxide 1 - <5 %	236-675-5 (022-006-00- 2)	13463-67-7	[C]	-	-	-	01-2119489379- 17-XXXX
Trimethoxyvinylsilane 0.1- <1 %	220-449-8 (014-049-00- 0)	2768-02-7	Skin Sens. 1B (H317) Acute Tox. 4 (H332) Flam. Liq. 3 (H226)	-	-	-	01-2119513215- 52-XXXX
Bis(2,2,6,6-tetramethyl-4 -piperidyl) sebacate 0.1 - <0.5 %	258-207-9	52829-07-9	Eye Dam. 1 (H318) Repr. 2 (H361f) Aquatic Acute 1 (H400) Aquatic Chronic 2 (H411)	-	-	-	01-2119537297- 32-XXXX
Dioctyltin oxide 0.1 - <0.5 %	212-791-1	870-08-6	STOT SE 2 (H371)	-	-	-	01-2119971268- 27-xxxx

# Air contaminants formed when using the substance or mixture as intended

Chemical name	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Methyl alcohol 67-56-1	200-659-6 (603-001-00-X)	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C>=10% STOT SE 2 :: 3%<=C<10%	-	-	01-2119433307- 44-XXXX

#### BOSTIK H565 GLASS'N'SEAL MULTI Supercedes Date: 12-Jan-2023

# Full text of H- and EUH-phrases: see section 16

<u>Classification according to Regulation (EC) No. 1272/2008 [CLP]</u> - Notes [C] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring

### Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg		Inhalation LC50 - 4 hour - vapour - mg/L	
Titanium dioxide	236-675-5 (022-006-00-2)	13463-67-7	-	-	-	-	-
Trimethoxyvinylsilane	220-449-8 (014-049-00-0)	2768-02-7	-	-	-	11	-
Bis(2,2,6,6-tetramethyl- 4-piperidyl) sebacate	258-207-9	52829-07-9	-	-	-	-	-
Dioctyltin oxide	212-791-1	870-08-6	-	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### Notes

See section 16 for more information

Chemical name	Notes	
Titanium dioxide - 13463-67-7	V,W,10	

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.		
Inhalation	Remove to fresh air. If symptoms persist, call a doctor.		
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.		
Ingestion	Small amounts of toxic methanol are released by hydrolysis. Call a doctor immediately. Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water.		
4.2. Most important symptoms and	d effects, both acute and delayed		
Symptoms	None known.		
Effects of Exposure	No information available.		

### 4.3. Indication of any immediate medical attention and special treatment needed

Note to doctorsSmall amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released, when<br/>the product is exposed to moisture or water. Small amounts of methanol (CAS 67-56-1)<br/>are formed by hydrolysis and released upon curing. Treat symptomatically.

# SECTION 5: Firefighting measures

5.1.	Exting	guishing	media

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

#### 5.2. Special hazards arising from the substance or mixture

**Specific hazards arising from the** Thermal decomposition can lead to release of irritating gases and vapours. **chemical** 

Hazardous combustion products Carbon oxides. Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx).

### 5.3. Advice for firefighters

**Special protective equipment and** Wear self contained breathing apparatus for fire fighting if necessary. **precautions for fire-fighters** 

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Use personal protective equipment as required. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing.			
For emergency responders	Use personal protection recommended in Section 8.			
6.2. Environmental precautions				
Environmental precautions	Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.			
6.3. Methods and material for cont	ainment and cleaning up			
Methods for containment	Do not scatter spilled material with high pressure water streams. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.			
Methods for cleaning up	Take up mechanically, placing in appropriate containers for disposal.			
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.			
6.4. Reference to other sections				
Reference to other sections	See section 8 for more information. See section 13 for more information.			
SECTION 7: Handling and storage				

### 7.1. Precautions for safe handling

Advice on safe handling

Ensure adequate ventilation. Avoid contact with skin, eyes or clothing. Use personal protection equipment.

BOSTIK H565 GLASS'N'SEAL MULTI Supercedes Date: 12-Jan-2023

General hygiene considerations	Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.						
7.2. Conditions for safe storage, inc	7.2. Conditions for safe storage, including any incompatibilities						
Storage Conditions	Keep containers tightly closed in a cool, well-ventilated place. Protect from moisture. Keep away from food, drink and animal feedingstuffs.						
Recommended storage temperature	Keep at temperatures between 10 and 35 °C.						
7.3. Specific end use(s)							
<b>Specific use(s)</b> Adhesives and/or sealants.							
Risk Management Methods (RMM)	The information required is contained in this Safety Data Sheet.						
Other information	Observe technical data sheet.						
SECTION 8: Exposure controls/personal protection							

# 8.1. Control parameters

**Exposure Limits** 

This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

# Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union
Methyl alcohol	TWA: 200 ppm
67-56-1	TWA: 260 mg/m <sup>3</sup>
	*

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)						
Titanium dioxide (13463-67-7)						
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor			
worker Long term Local health effects	Inhalation	10 mg/m³				

Trimethoxyvinylsilane (2768-02-7)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
worker Systemic health effects Long term	Inhalation	27,6 mg/m³			
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d			

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)						
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor			
worker Short term	Inhalation	2.82 mg/m³				

# BOSTIK H565 GLASS'N'SEAL MULTI

Supercedes Date: 12-Jan-2023

Long term Systemic health effects			
worker	Dermal	1.6 mg/kg	
Long term			
Systemic health effects			

Dioctyltin oxide (870-08-6)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Long term Systemic health effects	Dermal	0.05 mg/kg bw/d		
worker Long term Systemic health effects	Inhalation	0.004 mg/m³		

Derived No Effect Level (DNEL)				
Titanium dioxide (13463-67-7)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
Consumer	Oral	700 mg/kg bw/d		
Long term Systemic health effects				

Trimethoxyvinylsilane (2768-02-7)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m³	
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d	
Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d	

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
Consumer Long term Systemic health effects	Dermal	0.8 mg/kg		
Consumer Long term Systemic health effects	Oral	0.4 mg/kg		

Dioctyltin oxide (870-08-6)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	0.0005 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	0.025 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	0.0009 mg/m³	

BOSTIK H565 GLASS'N'SEAL MULTI Supercedes Date: 12-Jan-2023

# Predicted No Effect Concentration (PNEC)

Microorganisms in sewage treatment

Predicted No Effect Concentration (PNEC)	
Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l
Trimethoxyvinylsilane (2768-02-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.018 mg/l
Marine water	0.0018 mg/l
Freshwater sediment	29 mg/kg
Marine sediment	2.9 mg/kg
Soil	5.9 mg/kg

110 mg/l

Dioctyltin oxide (870-08-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater sediment	0.02798 mg/kg dry weight
Marine sediment	0.002798 mg/kg dry weight
Microorganisms in sewage treatment	100 mg/l

### 8.2. Exposure controls

Engineering controls	Ensure adequate ventilation, especially in confined areas.
Personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.
Hand protection	Wear suitable gloves. Recommended Use:. Neoprene <sup>™</sup> . Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
Skin and body protection	None under normal use conditions.
Respiratory protection	In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas.
Recommended filter type:	Organic gases and vapours filter conforming to EN 14387. White. Brown.
Environmental exposure controls	Do not allow uncontrolled discharge of product into the environment

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Paste
Colour	White

BOSTIK H565 GLASS'N'SEAL MULTI Supercedes Date: 12-Jan-2023 Revision date 25-Jan-2024 Revision Number 2

Odour	Characteristic.	
Property	Values	Remarks • Method
Melting point / freezing point	No data available	None known
Initial boiling point and boiling	No data available	None known
range		
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive	No data available	
limits		
Lower flammability or explosive	No data available	
limits	_	
Flash point	> 60 °C	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	No data available	None known.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	> 21 mm²/s	None known
Dynamic viscosity	No data available Product cures with moisture	None known
Water solubility Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk Density	No data available	
Density	1.33 g/cm <sup>3</sup>	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	
9.2. Other information		
Solid content (%)	No information available	
VOC content	No data	available
0.2.1 Information with regards to	physical bazard classes	
9.2.1. Information with regards to Not applicable	physical hazard classes	
9.2.2. Other safety characteristics		
No information available		
CECTION 40. Stability and		
SECTION 10: Stability and r	eactivity	
10.1. Reactivity		
Reactivity	Product cures with moisture.	
10.2. Chemical stability		
Stability	Stable under normal conditions.	
Explosion data		
Sensitivity to mechanical	None	

Sensitivity to mechanical<br/>impactNone.Sensitivity to static dischargeNone.

# 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid					
Conditions to avoid	Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.				
10.5. Incompatible materials					
Incompatible materials	None known based on information supplied.				
10.6. Hazardous decomposition p	roducts				
Hazardous decomposition products	Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.				
SECTION 11: Toxicological information					
11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008					
Information on likely routes of exposure					
Product Information					

Inhalation	Based on available data, the classification criteria are not met.		
Eye contact	Based on available data, the classification criteria are not met.		
Skin contact	May cause sensitisation in susceptible persons. Based on available data, the classification criteria are not met.		
Ingestion	Based on available data, the classification criteria are not met.		
Symptoms related to the physical, chemical and toxicological characteristics			

Symptoms	No information available.
Cymptomo	

Acute toxicity

Numerical measures of toxicity

### The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	>5000 mg/kg
ATEmix (dermal)	>5000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapour)	>20 mg/l

### **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus)4 h
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg (Rattus) OECD 401	= 3540 mg/kg (Oryctolagus cuniculus)	LC50 (4hr) 16.8 mg/l (Rattus) OECD TG 403
Bis(2,2,6,6-tetramethyl-4-piperi dyl) sebacate	LD50 (Rattus)> 2000 mg/kg OECD 423	LD50 (Rattus) > 3 170 mg/kg OECD 402	=500 mg/m <sup>3</sup> (Rattus) 4 h
Dioctyltin oxide	=2500 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus) OECD 402	-

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

# BOSTIK H565 GLASS'N'SEAL MULTI

Supercedes Date: 12-Jan-2023

### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit	Dermal			Non-irritant
Acute Dermal					
Irritation/Corrosion					

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit	Dermal			Non-irritant
Acute Dermal					
Irritation/Corrosion					

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

### Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	Eye			Non-irritant
Acute Eye					
Irritation/Corrosion					

# Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye			Eye Damage
Acute Eye					
Irritation/Corrosion					

# Respiratory or skin sensitisation

OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. No classification is proposed, based on conclusive negative data. May cause sensitisation in susceptible persons.

Product Information					
Method	Species	Exposure route	Results		
OECD Test No. 406: Skin	Guinea pig	Dermal	No sensitisation responses		
Sensitisation			were observed		

### Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	Not a skin sensitiser
Sensitisation			
OECD Test No. 429: Skin	Mouse	Dermal	Not a skin sensitiser
Sensitisation: Local Lymph Node			
Assay			

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig		No sensitisation responses
Sensitisation			were observed

### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Component Information

Trimetheve	a din doile n	- (0760 00 7)
Threenox	vvinvisiiani	e (2768-02-7)

Method	Species	Results
OECD Test No. 471: Bacterial Reverse	in vitro	Not mutagenic
Mutation Test		_

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

### Carcinogenicity

Based on available data, the classification criteria are not met.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	European Union
Titanium dioxide	Carc. 2

**Reproductive toxicity** 

Based on available data, the classification criteria are not met.

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Species	Results
OECD Test No. 414: Pre-natal Development	Rat, Rabbit	reproductive toxicant
Toxicity Study		

STOT - single exposure

Based on available data, the classification criteria are not met.

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9) Dioctyltin oxide (870-08-6)

			-	-	-
Method	Species	Exposure route	Effective dose	Exposure time	Results
		Oral	5 mg/kg		0.3 - 0.5 mg/kg
Combined Repeated Dose					bw/d May cause
Toxicity Study with the					damage to the
Reproduction/Developme					following organs:
ntal Toxicity Screening					Immune system
Test					

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413:	Rat	Inhalation vapour		90 days	0.058 NOAEL
Sub-chronic Inhalation					
Toxicity: 90-day Study					

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Dioctyltin oxide (870-08-6)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rat Rabbit				0.3 -0.5 mg/kg bw/d

#### Aspiration hazard

Based on available data, the classification criteria are not met.

# 11.2. Information on other hazards

# 11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

# **SECTION 12: Ecological information**

# 12.1. Toxicity

Ecotoxicity

Harmful to aquatic life.

		<b>_</b>	<b>—</b> • • •			
Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		microorganisms			(long-term)
Titanium dioxide	LC50 (96h)	-	-	-		
13463-67-7	>10000 mg/l					
	(Cyprinodon					
	variegatus)					
	OECD 203					
Trimethoxyvinylsilane	EC 50 (72h) >	LC50 (96h) =	-	EC50(48hr)		
2768-02-7	957 mg/l	191 mg/l		168.7mg/l		
	(Desmodesmus	(Oncorhynchus		(Daphnia		
	subspicatus)	mykiss)		magna)		
	EU Method C.3					
Bis(2,2,6,6-tetramethyl-	EC50 72Hr	LC50 (96h) =	-	LC50 48Hr 8.58		
4-piperidyl) sebacate	0.705 mg/l	5.29 mg/l		mg/l (Daphnia		
52829-07-9	(Pseudokirchner	(Oryzias latipes)		magna)		
	ella subcapitata)					
Dioctyltin oxide	EC50 (3hr)	LC50 (96hr)	-	EC50 (48Hr)		
870-08-6	>1.000 mg/l	>0,09 mg/l		>0,21 mg/l		
	(bacteria)	(Brachydanio		(Daphnia magna		
	(Activated	rerio (zebra))		(Dappnia		
	Sludge,	(Acute Toxicity		magna))		
	Respiration	Test)		(Daphnia sp.		
	Inhibition Test)			Acute		
				Immobilisation		
				Test)		

### 12.2. Persistence and degradability

Persistence and degradability No information available.

Trimethoxyvinylsilane (2768-02-7)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready	28 days	BOD	51 % Not readily
Biodegradability: Manometric			biodegradable
Respirometry Test (TG 301 F)			-

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Exposure time	Value	Results
OECD Test No. 303: Simulation Test	28 days	Total organic carbon (TOC)	24 % Moderate
- Aerobic Sewage Treatment A:			
Activated Sludge Units; B: Biofilms			

Dioctyltin oxide (870-08-6)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready	755 hours	biodegradation	Not readily biodegradable 2
Biodegradability: Manometric		-	%
Respirometry Test (TG 301 F)			

# 12.3. Bioaccumulative potential

# **Bioaccumulation**

### **Component Information**

Chemical name	Partition coefficient
Trimethoxyvinylsilane	1.1

### **BOSTIK H565 GLASS'N'SEAL MULTI**

Supercedes Date: 12-Jan-2023

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	0.35
Dioctyltin oxide	6

# 12.4. Mobility in soil

Mobility in soilNo information available.12.5. Results of PBT and vPvB assessment

# PBT and vPvB assessment

The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Titanium dioxide	The substance is not PBT / vPvB
Trimethoxyvinylsilane	The substance is not PBT / vPvB
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	The substance is not PBT / vPvB
Dioctyltin oxide	The substance is not PBT / vPvB

# 12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

### 12.7. Other adverse effects

No information available.

# SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste from residues/unused products	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
Contaminated packaging	Handle contaminated packages in the same way as the product itself.
European Waste Catalogue	08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

# **SECTION 14: Transport information**

### Land transport (ADR/RID)

14.1	UN number or ID number	Not regulated
14.2	UN proper shipping name	Not regulated
14.3	Transport hazard class(es)	Not regulated
14.4	Packing group	Not regulated
14.5	Environmental hazards	Not applicable
14.6	Special precautions for user	
S	pecial Provisions	None
IMDO	<u>)</u>	
14.1	UN number or ID number	Not regulated
14.2	UN proper shipping name	Not regulated
14.3	Transport hazard class(es)	Not regulated
14.4	Packing group	Not regulated
14.5	Marine pollutant	NP
14.6	Special precautions for user	
S	pecial Provisions	None
	-	

BOSTIK H565 GLASS'N'SEAL MULTI Supercedes Date: 12-Jan-2023

### 14.7 Maritime transport in bulk according to IMO instruments Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1	UN number or ID number	Not regulated
14.2	UN proper shipping name	Not regulated
14.3	Transport hazard class(es)	Not regulated
14.4	Packing group	Not regulated
14.5	Environmental hazards	Not applicable
14.6	Special precautions for user	
S	pecial Provisions	None

# Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

#### Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

#### SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
Dioctyltin oxide	870-08-6	20.

20 (6) DOT

### Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

### **Export Notification requirements**

This product contains substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals

Chemical name	European Export/Import Restrictions per (EC) 649/2012 - Annex Number
Dioctyltin oxide - 870-08-6	l.1

Ozone-depleting substances (ODS) regulation (EC) 1005/2009 Not applicable

#### Persistent Organic Pollutants Not applicable

BOSTIK H565 GLASS'N'SEAL MULTI Supercedes Date: 12-Jan-2023

### National regulations

France

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV No flammable liquids in accordance with BetrSichV

Water hazard class (WGK)	obviously hazardous to water (WGK 2)

TRGS - 510 Storage Class Storage Class 11 : Combustible solids

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands) Not Listed

<u>Sweden</u> Occupational exposure limits AFS 2018:1

DenmarkRegistration number(s)(P-no.)62699612MAL-Code1-1AT-Guide C.0.1 August 2007: Limit values for substances and materials

Norway Registration number(s) (PRN-no.) 655363

# 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

# SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

### Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour

- H317 May cause an allergic skin reaction
- H318 Causes serious eye damage
- H332 Harmful if inhaled H361f - Suspected of damaging fertility
- H400 Very toxic to aquatic life
- H411 Toxic to aquatic life with long lasting effects

# Notes relating to the identification, classification and labelling of substances

**Note V:** If the substance is to be placed on the market as fibres (with diameter <  $3 \mu m$ , length >  $5 \mu m$  and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied

**Note W:** It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung

### Notes relating to the classification and labelling of mixtures

BOSTIK H565 GLASS'N'SEAL MULTI

Supercedes Date: 12-Jan-2023

**Note 10:** The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq$  10 µm

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances

vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT RE: Specific target organ toxicity - Repeated exposure

STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

LOW: List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

### Legend SECTION 8: Exposure controls/personal protection

TWĂ	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	Sk*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	On basis of test data
mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

### Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA) European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA\_RAC) European Chemicals Agency (ECHA) (ECHA\_API) EPA (Environmental Protection Agency) Acute Exposure Guideline Level(s) (AEGL(s)) International Uniform Chemical Information Database (IUCLID) National Institute of Technology and Evaluation (NITE) NIOSH (National Institute for Occupational Safety and Health) Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme Organisation for Economic Co-operation and Development Screening Information Data Set Prepared By Product Safety & Regulatory Affairs

Revision date	25-Jan-2024

Training Advice No information available

BOSTIK H565 GLASS'N'SEAL MULTI Supercedes Date: 12-Jan-2023 Revision date 25-Jan-2024 Revision Number 2

**Further information** 

No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Regulation (EC) No. 1272/2008 and Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**