

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008
This SDS is for generic information purposes and does not reflect required country specific information for OEL

BOSTIK H785 HIGH TACK WHITE Supercedes Date: 20-Jul-2021

Revision date 11-Jan-2023 Revision Number 3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK H785 HIGH TACK WHITE

Other means of identification

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives and/or sealants

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik AB Strandbadsvaegen 22 PO Box 903 25109 Helsingborg, Sweden Tel: +46 42 19 50 00

Tel: +46 42 19 50 00 Fax: +46 42 19 50 20

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

Hazard statements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

EU Specific Hazard Statements

EUH208 - Contains Trimethoxyvinylsilane & N-(3-(trimethoxysilyl)propyl)ethylenediamine & N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine. May produce an allergic reaction EUH210 - Safety data sheet available on request

2.3. Other hazards

Europe - BE Page 1/16

BOSTIK H785 HIGH TACK WHITE Supercedes Date: 20-Jul-2021 Revision date 11-Jan-2023 Revision Number 3

_

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No.	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-ter m)	REACH registration number
Trimethoxyvinylsilane 1 - <2.5 %	(014-049-00- 0) 220-449-8	2768-02-7	Skin Sens. 1B (H317) Acute Tox. 4 (H332) Flam. Liq. 3 (H226)	-	-	-	01-2119513215- 52-XXXX
N-(3-(trimethoxysilyl)pro pyl)ethylenediamine 0.1- <1 %	217-164-6	1760-24-3	Eye Dam. 1 (H318) Skin Sens. 1 (H317) Acute Tox. 4 (H332) STOT SE 3 (H335)	-	-	-	01-2119970215- 39-XXXX
Dioctyltin oxide 0.1 - <0.5 %	212-791-1	870-08-6	STOT SE 2 (H371)	-	-	-	01-2119971268- 27-xxxx
N-[3-(Dimethoxymethylsil yl)propyl]-ethylenediamin e 0.1 - <0.5 %		3069-29-2	Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1A (H317)	-	-	-	01-2119963926- 21-xxxx

Air contaminants formed when using the substance or mixture as intended

Chemical name	EC No (EU	Weight-%	Classification	Specific	M-Factor	M-Factor	REACH
	Index No)		according to	concentration limit		(long-ter	registration
			Regulation (EC) No.	(SCL)		m)	number
			1272/2008 [CLP]				
Methyl alcohol	(603-001-00	1 - <2.5	Acute Tox. 3 (H301)	STOT SE 1 ::	-	-	01-211943330
67-56-1	-X)		Acute Tox. 3 (H311)	C>=10%			7-44-XXXX
	200-659-6		Acute Tox. 3 (H331)	STOT SE 2 ::			
			STOT SE 1 (H370)	3%<=C<10%			
			Flam. Liq. 2 (H225)				

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Europe - BE Page 2/16

BOSTIK H785 HIGH TACK WHITE
Supercedes Date: 20-Jul-2021
Revision Number 3

Chemical name	EC No (EU Index No)	CAS No	Oral LD50 mg/kg	Dermal LD50 mg/kg		Inhalation LC50 - 4 hour - vapour - mg/L	
Trimethoxyvinylsilane	(014-049-00-0) 220-449-8	2768-02-7	-	-	- -	11	-
N-(3-(trimethoxysilyl)pr opyl)ethylenediamine	217-164-6	1760-24-3	-	-	1.5	-	-
Dioctyltin oxide	212-791-1	870-08-6	-	-	-	-	-
N-[3-(Dimethoxymethyl silyl)propyl]-ethylenedia mine		3069-29-2	500	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice If medical advice is needed, have product container or label at hand.

Inhalation Remove to fresh air. If symptoms persist, call a doctor.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Consult an

ophthalmologist.

Skin contact Wash off immediately with soap and plenty of water. In the case of skin irritation or

allergic reactions see a doctor.

Ingestion Do NOT induce vomiting. Rinse mouth thoroughly with water. Never give anything by

mouth to an unconscious person. Call a doctor or poison control centre immediately.

Small amounts of toxic methanol are released by hydrolysis.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon

curing.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the Thermal decomposition can lead to release of irritating gases and vapours.

chemical

Europe - BE Page 3/16

Supercedes Date: 20-Jul-2021 **Revision Number** 3

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx).

5.3. Advice for firefighters

BOSTIK H785 HIGH TACK WHITE

Special protective equipment and Wear self contained breathing apparatus for fire fighting if necessary.

Revision date 11-Jan-2023

precautions for fire-fighters

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation. Use personal protective equipment as required. Do not get

in eyes, on skin, or on clothing.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section

12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Use a non-combustible material like vermiculite, sand or earth to soak up the product and

place into a container for later disposal.

Take up mechanically, placing in appropriate containers for disposal. Methods for cleaning up

Clean contaminated objects and areas thoroughly observing environmental regulations. Prevention of secondary hazards

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Use personal protection equipment. Avoid contact with skin,

eyes or clothing.

Do not eat, drink or smoke when using this product. Wash hands before breaks and after General hygiene considerations

work. Take off contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep containers tightly closed in a dry, cool and well-ventilated

place. Keep away from food, drink and animal feedingstuffs.

Recommended storage

temperature

Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)

Adhesives and/or sealants.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

Europe - BE Page 4 / 16

BOSTIK H785 HIGH TACK WHITE Supercedes Date: 20-Jul-2021 Revision date 11-Jan-2023 Revision Number 3

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon

curing

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union
Methyl alcohol	TWA: 200 ppm
67-56-1	TWA: 260 mg/m ³
	*

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)				
Trimethoxyvinylsilane (2768-	02-7)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Systemic health effects Long term	Inhalation	27,6 mg/m³		
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d		

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Systemic health effects Long term	Inhalation	35.5 mg/m³		
worker Systemic health effects Long term	Dermal	5 mg/kg bw/d		

Dioctyltin oxide (870-08-6)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Long term Systemic health effects	Dermal	0.05 mg/kg bw/d		
worker Long term Systemic health effects	Inhalation	0.004 mg/m³		

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)				
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Long term Systemic health effects	Inhalation	12 mg/m³		
worker Long term Systemic health effects	Dermal	1.7 mg/kg bw/d		

Derived No Effect Level (DNEL)

Europe - BE Page 5/16

BOSTIK H785 HIGH TACK WHITE Supercedes Date: 20-Jul-2021 Revision date 11-Jan-2023 Revision Number 3

Trimethoxyvinylsilane (2768	Trimethoxyvinylsilane (2768-02-7)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor			
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m³				
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d				
Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d				

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer Systemic health effects Long term	Oral	2.5 mg/kg bw/d			
Consumer Systemic health effects Long term	Inhalation	8.7 mg/m ³			
Consumer Systemic health effects Long term	Dermal	2.5 mg/kg bw/d			

Dioctyltin oxide (870-08-6)				
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
Consumer Long term Systemic health effects	Oral	0.0005 mg/kg bw/d		
Consumer Long term Systemic health effects	Dermal	0.025 mg/kg bw/d		
Consumer Long term Systemic health effects	Inhalation	0.0009 mg/m³		

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer Long term Systemic health effects	Inhalation	2.9 mg/m³			
Consumer Long term Systemic health effects	Dermal	0.83 mg/kg bw/d			
Consumer Long term Systemic health effects	Oral	0.83 mg/kg bw/d			

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Trimethoxyvinylsilane (2768-02-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l

Europe - BE Page 6 / 16

BOSTIK H785 HIGH TACK WHITE Supercedes Date: 20-Jul-2021

Revision date 11-Jan-2023 Revision Number 3

	
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.062 mg/l
Marine water	0.0062 mg/l
Sewage treatment plant	25 mg/l

Dioctyltin oxide (870-08-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater sediment	0.02798 mg/kg dry weight
Marine sediment	0.002798 mg/kg dry weight
Microorganisms in sewage treatment	100 mg/l

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)				
Environmental compartment	Predicted No Effect Concentration (PNEC)			
Freshwater	0.062 mg/l			
Marine water	0.006 mg/l			
Sewage treatment plant	25 mg/l			
Freshwater sediment	0.24 mg/kg dry weight			
Marine sediment	0.024 mg/kg dry weight			
Soil	0.01 mg/kg dry weight			

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Hand protection Wear suitable gloves. Recommended Use:. Neoprene™. Nitrile rubber. Butyl rubber.

Glove thickness > 0.7mm. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time for the mentioned glove material is in general greater than

480 min. Gloves must conform to standard EN 374

Skin and body protection

Respiratory protection In case of inadequate ventilation wear respiratory protection. Wear a respirator

conforming to EN 140 with Type A/P2 filter or better.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

Wear suitable protective clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid
Appearance Paste
Colour White

Odour Characteristic.

Odour threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

Melting point / freezing point
Initial boiling point and boiling
No data available
No data available

range

Flammability Not applicable for liquids .

Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Europe - BE Page 7/16

Revision date 11-Jan-2023

Supercedes Date: 20-Jul-2021 **Revision Number** 3

> 60 °C

CC (closed cup) Flash point **Autoignition temperature** No data available

Decomposition temperature None known

Not applicable. Reacts with water. No data available pH (as aqueous solution)

> 21 mm²/s @ 40°C Kinematic viscosity **Dynamic viscosity** No data available

Water solubility Product cures with moisture

Solubility(ies) No data available **Partition coefficient** No data available Vapour pressure No data available Relative density No data available No data available **Bulk Density Liquid Density** 1.54 g/cm³ No data available Relative vapour density

Particle characteristics

BOSTIK H785 HIGH TACK WHITE

No information available **Particle Size Particle Size Distribution** No information available

9.2. Other information

Solid content (%) No information available

No data available **VOC** content

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Product cures with moisture. Reactivity

10.2. Chemical stability

Stable under normal conditions. Stability

Explosion data

None Sensitivity to mechanical

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture.

10.5. Incompatible materials

None known based on information supplied. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon

products

Europe - BE Page 8/16

BOSTIK H785 HIGH TACK WHITE Supercedes Date: 20-Jul-2021

Revision date 11-Jan-2023 Revision Number 3

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (inhalation-vapour) 696.60 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg	= 3540 mg/kg (Oryctolagus	LC50 (4hr) 16.8 mg/l (Rattus)
	(Rattus) OECD 401	cuniculus)	OECD TG 403
N-(3-(trimethoxysilyl)propyl)eth	=2295 mg/kg (Rattus)	>2000 mg/Kg (Rattus)	LC50 4H (Aerosol)1.5 - 2.44
ylenediamine			mg/L air
Dioctyltin oxide	=2500 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus)	-
		OECD 402	
N-[3-(Dimethoxymethylsilyl)pro	=200 - 2000 mg/Kg (Rattus)	>5000 mg/Kg (Oryctolagus	> 5.2 mg/L (Rattus) 4 h
pyl]-ethylenediamine	(OECD 401)	cuniculus)	(OECD 403)
		(OECD 402)	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Third and A Trace of T						
Method	Species	Exposure route	Effective dose	Exposure time	Results	
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant	

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit	Dermal			irritant
Acute Dermal					
Irritation/Corrosion					

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Europe - BE Page 9/16

BOSTIK H785 HIGH TACK WHITE Supercedes Date: 20-Jul-2021

Revision date 11-Jan-2023 **Revision Number** 3

Trimothovyvinyleilana ((2768-02-7)	

Trimethoxyvinylsilane (276	8-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye		24 hours	Non-irritant
Acute Eye					
Irritation/Corrosion					

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit				Eye Damage
Acute Eye					
Irritation/Corrosion					

Respiratory or skin sensitisation

May produce an allergic reaction. OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. No classification is proposed, based on conclusive negative data.

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	sensitising
Sensitisation, Buehler test			

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig		Sensitizing
Sensitisation			_

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Component Information

Trimethoxyvinylsilane (2768-02-7)

Trimetroxy virty londing (27 de d2 1)					
Method	Species	Results			
OECD Test No. 471: Bacterial Reverse	in vitro	Not mutagenic			
Mutation Test					

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 422: Combined Repeated Dose	Rat	Not Classifiable
Toxicity Study with the		
Reproduction/Developmental Toxicity Screening		
Test		

STOT - single exposure

Based on available data, the classification criteria are not met.

Dioctvltin oxide (870-08-6)

Method Species Exposure route Effective dose Exposure time Results
--

Europe - BE Page 10/16

BOSTIK H785 HIGH TACK WHITE Supercedes Date: 20-Jul-2021 Revision date 11-Jan-2023 Revision Number 3

OECD Test No. 422:	Rat	Oral	5 mg/kg	28 days	0.3 - 0.5 mg/kg
Combined Repeated Dose				-	bw/d May cause
Toxicity Study with the					damage to the
Reproduction/Developme					following organs:
ntal Toxicity Screening					Immune system
Test					-

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413:	Rat	Inhalation vapour		90 days	0.058 NOAEL
Sub-chronic Inhalation					
Toxicity: 90-day Study					

Dioctyltin oxide (870-08-6)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rat Rabbit			28 days	0.3 -0.5 mg/kg bw/d

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Trimethoxyvinylsilane	EC 50 (72h) >	LC50 (96h) =	-	EC50(48hr)		
2768-02-7	957 mg/l	191 mg/l		168.7mg/l		
	(Desmodesmus	(Oncorhynchus		(Daphnia		
	subspicatus)	mykiss)		magna)		
	EU Method C.3					
N-(3-(trimethoxysilyl)pr	-	LC50 (96H)	-	EC50 (48h)		
opyl)ethylenediamine		=597 mg/L		=81mg/L		
1760-24-3		(Danio		Daphnia magna		
		rerio)Semi-static		Static		
Dioctyltin oxide	EC50 (3hr)	LC50 (96hr)	-	EC50 (48Hr)		
870-08-6	>1.000 mg/l	>0,09 mg/l		>0,21 mg/l		
	(bacteria)	(Brachydanio		(Daphnia magna		
	(Activated	rerio (zebra))		(Dappnia		
	Sludge,	(Acute Toxicity		magna))		
	Respiration	Test)		(Daphnia sp.		
	Inhibition Test)			Acute		
				Immobilisation		
				Test)		

12.2. Persistence and degradability

Europe - BE Page 11/16

Revision date 11-Jan-2023

Revision Number 3

BOSTIK H785 HIGH TACK WHITE Supercedes Date: 20-Jul-2021

•

Persistence and degradability

No information available.

Trimethoxyvinylsilane (2768-02-7)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready	28 days	BOD	51 % Not readily
Biodegradability: Manometric			biodegradable
Respirometry Test (TG 301 F)			-

Dioctyltin oxide (870-08-6)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready	755 hours	biodegradation	Not readily biodegradable 2
Biodegradability: Manometric		-	%
Respirometry Test (TG 301 F)			

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

00			
Chemical name		Partition coefficient	
	Trimethoxyvinylsilane	1.1	
	N-(3-(trimethoxysilyl)propyl)ethylenediamine	-0.3	
	Dioctyltin oxide	6	

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment	
Trimethoxyvinylsilane	The substance is not PBT / vPvB	
N-(3-(trimethoxysilyl)propyl)ethylenediamine	The substance is not PBT / vPvB	
Dioctyltin oxide	The substance is not PBT / vPvB	
N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine	The substance is not PBT / vPvB	

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products

Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Other information Waste codes should be assigned by the user based on the application for which the

Europe - BE Page 12/16

BOSTIK H785 HIGH TACK WHITE Supercedes Date: 20-Jul-2021

Revision date 11-Jan-2023 Revision Number 3

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable

14.6 Special Provisions None

IMDG

14.1UN number or ID numberNot regulated14.2Proper Shipping NameNot regulated14.3Transport hazard class(es)Not regulated14.4Packing groupNot regulated14.5Marine pollutantNP

14.6 Special Provisions None

14.7 Maritime transport in bulk Not applicable

according to IMO instruments

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable

14.6 Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Dioctyltin oxide	870-08-6	20.

Europe - BE Page 13/16

Revision date 11-Jan-2023

Revision Number 3

BOSTIK H785 HIGH TACK WHITE Supercedes Date: 20-Jul-2021

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product contains substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals

Chemical name	European Export/Import Restrictions per (EC) 689/2008 - Annex Number
Dioctyltin oxide - 870-08-6	l.1

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

France

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) slightly hazardous to water (WGK 1)

TRGS - 510 Storage Class Storage Class 11 : Combustible solids

<u>Netherlands</u>

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Not Listed

<u>Sweden</u>

Occupational exposure limits AFS 2018:1

Denmark

Registration number(s) (P-no.) XXXXX MAL-Code 1-1

AT-Guide C.0.1 August 2007: Limit values for substances and materials

Norway

Registration number(s) (PRN-no.) xxxxxx

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Europe - BE Page 14/16

BOSTIK H785 HIGH TACK WHITE Supercedes Date: 20-Jul-2021

Revision date 11-Jan-2023 Revision Number 3

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour

H302 - Harmful if swallowed

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H332 - Harmful if inhaled

H335 - May cause respiratory irritation

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

vPvB: Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE: Specific target organ toxicity - Repeated exposure

STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

LOW: List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

AGW Occupational exposure limit value BGW Biological limit value Ceiling Maximum limit value * Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	On basis of test data
mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)

European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)

European Chemicals Agency (ECHA) (ECHA_API)

EPA (Environmental Protection Agency)

Acute Exposure Guideline Level(s) (AEGL(s))

International Uniform Chemical Information Database (IUCLID)

National Institute of Technology and Evaluation (NITE)

NIOSH (National Institute for Occupational Safety and Health)

Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications

Europe - BE Page 15/16

Revision date 11-Jan-2023

Supercedes Date: 20-Jul-2021 Revision Number 3

Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme Organisation for Economic Co-operation and Development Screening Information Data Set

Prepared By Product Safety & Regulatory Affairs

Revision date 11-Jan-2023

BOSTIK H785 HIGH TACK WHITE

Revision note SDS sections updated

Training Advice No information available

Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Europe - BE Page 16/16