

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008
This SDS is for generic information purposes and does not reflect required country specific
information for OEL

BOSTIK MAXI BOND

Supercedes Date: 05-Jan-2022

Revision date 05-Dec-2022 Revision Number 4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK MAXI BOND

Other means of identification

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik SA 420 rue d'Estienne d'Orves 92700 Colombes FRANCE

Tel: +33 (0)1 49 00 90 00

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

Hazard statements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

EU Specific Hazard Statements

EUH208 - Contains Trimethoxyvinylsilane & Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine. May produce an allergic reaction

EUH210 - Safety data sheet available on request

2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

Europe - BE Page 1/19

BOSTIK MAXI BOND Revision date 05-Dec-2022 Supercedes Date: 05-Jan-2022 Revision Number 4

Combustible liquid.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No.	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-ter m)	REACH registration number
Trimethoxyvinylsilane 0.1 - <1%	(014-049-00- 0) 220-449-8	2768-02-7	Skin Sens. 1B (H317) Acute Tox. 4 (H332) Flam. Liq. 3 (H226)	-	-	-	01-2119513215- 52-XXXX
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine 1 - <2.5 %	309-629-8	100545-48-0	Skin Sens. 1B (H317)	Skin Sens. 1 :: C>=25%	-	1	01-2119979085- 27-XXXX
Titanium dioxide 0.1- <1 %	(022-006-00- 2) 236-675-5	13463-67-7	[C]	-	-	1	01-2119489379- 17-XXXX
Bis(2,2,6,6-tetramethyl-4 -piperidyl) sebacate 0.1- <1 %	258-207-9	52829-07-9	Eye Dam. 1 (H318) Repr. 2 (H361f) Aquatic Acute 1 (H400) Aquatic Chronic 2 (H411)		-	1	01-2119537297- 32-XXXX
Dioctyltin oxide 0.1 - <0.5 %	212-791-1	870-08-6	STOT SE 2 (H371)	-	-	-	01-2119971268- 27-xxxx
Ethyl silicate 0.1 - <0.3 %	(014-005-00- 0) 201-083-8	78-10-4	Acute Tox. 4 (H332) Eye Irrit. 2 (H319) STOT SE 3 (H335) Flam. Liq. 3 (H226)	-	-	-	01-2119496195- 28-xxxx

Air contaminants formed when using the substance or mixture as intended

Chemical name	EC No (EU Index No)	Weight-%	Classification according to Regulation (EC) No.	Specific concentration limit (SCL)	M-Factor	M-Factor (long-ter m)	_
			1272/2008 [CLP]				
Methyl alcohol	(603-001-00	1 - <2.5	Acute Tox. 3 (H301)	STOT SE 1 ::	-	-	01-211943330
67-56-1	-X)		Acute Tox. 3 (H311)	C>=10%			7-44-XXXX
	200-659-6		Acute Tox. 3 (H331)	STOT SE 2 ::			
			STOT SE 1 (H370)	3%<=C<10%			
			Flam. Liq. 2 (H225)				

Full text of H- and EUH-phrases: see section 16

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[C] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its

Europe - BE Page 2/19

BOSTIK MAXI BOND
Supercedes Date: 05-Jan-2022
Revision Number 4

components

Chemical name	EC No (EU Index No)	CAS No	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Trimethoxyvinylsilane	(014-049-00-0) 220-449-8	2768-02-7	-	-	-	11	-
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	309-629-8	100545-48-0	-	-	-	-	-
Titanium dioxide	(022-006-00-2) 236-675-5	13463-67-7	-	-	-	-	-
Bis(2,2,6,6-tetramethyl- 4-piperidyl) sebacate	258-207-9	52829-07-9	-	-	-	-	-
Dioctyltin oxide	212-791-1	870-08-6	-	-	-	-	-
Ethyl silicate	(014-005-00-0) 201-083-8	78-10-4	-	-	4.9	11	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Notes

See section 16 for more information

Chemical name	Notes
Titanium dioxide - 13463-67-7	V,W,10

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. If medical advice is needed,

have product container or label at hand.

Inhalation Remove to fresh air. If symptoms persist, call a doctor.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Skin contact In the case of skin irritation or allergic reactions see a doctor. Wash skin with soap and

water.

Ingestion Call a doctor immediately. Rinse mouth thoroughly with water. Never give anything by

mouth to an unconscious person. Small amounts of toxic methanol are released by

hydrolysis.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the

material(s) involved, take precautions to protect themselves and prevent spread of

contamination. Wear personal protective clothing (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Europe - BE Page 3/19

BOSTIK MAXI BOND
Supercedes Date: 05-Jan-2022
Revision Number 4

Note to doctors Treat symptomatically. Small amounts of methanol (CAS 67-56-1) are formed by

hydrolysis and released upon curing.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

Thermal decomposition can lead to release of irritating gases and vapours.

chemical

Hazardous combustion products Carbon oxides. Carbon monoxide. Carbon dioxide (CO2). Silicon dioxide.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters

Special protective equipment and Wear self contained breathing apparatus for fire fighting if necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

Use personal protective equipment as required. Ensure adequate ventilation. Do not get

in eyes, on skin, or on clothing.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section

12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Do not scatter spilled material with high pressure water streams. Stop leak if you can do

it without risk. Do not touch or walk through spilled material. Dyke far ahead of liquid spill

for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after

Europe - BE Page 4/19

BOSTIK MAXI BOND

Supercedes Date: 05-Jan-2022 Revision Number 4

work.

Storage Conditions Protect from moisture. Keep away from food, drink and animal feedingstuffs.

Recommended storage

temperature

Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)

Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

7.2. Conditions for safe storage, including any incompatibilities

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon

curing This product contains titanium dioxide in a non-respirable form. Inhalation of

Revision date 05-Dec-2022

titanium dioxide is unlikely to occur from exposure to this product

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union
Methyl alcohol	TWA: 200 ppm
67-56-1	TWA: 260 mg/m ³
	*
Ethyl silicate	TWA: 44 mg/m ³
78-10-4	TWA: 5 ppm

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)					
Trimethoxyvinylsilane (2768-02-7)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
worker Systemic health effects Long term	Inhalation	27,6 mg/m³			
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d			

Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine (100545-48-0)					
Туре	Exposure route	Derived No Effect Level	Safety factor		
		(DNEL)			
worker	Inhalation	3.35 mg/m ³			
Long term		_			
Local health effects					

Titanium dioxide (13463-67-7)					
Туре			Safety factor		
		(DNEL)			
worker	Inhalation	10 mg/m ³			
Long term					

Europe - BE Page 5/19

BOSTIK MAXI BOND Supercedes Date: 05-Jan-2022

Revision date 05-Dec-2022

Revision Number 4

Local health effects

Bis(2,2,6,6-tetramethyl-4-pip	eridyl) sebacate (52829-07-	-9)	
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Short term Long term Systemic health effects	Inhalation	2.82 mg/m³	
worker Long term Systemic health effects	Dermal	1.6 mg/kg	

Dioctyltin oxide (870-08-6)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Long term Systemic health effects	Dermal	0.05 mg/kg bw/d		
worker Long term Systemic health effects	Inhalation	0.004 mg/m³		

Ethyl silicate (78-10-4)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Short term Systemic health effects	Dermal	12.1 mg/kg bw/d	
worker Systemic health effects Long term	Dermal	12.1 mg/kg bw/d	
worker Short term Systemic health effects	Inhalation	85 mg/m³	
worker Short term Local health effects	Inhalation	85 mg/m³	
worker Long term Systemic health effects	Inhalation	85 mg/m³	
worker Long term Local health effects	Inhalation	85 mg/m³	

Derived No Effect Level (DN	Derived No Effect Level (DNEL)					
Trimethoxyvinylsilane (2768	Trimethoxyvinylsilane (2768-02-7)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor			
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m³				
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d				
Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d				

Europe - BE Page 6 / 19

BOSTIK MAXI BOND

Supercedes Date: 05-Jan-2022

Revision date 05-Dec-2022 Revision Number 4

·			
Octadecanoic acid, 12-hydr	oxy-, reaction products with	ethylenediamine (100545-48-0)	
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term	Inhalation	0.83 mg/m³	
Titanium dioxide (13463-67-			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	
Ris/2 2 6 6-tetramethyl-4-nir	peridyl) sebacate (52829-07	-9)	
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	0.8 mg/kg	
Consumer Long term Systemic health effects	Oral	0.4 mg/kg	
Dioctyltin oxide (870-08-6)	<u>'</u>	<u>'</u>	
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	0.0005 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	0.025 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	0.0009 mg/m³	
		<u>'</u>	
Ethyl silicate (78-10-4)	Evnours revits	Dariyod No Effect Lavel	Cofoty foots:
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Short term Systemic health effects	Dermal	8.4 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	8.4 mg/kg bw/d	
Consumer Short term	Inhalation	25 mg/m³	
Systemic health effects Consumer Short term Local health effects	Inhalation	25 mg/m³	
Consumer Long term Systemic health effects	Inhalation	25 mg/m³	
Consumer Long term Local health effects	Inhalation	25 mg/m³	

Predicted No Effect Concentration

Europe - BE Page 7/19

BOSTIK MAXI BOND

Supercedes Date: 05-Jan-2022 Revision Number 4

Revision date 05-Dec-2022

_

(PNEC)

Predicted No Effect Concentration (PNEC)				
Trimethoxyvinylsilane (2768-02-7)				
Environmental compartment	Predicted No Effect Concentration (PNEC)			
Freshwater	0.34 mg/l			
Marine water	0.034 mg/l			
Microorganisms in sewage treatment	110 mg/l			

Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.018 mg/l
Marine water	0.0018 mg/l
Freshwater sediment	29 mg/kg
Marine sediment	2.9 mg/kg
Soil	5.9 mg/kg

Dioctyltin oxide (870-08-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater sediment	0.02798 mg/kg dry weight
Marine sediment	0.002798 mg/kg dry weight
Microorganisms in sewage treatment	100 mg/l

Ethyl silicate (78-10-4)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.192 mg/l
Marine water	0.0192 mg/l
Freshwater sediment	0.18 mg/kg dry weight
Marine sediment	0.018 mg/kg dry weight
Soil	0.05 mg/kg

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Hand protection Wear suitable gloves. Recommended Use:. Neoprene™. Nitrile rubber. Butyl rubber.

Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific

gloves. Gloves must conform to standard EN 374

Skin and body protection Respiratory protection

None under normal use conditions.

In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation,

especially in confined areas.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

Europe - BE Page 8/19

BOSTIK MAXI BOND
Supercedes Date: 05-Jan-2022
Revision Number 4

9.1. Information on basic physical and chemical properties

Physical state Liquid
Appearance Paste
Colour Off-white

Odour Slight. Characteristic.
Odour threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

Melting point / freezing pointNo data availableNot applicableInitial boiling point and boilingNo data availableNot applicable

range

Flammability Not applicable for liquids .

Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Flash point > 61 °C Not applicable
Autoignition temperature No data available None known

Decomposition temperature
pH No data available Not applicable.

pH (as aqueous solution)No data available
None known
No data available
None known

Dynamic viscosity 7500 - 10500 Pa.s Spindle 4 @ 1 rpm @ 23 °C

Water solubility Slightly soluble.

Solubility(ies)No data availableNone knownPartition coefficientNo data availableNone knownVapour pressure< 1100</th>hPa @ 50 °CRelative densityNo data availableNone known

Bulk Density

Density

No data available
ca. 1.5 g/cm³

Relative vapour density No data available None known

Particle characteristics

Particle Size No information available Particle Size Distribution No information available

9.2. Other information

Solid content (%) No information available

VOC content No data available

9.2.1. Information with regards to physical hazard classes Not applicable

9.2.2. Other safety characteristics No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical

impact

None.

Europe - BE Page 9/19

BOSTIK MAXI BOND
Supercedes Date: 05-Jan-2022
Revision Number 4

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture. Exposure to air or moisture over

prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and

sources of ignition.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon

products curing.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met. May cause sensitisation in

susceptible persons.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (inhalation-dust/mist) 428.329 mg/l ATEmix (inhalation-vapour) 1,112.90 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50	
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg	= 3540 mg/kg (Oryctolagus	LC50 (4hr) 16.8 mg/l (Rattus)	
	(Rattus) OECD 401	cuniculus)	OECD TG 403	
Octadecanoic acid,	LD50 >2000 mg/kg (Rattus)	-	LC50 > 5.05 mg/kg (Rattus)	
12-hydroxy-, reaction products				
with ethylenediamine				
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus) 4 h	

Europe - BE Page 10/19

Revision date 05-Dec-2022

Revision Number 4

BOSTIK MAXI BOND

Supercedes Date: 05-Jan-2022

	-	<u> </u>	
Bis(2,2,6,6-tetramethyl-4-piperi	LD50 (Rattus)> 2000 mg/kg	LD50 (Rattus) > 3 170 mg/kg	=500 mg/m ³ (Rattus) 4 h
dyl) sebacate	OECD 423	OECD 402	, ,
Dioctyltin oxide	=2500 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus)	-
		OECD 402	
Ethyl silicate	LD50 > 2500 mg/kg (Rattus)	= 5878 mg/kg (Oryctolagus	= 10 mg/L (Rat male) 4 h
-	OECD 423	cuniculus) = 6300 μL/kg	> 16.8 mg/L (Rat female) 4 h
		(Oryctolagus cuniculus)	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant

Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine (100545-48-0)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 431: In	EPISKIN™	in vitro	0.02 g	4 hours	Non-irritant
Vitro Skin Corrosion:					
Human Skin Model Test					

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit	Dermal			Non-irritant
Acute Dermal					
Irritation/Corrosion					

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit	Dermal			Non-irritant
Acute Dermal					
Irritation/Corrosion					

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Thirtouroxy virry toliano (=1	00 02 . /				
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye		24 hours	Non-irritant
Acute Eye					
Irritation/Corrosion					

Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine (100545-48-0)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye	0.1 mL	72 hours	Non-irritant
Acute Eye					
Irritation/Corrosion					

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	Eye			Non-irritant
Acute Eye					
Irritation/Corrosion					

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

<u> </u>	iponaji, oobacato	(0=0=0 0. 0)			
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye			Eye Damage
Acute Eye					

Europe - BE Page 11/19

Supercedes Date: 05-Jan-2022 Revision Number 4

Respiratory or skin sensitisation

BOSTIK MAXI BOND

OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. No classification is proposed, based on conclusive negative data. May cause sensitisation in susceptible persons.

Revision date 05-Dec-2022

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	No sensitisation responses
Sensitisation			were observed

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	sensitising
Sensitisation, Buehler test			-

Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine (100545-48-0)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	Sensitizing > 25 %
Sensitisation			

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	Not a skin sensitiser
Sensitisation	_		
OECD Test No. 429: Skin	Mouse	Dermal	Not a skin sensitiser
Sensitisation: Local Lymph Node			
Assay			

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig		No sensitisation responses
Sensitisation			were observed

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Component Information

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 471: Bacterial Reverse	in vitro	Not mutagenic
Mutation Test		_

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Thirteenexy thry tenante (27 cc c2 7)		
Method	Species	Results
OECD Test No. 422: Combined Repeated Dos	e Rat	Not Classifiable
Toxicity Study with the		
Reproduction/Developmental Toxicity Screenin	g	
Test		

Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine (100545-48-0)

Method Species	Results
----------------	---------

Europe - BE Page 12/19

BOSTIK MAXI BOND

Supercedes Date: 05-Jan-2022

Revision date 05-Dec-2022 Revision Number 4

OECD Test No. 421:

Reproduction/Developmental Toxicity Screening
Test

Not Classifiable

Not Classifiable

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Species	Results
OECD Test No. 414: Pre-natal Development	Rat, Rabbit	reproductive toxicant
Toxicity Study		

STOT - single exposure

Based on available data, the classification criteria are not met.

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Dioctyltin oxide (870-08-6)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 422:	Rat	Oral	5 mg/kg	28 days	0.3 - 0.5 mg/kg
Combined Repeated Dose					bw/d May cause
Toxicity Study with the					damage to the
Reproduction/Developme					following organs:
ntal Toxicity Screening					Immune system
Test					

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413:	Rat	Inhalation vapour		90 days	0.058 NOAEL
Sub-chronic Inhalation					
Toxicity: 90-day Study					

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Dioctyltin oxide (870-08-6)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rat Rabbit			28 days	0.3 -0.5 mg/kg bw/d

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Trimethoxyvinylsilane	EC 50 (72h) >	LC50 (96h) =	-	EC50(48hr)		
2768-02-7	957 mg/l	191 mg/l		168.7mg/l		
	(Desmodesmus	(Oncorhynchus		(Daphnia		
	subspicatus)	mykiss)		magna)		

Europe - BE Page 13/19

BOSTIK MAXI BOND

Revision date 05-Dec-2022

Supercedes Date: 05-Jan-2022

Revision Number 4

	EU Method C.3				
Octadecanoic acid,	EL50 (72h) >100	LL50 (96h)	-	EL50 (48h)	
12-hydroxy-, reaction	mg/L Algae	>10mg/L		>10mg/L	
products with	(Pseudokirchner	(Onchohynchus		Daphnia	
ethylenediamine	iella subcapitata)	mykiss)		(Daphnia	
100545-48-0				magna)	
Titanium dioxide	LC50 (96h)	-	-	-	
13463-67-7	>10000 mg/l				
	(Cyprinodon				
	variegatus)				
	OECD 203				
Bis(2,2,6,6-tetramethyl-		LC50 (96h) =	-	LC50 48Hr 8.58	
4-piperidyl) sebacate	0.705 mg/l	5.29 mg/l		mg/l (Daphnia	
52829-07-9	(Pseudokirchner	(Oryzias latipes)		magna)	
	ella subcapitata)				
Dioctyltin oxide	EC50 (3hr)	LC50 (96hr)	-	EC50 (48Hr)	
870-08-6	>1.000 mg/l	>0,09 mg/l		>0,21 mg/l	
	(bacteria)	(Brachydanio		(Daphnia magna	
	(Activated	rerio (zebra))		(Dappnia	
	Sludge,	(Acute Toxicity		magna))	
	Respiration	Test)		(Daphnia sp.	
	Inhibition Test)			Acute	
				Immobilisation	
				Test)	
Ethyl silicate	EC 50 (72h) >	LC50 (96h)> 245	-	-	
78-10-4	100 mg/L	mg/L (Danio			
	(Pseudokirchner				
	iella subcapitata)	Method C.1			
	OECD 201				

12.2. Persistence and degradability

Persistence and degradability No information available.

Trimethoxyvinylsilane (2768-02-7)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready	28 days	BOD	51 % Not readily
Biodegradability: Manometric			biodegradable
Respirometry Test (TG 301 F)			

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Exposure time	Value	Results
OECD Test No. 303: Simulation Test	28 days	Total organic carbon (TOC)	24 % Moderate
- Aerobic Sewage Treatment A:			
Activated Sludge Units; B: Biofilms			

Dioctyltin oxide (870-08-6)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready	755 hours	biodegradation	Not readily biodegradable 2
Biodegradability: Manometric			%
Respirometry Test (TG 301 F)			

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Trimethoxyvinylsilane	1.1
Octadecanoic acid, 12-hydroxy-, reaction products with	5.86
ethylenediamine	

Europe - BE Page 14/19

BOSTIK MAXI BOND
Supercedes Date: 05-Jan-2022
Revision Number 4

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	0.35
Dioctyltin oxide	6
Ethyl silicate	3.18

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

Chemical name	PBT and vPvB assessment
Trimethoxyvinylsilane	The substance is not PBT / vPvB
Octadecanoic acid, 12-hydroxy-, reaction products with	The substance is not PBT / vPvB
ethylenediamine	
Titanium dioxide	The substance is not PBT / vPvB PBT assessment does
	not apply
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	The substance is not PBT / vPvB
Dioctyltin oxide	The substance is not PBT / vPvB
Ethyl silicate	The substance is not PBT / vPvB PBT assessment does
	not apply

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of contents/container in accordance with local, regional, national, and

international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable14.6 Special ProvisionsNone

IMDG

14.1 UN number or ID number
14.2 Proper Shipping Name
Not regulated
Not regulated

Europe - BE Page 15/19

BOSTIK MAXI BOND
Supercedes Date: 05-Jan-2022
Revision Number 4

14.3 Transport hazard class(es) Not regulated **14.4 Packing group** Not regulated

14.5 Marine pollutant NP
14.6 Special Provisions None

14.7 Maritime transport in bulk Not applicable

according to IMO instruments

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable

14.6 Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Dioctyltin oxide	870-08-6	20.

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product contains substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals

Chemical name	European Export/Import Restrictions per (EC) 689/2008 - Annex Number	
Dioctyltin oxide - 870-08-6	l.1	

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

Europe - BE Page 16/19

BOSTIK MAXI BOND
Supercedes Date: 05-Jan-2022
Revision Number 4

France

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) slightly hazardous to water (WGK 1)

TRGS - 510 Storage Class Storage Class 10 : Combustible liquids

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Not Listed

Denmark

Registration number(s) (P-no.) No information available

Norway

Registration number(s) (PRN-no.) No information available

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H335 - May cause respiratory irritation

H361f - Suspected of damaging fertility

H400 - Very toxic to aquatic life

H411 - Toxic to aquatic life with long lasting effects

Notes relating to the identification, classification and labelling of substances

Note V: If the substance is to be placed on the market as fibres (with diameter < 3 μ m, length > 5 μ m and aspect ratio \geq 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied

Note W: It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung

Notes relating to the classification and labelling of mixtures

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 μm

SVHC: Substances of Very High Concern for Authorisation: PBT: Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

vPvB: Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE: Specific target organ toxicity - Repeated exposure

STOT SE: Specific target organ toxicity - Single exposure

Europe - BE Page 17 / 19

BOSTIK MAXI BOND
Supercedes Date: 05-Jan-2022
Revision Number 4

O. F.....

EWC: European Waste Catalogue

LOW: List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

AGW Occupational exposure limit value BGW Biological limit value Ceiling Maximum limit value * Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	On basis of test data
mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)

European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)

European Chemicals Agency (ECHA) (ECHA_API)

EPA (Environmental Protection Agency)

Acute Exposure Guideline Level(s) (AEGL(s))

International Uniform Chemical Information Database (IUCLID)

National Institute of Technology and Evaluation (NITE)

NIOSH (National Institute for Occupational Safety and Health)

Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme

Organisation for Economic Co-operation and Development Screening Information Data Set

Prepared By Product Safety & Regulatory Affairs

Revision date 05-Dec-2022

Revision note SDS sections updated: 3 11 12 16

Training Advice No information available

Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at

Europe - BE Page 18/19

BOSTIK MAXI BOND Supercedes Date: 05-Jan-2022 Revision date 05-Dec-2022 Revision Number 4

the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Europe - BE Page 19/19