



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008
This SDS is for generic information purposes and does not reflect required country specific information for OEL

BOSTIK P535 FOAM'N'FIX STONE PRO B3
Supersedes Date: 23-Oct-2022

Revision date 24-Oct-2022
Revision Number 1.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK P535 FOAM'N'FIX STONE PRO B3
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesive Aerosol Building and construction work
Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Romania SRL
51, Rasaritului Street (DN7)
070000 Buftea
Ilfov
Romania
Phone: +40 372 833 300
Fax: +40 372 833 301
www.bostik.com

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Respiratory sensitisation	Category 1 - (H334)
Skin sensitisation	Category 1 - (H317)
Carcinogenicity	Category 2 - (H351)
Effects on or via lactation	Yes - (H362)
Specific target organ toxicity — single exposure	Category 3 - (H335)
Category 3 Respiratory irritation	
Specific target organ toxicity — repeated exposure	Category 2 - (H373)
Chronic aquatic toxicity	Category 4 - (H413)
Aerosols	Category 1 - (H222, H229)

2.2. Label elements

Contains Diphenylmethane-diisocyanate, isomers and homologues , Alkanes, C14-17, chloro

SAFETY DATA SHEET

BOSTIK P535 FOAM'N'FIX STONE PRO B3
Supersedes Date: 23-Oct-2022

Revision date 24-Oct-2022
Revision Number 1.01



Signal word
Danger

Hazard statements

H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335 - May cause respiratory irritation
H351 - Suspected of causing cancer
H362 - May cause harm to breast-fed children
H373 - May cause damage to organs through prolonged or repeated exposure
H413 - May cause long lasting harmful effects to aquatic life
H222 - Extremely flammable aerosol
H229 - Pressurised container: May burst if heated

EU Specific Hazard Statements

EUH204 - Contains isocyanates. May produce an allergic reaction
EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211 - Do not spray on an open flame or other ignition source
P251 - Do not pierce or burn, even after use
P260 - Do not breathe mist/vapours/spray
P263 - Avoid contact during pregnancy and while nursing
P271 - Use only outdoors or in a well-ventilated area
P273 - Avoid release to the environment
P280 - Wear protective gloves and eye/face protection
P302 + P352 - IF ON SKIN: Wash with plenty of water and soap
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P405 - Store locked up
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
P501 - Dispose of contents/ container to an approved waste disposal plant

Special provisions concerning the labelling of certain mixtures

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used. As from 24 August 2023 adequate training is required before industrial or professional use.

Additional information

This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

During transportation by car the cans should stand upright in the cargo space. In case of insufficient ventilation and/or through use, the formation of a explosive/highly flammable mixture is possible. The mentioned hazards are valid for the non-reacted

SAFETY DATA SHEET

BOSTIK P535 FOAM'N'FIX STONE PRO B3
Supersedes Date: 23-Oct-2022

Revision date 24-Oct-2022
Revision Number 1.01

content of the can or of the fresh foam. When foaming the propellants are highly flammable.

PBT & vPvB

This mixture contains substances considered to be persistent, bio-accumulating and toxic (PBT). This mixture contains substances considered to be very persistent and very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No.	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Diphenylmethane-diisocyanate, isomers and homologues 40 - <80 %	618-498-9	9016-87-9	STOT SE 3 (H335) STOT RE 2 (H373) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Resp. Sens. 1 (H334) Skin Sens. 1 (H317) Carc. 2 (H351) Acute Tox. 4 (H332)	STOT SE 3 :: C>=5% Skin Irrit. 2 :: C>=5% Eye Irrit. 2 :: C>=5% Resp. Sens. 1 :: C>=0.1%	-	-	[7]
Dimethyl ether 10 - <20 %	(603-019-00-8) 204-065-8	115-10-6	Flam. Gas 1 (H220) Press. Gas (H280)	-	-	-	01-2119472128-37-XXXX
Alkanes, C14-17, chloro 10 - <20 %	(602-095-00-X) 287-477-0	85535-85-9	Lact. (H362) (EUH066) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) [H]	-	100	10	01-2119519269-33-XXXX

Full text of H- and EUH-phrases: see section 16

NOTE [7] - No registration number is given for this substance because it is a polymer exempted from registration according to the provisions of Article 2(9) of REACH. All monomers or other substances within the polymer are registered or exempt from registration

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Diphenylmethane-diisocyanate, isomers and homologues	618-498-9	9016-87-9	-	-	1.5	-	-
Dimethyl ether	(603-019-00-8) 204-065-8	115-10-6	-	-	-	-	-
Alkanes, C14-17, chloro	(602-095-00-X) 287-477-0	85535-85-9	-	-	-	-	-

SAFETY DATA SHEET

BOSTIK P535 FOAM'N'FIX STONE PRO B3
Supersedes Date: 23-Oct-2022

Revision date 24-Oct-2022
Revision Number 1.01

This product contains one or more candidate substance(s) of very high concern (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Chemical name	CAS No	SVHC candidates
Alkanes, C14-17, chloro	85535-85-9	X

Chemical name	Notes
Dimethyl ether - 115-10-6	U

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention.
Inhalation	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Seek immediate medical attention/advice.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Get medical attention if irritation develops and persists.
Skin contact	May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes. Do not use solvents or thinners to dissolve the material.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Get immediate medical attention.
Self-protection of the first aider	Remove all sources of ignition. Do not breathe vapour or mist. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. See section 8 for more information.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	May cause allergy or asthma symptoms or breathing difficulties if inhaled. Coughing and/or wheezing. Itching. Rashes. Burning sensation. May cause redness and tearing of the eyes. Difficulty in breathing.
-----------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	May cause sensitisation in susceptible persons. Treat symptomatically.
------------------------	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Water spray, carbon dioxide (CO ₂), dry chemical, alcohol-resistant foam.
Unsuitable extinguishing media	Full water jet. DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. Containers may explode when heated. In the event of fire, cool tanks with water spray.
---	---

SAFETY DATA SHEET

BOSTIK P535 FOAM'N'FIX STONE PRO B3
Supersedes Date: 23-Oct-2022

Revision date 24-Oct-2022
Revision Number 1.01

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO₂). Nitrogen oxides (NO_x). Hydrogen cyanide. Isocyanates.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Wear self contained breathing apparatus for fire fighting if necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Do not breathe vapour or mist. Ensure adequate ventilation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. See section 8 for more information. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Avoid breathing vapours or mists.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. Refer to protective measures listed in Sections 7 and 8.

6.3. Methods and material for containment and cleaning up

Methods for containment Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

Methods for cleaning up Take precautionary measures against static discharges. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protection equipment. Do not breathe vapour or mist. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes or clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Do not puncture or incinerate cans. Do not spray on an open flame or other ignition source.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Wash hands before breaks and after work. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Store in a cool, dry area away from

SAFETY DATA SHEET

BOSTIK P535 FOAM'N'FIX STONE PRO B3
Supersedes Date: 23-Oct-2022

Revision date 24-Oct-2022
Revision Number 1.01

potential sources of heat, open flames, sunlight or other chemicals. Do not store near combustible materials. Keep from freezing.

Recommended storage temperature Keep at temperatures between 10 and 20 °C.

7.3. Specific end use(s)

Specific use(s)
Aerosol. Adhesive. Building and construction work.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union
Dimethyl ether 115-10-6	TWA: 1000 ppm TWA: 1920 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL) Dimethyl ether (115-10-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	1894 mg/m ³	

Alkanes, C14-17, chloro (85535-85-9)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	6.7 mg/m ³	
worker Systemic health effects Long term	Dermal	47.9 mg/kg bw/d	

Derived No Effect Level (DNEL) Dimethyl ether (115-10-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	471 mg/m ³	

Alkanes, C14-17, chloro (85535-85-9)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term	Inhalation	2 mg/m ³	

SAFETY DATA SHEET

BOSTIK P535 FOAM'N'FIX STONE PRO B3
Supersedes Date: 23-Oct-2022

Revision date 24-Oct-2022
Revision Number 1.01

Systemic health effects			
Consumer Long term Systemic health effects	Dermal	28.75 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.58 mg/kg bw/d	

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)	
Dimethyl ether (115-10-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.155 mg/l
Marine water	0.016 mg/l
Microorganisms in sewage treatment	160 mg/l
Freshwater sediment	0.681 mg/kg dry weight
Soil	0.45 mg/kg dry weight

Alkanes, C14-17, chloro (85535-85-9)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	1 µg/l
Marine water	0.2 µg/l
Microorganisms in sewage treatment	80 mg/l
Freshwater sediment	13 mg/kg dry weight
Marine sediment	2.6 mg/kg dry weight
Soil	11.9 mg/kg dry weight

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.

Hand protection Wear suitable gloves. Recommended Use: Butyl rubber. Nitrile rubber. Glove thickness > 0.4 mm. The breakthrough time for the mentioned glove material is in general greater than 60 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374

Skin and body protection Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387. Wear a respirator conforming to EN 140 with Type A filter or better. AX.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Aerosol
Appearance Foam
Colour Beige
Odour Characteristic.
Odour threshold No information available

Property	Values	Remarks • Method
Melting point / freezing point	No data available	None known
Initial boiling point and boiling	Not applicable, Aerosol	Not applicable, Aerosol

SAFETY DATA SHEET

BOSTIK P535 FOAM'N'FIX STONE PRO B3
Supersedes Date: 23-Oct-2022

Revision date 24-Oct-2022
Revision Number 1.01

range		
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	18.6%	
Lower flammability or explosive limits	1.7 Vol.%	
Flash point	Not applicable, Aerosol .	Not applicable, Aerosol
Autoignition temperature	235 °C	
Decomposition temperature		None known
pH	No data available	None known.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	
Water solubility	Immiscible in water.	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	4 - 6	bar @ 23 °C
Relative density	1.022	
Bulk Density	No data available	
Density	1.02 - 1.03 g/cm ³	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	
9.2. Other information		
Solid content (%)	No information available	
VOC content	No data available 187 g/L	European directive n°2010/75/UE

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available Not applicable .

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Stable under recommended storage conditions.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.
Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. Excessive heat. Keep away from open flames, hot surfaces and sources of ignition. Extremes of temperature and direct sunlight.

10.5. Incompatible materials

SAFETY DATA SHEET

BOSTIK P535 FOAM'N'FIX STONE PRO B3
Supersedes Date: 23-Oct-2022

Revision date 24-Oct-2022
Revision Number 1.01

Incompatible materials Strong acids. Strong bases. Strong oxidising agents. Water. Alcohols. Amines.
Incompatible with oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Harmful by inhalation. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

Eye contact Causes serious eye irritation.

Skin contact Causes skin irritation.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Coughing and/ or wheezing. Itching. Rashes.

Acute toxicity

Based on available data, the classification criteria are not met

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal) 25,594.10 mg/kg
ATEmix (inhalation-dust/mist) 2.87 mg/l
ATEmix (inhalation-vapour) 21.10 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Diphenylmethane-diisocyanate, isomers and homologues	LD50 > 10000 mg/kg (Rattus)	LD 50 > 9400 mg/kg (Oryctolagus cuniculus)	=1.5 mg/L (Rattus) 4 h
Dimethyl ether	-	-	=164000 ppm (Rattus) 4 h
Alkanes, C14-17, chloro	>4000 mg/kg (Rattus)	> 2000 mg/kg (Rattus)	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Irritating to skin.

Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit				Mild skin irritant

SAFETY DATA SHEET

BOSTIK P535 FOAM'N'FIX STONE PRO B3
Supersedes Date: 23-Oct-2022

Revision date 24-Oct-2022
Revision Number 1.01

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitisation May cause sensitisation by inhalation. May cause sensitisation by skin contact.

Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)

Method	Species	Exposure route	Results
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse		sensitising

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Contains a known or suspected carcinogen. Suspected of causing cancer.

Component Information

Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)

Method	Species	Results
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat	Carcinogenic

Reproductive toxicity May cause harm to breast-fed children.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Alkanes, C14-17, chloro	Lact.

STOT - single exposure May cause respiratory irritation.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity May cause long lasting harmful effects to aquatic life. Cured foam has no C14-C17 chloroalkanes leaching in water for a maximum 20% C14-C17 chloroalkanes in mixture. Study: "Pulverized PU Foam HM23. Leaching study, Limit test" by Dr. Christine Jahns and sponsored by FEICA AISBL, 09.12.2014.

Method	Species	Endpoint type	Effective dose	Exposure time	Results
OECD Test No. 202:	Daphnia magna	EC50	1000 mg/L	48 hours	Harmless to aquatic

SAFETY DATA SHEET

BOSTIK P535 FOAM'N'FIX STONE PRO B3
Supersedes Date: 23-Oct-2022

Revision date 24-Oct-2022
Revision Number 1.01

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Diphenylmethane-diisocyanate, isomers and homologues 9016-87-9	ErC50 (72h) >1640 mg/L Algae (scenedesmus subspicatus) (OECD 201)	CL50 (96h) >1000 mg/L (Danio rerio)	-	EC50 (24H) >1000 mg/L Daphnia magna		
Dimethyl ether 115-10-6	-	LC50: >4.1g/L (96h, Poecilia reticulata)	-	> 4400 mg/L (Daphnia) (NEN 6501)		
Alkanes, C14-17, chloro 85535-85-9	-	LC50: >500mg/L (48h, Leuciscus idus)	-	EC50 (48h) = 0.007 mg/l (Daphnia magna) OECD 202	100	10

12.2. Persistence and degradability

Persistence and degradability No information available.

Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)

Method	Exposure time	Value	Results
OECD Test No. 302C: Inherent Biodegradability: Modified MITI Test (II)	28 days	0% biodegradation	Not readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Dimethyl ether	-0.18
Alkanes, C14-17, chloro	7

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

Chemical name	PBT and vPvB assessment
Dimethyl ether	The substance is not PBT / vPvB
Alkanes, C14-17, chloro	PBT & vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

SAFETY DATA SHEET

BOSTIK P535 FOAM'N'FIX STONE PRO B3
Supersedes Date: 23-Oct-2022

Revision date 24-Oct-2022
Revision Number 1.01

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
Contaminated packaging	Handle contaminated packages in the same way as the product itself. Empty containers should be taken to an approved waste handling site for recycling or disposal. Pressurized container: Do not pierce or burn, even after use.
European Waste Catalogue	08 05 01* waste isocyanates 16 05 04* gases in pressure containers (including halons) containing dangerous substances 17 06 04 insulation materials other than those mentioned in 17 06 01 and 17 06 03
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number	UN1950
14.2 Proper Shipping Name	Aerosols
14.3 Transport hazard class(es)	2
Labels	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, 2, (D)
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	190, 327, 344, 625
Classification code	5F
Tunnel restriction code	(D)
Limited quantity (LQ)	1 L

IMDG

14.1 UN number or ID number	UN1950
14.2 Proper Shipping Name	Aerosols
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, 2.1, (0°C c.c.)
14.5 Marine pollutant	NP
14.6 Special Provisions	63,190, 277, 327, 344, 381, 959
Limited Quantity (LQ)	See SP277
EmS-No	F-D, S-U
14.7 Maritime transport in bulk according to IMO instruments	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	UN1950
14.2 Proper Shipping Name	Aerosols, flammable
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, flammable, 2.1
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	A145, A167, A802
Limited quantity (LQ)	30 kg G
ERG Code	10L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

SAFETY DATA SHEET

BOSTIK P535 FOAM'N'FIX STONE PRO B3
Supersedes Date: 23-Oct-2022

Revision date 24-Oct-2022
Revision Number 1.01

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product contains one or more candidate substance(s) of very high concern (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Chemical name	CAS No
Alkanes, C14-17, chloro	85535-85-9

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Diphenylmethane-diisocyanate, isomers and homologues	9016-87-9	56 74.
Diisocyanates	--	74

56

If product supplied to the general public with substance $\geq 0.1\%$, then gloves must be provided with the product

74 If product supplied to the industrial or professional users with total monomeric diisocyanates $\geq 0.1\%$, then its packaging must mention "As from 24 August 2023 adequate training is required before industrial or professional use"

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P3a - FLAMMABLE AEROSOLS

P3b - FLAMMABLE AEROSOLS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

France

Occupational Illnesses (R-463-3, France)

Chemical name	French RG number
Diphenylmethane-diisocyanate, isomers and homologues 9016-87-9	RG 62

SAFETY DATA SHEET

BOSTIK P535 FOAM'N'FIX STONE PRO B3
Supersedes Date: 23-Oct-2022

Revision date 24-Oct-2022
Revision Number 1.01

Dimethyl ether 115-10-6	RG 84
Alkanes, C14-17, chloro 85535-85-9	RG 73

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

Flammable liquid (R10), EEC: refer to Annex III No. 1 (fire and explosion hazards) and § 7 paragraph 3

Water hazard class (WGK) obviously hazardous to water (WGK 2)

TRGS - 510 Storage Class Storage Class 2B : Aerosols

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Chemical name	Netherlands - List of Carcinogens
Alkanes, C14-17, chloro 85535-85-9	Can be harmful via breastfeeding

Sweden

Occupational exposure limits AFS 2018:1

Special care should be applied for employees under the age of 18. Young people under the age of 18 may not carry out any work causing harmful exposure to this product. AFS 2012:3

AFS 2011: 19 - Chemical working environment risks (Amended and reprinted in AFS 2014: 43), §§37a-g

Denmark

Registration number(s) (P-no.) 4456751

MAL-Code 1-3

AT-Guide C.0.1 August 2007: Limit values for substances and materials

Norway

Registration number(s) (PRN-no.) 654568

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking

H220 - Extremely flammable gas

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 - May cause respiratory irritation

H351 - Suspected of causing cancer

H362 - May cause harm to breast-fed children

H373 - May cause damage to organs through prolonged or repeated exposure

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

SAFETY DATA SHEET

BOSTIK P535 FOAM'N'FIX STONE PRO B3
Supersedes Date: 23-Oct-2022

Revision date 24-Oct-2022
Revision Number 1.01

vPvB: Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE: Specific target organ toxicity - Repeated exposure
STOT SE: Specific target organ toxicity - Single exposure
EWC: European Waste Catalogue
LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
IATA: International Air Transport Association
ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG: International Maritime Dangerous Goods
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	On basis of test data
Chronic aquatic toxicity	On basis of test data
Aspiration hazard	Calculation method
Ozone	Calculation method
	On basis of test data

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)
European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)
European Chemicals Agency (ECHA) (ECHA_API)
EPA (Environmental Protection Agency)
Acute Exposure Guideline Level(s) (AEGl(s))
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
NIOSH (National Institute for Occupational Safety and Health)
Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications
Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme
Organisation for Economic Co-operation and Development Screening Information Data Set

Prepared By Product Safety & Regulatory Affairs

Revision date 24-Oct-2022

Revision note SDS sections updated 2 4 15 16

Training Advice When working with hazardous materials, regular training of operators is required by law
AS FROM 24 AUGUST 2023 ADEQUATE TRAINING IS REQUIRED BEFORE
INDUSTRIAL OR PROFESSIONAL USE

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

SAFETY DATA SHEET

BOSTIK P535 FOAM'N'FIX STONE PRO B3
Supersedes Date: 23-Oct-2022

Revision date 24-Oct-2022
Revision Number 1.01

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet