



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008
This SDS is for generic information purposes and does not reflect required country specific information for OEL

BOSTIK SL C900 INDUSTRY HEAVY
Supersedes Date: 28-Mar-2022

Revision date 20-Sep-2022
Revision Number 1.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK SL C900 INDUSTRY HEAVY
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Building and construction work Cement
Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik AB
Strandbadsvaegen 22
PO Box 903
25109 Helsingborg, Sweden
Tel: +46 42 19 50 00
Fax: +46 42 19 50 20

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Serious eye damage/eye irritation	Category 1 - (H318)
--	---------------------

2.2. Label elements

Contains Cement, portland, chemicals (Chromium VI reduced)



Signal word
Danger

Hazard statements
H318 - Causes serious eye damage

SAFETY DATA SHEET

BOSTIK SL C900 INDUSTRY HEAVY
Supercedes Date: 28-Mar-2022

Revision date 20-Sep-2022
Revision Number 1.01

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P103 - Read label before use
P280 - Wear eye protection/ face protection
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor

Additional information

Cement product for which the amount of chromium VI was decreased to < 0,0002 % by a reduction agent (related to the total dry weight).

2.3. Other hazards

Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease. Product dust may be irritating to eyes, skin and respiratory system. Repeated exposure may cause skin dryness or cracking. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers. Causes mild skin irritation.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No.	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Quartz 40 - <80 %	238-878-4	14808-60-7	[B]	-	-	-	[5]
Cement, portland, chemicals (Chromium VI reduced) 1 - <5 %	266-043-4	65997-15-1	STOT SE 3 (H335) Skin Irrit. 2 (H315) Eye Dam. 1 (H318)	-	-	-	Exempt

Full text of H- and EUH-phrases: see section 16

NOTE [5] - This substance is exempted from registration according to the provisions of Article 2(7)(a) and Annex V of REACH

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[B] - Substance with a Community workplace exposure limit

[C] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

SAFETY DATA SHEET

BOSTIK SL C900 INDUSTRY HEAVY
Supercedes Date: 28-Mar-2022

Revision date 20-Sep-2022
Revision Number 1.01

Chemical name	EC No (EU Index No)	CAS No	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Quartz	238-878-4	14808-60-7	-	-	-	-	-
Cement, portland, chemicals (Chromium VI reduced)	266-043-4	65997-15-1	-	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	If medical advice is needed, have product container or label at hand.
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.
Eye contact	Do not rub affected area. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.
Skin contact	Brush off loose particles from skin. Remove material from skin immediately. Take off contaminated clothing and wash it before reuse.
Ingestion	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Burning sensation. Prolonged contact may cause redness and irritation. Causes serious eye damage. Irritating to skin. Inhalation of dust in high concentration may cause irritation of respiratory system. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers.
-----------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Treat symptomatically.
------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
-------------------------------------	---

Unsuitable extinguishing media	Full water jet. Do not scatter spilled material with high pressure water streams.
---------------------------------------	---

5.2. Special hazards arising from the substance or mixture

SAFETY DATA SHEET

BOSTIK SL C900 INDUSTRY HEAVY
Supercedes Date: 28-Mar-2022

Revision date 20-Sep-2022
Revision Number 1.01

Specific hazards arising from the chemical No information available.

Hazardous combustion products Carbon oxides. Carbon dioxide (CO₂). Sulphur oxides. Silicon dioxide.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid generation of dust. Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

Methods for containment Cover powder spill with plastic sheet or tarp to minimise spreading and keep powder dry. Prevent dust cloud.

Methods for cleaning up Do not dry sweep dust. Wet dust with water before sweeping or use a vacuum to collect dust. Use appropriate personal protective equipment (PPE). Carefully shovel or sweep up spilled material and place in suitable container. Avoid generating dust.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Avoid generation of dust. Avoid contact with skin, eyes or clothing. Use personal protection equipment. Take off contaminated clothing and wash it before reuse.

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Keep the packing dry and well sealed to prevent contamination and absorption of humidity.

7.3. Specific end use(s)

Specific use(s)
Building and construction work. Cement.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

SAFETY DATA SHEET

BOSTIK SL C900 INDUSTRY HEAVY
Supercedes Date: 28-Mar-2022

Revision date 20-Sep-2022
Revision Number 1.01

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union
Quartz 14808-60-7	TWA: 0.1 mg/m ³

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration (PNEC) No information available.

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Hand protection

For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn. Gloves made of plastic or rubber. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves.

Skin and body protection

Avoid contact with skin, eyes or clothing. Wear appropriate personal protective clothing to prevent skin contact.

Respiratory protection

None under normal use conditions. Avoid generation of dust. Possible nuisance dust. In case of inadequate ventilation wear respiratory protection.

Recommended filter type:

Wear a respirator conforming to EN 140 with Type P2/P3 filter or better.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Powder
Colour	Grey
Odour	Characteristic.
Odour threshold	No information available

Property	Values	Remarks • Method
Melting point / freezing point	Not applicable .	None known
Initial boiling point and boiling range	Not applicable .	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	Not applicable .	None known
Autoignition temperature	No data available	None known

SAFETY DATA SHEET

BOSTIK SL C900 INDUSTRY HEAVY
Supersedes Date: 28-Mar-2022

Revision date 20-Sep-2022
Revision Number 1.01

Decomposition temperature		None known
pH	No data available -	None known.
pH (as aqueous solution)	11 - 11.5	None known
Kinematic viscosity	Not applicable .	None known
Dynamic viscosity	.	
Water solubility	No data available. Cement based products react and solidify in contact with water	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk Density	No data available	
Density	No data available	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

Solid content (%)	100	
Softening Point	Not relevant	
VOC content		No data available

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available Not applicable .

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Keep away from Incompatible materials. Stable under recommended storage conditions.

Explosion data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Exposure to water. Product cures with moisture.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents. Acids. Aluminium.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SAFETY DATA SHEET

BOSTIK SL C900 INDUSTRY HEAVY
Supercedes Date: 28-Mar-2022

Revision date 20-Sep-2022
Revision Number 1.01

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available.
Eye contact	Causes serious eye damage. May cause irreversible damage to eyes.
Skin contact	May cause irritation.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	Redness. Burning. May cause blindness. Prolonged contact may cause redness and irritation.
-----------------	--

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (inhalation-dust/mist) 40.80 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Quartz	>2000 mg/kg (Rattus)	-	-
Cement, portland, chemicals (Chromium VI reduced)	-	>2000 Kg/mg (Lapin)	>5 g/m ³ (Rattus)

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Risk of serious damage to eyes.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

BOSTIK SL C900 INDUSTRY HEAVY
Supercedes Date: 28-Mar-2022

Revision date 20-Sep-2022
Revision Number 1.01

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of waste in accordance with environmental legislation. Dispose of in accordance with local regulations.

Contaminated packaging Do not reuse empty containers.

European Waste Catalogue 16 03 03* inorganic wastes containing hazardous substances

SAFETY DATA SHEET

BOSTIK SL C900 INDUSTRY HEAVY
Supersedes Date: 28-Mar-2022

Revision date 20-Sep-2022
Revision Number 1.01

15 01 10*: Packaging containing residues of or contaminated by dangerous substances

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number Not regulated
14.2 Proper Shipping Name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Environmental hazards Not applicable
14.6 Special Provisions None

IMDG

14.1 UN number or ID number Not regulated
14.2 Proper Shipping Name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Marine pollutant NP
14.6 Special Provisions None
14.7 Maritime transport in bulk according to IMO instruments Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number Not regulated
14.2 Proper Shipping Name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Environmental hazards Not applicable
14.6 Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Cement, portland, chemicals (Chromium VI reduced)	65997-15-1	47.

47 where product supplied with reducing agent the packaging must be marked with the storage conditions and storage period appropriate to maintaining the activity of the reducing agent to keep the content of soluble chromium VI below 2mg/Kg

Substance subject to authorisation per REACH Annex XIV

SAFETY DATA SHEET

BOSTIK SL C900 INDUSTRY HEAVY
Supersedes Date: 28-Mar-2022

Revision date 20-Sep-2022
Revision Number 1.01

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009
Not applicable

Persistent Organic Pollutants
Not applicable

National regulations

France

Occupational Illnesses (R-463-3, France)

Chemical name	French RG number
Quartz 14808-60-7	RG 25
Cement, portland, chemicals (Chromium VI reduced) 65997-15-1	RG 8, RG 10 RG 8

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV
No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) slightly hazardous to water (WGK 1)

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Chemical name	Netherlands - List of Carcinogens
Quartz 14808-60-7	Present (respirable dust, crystalline)

Sweden

Occupational exposure limits AFS 2018:1
Swedish Work Environment Authority's Statute (AFS 2015:2) QUARTZ AFS 2015:2
Special care should be applied for employees under the age of 18. Young people under the age of 18 may not carry out any work causing harmful exposure to this product. AFS 2012:3

Denmark

Registration number(s) (P-no.) 4205055
MAL-Code 00-4
AT-Guide C.0.1 August 2007: Limit values for substances and materials

Norway

Registration number(s) (PRN-no.) 617526

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

SAFETY DATA SHEET

BOSTIK SL C900 INDUSTRY HEAVY
Supercedes Date: 28-Mar-2022

Revision date 20-Sep-2022
Revision Number 1.01

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H315 - Causes skin irritation
H318 - Causes serious eye damage
H335 - May cause respiratory irritation

SVHC: Substances of Very High Concern for Authorisation:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB: Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE: Specific target organ toxicity - Repeated exposure
STOT SE: Specific target organ toxicity - Single exposure
EWC: European Waste Catalogue
LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
IATA: International Air Transport Association
ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG: International Maritime Dangerous Goods
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)
European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)
European Chemicals Agency (ECHA) (ECHA_API)
EPA (Environmental Protection Agency)
Acute Exposure Guideline Level(s) (AEGl(s))
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
NIOSH (National Institute for Occupational Safety and Health)
Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications
Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme
Organisation for Economic Co-operation and Development Screening Information Data Set

Prepared By Product Safety & Regulatory Affairs

SAFETY DATA SHEET

BOSTIK SL C900 INDUSTRY HEAVY
Supersedes Date: 28-Mar-2022

Revision date 20-Sep-2022
Revision Number 1.01

Revision date	20-Sep-2022
Training Advice	No information available
Further information	No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet