



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008
This SDS is for generic information purposes and does not reflect required country specific information for OEL

BOSTIK WOOD ADHESIVE 800 PU
Supersedes Date: 24-Aug-2022

Revision date 03-Jan-2024
Revision Number 2.02

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK WOOD ADHESIVE 800 PU

Other means of identification

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives

Uses advised against No information available.

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik AB
Strandbadsvaegen 22
PO Box 903
25109 Helsingborg, Sweden
Tel: +46 42 19 50 00
Fax: +46 42 19 50 20

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to
Regulation (EC) No. 1272/2008
[CLP]

Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Respiratory sensitisation	Category 1 - (H334)
Skin sensitisation	Category 1 - (H317)
Carcinogenicity	Category 2 - (H351)
Specific target organ toxicity — single exposure	Category 3 - (H335)
Category 3 Respiratory irritation	
Specific target organ toxicity — repeated exposure	Category 2 - (H373)
Chronic aquatic toxicity	Category 3 - (H412)

2.2. Label elements

Contains Prepolymer, based on aromatic polyisocyanate; Diphenylmethane-diisocyanate, isomers and homologues;

SAFETY DATA SHEET

BOSTIK WOOD ADHESIVE 800 PU
Supercedes Date: 24-Aug-2022

Revision date 03-Jan-2024
Revision Number 2.02

4,4'-Methylenediphenyl diisocyanate; o-(p-isocyanatobenzyl)phenyl isocyanate



Signal word
Danger

Hazard statements

H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335 - May cause respiratory irritation
H351 - Suspected of causing cancer
H373 - May cause damage to organs through prolonged or repeated exposure
H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements - EU (§28, 1272/2008)

P102 - Keep out of reach of children
P260 - Do not breathe vapour
P271 - Use only outdoors or in a well-ventilated area
P273 - Avoid release to the environment
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor
P405 - Store locked up

Special provisions concerning the labelling of certain mixtures

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used. As from 24 August 2023 adequate training is required before industrial or professional use.

Additional information

This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

No information available.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Europe - BE

Page 2 / 17

SAFETY DATA SHEET

BOSTIK WOOD ADHESIVE 800 PU
Supersedes Date: 24-Aug-2022

Revision date 03-Jan-2024
Revision Number 2.02

Chemical name	EC No (EU Index No).	CAS No..	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Prepolymer, based on aromatic polyisocyanate 40 - <80 %	642-899-8	67815-87-6	Acute Tox. 4 (H332) STOT SE 3 (H335) STOT RE 2 (H373) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Resp. Sens. 1 (H334) Skin Sens. 1 (H317)	-	-	-	[7]
Diphenylmethane-diisocyanate, isomers and homologues >25 - <40 %	618-498-9	9016-87-9	STOT SE 3 (H335) STOT RE 2 (H373) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Resp. Sens. 1 (H334) Skin Sens. 1 (H317) Carc. 2 (H351) Acute Tox. 4 (H332)	STOT SE 3 :: C>=5% Skin Irrit. 2 :: C>=5% Eye Irrit. 2 :: C>=5% Resp. Sens. 1 :: C>=0.1%	-	-	[7]
4,4'-Methylenediphenyl diisocyanate 1 - <5 %	202-966-0 (615-005-00-9)	101-68-8	Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Resp. Sens. 1 (H334) Skin Sens. 1 (H317) Carc. 2 (H351) STOT SE 3 (H335) STOT RE 2 (H373)	STOT SE 3 :: C>=5% Skin Irrit. 2 :: C>=5% Eye Irrit. 2 :: C>=5% Resp. Sens. 1 :: C>=0.1%	-	-	01-2119457014-47-XXXX
o-(p-isocyanatobenzyl)phenyl isocyanate 1 - <5 %	227-534-9 (615-005-00-9)	5873-54-1	Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Resp. Sens. 1 (H334) Skin Sens. 1 (H317) Carc. 2 (H351) STOT SE 3 (H335) STOT RE 2 (H373)	Eye Irrit. 2 :: C>=5% Resp. Sens. 1 :: C>=0.1% Skin Irrit. 2 :: C>=5% STOT SE 3 :: C>=5%	-	-	01-2119480143-45-XXXX
2,2'-methylene-diphenyl diisocyanate 0.01 - <0.1 %	219-799-4 (615-005-00-9)	2536-05-2	Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Resp. Sens. 1 (H334) Skin Sens. 1 (H317) Carc. 2 (H351) STOT SE 3 (H335) STOT RE 2 (H373)	Eye Irrit. 2 :: C>=5% Resp. Sens. 1 :: C>=0.1% Skin Irrit. 2 :: C>=5% STOT SE 3 :: C>=5%	-	-	01-2119927323-43-XXXX

Full text of H- and EUH-phrases: see section 16

NOTE [7] - No registration number is given for this substance because it is a polymer exempted from registration according to the provisions of Article 2(9) of REACH. All monomers or other substances within the polymer are registered or exempt from registration

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Prepolymer, based on aromatic polyisocyanate	642-899-8	67815-87-6	-	-	1.5	-	-
Diphenylmethane-diiso	618-498-9	9016-87-9	-	-	1.5	-	-

SAFETY DATA SHEET

BOSTIK WOOD ADHESIVE 800 PU
Supercedes Date: 24-Aug-2022

Revision date 03-Jan-2024
Revision Number 2.02

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
cyanate, isomers and homologues							
4,4'-Methylenediphenyl diisocyanate	202-966-0 (615-005-00-9)	101-68-8	-	-	1.5	-	-
o-(p-isocyanatobenzyl) phenyl isocyanate	227-534-9 (615-005-00-9)	5873-54-1	-	-	1.5	-	-
2,2'-methylenediphenyl diisocyanate	219-799-4 (615-005-00-9)	2536-05-2	-	-	1.5	-	-

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Notes

See section 16 for more information

Chemical name	Notes
4,4'-Methylenediphenyl diisocyanate - 101-68-8	C,2
o-(p-isocyanatobenzyl)phenyl isocyanate - 5873-54-1	C,2
2,2'-methylenediphenyl diisocyanate - 2536-05-2	C,2

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention.
Inhalation	May cause allergic respiratory reaction. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Get immediate medical attention.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes.
Ingestion	May produce an allergic reaction. Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Get immediate medical attention.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. See section 8 for more information. Avoid breathing vapours or mists.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	May cause allergy or asthma symptoms or breathing difficulties if inhaled. Coughing and/ or wheezing. Itching. Rashes. Hives. May cause redness and tearing of the eyes.
-----------------	--

SAFETY DATA SHEET

BOSTIK WOOD ADHESIVE 800 PU
Supercedes Date: 24-Aug-2022

Revision date 03-Jan-2024
Revision Number 2.02

Burning sensation. Difficulty in breathing.

Effects of Exposure May cause damage to organs through prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors May cause sensitisation in susceptible persons. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical, CO₂, water spray or alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Product is or contains a sensitiser. May cause sensitisation by inhalation. May cause sensitisation by skin contact.

Hazardous combustion products Carbon oxides. Carbon monoxide. Carbon dioxide (CO₂). Nitrogen oxides (NO_x). Hydrogen cyanide. Isocyanates.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Avoid breathing vapours or mists.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so.

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up 2%, Liquid dishwashing soap, a mixture of 90% water and 8-10% sodium carbonate.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

SAFETY DATA SHEET

BOSTIK WOOD ADHESIVE 800 PU
Supersedes Date: 24-Aug-2022

Revision date 03-Jan-2024
Revision Number 2.02

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Avoid breathing vapours or mists.

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and immediately after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from food, drink and animal feedingstuffs. Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.

Recommended storage temperature Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)
Adhesives.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
4,4'-Methylenediphenyl diisocyanate (101-68-8)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Short term Systemic health effects	Dermal	50 mg/kg bw/d	
worker Short term Systemic health effects	Inhalation	0.1 mg/m ³	
worker Short term Local health effects	Dermal	28700 µg/cm ²	
worker Short term Local health effects	Inhalation	0.1 mg/m ³	
worker Long term Systemic health effects	Inhalation	0.05 mg/m ³	
worker Long term	Inhalation	0.05 mg/m ³	

SAFETY DATA SHEET

BOSTIK WOOD ADHESIVE 800 PU
Supersedes Date: 24-Aug-2022

Revision date 03-Jan-2024
Revision Number 2.02

Local health effects		
----------------------	--	--

o-(p-isocyanatobenzyl)phenyl isocyanate (5873-54-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	0.05 mg/m ³	
worker Short term Local health effects	Inhalation	0.1 mg/m ³	

Derived No Effect Level (DNEL)			
4,4'-Methylenediphenyl diisocyanate (101-68-8)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Short term Systemic health effects	Dermal	25 mg/kg bw/d	
Consumer Short term Systemic health effects	Inhalation	0.05 mg/m ³	
Consumer Short term Systemic health effects	Oral	20 mg/kg bw/d	
Consumer Short term Local health effects	Dermal	17200 µg/cm ²	
Consumer Short term Local health effects	Inhalation	0.05 mg/m ³	
Consumer Long term Systemic health effects	Inhalation	0.025 mg/m ³	
Consumer Long term Local health effects	Inhalation	0.025 mg/m ³	

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)	
4,4'-Methylenediphenyl diisocyanate (101-68-8)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	1 mg/l
Marine water	0.1 mg/l
Soil	1 mg/kg dry weight
Sewage treatment plant	1 mg/l
Freshwater - intermittent	10 mg/l

o-(p-isocyanatobenzyl)phenyl isocyanate (5873-54-1)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	1 mg/l
Marine water	0.1 mg/l
Sewage treatment plant	1 mg/l
Soil	1 mg/kg dry weight
Freshwater - intermittent	10 mg/l

2,2'-methylene-diphenyl diisocyanate (2536-05-2)

SAFETY DATA SHEET

BOSTIK WOOD ADHESIVE 800 PU
Supersedes Date: 24-Aug-2022

Revision date 03-Jan-2024
Revision Number 2.02

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	1 mg/l
Marine water	0.1 mg/l
Sewage treatment plant	1 mg/l
Soil	1 mg/kg dry weight
Freshwater - intermittent	10 mg/l

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.

Hand protection Nitrile rubber. Butyl rubber. Glove thickness > 0.4 mm. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. The breakthrough time for the mentioned glove material is in general greater than 60 min. Gloves must conform to standard EN 374

Skin and body protection Suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Recommended filter type: Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Organic gases and vapours filter conforming to EN 14387.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid
Appearance Liquid
Colour dark brown
Odour Earthy.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	~368 @1.013 hPa	
Flammability	No data available	
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	> 250 °C	DIN 22719
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	No data available	None known.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	~5.400 mPa s	@ 25 °C
Water solubility	No data available.	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	1.6	@20°C EG A4
Relative density	~1.15	None known
Bulk Density	No data available	
Density	1.15 g/cm ³	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

SAFETY DATA SHEET

BOSTIK WOOD ADHESIVE 800 PU
Supercedes Date: 24-Aug-2022

Revision date 03-Jan-2024
Revision Number 2.02

9.2. Other information

Solid content (%) No information available
VOC content No data available

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.
Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Hazardous polymerisation Hazardous polymerisation may take place during a fire due to heat. Closed containers could violently rupture.

10.4. Conditions to avoid

Conditions to avoid Excessive heat.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause sensitisation in susceptible persons. (based on components). May cause irritation of respiratory tract. Harmful by inhalation.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.

SAFETY DATA SHEET

BOSTIK WOOD ADHESIVE 800 PU
Supersedes Date: 24-Aug-2022

Revision date 03-Jan-2024
Revision Number 2.02

Skin contact Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). May cause sensitisation by skin contact. Causes skin irritation.

Ingestion Specific test data for the substance or mixture is not available. May cause additional effects as listed under "Inhalation". Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Coughing and/ or wheezing. Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) >5000 mg/kg
ATEmix (dermal) >5000 mg/kg
ATEmix (inhalation-gas) >20000 ppm
ATEmix (inhalation-dust/mist) 1.50 mg/l
ATEmix (inhalation-vapour) >20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Prepolymer, based on aromatic polyisocyanate	LD 50 > 2000 mg/kg (Rattus) Richtlinie 84/449/EWG, B.1	LD 50 > 9400 mg/kg (Oryctolagus cuniculus) OECD 402	-
Diphenylmethane-diisocyanate, isomers and homologues	LD50 > 10000 mg/kg (Rattus)	LD 50 > 9400 mg/kg (Oryctolagus cuniculus)	1.5 mg/L (Rattus) 4 h
4,4'-Methylenediphenyl diisocyanate	=31600 mg/kg (Rattus) = 9200 mg/kg (Rattus)	LD 50 > 9400 mg/kg (Oryctolagus cuniculus) OECD 402	1.5 mg/L (Rattus) 4 h
o-(p-isocyanatobenzyl)phenyl isocyanate	LD50 >2000 mg/Kg (Rattus)	LD 50 > 9400 mg/kg (Oryctolagus cuniculus) OECD 402	1.5 mg/L (4h) Rat
2,2'-methylenediphenyl diisocyanate	LD50 > 2000 mg/kg (Rattus)	LD 50 > 9400 mg/kg (Oryctolagus cuniculus) OECD 402	1.5 mg/L (4h) Rat

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Causes skin irritation.

Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit				Mild skin irritant

o-(p-isocyanatobenzyl)phenyl isocyanate (5873-54-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit				irritant

SAFETY DATA SHEET

BOSTIK WOOD ADHESIVE 800 PU
Supersedes Date: 24-Aug-2022

Revision date 03-Jan-2024
Revision Number 2.02

Acute Dermal Irritation/Corrosion					
-----------------------------------	--	--	--	--	--

Serious eye damage/eye irritation Causes serious eye irritation.

4,4'-Methylenediphenyl diisocyanate (101-68-8)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye	0.1 mL	24 hours	Non-irritant

Respiratory or skin sensitisation May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Prepolymer, based on aromatic polyisocyanate (67815-87-6)

Method	Species	Exposure route	Results
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse		sensitising

Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)

Method	Species	Exposure route	Results
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse		sensitising

4,4'-Methylenediphenyl diisocyanate (101-68-8)

Method	Species	Exposure route	Results
OECD GD 39	Rat	Inhalation	Sensitizing

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Contains a known or suspected carcinogen. Suspected of causing cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component Information

Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)

Method	Species	Results
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat	Carcinogenic

4,4'-Methylenediphenyl diisocyanate (101-68-8)

Method	Species	Results
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat	Limited evidence of a carcinogenic effect

o-(p-isocyanatobenzyl)phenyl isocyanate (5873-54-1)

Method	Species	Results
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat	Carcinogenic

Chemical name	European Union
4,4'-Methylenediphenyl diisocyanate	Carc. 2
o-(p-isocyanatobenzyl)phenyl isocyanate	Carc. 2
2,2'-methylenediphenyl diisocyanate	Carc. 2

SAFETY DATA SHEET

BOSTIK WOOD ADHESIVE 800 PU
Supersedes Date: 24-Aug-2022

Revision date 03-Jan-2024
Revision Number 2.02

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause respiratory irritation.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

H373 - May cause damage to the following organs through prolonged or repeated exposure if inhaled: lungs;inhalation.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Prepolymer, based on aromatic polyisocyanate 67815-87-6	ErC50 (72h) > 1.640 mg/l Scenedesmus subspicatus (OECD 201)	LC50 (96h) > 1.000 mg/l Danio rerio (OECD 203)	-	EC50 (24h) > 1.000 mg/l Daphnia magna (OECD 202)		
Diphenylmethane-diisocyanate, isomers and homologues 9016-87-9	ErC50 (72h) >1640 mg/L Algae (scenedesmus subspicatus) (OECD 201)	CL50 (96h) >1000 mg/L Danio rerio	-	EC50 (24H) >1000 mg/L Daphnia magna		
4,4'-Methylenediphenyl diisocyanate 101-68-8	ErC50 (72h) >1640 mg/L Algae (scenedesmus subspicatus) (OECD 201)	>1000 mg/l Danio rerio	-	EC50 (24H) >1000 mg/L Daphnia magna		
o-(p-isocyanatobenzyl) phenyl isocyanate 5873-54-1	ErC50 (72h) >1640 mg/L Algae (scenedesmus subspicatus) (OECD 201)	LC50 (96 h) > 1000 mg/l Danio rerio (OECD 203)	-	EC50 (24H) >1000 mg/L Daphnia magna		
2,2'-methylenediphenyl diisocyanate 2536-05-2	-	LC50 (96 h) > 1000 mg/l Danio rerio (OECD 203)	-	-		

SAFETY DATA SHEET

BOSTIK WOOD ADHESIVE 800 PU
Supersedes Date: 24-Aug-2022

Revision date 03-Jan-2024
Revision Number 2.02

12.2. Persistence and degradability

Persistence and degradability No information available.

Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)

Method	Exposure time	Value	Results
OECD Test No. 302C: Inherent Biodegradability: Modified MITI Test (II)	28 days	0% biodegradation	Not readily biodegradable

4,4'-Methylenediphenyl diisocyanate (101-68-8)

Method	Exposure time	Value	Results
OECD Test No. 302C: Inherent Biodegradability: Modified MITI Test (II)	28 days	0% biodegradation	Not readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
4,4'-Methylenediphenyl diisocyanate	4.51

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
4,4'-Methylenediphenyl diisocyanate	The substance is not PBT / vPvB
o-(p-isocyanatobenzyl)phenyl isocyanate	The substance is not PBT / vPvB
2,2'-methylenediphenyl diisocyanate	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

European Waste Catalogue
08 05 01* waste isocyanates
08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
15 01 10*: Packaging containing residues of or contaminated by dangerous substances

SAFETY DATA SHEET

BOSTIK WOOD ADHESIVE 800 PU
Supersedes Date: 24-Aug-2022

Revision date 03-Jan-2024
Revision Number 2.02

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None

IMDG

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special precautions for user	
Special Provisions	None
14.7 Maritime transport in bulk according to IMO instruments	
Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

SAFETY DATA SHEET

BOSTIK WOOD ADHESIVE 800 PU
Supersedes Date: 24-Aug-2022

Revision date 03-Jan-2024
Revision Number 2.02

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
Diphenylmethane-diisocyanate, isomers and homologues	9016-87-9	56 74.
4,4'-Methylenediphenyl diisocyanate	101-68-8	56[a]. 75. 74.
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	56[b]. 75. 74.
Diisocyanates	--	74

56

If product supplied to the general public with substance $\geq 0.1\%$, then gloves must be provided with the product

74 If product supplied to the industrial or professional users with total monomeric diisocyanates $\geq 0.1\%$, then its packaging must mention "As from 24 August 2023 adequate training is required before industrial or professional use"

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

France

Occupational Illnesses (R-463-3, France)

Chemical name	French RG number
Diphenylmethane-diisocyanate, isomers and homologues 9016-87-9	RG 62
4,4'-Methylenediphenyl diisocyanate 101-68-8	RG 62
o-(p-isocyanatobenzyl)phenyl isocyanate 5873-54-1	RG 62
2,2'-methylenediphenyl diisocyanate 2536-05-2	RG 62

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) slightly hazardous to water (WGK 1)

TRGS - 510 Storage Class Storage Class 10 : Combustible liquids
TA Luft (German Air Pollution Control Regulation)

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

SAFETY DATA SHEET

BOSTIK WOOD ADHESIVE 800 PU
Supersedes Date: 24-Aug-2022

Revision date 03-Jan-2024
Revision Number 2.02

Not Listed

Sweden

Occupational exposure limits AFS 2018:1

Special care should be applied for employees under the age of 18. Young people under the age of 18 may not carry out any work causing harmful exposure to this product. AFS 2012:3

AFS 2011: 19 - Chemical working environment risks (Amended and reprinted in AFS 2014: 43), §§37a-g

Denmark

Registration number(s) (P-no.) 534177

MAL-Code 0-3 (1993)

Norway

Registration number(s) (PRN-no.) 38555

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 - May cause respiratory irritation

H351 - Suspected of causing cancer

H373 - May cause damage to organs through prolonged or repeated exposure

Notes relating to the identification, classification and labelling of substances

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers

Notes relating to the classification and labelling of mixtures

Note 2: The concentration of isocyanate stated is the percentage by weight of the free monomer calculated with reference to the total weight of the mixture

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances

vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT RE: Specific target organ toxicity - Repeated exposure

STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	SK*	Skin designation

Classification procedure

Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method

SAFETY DATA SHEET

BOSTIK WOOD ADHESIVE 800 PU
Supersedes Date: 24-Aug-2022

Revision date 03-Jan-2024
Revision Number 2.02

Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)
European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)
European Chemicals Agency (ECHA) (ECHA_API)
EPA (Environmental Protection Agency)
Acute Exposure Guideline Level(s) (AEGL(s))
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
NIOSH (National Institute for Occupational Safety and Health)
Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications
Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme
Organisation for Economic Co-operation and Development Screening Information Data Set

Prepared By Product Safety & Regulatory Affairs

Revision date 03-Jan-2024

Training Advice AS FROM 24 AUGUST 2023 ADEQUATE TRAINING IS REQUIRED BEFORE INDUSTRIAL OR PROFESSIONAL USE
For further information, please contact:
<https://www.safeusediisocyanates.eu/>

Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Regulation (EC) No. 1272/2008 and Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet