



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008  
This SDS is for generic information purposes and does not reflect required country specific information for OEL

**BOSTIK WOOD PASTE OAK**  
Supersedes Date: 02-Sep-2022

Revision date 05-Sep-2022  
Revision Number 1.01

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product Name** BOSTIK WOOD PASTE OAK

**Pure substance/mixture** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Fillers, putties, plasters, modelling clay

**Uses advised against** None known.

### 1.3. Details of the supplier of the safety data sheet

#### **Company Name**

Bostik AB  
Strandbadsvaegen 22  
PO Box 903  
25109 Helsingborg, Sweden  
Tel: +46 42 19 50 00  
Fax: +46 42 19 50 20

**E-mail address** SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

**Emergency Telephone**

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

<b>Serious eye damage/eye irritation</b>	Category 2 - (H319)
<b>Specific target organ toxicity — single exposure</b>	Category 3 - (H336)
Category 3 Narcotic effects	
<b>Flammable solids</b>	Category 1 - (H228)

### 2.2. Label elements

Contains Ethyl acetate



# SAFETY DATA SHEET

**BOSTIK WOOD PASTE OAK**  
**Supersedes Date:** 02-Sep-2022

**Revision date** 05-Sep-2022  
**Revision Number** 1.01

**Signal word**  
Danger

**Hazard statements**  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness  
H228 - Flammable solid

**EU Specific Hazard Statements**  
EUH066 - Repeated exposure may cause skin dryness or cracking

**Precautionary Statements - EU (§28, 1272/2008)**  
P101 - If medical advice is needed, have product container or label at hand  
P102 - Keep out of reach of children  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P271 - Use only outdoors or in a well-ventilated area  
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed  
P501 - Dispose of contents/ container to an approved waste disposal plant

## 2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No.	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Ethyl acetate 40 - <80 %	205-500-4	141-78-6	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)	-	-	-	01-2119475103-46-XXXX
Nitrocellulose 10 - <20 %	-	9004-70-0	Expl. 1.1 (H201)	-	-	-	-
Isopropyl alcohol 1 - <5 %	200-661-7	67-63-0	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225)	-	-	-	01-2119457558-25-XXXX
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics 1 - <3 %	919-857-5	64742-48-9	STOT SE 3 (H336) Asp. Tox. 1 (H304) (EUH066) Flam. Liq. 3 (H226)	-	-	-	01-2119463258-33-XXXX
Xylenes (o-, m-, p-isomers) 0.1 - <1 %	215-535-7	1330-20-7	STOT SE 3 (H335) STOT RE 2 (H373) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Acute Tox. 4 (H312) Acute Tox. 4 (H332) Flam Liq. 3 (H226) Aquatic Chronic 3 (H412)	-	-	-	01-2119488216-32-XXXX

# SAFETY DATA SHEET

**BOSTIK WOOD PASTE OAK**  
**Supersedes Date:** 02-Sep-2022

**Revision date** 05-Sep-2022  
**Revision Number** 1.01

**Full text of H- and EUH-phrases: see section 16**

## Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Ethyl acetate	205-500-4	141-78-6	-	-	-	14.4131	-
Isopropyl alcohol	200-661-7	67-63-0	-	-	-	-	-
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	919-857-5	64742-48-9	6006	5005	-	-	-
Xylenes (o-, m-, p-isomers)	215-535-7	1330-20-7	2500	1990	4.8	-	-

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## Notes

See section 16 for more information

Chemical name	Notes
Nitrocellulose - 9004-70-0	T
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics - 64742-48-9	P
Xylenes (o-, m-, p-isomers) - 1330-20-7	C

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	Show this safety data sheet to the doctor in attendance.
<b>Inhalation</b>	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
<b>Skin contact</b>	Shower and wash with soap and water. Take off contaminated clothing and wash it before reuse. In the case of skin irritation or allergic reactions see a doctor.
<b>Ingestion</b>	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a doctor.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid contact with skin, eyes or clothing.

# SAFETY DATA SHEET

BOSTIK WOOD PASTE OAK  
Supersedes Date: 02-Sep-2022

Revision date 05-Sep-2022  
Revision Number 1.01

## 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** May cause redness and tearing of the eyes. Burning sensation. Prolonged contact may cause redness and irritation. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

## 4.3. Indication of any immediate medical attention and special treatment needed

**Note to doctors** Treat symptomatically.

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

**Suitable Extinguishing Media** Dry chemical. Carbon dioxide (CO<sub>2</sub>). Water spray. Alcohol resistant foam.

**Unsuitable extinguishing media** Full water jet. Do not scatter spilled material with high pressure water streams.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards arising from the chemical** Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

**Hazardous combustion products** Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

### 5.3. Advice for firefighters

**Special protective equipment and precautions for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

**Other information** Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

**For emergency responders** Use personal protection recommended in Section 8.

### 6.2. Environmental precautions

**Environmental precautions** Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

### 6.3. Methods and material for containment and cleaning up

**Methods for containment** Do not scatter spilled material with high pressure water streams. Stop leak if you can do it without risk. Do not touch or walk through spilled material. Keep out of drains, sewers, ditches and waterways.

**Methods for cleaning up** Take precautionary measures against static discharges. Use clean non-sparking tools to collect absorbed material. Pick up and transfer to properly labelled containers. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

# SAFETY DATA SHEET

BOSTIK WOOD PASTE OAK  
Supersedes Date: 02-Sep-2022

Revision date 05-Sep-2022  
Revision Number 1.01

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

## 6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

**Advice on safe handling** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use spark-proof tools and explosion-proof equipment. Use according to package label instructions. Use personal protection equipment.

**General hygiene considerations** Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials.

**Recommended storage temperature** Keep at temperatures between 5 and 25 °C.

### 7.3. Specific end use(s)

**Specific use(s)**  
Fillers, putties, plasters, modelling clay.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

#### **Exposure Limits**

**Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.**

Chemical name	European Union
Ethyl acetate 141-78-6	TWA: 734 mg/m <sup>3</sup> TWA: 200 ppm STEL: 1468 mg/m <sup>3</sup> STEL: 400 ppm
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 50 ppm TWA: 221 mg/m <sup>3</sup> STEL: 100 ppm STEL: 442 mg/m <sup>3</sup> *

**Derived No Effect Level (DNEL)** No information available

## **Derived No Effect Level (DNEL)**

# SAFETY DATA SHEET

**BOSTIK WOOD PASTE OAK**  
**Supersedes Date:** 02-Sep-2022

**Revision date** 05-Sep-2022  
**Revision Number** 1.01

<b>Ethyl acetate (141-78-6)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	63 mg/kg bw/d	
worker Short term Systemic health effects	Inhalation	1468 mg/m <sup>3</sup>	
worker Long term Local health effects	Inhalation	734 mg/m <sup>3</sup>	
worker Short term Local health effects	Inhalation	1468 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Inhalation	734 mg/m <sup>3</sup>	

<b>Isopropyl alcohol (67-63-0)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	500 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	888 mg/kg bw/d	

<b>Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics (64742-48-9)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	208 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	871 mg/m <sup>3</sup>	

<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	180 mg/kg bw/d	
Long term Systemic health effects worker	Inhalation	77 mg/m <sup>3</sup>	
Short term Local health effects Systemic health effects worker	Inhalation	289 mg/m <sup>3</sup>	

<b>Derived No Effect Level (DNEL)</b>			
<b>Ethyl acetate (141-78-6)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term	Oral	4.5 mg/kg bw/d	

# SAFETY DATA SHEET

**BOSTIK WOOD PASTE OAK**  
**Supersedes Date:** 02-Sep-2022

**Revision date** 05-Sep-2022  
**Revision Number** 1.01

Systemic health effects			
Consumer Long term Systemic health effects	Dermal	37 mg/kg bw/d	
Consumer Short term Systemic health effects	Inhalation	734 mg/m <sup>3</sup>	
Consumer Long term Local health effects	Inhalation	367 mg/m <sup>3</sup>	
Consumer Short term Local health effects	Inhalation	734 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Inhalation	367 mg/m <sup>3</sup>	

<b>Isopropyl alcohol (67-63-0)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	89 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	319 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	26 mg/kg bw/d	

<b>Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics (64742-48-9)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	125 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	185 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Oral	125 mg/kg bw/d	

**Predicted No Effect Concentration (PNEC)** No information available.

<b>Predicted No Effect Concentration (PNEC)</b>	
<b>Ethyl acetate (141-78-6)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.26 mg/l
Marine water	0.026 mg/l
Freshwater sediment	1.25 mg/kg
Marine sediment	0.125 mg/kg
Soil	0.24 mg/kg
Microorganisms in sewage treatment	650 mg/l

<b>Isopropyl alcohol (67-63-0)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	140.9 mg/l
Marine water	140.9 mg/l

# SAFETY DATA SHEET

BOSTIK WOOD PASTE OAK  
Supersedes Date: 02-Sep-2022

Revision date 05-Sep-2022  
Revision Number 1.01

Sewage treatment plant	2251 mg/l
Freshwater sediment	552 mg/kg dry weight
Marine sediment	552 mg/kg dry weight
Soil	28 mg/kg dry weight

## 8.2. Exposure controls

<b>Engineering controls</b>	Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.
<b>Personal protective equipment</b>	
<b>Eye/face protection</b>	Goggles.
<b>Hand protection</b>	Wear protective butyl rubber gloves. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Gloves must conform to standard EN 374.
<b>Skin and body protection</b>	Suitable protective clothing.
<b>Respiratory protection</b>	In case of inadequate ventilation wear respiratory protection. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
<b>Recommended filter type:</b>	Organic gases and vapours filter conforming to EN 14387. Brown.
<b>Environmental exposure controls</b>	No information available.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Solid
<b>Appearance</b>	Paste
<b>Colour</b>	See section 1 for more information
<b>Odour</b>	Solvent.
<b>Odour threshold</b>	No information available

<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>
<b>Melting point / freezing point</b>	No data available	None known
<b>Initial boiling point and boiling range</b>	76 °C	None known
<b>Flammability</b>	No data available	None known
<b>Flammability Limit in Air</b>		None known
<b>Upper flammability or explosive limits</b>	No data available	
<b>Lower flammability or explosive limits</b>	No data available	
<b>Flash point</b>	-4 °C	None known
<b>Autoignition temperature</b>	No data available	None known
<b>Decomposition temperature</b>		None known
<b>pH</b>	No data available	Not applicable. Insoluble in water.
<b>pH (as aqueous solution)</b>	No data available	None known
<b>Kinematic viscosity</b>	No data available	None known
<b>Dynamic viscosity</b>	No data available	
<b>Water solubility</b>	No data available.	None known
<b>Solubility(ies)</b>	No data available	None known
<b>Partition coefficient</b>	No data available	None known
<b>Vapour pressure</b>	No data available	None known
<b>Relative density</b>	No data available	None known
<b>Bulk Density</b>	No data available	
<b>Liquid Density</b>	1.1 g/cm <sup>3</sup>	
<b>Relative vapour density</b>	No data available	None known
<b>Particle characteristics</b>		
<b>Particle Size</b>	No information available	
<b>Particle Size Distribution</b>	No information available	

### 9.2. Other information

<b>Solid content (%)</b>	48
--------------------------	----



# SAFETY DATA SHEET

**BOSTIK WOOD PASTE OAK**  
**Supersedes Date:** 02-Sep-2022

**Revision date** 05-Sep-2022  
**Revision Number** 1.01

**VOC content** No data available

9.2.1. Information with regards to physical hazard classes  
Not applicable

9.2.2. Other safety characteristics  
No information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** No information available.

### 10.2. Chemical stability

**Stability** Stable under normal conditions.

### Explosion data

**Sensitivity to mechanical impact** None.

**Sensitivity to static discharge** Yes.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** None under normal processing.

### 10.4. Conditions to avoid

**Conditions to avoid** Extremes of temperature and direct sunlight. Heat, flames and sparks.

### 10.5. Incompatible materials

**Incompatible materials** Strong acids. Strong bases. Strong oxidising agents. and. Strong reducing agents.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** None under normal use conditions. Stable under recommended storage conditions.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

#### Product Information

**Inhalation** Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness or dizziness.

**Eye contact** Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.

**Skin contact** Specific test data for the substance or mixture is not available. May cause irritation. Prolonged contact may cause redness and irritation.

**Ingestion** Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

# SAFETY DATA SHEET

BOSTIK WOOD PASTE OAK  
Supersedes Date: 02-Sep-2022

Revision date 05-Sep-2022  
Revision Number 1.01

## Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** May cause redness and tearing of the eyes. Prolonged contact may cause redness and irritation. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

## Acute toxicity

## Numerical measures of toxicity

## Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Ethyl acetate	=5620 mg/kg (Rattus)	> 18000 mg/kg (Oryctolagus cuniculus) > 20 mL/kg (Oryctolagus cuniculus)	LC0 29.3 mg/l air
Nitrocellulose	>5 g/kg (Rattus)	-	-
Isopropyl alcohol	>5000 mg/Kg	= 4059 mg/kg (Oryctolagus cuniculus)	=72600 mg/m <sup>3</sup> (Rattus) 4 h
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	LD50 >2000 mg/kg (Rattus)	>3000 mg/Kg (Rattus)	Ld50 (4h)>5.6mg/L (Rattus)
Xylenes (o-, m-, p- isomers)	=3500 mg/kg (Rattus)	> 1700 mg/kg (Oryctolagus cuniculus) > 4350 mg/kg (Oryctolagus cuniculus)	= 11 mg/L (ATE)

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Mild skin irritant Read-across

**Serious eye damage/eye irritation** Causes serious eye irritation.

Isopropyl alcohol (67-63-0)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			Irritant

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

Ethyl acetate (141-78-6)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed

Isopropyl alcohol (67-63-0)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig		No sensitisation responses

# SAFETY DATA SHEET

**BOSTIK WOOD PASTE OAK**  
**Supersedes Date:** 02-Sep-2022

**Revision date** 05-Sep-2022  
**Revision Number** 1.01

Sensitisation			were observed
---------------	--	--	---------------

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation		Dermal	Not a skin sensitiser Read Across Data

Xylenes (o-, m-, p- isomers) (1330-20-7)

Method	Species	Exposure route	Results
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse	Dermal	No sensitisation responses were observed

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

Component Information  
Isopropyl alcohol (67-63-0)

Method	Species	Results
OECD Test No. 476: In vitro Mammalian Cell Gene Mutation Test	Hamster, in vitro	Not mutagenic

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as mutagenic.

Chemical name	European Union
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	Muta. 1B

**Carcinogenicity** Based on available data, the classification criteria are not met.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	European Union
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	Carc. 1B

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** May cause drowsiness or dizziness.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 11.2.2. Other information

**Other adverse effects** No information available.

## SECTION 12: Ecological information

# SAFETY DATA SHEET

**BOSTIK WOOD PASTE OAK**  
**Supersedes Date:** 02-Sep-2022

**Revision date** 05-Sep-2022  
**Revision Number** 1.01

## 12.1. Toxicity

### Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Ethyl acetate 141-78-6	EC50: =3300mg/L (48h, Desmodesmus subspicatus)	LC50: =484mg/L (96h, Oncorhynchus mykiss) LC50: 352 - 500mg/L (96h, Oncorhynchus mykiss) LC50: 220 - 250mg/L (96h, Pimephales promelas)	EC50 = 1180 mg/L 5 min EC50 = 1500 mg/L 15 min EC50 = 5870 mg/L 15 min EC50 = 7400 mg/L 2 h	EC50: =560mg/L (48h, Daphnia magna)		
Isopropyl alcohol 67-63-0	EC50 72 h > 1000 mg/L (Desmodesmus subspicatus)	LC50 96 h > 1400000 ?g/L (Lepomis macrochirus )	-	EC50: =13299mg/L (48h, Daphnia magna)		
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	-	LC50 (96h) >1000 mg/L Oncorhynchus mykiss	-	LL50 (48h) >1000 mg/L Daphnia magna		
Xylenes (o-, m-, p- isomers) 1330-20-7	-	LC50 96 h 2.6 mg/L (Oncorhynchus mykiss ) (OECD 203)	EC50 = 0.0084 mg/L 24 h	EC50 48 h = 3.4 mg/L (Daphnia magna)		

## 12.2. Persistence and degradability

**Persistence and degradability** No information available.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	biodegradation	>60 % Readily biodegradable

Xylenes (o-, m-, p- isomers) (1330-20-7)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	biodegradation	87.8 % Readily biodegradable

## 12.3. Bioaccumulative potential

### Bioaccumulation

#### Component Information

Chemical name	Partition coefficient
Ethyl acetate	0.73
Isopropyl alcohol	0.05
Xylenes (o-, m-, p- isomers)	3.15

## 12.4. Mobility in soil

**Mobility in soil** No information available.

# SAFETY DATA SHEET

BOSTIK WOOD PASTE OAK  
Supersedes Date: 02-Sep-2022

Revision date 05-Sep-2022  
Revision Number 1.01

## 12.5. Results of PBT and vPvB assessment

### PBT and vPvB assessment

Chemical name	PBT and vPvB assessment
Ethyl acetate	The substance is not PBT / vPvB PBT assessment does not apply
Isopropyl alcohol	The substance is not PBT / vPvB PBT assessment does not apply
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	The substance is not PBT / vPvB
Xylenes (o-, m-, p- isomers)	The substance is not PBT / vPvB

## 12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

## 12.7. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances 15 01 10*: Packaging containing residues of or contaminated by dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

### Land transport (ADR/RID)

14.1 UN number or ID number	UN1325
14.2 Proper Shipping Name	Flammable solid, n.o.s (Ethyl acetate)
14.3 Transport hazard class(es)	4.1
Labels	4.1
14.4 Packing group	II
Description	UN1325, Flammable solid, n.o.s (Ethyl acetate), 4.1, II, (E)
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	274
Classification code	F1
Tunnel restriction code	(E)
Limited quantity (LQ)	1 kg
ADR Hazard Id (Kemmler Number)	40

### IMDG

14.1 UN number or ID number	UN1325
-----------------------------	--------

# SAFETY DATA SHEET

BOSTIK WOOD PASTE OAK  
Supersedes Date: 02-Sep-2022

Revision date 05-Sep-2022  
Revision Number 1.01

14.2 Proper Shipping Name Flammable solid, n.o.s (Ethyl acetate)  
14.3 Transport hazard class(es) 4.1  
14.4 Packing group II  
Description UN1325, Flammable solid, n.o.s (Ethyl acetate), 4.1, II  
14.5 Marine pollutant NP  
14.6 Special Provisions 274  
Limited Quantity (LQ) 1 kg  
EmS-No F-A, S-G  
14.7 Maritime transport in bulk according to IMO instruments Not applicable

## Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number UN1325  
14.2 Proper Shipping Name Flammable solid, n.o.s (Ethyl acetate)  
14.3 Transport hazard class(es) 4.1  
14.4 Packing group II  
Description UN1325, Flammable solid, n.o.s (Ethyl acetate), 4.1, II  
14.5 Environmental hazards Not applicable  
14.6 Special Provisions A3, A803  
Limited quantity (LQ) 5 kg  
ERG Code 3L

## Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

#### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

##### SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	28. 29. 75.

#### Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

#### Named dangerous substances per Seveso Directive (2012/18/EU)

Chemical name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics - 64742-48-9		25000

#### Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

# SAFETY DATA SHEET

**BOSTIK WOOD PASTE OAK**  
**Supercedes Date:** 02-Sep-2022

**Revision date** 05-Sep-2022  
**Revision Number** 1.01

**Persistent Organic Pollutants**  
Not applicable

## National regulations

### France

#### **Occupational Illnesses (R-463-3, France)**

Chemical name	French RG number
Ethyl acetate 141-78-6	RG 84
Nitrocellulose 9004-70-0	RG 2, RG 13, RG 14, RG 42, RG 64, RG 72
Isopropyl alcohol 67-63-0	RG 84
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	RG 84
Xylenes (o-, m-, p- isomers) 1330-20-7	RG 4bis, RG 84

### Germany

#### **Ordinance on Industrial Safety and Health - Germany - BetrSichV**

Flammable liquid (R11), EEC: refer to Annex III No. 1 (fire and explosion hazards) and § 7 paragraph 4

**Water hazard class (WGK)** slightly hazardous to water (WGK 1)

### Netherlands

#### **List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)**

Chemical name	Netherlands - List of Carcinogens
Xylenes (o-, m-, p- isomers) 1330-20-7	Development (Category 2)

### Sweden

Occupational exposure limits AFS 2018:1

### Denmark

**Registration number(s) (P-no.)** 1431284

**MAL-Code** 3-1

AT-Guide C.0.1 August 2007: Limit values for substances and materials

### Norway

**Registration number(s) (PRN-no.)** 621419

## 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

## **SECTION 16: Other information**

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### **Full text of H-Statements referred to under section 3**

EUH066 - Repeated exposure may cause skin dryness or cracking

H201 - Explosive; mass explosion hazard

# SAFETY DATA SHEET

**BOSTIK WOOD PASTE OAK**  
**Supersedes Date:** 02-Sep-2022

**Revision date** 05-Sep-2022  
**Revision Number** 1.01

H225 - Highly flammable liquid and vapour  
H226 - Flammable liquid and vapour  
H304 - May be fatal if swallowed and enters airways  
H312 - Harmful in contact with skin  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H332 - Harmful if inhaled  
H335 - May cause respiratory irritation  
H336 - May cause drowsiness or dizziness  
H373 - May cause damage to organs through prolonged or repeated exposure  
H412 - Harmful to aquatic life with long lasting effects

## Notes assigned to an entry

**Note C:** Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers

**Note P:** The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes.

Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102)-P260-P262-P301 + P310-P331 shall apply

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

vPvB: Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE: Specific target organ toxicity - Repeated exposure

STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

## Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method
Flammable solids	On basis of test data



# SAFETY DATA SHEET

**BOSTIK WOOD PASTE OAK**  
**Supersedes Date:** 02-Sep-2022

**Revision date** 05-Sep-2022  
**Revision Number** 1.01

---

## Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)  
European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA\_RAC)  
European Chemicals Agency (ECHA) (ECHA\_API)  
EPA (Environmental Protection Agency)  
Acute Exposure Guideline Level(s) (AEGL(s))  
International Uniform Chemical Information Database (IUCLID)  
National Institute of Technology and Evaluation (NITE)  
NIOSH (National Institute for Occupational Safety and Health)  
Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications  
Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme  
Organisation for Economic Co-operation and Development Screening Information Data Set

**Prepared By** Product Safety & Regulatory Affairs

**Revision date** 05-Sep-2022

**Training Advice** No information available

**Further information** No information available

**This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**