



# 3055 Light Wall

## TECHNICAL DATASHEET

Version: 2023-11-06

### PRODUCT DESCRIPTION

3055 Light Wall is a cement based light filler for repairing and finishing walls and ceiling inside.

### AREA OF USAGE

3055 Light Wall is intended for use indoors in new production and renovation of concrete, light concrete, plaster or brick (Leka blocks). The filler is based on the light filler technique which makes it very easy to mix and apply. Up to 25 mm per layer and it is quick drying. New priming when there are more layers. Up to 35 % higher filling grade compared to common cement based wall filler due to the light filler content.

### WORKING INSTRUCTION

**Cleaning:** The surface must be clean and free from dust, cement, grease or other contaminants. Porous surfaces must be primed with GRIP A560 CLASSIC and non-absorbent surfaces with GRIP A936 XPRESS. The temperature of the base and on the premises must be between + 10 ° C - + 25 ° C Newly poured concrete and plaster must be at least 1 month old. **Mixture:** Mix 6 liters of clean water to one sack (20 kg). Mix with a strong drill fitted with a whisk to a lump-free mass. **Application:** The mass is applied with a steel trowel or in case of thicker layers, with a trowel. First apply a thin layer and then build up to the desired thickness (max 25 mm / layer). After approx. 1 hour (+20 C, the mass is semi-hardened and can be smoothed and shaped. After approx. 3 hours (+20 C), the mass has dried and is ready for tiling or waterproofing.

### SAFETY

The product contains cement and can cause irritation. Avoid inhaling dust and use facial protection. Should the product get into your eyes, rinse immediately with water for 15 minutes and seek medical help. For further information, please see material safety data sheet.

### CONTACT US

TEL +46 (0)42-19 50 00  
info.se@bostik.com



## TECHNICAL DATA

Characteristics before use	
Binder	Special cement
Ballast	Light filler
Thickness	2-25 mm
Water amount	6 liters to 20 kg powder
Coverage	approx. 1,1 kg / kvm / mm
Time to use	30 - 40 minutes
Characteristics after use	
Coverable	approx. 3 hours (+20 C)
Colour	Grey
Cleaning of tools	Immediately with water
Storage	6 months in a dry, cool place in an unopened package

## CONTACT US

TEL +46 (0)42-19 50 00

[info.se@bostik.com](mailto:info.se@bostik.com)

