



8060 RAPID

White, fast-curing, flexible adhesive

2023-12

BENEFITS

- Cement-based floor and wall adhesive
- For indoor and outdoor use
- C2 FT-S1 (DIN EN12004)
- F: Fast-curing
- T: Adhesive, max. slip requirement 0.5 mm
- Based on white cement
- Suitable for most deformation-stable stone types
- Part of the ETAG 022 wet room system



PRODUCT DESCRIPTION

Bostik 8060 Rapid is a fast-curing, white, cement-based, flexible adhesive.

The adhesive has excellent adhesion properties and is particularly suitable for installing ceramic tiles and a wide range of natural stones. Approved for Bostik's waterproofing/wet room systems in accordance with the Swedish Ceramic Tile Council's regulations BBV 21:1.

AREA OF APPLICATION

Designed for installation of ceramic tiles, granite ceramics, glass and porcelain mosaics on suitable and stable indoor and outdoor surfaces as well as various types of natural stone on walls and floors. Can be used on various types of firm and clean surfaces, such as concrete, cement plaster, cement filler, plasterboard, suitable wet room boards together with Bostik waterproofing system. Bostik 8060 Rapid can be used with both electric and waterborne underfloor heating. For other surfaces, please contact Bostik AB.

TECHNICAL DATA

Working temperature	+5°C to +25°C – both tiles and surfaces
Application thickness	Max. 10 mm
Water consumption	3.6 L for 15 kg
Consumption	1.5 kg/m ² (4 mm adhesive trowel) 2.1 kg/m ² (6 mm adhesive trowel) 2.6 kg/m ² (8 mm adhesive trowel) 3.0 kg/m ² (10 mm adhesive trowel)
Adhesion time	Up to 10-15 min at 20°C
Application time	Approx. 30–40 min at 20°C
Can be grouted	Walls: approx. 3 hours Floors: after 3 hours
Can be walked on	After approx. 3 hours at 20°C
Fully loadable	24 hours at 20°C
EN 12004	C2 FT S1
Approvals	ETA, M1
Packaging	15 kg
Shelf life	6 months at 20°C in unopened packaging. Store in a dry and cool place.

Article number	Colour	Contents	Quantity per pallet:	EAN
30832250	White	15 kg	72	7311020025892

INSTRUCTIONS FOR USE

PREPARING THE SURFACE

Make sure that the surface is dry, free from dust, dirt, paint, glue residue, oil, grease, wax, etc., and is stable and firm. Loose layers, surfaces with unsatisfactory strength and any sludge layer should be removed mechanically. Board materials must be fixed properly in accordance with the applicable building code. Underfloor heating must be turned off and have a surface temperature of a max. +20°C.

The surface may be damp, but not wet, and should be +10°C to +20°C.

PRE-TREATMENT

Dry rooms: Absorbent surfaces should generally always be pre-treated with GRIP A560 Classic, applied once diluted with water 1:3 (primer:water). Two applications are recommended on highly absorbent surfaces. On floor plasterboards and suitable absorbent wet room boards, apply the primer diluted with water 5:1 (primer:water). Always start by measuring the water to get the right mixing ratio. Water temperature +5 to +20°C. Wet rooms: In wet rooms etc., the surface must always be treated with one of Bostik's waterproofing systems in accordance with applicable installation instructions.

MIXING AND APPLICATION

Walls: Mix 15 kg of powder with approx. 3.6 litres of clean, cold water, for floors you can go up to 3.8 litres. Stir vigorously with a whisk/machine to a homogeneous consistency. Wait for 2-3 minutes and stir again. The temperature of the adhesive should be between +10°C and +20°C so as not to affect the usage time and working time. Mixed adhesive can be used up to 40 minutes. Adhesive that has started to cure must not be remixed with more water. APPLICATION: Apply a thin layer of adhesive with the smooth side of the trowel for optimum adhesion (possibly another trowel) to the ceramic tile. Apply adhesive to the surface for approx. 10-15 minutes of tiling. Distribute the adhesive with the notched side of the trowel. The choice of adhesive trowel depends on the back and size of the tile.

Make sure that the temperature of the tiles is at least +5°C and that they are free of weak layers. Install the tile by pressing it firmly into the adhesive and moving it into place. The tiles can normally be corrected within 15 minutes. For demanding applications such as outdoor use, floors exposed to heavy use, adhesive should be applied to both the tile and the surface. Remove any adhesive that reaches more than half the depth of the joint. Residues and stains must be removed immediately with water or a damp cloth.

GROUTING

Grouting can normally be carried out after 3 hours. It is important that the adhesive is dry before grouting begins to prevent discoloration of the joint. Floors can be fully loaded after about 14 days.

ENVIRONMENT AND HEALTH

This product contains cement and is an irritant. All users must understand and use the safety data sheet before using the product. The safety data sheet can be obtained on request and is available on the manufacturer's website See also på www.bostik.se

RECYCLING

Waste generation should be avoided or minimised whenever possible. Empty containers may retain some product residue. Product and packaging must be disposed of safely. Hire an authorised waste management company to dispose of surplus products and non-recyclable products. Always dispose of this product in accordance with environmental protection requirements and waste management legislation. Avoid spreading spilled material, runoff, contact with soil, waterways and drains.

NOTE

Rooms that are temporarily exposed to moisture, e.g. in kitchens, hallways, etc., can be protected against moisture with Bostik Moisture Barrier 6030. Surfaces with direct contact with the ground or with a risk of additional moisture formation must be carried out in consultation with Bostik Technical Department.

NOTE: Do not apply any more adhesive to an area of surface than required for the tiles to be installed before the adhesive starts to harden. The adhesive must be protected from sunlight, high temperatures, strong ventilation, etc., as this reduces the working time significantly. Dehumidifiers and heating fans should not be used and underfloor heating should be switched off for 28 days after the tiles are laid and then gradually increased.

The information and recommendations provided in this document are based solely on Bostik's research and are not guaranteed to be exact. The performance of the product, its durability and its usage characteristics depend on multiple variables, including the type of material to which the product is to be applied, the environment in which the product is stored or applied and the equipment used for application. Changes to any of these variables may affect the performance of the product. Before using the product, the buyer must test the suitability of the product for the intended use under the conditions that will exist at the time of the intended use. Bostik does not guarantee the suitability of the product for a particular use. The product is sold in accordance with Bostik's terms and conditions of sale, which are included with the product at the time of sale. Nothing in this document should be construed to mean that no relevant patents exist or to constitute an authorisation, encouragement or recommendation to use any of the inventions covered by a patent without the permission of the owner of the patent.

SAFETY

For more information, see the safety data sheet at:
www.bostik.com

BOSTIK SERVICE

info.se@bostik.com
www.bostik.com

