

STIX A760 TECH

ULTRA-HIGH PERFORMANCE TACKIFIER ADHESIVE

BENEFITS/CHARACTERISTICS

- ✓ Enables smooth replacement of floor tiles
- ✓ Ultra-high performance, permanent tack
- ✓ Long adhesion time
- ✓ For absorbent and dense surfaces
- ✓ High spreading capacity – low coverage



AREA OF APPLICATION

PRODUCT DESCRIPTION

FIX A760 TECH is a water-based tackifier adhesive with very good tack for different types of flooring materials on both absorbent and dense surfaces. The adhesive has a long adhesion time, and the surface is tacky for a long time. Environmentally friendly with low emission values, compliant with emission class EC1 Plus.

USES

Tackifier adhesive for adhesion of dimensionally stable design flooring (LVT), in the form of tiles or planks, please refer to the list of approved suppliers. Can also be used on textile floor tiles and PVC tiles. The substrate may be a floor-plastered surface, chip-board or an old covering. For adhesion of LVT materials, the substrate must be of solid material, e.g. concrete or screed. PLEASE NOTE - certain LVT materials must be permanently glued with conventional floor adhesive to prevent dimensional changes when subjected to sunlight or heavy loads. For this type of adhesion we recommend that you use STIX A555 ULTRA, STIX A600 EVOLUTION, STIX A720 POWER or STIX A800 PREMIUM.

Recommended materials:

- ✓ LVT – tiles and planks
- ✓ Textile floor tiles
- ✓ PVC floor tiles
- ✓ Patterned textile flooring with felt backing

PRODUCT INFORMATION

ART. NO.	PACK SIZE	VOLUME	EAN
30619614	5 L	5 kg	7311020081119

PRODUCT CHARACTERISTICS

Colour	Pink
Density	1.0 kg/litre
Binder	Polymer dispersion of acrylate type
Adhesion time*	Normally absorbent surface: 45–60 min Dense surface: 2–2.5 hours
Open time*	Permanent tacky film (in dust-free conditions)
Walkable	Can be walked on immediately. Full strength is achieved after 12 hours.
Curing time	30–120 minutes
Coverage	5–10 m ² /L
Working conditions	Temperature at least +15°C. The best results are achieved at around 20°C with around 60% RH.
Storage/shelf life	12 months at +10 to +20°C. Protect against frost.

* These values are measured at +23°C with 50% relative humidity on a normally absorbent surface. These values may deviate from the above depending on the surface and temperature.



APPLICATION INSTRUCTIONS

PREPARING THE SURFACE

Always follow the flooring manufacturer's directions. The information below is only intended as supplementary information regarding the actual adhesion process. The surface must be clean, flat, strong and free of dust, dirt, glue residue and old paint. If you need to level out the surface, we recommend that you use a Bostik Floor Screed intended for the purpose. For adhesion to concrete surfaces, the moisture content must not exceed the maximum values specified in AMA Hus. The adhesive, floor covering and substrate should have a temperature of at least +15°C. The relative humidity (RH) in the substrate must not exceed 85% for concrete and 8-12% for chipboard. PLEASE NOTE! For adhesion of LVT materials, the substrate must be of solid material, e.g. concrete or screed. For non-absorbent surfaces such as high-performance concrete, we recommend application of at least a 10 mm thick layer of Bostik Floor Screed. For particularly absorbent surfaces we recommend the use of Bostik Primer 6000.

APPLICATION METHOD

ABSORBENT SURFACES: Apply the adhesive with a roller (approx. 12 mm) and allow it to dry for approx. 45-60 minutes. Install the flooring material as soon as possible to reduce the risk of dust gathering on the adhesive film. If the adhesive is to be used for permanent adhesion, allow it to dry for 5-10 minutes before installing the flooring material.

DENSE SURFACES: Apply the adhesive with a roller and allow it to dry for approx. 90-120 minutes until the adhesive no longer feels wet to the touch. Lay the flooring material on the adhesive. Press/rub out all of the air under the flooring material.

For best results, a floor roller should be used. NOTE - Always follow the flooring manufacturer's directions.

COVERAGE

5-10 m²/L depending on the surface and choice of application method. Apply with a roller.

STORAGE/SHELF LIFE

12 months in a dry, cool location in unopened packaging at a storage temperature between +10 to +20°C. The product should be stored frost-free.

CLEANING

With water before the adhesive has dried. Dried adhesive can be removed mechanically or with white spirit.

SAFETY

A safety data sheet is available on request. Always have the packaging or label at hand if you need to seek medical care. Keep the product out of the reach of children. If the adhesive comes into contact with your eyes, immediately rinse your eyes with water. If the adhesive comes into contact with your skin, wash your skin with soap and water. www.bostik.se

LIABILITY

Disclaimer: The technical data we report, as well as our instructions and recommendations, are all based on a variety of tests and on our experience. They are intended to help the user achieve the best possible results. As the conditions at the user's premises are beyond our control, we cannot accept any liability for the results achieved when using the product.

BOSTIK SERVICE

info.se@bostik.com
www.bostik.se

