



# GRIP A920 PREMIUM

PRIMER FOR SUB FLOOR PREPARATION INDOORS OR OUTDOORS 10/20/2022

## BENEFITS

- For indoor and outdoor use
- Quick-drying
- Approved for up-coming moisture
- Clean with water
- Water-based



## AREA OF APPLICATION

GRIP A920 PREMIUM is a primer for subfloor preparation of absorbent substrates indoors and outdoors before applying screed or ceramic tile adhesive. GRIP A920 PREMIUM is used to improve adhesion, reduce the substrate's suction power and as a dust binder.

The recommendations of the Swedish Flooring Trade Association (GBR) with regard to gluing must always be followed in terms of moisture, surface strength, etc. for the substrate.

### SUBSTRATE:

Suitable for non-absorbent surfaces that can be coated with Bostik Floor Screed or Ceramic Tile Adhesive.

\*The drying times stated presuppose +20°C and max. 50% RH and a certain exchange of air as well as RH in the substrate of less than 85%.

## TECHNICAL DATA

<b>Mixing ratio</b>	Ready to use
<b>Colour</b>	Light green
<b>Material consumption</b>	Approx. 200 g/m <sup>2</sup>
<b>Can be walked on after</b>	30-180 min

## INSTRUCTIONS FOR USE

### PREPARING THE SUBSTRATE

For best work results, the temperature in the room should be between +10°C and +25°C

**Cleaning:** Make sure that the substrate is free from dust, dirt, paint, adhesive residues, oil, grease, wax, etc. and that it is solid and hard without cracks on the surface or the like. Any sludge layer should be ground or milled away. Any ceramic floor covering should be fixed, and any homogeneous PVC carpeting should be fixed and should be degreased and ground. All residues of water-soluble floor adhesives should be removed. If unsure, contact Bostik for further advice.

### MIXING AND USE

**Application:** GRIP A920 PREMIUM must be stirred before use. Work the primer undiluted into the substrate with a brush. Avoid the formation of pools of primer. The primer must not be left exposed for more than 24 hours before tiling or levelling.

**NB!** In case of solar radiation, high temperature, strong ventilation or other factors that can accelerate the drying, the surface must be protected against drying too rapidly. Neither a dehumidifier nor a heating fan should be used.

## STORAGE

12 months in a dry, cool and unopened package. Protect against frost.

## ENVIRONMENT AND HEALTH

The contents of the product are, according to current legislation, not classified as hazardous to health or flammable, but all users must understand and use the safety data sheet before using the product. The safety data sheet is available on request and is available on the manufacturer's website

## RECYCLING

Waste generation should be avoided or minimised whenever possible. Empty containers may retain some product residues. Product and packaging must be disposed of safely. Hire an authorised waste management company to dispose of surplus products and non-recyclable products. Disposal of this product must always be in accordance with the requirements of environmental protection and legislation for waste management. Avoid spreading spilled material, runoff, contact with soil, waterways and drains.

## REMARKS

Clean tools with water before the primer is dry.

In the case of additional moisture and outdoors, the fixing and levelling compound must be suitable for this purpose.

For more information, refer to Bostik's construction descriptions.

Article number	Packaging	Quantity per pallet	EAN
30623201	5 KG bucket	60	7311020081492

## SAFETY

**For more information, see safety data sheets on:**  
[www.bostik.se](http://www.bostik.se)

Saving clause: The technical data we report, as well as our instructions and recommendations, are all based on a variety of tests and on our experience. They are intended to help the user achieve the best possible results. As the conditions at the user's premises are beyond our control, we cannot accept any liability for the results achieved when using the product.

## BOSTIK SERVICE

[info.se@bostik.com](mailto:info.se@bostik.com)  
[www.bostik.se](http://www.bostik.se)

