



GRIP A936 XPRESS

PRIMER FOR SUB FLOOR PREPARATION OF NON-ABSORBENT SURFACES

20/10/2022

BENEFITS

- **Excellent adhesion to non-absorbent substrates**
- **Approved for inside and outside use**
- **Contains quartz sand for better adhesion**
- **Suitable for outside use**
- **Low emission levels**
- **Clean with water**



AREA OF APPLICATION

GRIP A963 XPRESS is used as a primer on dense, smooth non-absorbent surfaces that are to be coated with screed or ceramic tile adhesive. Fixed ceramic floor covering and ground homogeneous PVC carpeting can be primed with GRIP A963 XPRESS before it is coated with tiles or clinker or levelling compound. GRIP A963 XPRESS is suitable as a primer for non-porous, non-absorbent concrete, terrazzo, natural stone or artificial stone.

The recommendations of the Swedish Flooring Trade Association (GBR) with regard to gluing must always be followed in terms of moisture, surface strength, etc. for the substrate.

SUBSTRATE:

Suitable for non-absorbent surfaces that can be coated with Bostik Floor Screed or Ceramic Tile Adhesive.

*The drying times stated presuppose +20°C and max. 50% RH and a certain exchange of air as well as RH in the substrate of less than 85%.

TECHNICAL DATA

| | |
|------------------------|------------------------------|
| Mixing ratio | Ready to use |
| Colour | Red |
| Material consumption | Approx. 100 g/m ² |
| Can be walked on after | 30-180 min |

INSTRUCTIONS FOR USE

PREPARING THE SUBSTRATE

For best work results, the temperature in the room should be between +10°C and +25°C

Cleaning: Make sure that the substrate is free from dust, dirt, paint, adhesive residues, oil, grease, wax, etc. and that it is solid and hard without cracks on the surface or the like. Any sludge layer should be ground or milled away. If unsure, contact Bostik for further advice.

MIXING AND USE

Application: GRIP A963 XPRESS . The primer should be applied evenly to the substrate with a short-bristle roller or brush. Avoid the formation of puddles during application. GRIP A963 XPRESS must be completely dry before the smoothing compound, ceramic tile adhesive or waterproofing compound is applied. The drying time is 0.5 – 3 hours depending on the substrate, temperature and exchange of air. The dry primer is reddish in colour and almost totally tack-free.

NB! In case of solar radiation, high temperature, strong ventilation or other factors that can accelerate the drying, the surface must be protected against drying too rapidly. Neither a dehumidifier nor a heating fan should be used.

STORAGE

12 months in a dry, cool and unopened package. Protect against frost.

ENVIRONMENT AND HEALTH

The contents of the product are, according to current legislation, not classified as hazardous to health or flammable, but all users must understand and use the safety data sheet before using the product. The safety data sheet is available on request and is available on the manufacturer's website

RECYCLING

Waste generation should be avoided or minimised whenever possible. Empty containers may retain some product residues. Product and packaging must be disposed of safely. Hire an authorised waste management company to dispose of surplus products and non-recyclable products. Disposal of this product must always be in accordance with the requirements of environmental protection and legislation for waste management. Avoid spreading spilled material, runoff, contact with soil, waterways and drains.

REMARKS

Clean tools with water before the primer is dry.

For more information, refer to Bostik's construction descriptions.

| Article number | Packaging | Quantity per pallet | EAN |
|----------------|-------------|---------------------|---------------|
| 30623633 | 5 kg bucket | 51 | 7311020081485 |

SAFETY

For more information, see safety data sheets on:
www.bostik.se

Saving clause: The technical data we report, as well as our instructions and recommendations, are all based on a variety of tests and on our experience. They are intended to help the user achieve the best possible results. As the conditions at the user's premises are beyond our control, we cannot accept any liability for the results achieved when using the product.

BOSTIK SERVICE

info.se@bostik.com
www.bostik.se

