



# Ultra Fino Skimcoat

## CONCRETE SURFACE FINISHER

### DESCRIPTION

UltraFino Skimcoat cement-based powder for thin plastering applications. When mixed with water, the smooth creamy consistency makes it easy to correct surface imperfections prior to painting.

### FEATURES AND BENEFITS

- Excellent workability
- Good adhesion to concrete surfaces
- No cracking or flaking
- Minimal powdering of surface when sanded
- No primer needed (for White finish)

### RECOMMENDED USES

- For EXTERIOR and INTERIOR plastered concrete applications. (Surface of walls, ceilings, beams and columns)
- For pre-cast and formed concrete

### PREPARATION & USE

- Surface must be structurally sound, clean and free from dust, oil, paint, grease and other contaminants.
- For holes that are more than 2mm deep, pre-patching and filling is required or build-up application may be employed.

### MIXING

1. Into a clean plastic container, pour the amount of UltraFino Skimcoat needed for the job at hand and considering a potlife of 3-5 hours.
2. Mix by hand or by a low speed (300rpm) mechanical mixer for 2-3 minutes. Mix thoroughly to a smooth lump-free consistency.
3. Let stand for 15 minutes and mix occasionally during use. Sufficient water can be added if the mixture becomes dehydrated.

### APPLICATION

1. Damp the substrate with water.
2. UltraFino Skimcoat can be applied onto the substrate using a flat-edge steel trowel.
3. To increase thickness, a second coat may be applied just before the first coat is about to set.
4. When sanding, use sandpaper 120 or above.

### COVERAGE

1 – 1.2 Kg UltraFino Skimcoat per Sqm area, per mm thickness.



### Area Covered per 20Kg Bag

Thickness	
1mm	20 sqm
2mm	10 sqm

### Physical Properties

Form	Form
Color	White or Grey
Setting Time	30 minutes to 1 hour (depending on weather conditions)
Pot Life	3-5 hours
Curing Time	12-48 hours
Thickness	Featheredge 0 – 2mm

### PACKAGING

20-Kg Bag

### STORAGE

Store in a cool, dry place and away from direct sunlight

### **SHELF LIFE**

Twelve (12) months from manufacturing date

### **HEALTH AND SAFETY**

Wear appropriate respirators and safety glasses. Keep out of reach of children.

Refer to Material Safety Data Sheet for more information on Health and Safety.

### **DISCLAIMER:**

The information in this Technical Data Sheet is intended for the assistance of users and is of a general nature. It reflects the extent of our knowledge and experience of our products and is based on tests which we believe to be reliable. However, no guarantee of accuracy can be given due to the wide range of surfaces, environmental and field conditions and variations encountered in raw materials, manufacturing equipment and methods at the place where the work is performed. Some of these will be beyond our knowledge and control. Users are asked to make sure that the TDS in their possession is the latest issue. Likewise, we recommend users carry out their own tests to determine the suitability of the product for their particular purposes.

Any claim for a defective product must be filed within 30 days of discovery of a problem and must be submitted with written proof of purchase. Claims are not transferrable or assignable and extend only to the original purchaser/user. Bostik reserves the right to inspect alleged failure and no responsibility will be accepted unless Bostik is given the opportunity to do so. Bostik limits its liability to the replacement of the product/s proven faulty.

### **BOSTIK PHILIPPINES, INC.**

35/F Penthouse Raffles Corporate Center  
F. Ortigas Jr. Road, Ortigas Business Center  
Pasig City Philippines  
Tel No: +63 2 900 5856 | Fax: +63 2 900 5616

**BOSTIK HOTLINE**

**Smart help +63 2 900 5656**

