

GUIDE

- FLYTSPACKEL
- TUNNFLYT
- INDUSTRI

	SL C300 THICK FLOW	SL C400 FIBER	SL C500 FIBER QUICK	SL C600 EVOLUTION	SL C655 FIBER MAXI	SL C700 FIBER QUICK+	SL C620 FLEXI	SL C800 LEVEL+	SL C900 INDUSTRY HEAVY
	FLYTSPACKEL						TUNNFLYT	INDUSTRI	
EGENSKAPER									
Självtrökande		x	x	x	x	x	x	x	x
Normaltrökande	x								
Cementbaserad	x	x	x	x	x	x	x	x	x
Fiberförstärkt		x	x	x	x	x			
Lättbetong	x								x
Gipsskivor/anpassade våtrums- & golvskivor		x	x	x	x	x	x	x	x
Klinker/sten	x	x	x	x	x	x	x	x	x
Trä-/golvspånplattor		x	x	x	x	x	x	x	x
Inspacklade värmeslingor		x	x	x	x	x			
Värmeslingor i betong	x	x	x	x	x	x	x	x	x
Flytande konstruktioner	x	x	x	x	x	x			x
Svaga underlag									x
Krympfri									x
TEKNISK DATA									
Pumpbar	x	x	x	x	x	x	x	x	x
Klarar tillskjutande fukt				x		x			x
Tryckhållfasthet	C25	C30	C30	C30	C30	C30	C30	C30	C30
Böjdraghållfasthet	F5	F8	F8	F8	F8	F8	F8	F8	F8
Skiktjocklek mm	8-50	6-60	4-40	4-50	6-50	4-50	3-20	2-10	3-30

