

SPECIAL FLOORING



STIX P956 2K
2-PART POLYURETHANE ADHESIVE FOR BONDING FLEXIBLE AND RIGID FLOOR COVERINGS

- Exceptional performance (high adhesion and cohesion).
- Resistance to moisture (suitable for use in wet areas: kitchens)
- Weather resistance (Collages outdoors) up to 120 ° C.
- Adheres on a large number of substrates: concrete, metals, smoothing coatings
- Waiting time: none
- Open time: 60 minutes
- Walk-on time: Around 24 hours



HARDWOOD ADHESIVE



WOOD H180 CLASSIC
UNIVERSAL HIGH PERFORMANCE HYBRID ADHESIVE FOR ALL PARQUET TYPES

- Fast setting and high performance adhesive Excellent mechanical performance
- Permanently elastic at temperatures from -40°C to 120°C
- Resistance to moisture
- Practical packaging: 7 kg Pouch, long storage: 18 months
- Waiting time: none
- Open time: 50 minutes
- Walk-on time: Around 12 hours depend on traffic



PANEL ADHESIVE



ARDAFLEX MULTI
MULTI-PURPOSE 1C HYBRID

- On Wall & floor surfaces
- On metal, aluminum, steel
- Ready to use
- Excellent adhesion
- Ready to use
- Waiting time: 12 hours
- Suitable for FR Panel
- Suitable for use on underfloor heating
- Applicable for tile on tile.
- Packed in minimum Pouch



SELECTION GUIDE

	HYTEC E326	GRIP A926	GRIP A500	GRIP A370	SL C320	SL C510	SL C740	SL C860
Screed & concrete floor	•		•	•	•	•	•	•
Concrete surfaced helicopter finish, precast concrete (stairs)	•	•	•	•	•	•	•	•
Sanded and degreased floor paint		•		•			•	
Floor ceramic tiles	•	•	•	•	•	•	•	•
Semi-flexible slabs		•	•			•	•	
Traces of glues		•	•	•	•	•	•	•
Outdoor	•		•				•	•
Metal surface	•						•	



STIX A100 STIX A200 STIX A800 STIX A790 FIX A760 CONTACT N925 SPORTCOL 2K STIX P956 BOSTIK ROLL 25-50-85 BOSTIK ROLL 240 BOSTIK ROLL 740 BOSTIK ROLL RF50 / RF100 ARDAFLEX MULTI

	STIX A100	STIX A200	STIX A800	STIX A790	FIX A760	CONTACT N925	SPORTCOL 2K	STIX P956	BOSTIK ROLL 25-50-85	BOSTIK ROLL 240	BOSTIK ROLL 740	BOSTIK ROLL RF50 / RF100	ARDAFLEX MULTI
Carpets (Action Bac®, coco, sisal)	•	•	•		•	•			•	•	•	•	•
PVC Heterogeneous	•	•	•		•			•	•	•	•	•	•
PVC Homogeneous		•	•					•	•	•	•	•	•
PVC on old PVC		•	•		•			•	•	•	•	•	•
PVC in shower		•	•					•	•	•	•	•	•
LVT			•					•	•	•	•	•	•
Linoleum			•					•	•	•	•	•	•
Linoleum Acoustic			•					•	•	•	•	•	•
Rubber			•					•	•	•	•	•	•
Rubber up to 3.5mm			•					•	•	•	•	•	•
Conductive flooring (PVC, rubber etc.)				•				•	•	•	•	•	•
Removable flooring					•						•	•	
Turf indoor		•	•			•	•	•					
Turf outdoor							•	•					
Stairs/skirtings						•			•	•			
Wall Protection Panels		•	•			•			•	•			
Panel Adhesive													•



BOSTIK ROLL 25/50/85
SPECIAL SKIRTING ADHESIVE

- 3 widths: 25, 50 and 85 mm in roll of 50 m.
- Fast and lasting fixation.
- Ultra resistant.
- Fast, easy and clean.
- Immediate commissioning.
- Does not alter the PVC.
- High temperature resistance (-40 ° C to + 120 ° C)



BOSTIK ROLL 240
STAIR SPECIAL ADHESIVE

- Width 240 mm in roll of 25 m.
- Suitable for the installation of integral steps.
- Fast and lasting fixation.
- Ultra resistant.
- Fast, easy and clean.
- Opening to immediate walking.
- Does not alter the PVC.
- High temperature resistance (-40 ° C to + 120 ° C)



BOSTIK ROLL 740/50
SPECIAL ADHESIVE

- Width 740 mm in roll of 25 m + small roll 50 mm x 25 m.
- Close clean, fast and easy without bubbling.
- Complementary roll provided.
- Fast subsequent removal.
- Circularly during the construction.
- Opening to immediate walking.



BOSTIK ROLL RF50 / RF100
SPECIAL FLOOR RENOVATION

- Width 48 mm and 96 mm in roll of 25 m.
- Close clean, fast and easy without bubbling.
- Fast subsequent removal.
- Opening to immediate walking.
- Does not alter the PVC.



Arkema Middle East DMCC
Unit 1108, JBC3 Tower Cluster Y, JLT
Dubai, United Arab Emirates
E-mail: bostik.mena-info@bostik.com
Phone: +971 4 875 1700
www.bostik.com



www.bostik.com

BOSTIK
Smart solutions for professional flooring

HUMIDITY BARRIER SYSTEM



HYTEC E336 XTREM MOISTURE BARRIER EPOXY SYSTEM

- Creates a unique barrier, preventing rising moisture from screed
- Protects from all levels of moisture, even for 100% saturated damp substrates
- High mechanical resistance properties
- Proven effectiveness over a period of 25 years
- New buildings, refurbishing operations, all job types
- Compressive strength: 75 MPa
- Tensile strength: 45 MPa



500/1000
g/m² 5 KG
25 KG



GRIP A936 XTREM HIGH PERFORMANCE REINFORCED PRIMER FOR NON-ABSORBENT SUBFLOORS

- Time saving for the humidity barrier process: substitutes sand blasting plus priming operations in damp substrates
- Hytec E336 Xtrem process
- Appearance of dry film: rough surface ensuring self-levelling adherence
- High performance primer for all non-porous subfloors



SLC
2 hours
dry surface 80/120
g/m² 20 KG

PRIMERS



GRIP A310 PROJECT ACRYLIC PRIMER FOR INDOOR FLOOR USES

- To regulate the porosity on cementitious subfloors
- Ready to spread, without any dilution
- Odor free : can be used everywhere, even in occupied premises
- Non flammable
- Quick drying time



SLC
30 - 60
hours
dry surface WHITE
resistant to
stains 20 KG



GRIP A500 MULTI PRIMER FOR POROUS AND NON POROUS SURFACES

- Highly effective resin based primer for floors and walls indoor and floors outdoor
- Guarantees levelling compounds adhesion for all types of traffic areas, such as malls, hotels, airports and railway stations, etc.
- Odorless, can be used in all types of premises



SLC
1 - 2
hours
dry surface BLUE
with maximum
resistance to
stains 20 KG

SELF LEVELING COMPOUNDS



SL C320 ARDASOL SELF-LEVELLING COMPOUND FOR INDOOR USE IN ALL TYPES OF PREMISES

- Excellent surface finish without sanding
- Smooth all concrete substrates, cements and old tiles
- Use in premises with light & heavy traffic
- Compressive strength: 20 MPa (>28 days)



1-10 mm 4 to 6
hours 1.5
kg/m²/mm 25 KG



SL C510 PRO HEAVY-DUTY SELF-LEVELLING COMPOUND FOR USE ON INTERNAL FLOORS

- Very high mechanical resistance with no shrinkage
Suitable for supermarkets and hypermarkets
- No sanding
- Compressive strength: 30 MPa (>28 days)



1-20 mm 3 to 5
hours 1.5
kg/m²/mm 25 KG



SL C740 FIBERMAXI FIBRE-REINFORCED HEAVY-DUTY SELF-LEVELLING COMPOUND

- Heavy-duty thickness
- Suitable for use on external covered floors
- Very high mechanical resistance with no shrinkage



1-10 mm 4 to 6
hours 1.5
kg/m²/mm 25 KG



SL C980XPS FAST DRYING SELF LEVELLING COMPOUND FOR INDOOR AND OUTDOOR USE IN VERY HEAVY TRAFFIC

- All uses: Indoor / Outdoor, heavy or light loads, rolling or static loads. Withstands movement of heavy equipment specifically suited to mass retail, industrial, hospitals, parking
- All finishes: Polyurethane paint, Epoxy paint, Flexible or rigid bonded flooring (rubbers, parquet, tiles, etc ...)
- Pure without finishing
- Very high resistance to abrasion and punching
Compressive strength: 37 MPa (>28 days)



3-15 mm 1
hour 1.6
kg/m²/mm 25 KG

SOFT FLOOR ADHESIVES



STIX A100 PROJECT SOLVENT FREE ACRYLIC ADHESIVE

- PVC & Carpet floorings
- For residential premises, offices & areas with moderate traffic
- Solvent-free, odorless, low VOC class A+
- Waiting time: 10 to 15 minutes
- Open time: 40 to 45 minutes
- Walk-on time: Around 18 hours



20/100
g/m² 20 KG



STIX A200 MULTIVINYL HIGH GRIP SOLVENT FREE ACRYLIC ADHESIVE - SPECIAL PROJECTS

- PVC Heterogeneous & Homogeneous, Carpet floorings, PVC on old PVC
- For premises with heavy traffic (hospitals, schools, shopping premises, offices)
- Bonding wall and floor coverings
Suitable for WETROOM PVC concept
- Waiting time: 5 to 10 minutes
- Open time: 40 to 55 minutes
- Walk-on time: Around 18 hours



20/100
g/m² 6 KG
20 KG



STIX A800 PREMIUM HIGH PERFORMANCE SOLVENT FREE ACRYLIC ADHESIVE

- PVC, Expanded vinyl, Semi-flexible tiles, LVT in planks or tiles, Linoleums, Carpets, rubber flooring
- PVC on non porous surface e.g. metal
- Waiting time: 10 to 15 minutes
- Open time: 60 minutes
- Walk-on time: Around 12 hours



20/100
g/m² 6 KG
18 KG



STIX A970 ELECTRO CONDUCTIVE ADHESIVE

- For installation of conductive and static dissipative Anti Static floor coverings,
- Designed for sticking down PVC, carpet, and rubber coverings
- Waiting time: 10 to 15 minutes
- Open time: 45 to 60 minutes
- Walk-on time: Around 24 hours



30/500
g/m² 12 KG



FIX A760 TECH PRESSURE SENSITIVE ADHESIVE - REMOVABLE FLOORINGS

- Double functions : pressure sensitive adhesive and wet-set adhesive
- Permanent residual tackifying effect, no time limit
- Suitable on old PVC flooring or non-porous surfaces (e.g. metal)
- Waiting time (Porous): 30 to 45 min
- Waiting time (Non-Porous): 90 to 120 min
- Open time: No limit (if dust free)
- Walk-on time: Around 12 hours



10/120
g/m² 2 KG
5 KG
19 KG



CONTACT N525 MULTI SPECIAL NEOPRENE GLUE

- Designed for heavy-duty areas
- Long working time
- Suitable on vertical surfaces (e.g. stair risers & skirtings)
- Waiting time: 5 to 15 minutes
- Open time: 45 to 60 minutes
- Walk-on time: Immediately



150 g/m²
/face 1 Ltr
5 Ltr
15 Ltr