




# FLOORING SYSTEMS

by market segments




# INTRO

## OUR TEAM IS YOUR TEAM

Each building has specific features depending on its use, constraints and environment. This new guide highlights Bostik flooring systems and offers a precise solution to the most demanding technical needs. It shows a specific approach by six major market segments to meet the requirements of each type of building: **HEALTHCARE, EDUCATION, HOSPITALITY, WORKPLACE, STORES AND RESIDENTIAL.** For each segment, we have identified several technical cases along with the appropriate Bostik solution associated.

This guide is dedicated to the various players in the building sector: contractors, installers, architects, engineering offices and all Bostik partners. Our high competitive global team will provide key resources and solutions for each market segment! We introduce your Bostik ACADEMY, which will serve as a digital tool and online platform to boost our immediate availability to you and your end customer. You will find all of our technical solutions, from the support to the final covering. You will find tips and key recommendations not to be missed for a successful installation!

OUR BOSTIK TEAM REMAINS AT YOUR DISPOSAL AND STAYS BY YOUR SIDE ON YOUR CONSTRUCTION PROJECTS.











# HEALTHCARE

In hospitals, surfaces must be strong, resistant and durable. At the same time, they must be easy to clean and maintain, particularly in clean rooms like operating rooms. Flooring systems must always be chosen according to the type of floor covering and the type of use. Our systems meet environmental requirements and allow preserving the indoor air quality.


BOSTIK has always been developing high-performance and long-lasting solutions that meet the installation requirements of specific healthcare facilities:

- **CLEAN, HIGH-PERFORMANCE AND LONG-LASTING**
- **WET ROOM VINYL SYSTEMS**
- **FULL FLOOR AND CAPPING & COVING**
- **STAIR NOSING INSTALLATION**
- **CONTROLLING ELECTROSTATIC CHARGES**
- **HEAVY TRAFFIC**
- **WALL PROTECTIVE PANNELS**






# HEALTHCARE FLOORING SYSTEMS SOLUTIONS




**CLEAN, HIGH-  
PERFORMANCE  
AND LONG-  
LASTING**  
● 10



**WET ROOM  
VINYL SYSTEMS**  
● 12



**FULL FLOOR  
AND CAPPING  
& COVING**  
● 16



**STAIR NOSING  
INSTALLATION**  
● 18



**CONTROLLING  
ELECTROSTATIC  
CHARGES**  
● 20



**HEAVY  
TRAFFIC**  
● 22



**WALL  
PROTECTIVE  
PANELS**  
● 24



# CLEAN, HIGH-PERFORMANCE AND LONG-LASTING

COVERING: HOMOGENEOUS PVC SHEET

Healthcare institutions are sensitive areas, which require eco-responsible and high-performance products that can meet the requirements of heavy traffic or specific constraints such as medical beds or floor cleaning machines. Bostik offers products with very low VOC emissions (EC1+) that contribute to preserve the indoor air quality in the buildings. These products are solvent-free and phthalate-free, which also allow the application in the presence of public.

## FLOOR PREPARATION

### 1 HYTEC A370 RAPID

1K RAPID DAMP PROOF  
MEMBRANE TO SUPPRESS  
RESIDUAL MOISTURE

- EASY TO USE:  
ROLLER APPLICATION
- NO PRIMING REQUIRED
- UP TO 95% RH  
AND 5% CM METHOD

#### CHARACTERISTICS

- Coverage: 300 g/m²
- Color : applied blue and dried black

▶ Watch on Bostik ACADEMY

### 2 SL C510 PRO

HEAVY-DUTY SELF  
LEVELLING COMPOUND

- HIGH MECHANICAL  
RESISTANCE,  
NO SHRINKAGE
- SUITABLE FOR  
SUPERMARKETS
- NO SANDING

#### CHARACTERISTICS

- Application thickness: 1 – 20 mm
- Coverage: 1,5 kg/mm/m²
- C30/F7

▶ Watch on Bostik ACADEMY

## SOFT FLOOR ADHESIVE

### 3 STIX A800 PREMIUM

ULTRA HIGH PERFORMANCE  
ADHESIVE FOR ALL TYPES OF  
SOFT FLOOR COVERINGS

- IDEAL FOR LVT AND RUBBER
- SHORT DRYING TIME
- HIGH INITIAL GRAB

#### CHARACTERISTICS


- Waiting time: PVC: 10 – 15 min / Rubber: 5 min
- Open time: PVC: 60 min / Rubber: 30 min
- Coverage: 240 – 400 g/m²




▶ Watch on Bostik ACADEMY



## SUPPRESS RESIDUAL MOISTURE



**HYTEC A370 RAPID**  
Two coats must be applied  
and will provide protection  
up to a maximum hygrometer  
reading of 95% RH / 5,5% cm.





# WET ROOM VINYL SYSTEMS

COVERING: WALL — VERY THIN HETEROGENEOUS PVC  
FLOOR — COMPACT PVC ANTI-SLIP

The shower system concept is specially designed for health and elderly care facilities. It integrates floor and wall coverings. Bostik offers a complete, tailor-made and high-performance solution for the implementation of this specific system.



## FLOOR PREPARATION

### 1 TECHNIS C560 RAPID

READY-TO-USE RAPID DRYING SCREED FOR SLOPES

- IDEAL FOR SLOPES IN SHOWERS
- SUITABLE FOR SUPERMARKETS
- RAPID COVERING AND DRYING

#### CHARACTERISTICS

- Application thickness: 5 - 60 mm
- Coverage: 2 kg/mm/m²
- C40/F7

Watch on Bostik ACADEMY

### 2 GRIP A500 MULTI

MULTI-PURPOSE PRIMER FOR NEW WORK AND RENOVATION

- FACILITATES APPLICATION OF SMOOTHING COMPOUNDS
- NON-ABSORBENT AND ABSORBENT SURFACES
- ODOURLESS, READY TO USE

#### CHARACTERISTICS

- Coverage: 90-100 g/m²



Watch on Bostik ACADEMY

### 3 SL C320 ARDASOL

STANDARD SELF-LEVELLING COMPOUND FOR USE ON INTERNAL FLOORS

- SELF-LEVELLING
- NO SHRINKAGE
- EXCELLENT SURFACE FINISH

#### CHARACTERISTICS

- Application thickness: 1-10 mm
- Coverage: 1.5 kg/mm/m²
- C20



Watch on Bostik ACADEMY

## SOFT FLOOR ADHESIVE

### 4 STIX A200 MULTI VINYL

MULTI-PURPOSE ADHESIVE FOR ALL PVC COVERINGS

- RAPID CURING
- HIGH INITIAL GRAB
- PVC BONDING ON OLD PVC

#### CHARACTERISTICS

- Waiting time: 10 - 15 min
- Open time: 45 - 50 min
- Coverage: 250 - 400 g/m²

Watch on Bostik ACADEMY

### 5 BOSTIK ROLL SD50

THIN ADHESIVE STRIP SPECIALLY DESIGNED FOR USE WITH PVC WALL COVERINGS IN SHOWER UNITS

- IMMEDIATE GRIP AND EXTRA-STRONG
- VERY THIN, NO BULGES
- QUICK, EASY AND CLEAN INSTALLATION

#### CHARACTERISTICS

- Reel widths: 48 mm
- Reel length: 50 m

### 6 BOSTIK ROLL 25/50/85

REINFORCED ADHESIVE STRIP FOR FITTING ALL TYPES OF SKIRTING, ACCESSORIES AND PROTECTIVE WALL PANELS AND FOR COVING UP FLOOR COVERING TO FORM SKIRTING


- IMMEDIATE GRIP AND EXTRA-STRONG
- QUICK, EASY AND CLEAN INSTALLATION
- NO WAITING TIME REQUIRED

#### CHARACTERISTICS

- Reel widths: 25 or 50 or 85 mm
- Reel length: 50 m




## BONDS CORNERS IN SHOWER UNITS



BOSTIK ROLL SD50  
Only for external corners.




## INSTALLATION CAPPING & COVING




### BOSTIK ROLL 25/50/85

- 1 — Choose the width of the strip according to the height of the skirting board.
- 2 — Fit the tape ensuring a straight line.



- 3 — Apply pressure and release the tape.
- 4 — Fit accessories according to the relevant position.



- 5 — Roll vinyl into position.







MOISTURE  
RESISTANT  
PLASTERBOARD

BOSTIK ROLL  
SD50



BOSTIK ROLL  
25/50/85



STIX A200  
MULTI VINYL



VERY THIN  
HETEROGENEOUS PVC

COMPACT PVC  
ANTI-SLIP

CONCRETE FLOOR

TECHNIS C560  
RAPID



GRIP A500  
MULTI



SL C320  
ARDASOL



STIX A200  
MULTI VINYL





# FULL FLOOR AND CAPPING & COVING

COVERING: RUBBER SHEET

The installation of a floor covering in a hospital environment requires a skirting board finish in order to meet the strict health requirements. Bostik offers a complete solution for the installation of flooring in hospital rooms with sustainable and high-performance products. The BOSTIK ROLL range ready-to-use is the ideal solution for this type of installation: quick, easy and clean. These products are solvent-free and phthalate-free.

## FLOOR PREPARATION

### 1 GRIP A500 MULTI

MULTI-PURPOSE PRIMER FOR NEW WORK AND RENOVATION

- FACILITATES APPLICATION OF SMOOTHING COMPOUNDS
- NON-ABSORBENT AND ABSORBENT SURFACES
- ODOURLESS, READY TO USE

#### CHARACTERISTICS

- Coverage: 90-100 g/m²



Watch on Bostik ACADEMY

### 2 SL C510 PRO

HEAVY-DUTY SELF-LEVELLING COMPOUND FOR USE ON INTERNAL FLOORS

- VERY HIGH MECHANICAL RESISTANCE WITH NO SHRINKAGE
- SUITABLE FOR SUPERMARKETS AND HYPERMARKETS
- NO SANDING

#### CHARACTERISTICS

- Application thickness: 1 - 20 mm
- Coverage: 1.5 kg/mm/m²
- C30/F7

Watch on Bostik ACADEMY

## SOFT FLOOR ADHESIVE

### 3 STIX A800 PREMIUM

ULTRA HIGH PERFORMANCE ADHESIVE FOR ALL TYPES OF SOFT FLOOR COVERINGS

- IDEAL FOR LVT AND RUBBER
- SHORT DRYING TIME
- HIGH INITIAL GRAB

#### CHARACTERISTICS

- Waiting time: PVC: 10 - 15 min / Rubber: 5 min
- Open time: PVC: 60 min / Rubber: 30 min
- Coverage: 240 - 400 g/m²



Watch on Bostik ACADEMY

### 4 BOSTIK ROLL 25/50/85

REINFORCED ADHESIVE STRIP FOR FITTING ALL TYPES OF SKIRTING, ACCESSORIES AND PROTECTIVE WALL PANELS AND FOR COVING UP FLOOR COVERING TO FORM SKIRTING

- IMMEDIATE GRIP AND EXTRA-STRONG
- QUICK, EASY AND CLEAN INSTALLATION
- NO WAITING TIME REQUIRED

#### CHARACTERISTICS

- Reel widths: 85 mm
- Reel length: 50 m






# STAIR NOSING INSTALLATION

COVERING: PVC INTEGRATED STEP


The installation of stair nosing ensures the safety for users. Bostik offers two complementary products: the first one for the installation of soft floor covering and the second one for the installation of stair nosings. The STIX A200 MULTI VINYL adhesive offers good mechanical performance. It allows an initial grab to immediately lay the floor covering on the flat step and riser. BOSTIK ROLL MT35 is a double-sided high-performance and multi-purpose adhesive on foam, ideal to perfectly maintain the stair nosing.




## INSTALLATION OF STAIR NOSING



**1 – BOSTIK ROLL MT35**  
Apply the Bostik Roll MT35 on the board of the flat step. (and not on the riser)



**2 –** Apply the stair nosing on the Bostik Roll MT35. The stair nosing has to cover the edge of the covering.



**3 –** Apply the covering on the flat step until the Bostik Roll MT35

### SOFT FLOOR ADHESIVE

**1 STIX A200 MULTI VINYL**  
MULTI-PURPOSE ADHESIVE FOR ALL PVC COVERINGS

- **RAPID CURING**
- **HIGH INITIAL GRAB**
- **PVC BONDING ON OLD PVC**

#### CHARACTERISTICS

- Waiting time: 10 - 15 min
- Open time: 45 - 50 min
- Coverage: 250 - 400 g/m²


Watch on Bostik ACADEMY

**2 BOSTIK ROLL MT35**  
REINFORCED ADHESIVE STRIP FOR FITTING ALL TYPES OF SKIRTING, ACCESSORIES AND PROTECTIVE WALL PANELS AND FOR COVING UP FLOOR COVERING TO FORM SKIRTING

- **IMMEDIATE GRIP AND EXTRA-STRONG**
- **QUICK, EASY AND CLEAN INSTALLATION**
- **NO WAITING TIME REQUIRED**

#### CHARACTERISTICS

- Reel widths: 85 mm
- Reel length: 50 m





# CONTROLLING ELECTROSTATIC CHARGES

## COVERING: ELECTROSTATIC DISSIPATIVE FLOORING

Operating room requires a specific system for the removal of electrostatic charges from the floor to protect precision electronic equipment. A suitable dissipative floor covering should be used. Bostik offers a complementary system, including the conductive adhesive STIX A970 ELECTRO, specially formulated with carbon fibres to ensure conductivity that helps to eliminate electrostatic charges. It is also recommended to apply a high-performance levelling compound to support the heavy loads specific to this type of room.

### FLOOR PREPARATION

#### 1 GRIP A500 MULTI

MULTI-PURPOSE PRIMER FOR NEW WORK AND RENOVATION

- FACILITATES APPLICATION OF SMOOTHING COMPOUNDS
- NON-ABSORBENT AND ABSORBENT SURFACES
- ODOURLESS, READY TO USE

#### CHARACTERISTICS

- Coverage: 90-100 g/m²



▶ Watch on Bostik ACADEMY

#### 2 SL C510 PRO

HEAVY-DUTY SELF-LEVELLING COMPOUND

- HIGH MECHANICAL RESISTANCE, NO SHRINKAGE
- SUITABLE FOR SUPERMARKETS
- NO SANDING

#### CHARACTERISTICS

- Application thickness: 1 - 20 mm  
- Coverage: 1,5 kg/mm/m²  
- C30/F7

▶ Watch on Bostik ACADEMY

### SOFT FLOOR ADHESIVE

#### 3 STIX A970 ELECTRO

CONDUCTIVE ADHESIVE FOR ELIMINATING ELECTROSTATIC LOADS

- GOOD INITIAL GRAB
- PRIMING NOT REQUIRED
- FLAWLESS ELECTRICAL CONDUCTIVITY

#### CHARACTERISTICS

- Waiting time: 10 - 15 min  
- Open time: 40 - 45 min  
- Coverage: 400 - 550 g/m²




#### 4 BOSTIK ROLL 25/50/85

REINFORCED ADHESIVE STRIP FOR FITTING ALL TYPES OF SKIRTING, ACCESSORIES AND PROTECTIVE WALL PANELS AND FOR COVING UP FLOOR COVERING TO FORM SKIRTING

- IMMEDIATE GRIP AND EXTRA-STRONG
- QUICK, EASY AND CLEAN INSTALLATION
- NO WAITING TIME REQUIRED

#### CHARACTERISTICS

- Reel widths: 85 mm  
- Reel length: 50 m





HEAVY TRAFFIC

COVERING: HOMOGENEOUS SHEET PVC

In hospitals, areas subject to very high mechanical stress requires high resistant covering due to heavy loads (classified as P4). Bostik offers a very high performance system combining a high strength C30F7 levelling compound and a two-component polyurethane adhesive resistant to high mechanical stress and humidity.

FLOOR PREPARATION

1 HYTEC E336 XTREM

VERY HIGH-PERFORMANCE 2K EPOXY DAMP PROOF MEMBRANE

- MOISTURE LEVEL: NO LIMIT
- RESISTS TO HYDROSTATIC PRESSURE
- RADON BARRIER

CHARACTERISTICS

- Coverage: B2 trowel if residual damp <6,5%: 400 g/m² C1 trowel if residual damp > 6,5%: 800 g/m²
- Sand: 3 to 4 kg/m²
- Color: clear amber

Watch on Bostik ACADEMY

2 GRIP A936 XPRESS

HIGH-PERFORMANCE SPECIAL PRIMER FOR NON-ABSORBENT SURFACES

- FAST DRYING
- HIGH GRIP: CONTAINS QUARTZ
- EASY TO USE: ROLLER APPLICATION

CHARACTERISTICS

- Coverage: 180 – 120 g/m² per layer



Watch on Bostik ACADEMY

3 SL C510 PRO

HEAVY-DUTY SELF LEVELLING COMPOUND

- HIGH MECHANICAL RESISTANCE, NO SHRINKAGE
- SUITABLE FOR SUPERMARKETS
- NO SANDING

CHARACTERISTICS

- Application thickness: 1 - 20 mm
- Coverage: 1,5 kg/mm/m²
- C30/F7

Watch on Bostik ACADEMY

SOFT FLOOR ADHESIVE


4 STIX P956 2K

TWO-COMPONENT POLYURETHANE ADHESIVE FOR FLOOR COVERINGS

- VERY HIGH BONDING PERFORMANCE
- MOISTURE AND HEAT RESISTANT
- INDOOR - OUTDOOR

CHARACTERISTICS

- Open time: 1h
- Coverage: 300-900 g/m²
- Color: yellow/ light brown





## WALL PROTECTIVE PANELS

## COVERING: PROTECTIVE PANELS

To protect walls and circulation in sterile and sensitive environments, several solutions are possible: wall protection plate, corners, headboards... Bostik offers multiple solutions depending on the type of material and quality of the substrate to apply these elements: STIX A200 MULTI VINYL multi-purpose adhesive or BOSTIK ROLL 25/50/85 range ready-to-use for wall plates installation or HIGH TACK H785 ultra strong instant grab adhesive for corner installation.

## SOFT FLOOR ADHESIVE

**1 STIX A200**  
MULTI VINYL

MULTI-PRUPOSE ADHESIVE  
FOR ALL PVC COVERINGS

- **RAPID CURING**
- **HIGH INITIAL GRAB**
- **PVC BONDING ON OLD PVC**

## CHARACTERISTICS

- Waiting time: 10 - 15 min
- Open time: 45 - 50 min
- Coverage: 250 - 400 g/m<sup>2</sup>



**Watch on Bostik ACADEMY**

**2 BOSTIK ROLL**  
25/50/85

REINFORCED ADHESIVE  
STRIP FOR FITTING ALL TYPES  
OF SKIRTING, ACCESSORIES  
AND PROTECTIVE WALL PANELS  
AND FOR COVING UP FLOOR  
COVERING TO FORM SKIRTING

- IMMEDIATE GRIP AND EXTRA-STRONG
- QUICK, EASY AND CLEAN INSTALLATION
- NO WAITING TIME REQUIRED

## CHARACTERISTICS

- Reel widths: 25 or 50 or 85 mm
- Reel length: 50 m



## GRABS & ADHESIVES

### 3 HIGH TACK H785

ULTRA STRONG INSTANT GRAB  
ADHESIVE


- **DIRECT TACK, NO SUPPORT REQUIRED**
- **HIGH STRENGTH**
- **NO ISOCYANATES AND SOLVENTS**



**Watch on Bostik ACADEMY**



## SAVE TIME ON SITE



**BOSTIK ROLL 25/50/85**

Apply a strip of Bostik Roll vertically to the back of the panel every 15-20 cm. Apply stripes as well on the periphery of the panel.







# EDUCATION

School buildings are subject to very specific requirements and the construction guidelines have to respond to different specifications in order to provide a safe and secure environment.

Bostik has always been developing high-performance and durable solutions that meet the installation requirements of specific education facilities:

- LINOLEUM AND PHTHALATE-FREE SOLUTIONS
- STAIRS COVERING SAFETY
- SPORT SOLUTION
- MOISTURE RESISTANCE, HIGH PERFORMANCE





# > EDUCATION FLOORING SYSTEMS SOLUTIONS



**LINOLEUM AND  
PHTHALATE-FREE  
SOLUTIONS**  
● 30



**STAIRS  
COVERING  
SAFETY**  
● 32



**SPORT  
SOLUTION**  
● 34



**MOISTURE  
RESISTANCE,  
HIGH  
PERFORMANCE**  
● 36





# LINOLEUM AND PHTHALATE-FREE SOLUTIONS

## COVERING: LINOLEUM SHEET

For a safe and healthy environment for children, schools require highly resistant and eco-responsible materials. Linoleum is an extremely durable, clean, phthalate-free floor covering made from natural raw materials such as solidified linseed oil and pine resin... Bostik offers a high-performance adhesive for linoleum installation with high resistance and great durability. Bostik STIX A800 PREMIUM is a solvent-free, phthalate-free adhesive with very low VOC emissions (EC1+) to preserve indoor air quality.

### FLOOR PREPARATION

#### 1 GRIP A500 MULTI

MULTI-PURPOSE PRIMER FOR NEW WORK AND RENOVATION

- FACILITATES APPLICATION OF SMOOTHING COMPOUNDS
- NON-ABSORBENT AND ABSORBENT SURFACES
- ODOURLESS, READY TO USE

#### CHARACTERISTICS

- Coverage: 90-100 g/m²



Watch on Bostik ACADEMY

#### 2 SL C320 ARDASOL

STANDARD SELF-LEVELLING COMPOUND FOR USE ON INTERNAL FLOORS

- SELF-LEVELLING
- NO SHRINKAGE
- EXCELLENT SURFACE FINISH

#### CHARACTERISTICS

- Application thickness: 1 - 10 mm
- Coverage: 1,5 kg/mm/m²
- C20



Watch on Bostik ACADEMY

### SOFT FLOOR ADHESIVE

#### 3 STIX A800 PREMIUM

ULTRA HIGH PERFORMANCE ADHESIVE FOR ALL TYPES OF SOFT FLOOR COVERINGS

- IDEAL FOR LVT AND RUBBER
- SHORT DRYING TIME
- HIGH INITIAL GRAB

#### CHARACTERISTICS


- Waiting time: PVC: 10 - 15 min / Rubber: 5 min
- Open time: PVC: 60 min / Rubber: 30 min
- Coverage: 240 - 400 g/m




Watch on Bostik ACADEMY



### HEAVY METAL ROLL APPLICATION



For the linoleum flooring, use a heavy metal roll (+/- 60 kg) to ensure the perfect transfer of the adhesive and obtain the right final result.






# STAIRS COVERING SAFETY

## COVERING: INTEGRAL STAIRS PVC


To ensure the safety of users on stairs in public buildings it is common to use special PVC coverings with a non-slip stair nosing. Bostik Roll 240 is a solution perfectly adapted to the implementation of this type of covering: quick, easy and durable installation. Before application of a floor covering, make sure that the substrate is clean, sound and dry. For the renovation of stair treads, our repair plaster SL C950 RENOQUICK allows for reprofiling and resurfacing vertical and horizontal parts.



### PVC INSTALLATION ON THE STAIRS



- BOSTIK ROLL 240**
- 1 — Unroll the Bostik Roll 240 from top to bottom perpendicular to the steps.
  - 2 — Only remove the protective paper from Bostik Roll 240 before laying the flooring.



- 3 — The step edge must be rounded with at least a 12 mm radius corner.

### FLOOR PREPARATION

#### 1 SL C950 RENOQUICK

LEVELLING COMPOUND AND FILLER FOR RENOVATION PROJECTS AND CREATING INDOOR SLOPES

- RAPID DRYING
- CREATION OF 1 - 50 MM SLOPES
- 1 - 5 MM: VERTICAL SKIMCOATS: WALLS AND RISERS

#### CHARACTERISTICS

- Application thickness: 1 - 50 mm
- Coverage: 1,6 kg/mm/m²
- C30/F6

Watch on Bostik ACADEMY

### SOFT FLOOR ADHESIVE


#### 2 BOSTIK ROLL 240

REINFORCED ADHESIVE STRIP FOR THE IMPLEMENTATION OF SOFT FLOOR COVERINGS IN STAIRS.

- IMMEDIATE GRIP AND EXTRA-STRONG
- QUICK, EASY AND CLEAN INSTALLATION
- NO WAITING TIME REQUIRED

#### CHARACTERISTICS

- Reel widths: 240 mm
- Reel length: 25 m



CONCRETE STEP

1

SL C950 RENOQUICK



2

BOSTIK ROLL 240



INTEGRAL STAIRS PVC





SPORT SOLUTION

COVERING: HETEROGENEOUS PVC MULTI-SPORT

There are several sport coverings in the market. We have chosen in this case a heterogeneous PVC multi-sport, which meets the need of the school gymnasiums. This gymnasium located on solid ground requires a moisture treatment in order to block the potential rising damp from the subfloor. Bostik offers a moisture barrier that allows the subfloor moisture to be blocked with no limit to residual humidity. This is a two-component kit (resin + hardener) with associated primer. Bostik also offers a thick self-levelling compound in order to catch up the ground level up to 60mm.

FLOOR PREPARATION

1 HYTEC E336 XTREM

VERY HIGH-PERFORMANCE 2K EPOXY DAMP PROOF MEMBRANE

- MOISTURE LEVEL: NO LIMIT
- RESISTS TO HYDROSTATIC PRESSURE
- RADON BARRIER

CHARACTERISTICS

- Coverage: B2 trowel if residual damp <6,5%: 400 g/m² C1 trowel if residual damp > 6,5%: 800 g/m²
- Sand: 3 to 4 kg/m²
- Color: clear amber

Watch on Bostik ACADEMY

2 GRIP A936 XPRESS

HIGH-PERFORMANCE SPECIAL PRIMER FOR NON-ABSORBENT SURFACES

- FAST DRYING
- HIGH GRIP: CONTAINS QUARTZ
- EASY TO USE: ROLLER APPLICATION

CHARACTERISTICS

- Coverage: 80 – 120 g/m² per layer



Watch on Bostik ACADEMY

2 SL C740 FIBER MAXI

FIBRE-REINFORCED HEAVY-DUTY SELF-LEVELLING COMPOUND FOR USE ON INTERNAL & EXTERNAL FLOORS

- HEAVY-DUTY THICKNESS
- SUITABLE FOR USE ON EXTERNAL COVERED FLOORS
- VERY HIGH MECHANICAL RESISTANCE WITH NO SHRINKAGE

CHARACTERISTICS

- Application thickness: 1 - 40 mm
- Coverage: 1,5 kg/mm/m²
- C30/F6

Watch on Bostik ACADEMY

SOFT FLOOR ADHESIVE

4 STIX A800 PREMIUM

ULTRA HIGH PERFORMANCE ADHESIVE FOR ALL TYPES OF SOFT FLOOR COVERINGS

- IDEAL FOR LVT AND RUBBER
- SHORT DRYING TIME
- HIGH INITIAL GRAB

CHARACTERISTICS

- Waiting time: PVC: 10 - 15 min / Rubber: 5 min
- Open time: PVC: 60 min / Rubber: 30 min
- Coverage: 240 - 400 g/m²



Watch on Bostik ACADEMY





AREA: SCHOOL COLLECTIVE KITCHENS

MOISTURE RESISTANCE,  
HIGH PERFORMANCE

COVERING: HOMOGENEOUS PVC SHEET

The specifications for collective kitchens have to respect hygiene rules and sanitary standards (classified as P4S). For that, implementation requires a technical know-how with specific systems. Bostik offers a high-performance adhesive for areas subject to significant mechanical or thermal stress: high-shear strength, moisture resistance solutions...

FLOOR PREPARATION

1 GRIP A500  
MULTI

MULTI-PURPOSE PRIMER FOR NEW WORK AND RENOVATION

- FACILITATES APPLICATION OF SMOOTHING COMPOUNDS
- NON-ABSORBENT AND ABSORBENT SURFACES
- ODOURLESS, READY TO USE

CHARACTERISTICS

- Coverage: 90-100 g/m²



▶ Watch on Bostik ACADEMY

2 SL C950  
RENOQUICK

LEVELLING COMPOUND AND FILLER FOR RENOVATION PROJECTS AND CREATING INDOOR SLOPES

- RAPID DRYING
- CREATION OF 1 - 50 MM SLOPES
- 1 - 5 MM: VERTICAL SKIMCOATS: WALLS AND RISERS

CHARACTERISTICS

- Application thickness: 1 - 50 mm  
- Coverage: 1,6 kg/mm/m²  
- C30/F6

▶ Watch on Bostik ACADEMY

3 SL C510  
PRO

HEAVY - DUTY SELF LEVELLING COMPOUND

- HIGH MECHANICAL RESISTANCE, NO SHRINKAGE
- SUITABLE FOR SUPERMARKETS
- NO SANDING

CHARACTERISTICS

- Application thickness: 1 - 20 mm  
- Coverage: 1,5 kg/mm/m²  
- C30/F7

▶ Watch on Bostik ACADEMY

SOFT FLOOR ADHESIVE

4 STIX P956  
2K

TWO-COMPONENT POLYURETHANE ADHESIVE FOR FLOOR COVERINGS

- VERY HIGH BONDING PERFORMANCE
- MOISTURE AND HEAT RESISTANT
- INDOOR - OUTDOOR

CHARACTERISTICS

- Open time: 1h  
- Coverage: 300-900 g/m²  
- Color: yellow/ light brown







# WORKPLACE

Companies do not always think ahead about the layout of workplaces; however, they have to be flexible, depending on the activity, the number of employees, or any other reasons that could affect the organization of the offices. Workplaces can also evolve in order to improve quality of life at work. Indeed, the well-being of people is becoming more and more important for companies as it is part of a good productivity. That is why Bostik offers systems adapted to the different types of coverings accessible on the market. Our products allow you to renovate or improve your workplaces easily.

Bostik offers solutions for a large array of areas, not limited to:


- **REMOVABLE CARPET TILES**
- **REMOVABLE PVC TILES**
- **RENOVATION WITH LVT**



# WORKPLACE FLOORING SYSTEMS SOLUTIONS



REMOVABLE  
CARPET TILES  
● 42



REMOVABLE  
PVC TILES  
● 42



RENOVATION  
WITH LVT  
● 44





# REMOVABLE TILES

COVERING: REMOVABLE CARPET TILES / HETEROGENEOUS PVC TILES

Workplaces are often equipped with raised access floors, which allows quick and easy access to mechanical services and electrical cables. Bostik offers different quality of tackifiers for the installation of carpet and PVC tiles. These tackifiers facilitate the removal and replacement of carpet tiles on raised wood floors.

SOFT FLOOR ADHESIVE

1 **FIX A320**  
TACK

TACKIFIER ADHESIVE FOR  
REMOVABLE CARPET TILES

- SPECIFICALLY  
FOR OFFICE FLOORS
- EASY-ROLL ON  
APPLICATION
- REDUCED COVERAGE

CHARACTERISTICS

- Waiting time: 30 - 45 min
- Open time: no limit
- Coverage: 60 -100 g/m²



Watch on Bostik ACADEMY

2 **FIX A570**  
MULTI TACK

TACKIFIER ADHESIVE  
FOR ALL TYPES OF  
REMOVABLE SOFT TILES

- HIGH-PERFORMANCE,  
PERMANENT GRAB
- ALL TYPES OF REMOVABLE TILES
- ALL TYPES OF ABSORBENT OR  
NON-ABSORBENT SUBFLOORS

CHARACTERISTICS


- Waiting time:  
normally absorbent subfloors: 30 min  
and non-absorbent subfloors: 2h
- Open time: no limit
- Coverage: 40-100 g/m²



Watch on Bostik ACADEMY



ROLL  
APPLICATION



Consumption: 40-100 g/m²



RAISED ACCESS  
FLOOR

1

FIX A320  
TACK

CARPET TILES



RAISED ACCESS  
FLOOR

2

FIX A570  
MULTI TACK

HETEROGENEOUS  
PVC TILES





# RENOVATION WITH LVT

COVERING: LVT

Resistant and trendy, LVT offers a wide decorative choice. Easy to install, this covering nevertheless requires a high-performance adhesive that allows the flooring to be quickly blocked. The application of a fast, fibre-reinforced levelling compound is recommended to save time on site preparation. Bostik offers a very high performance adhesive for the installation of LVT with high initial grab and high final bonding strength. STIX A800 PREMIUM avoids movements, preventing dimensional variations due to temperature.

FLOOR PREPARATION

1 HYTEC E336 XTREM

VERY -RESISTANCE 2K EPOXY DAMP PROOF MEMBRANE

- MOISTURE LEVEL: NO LIMIT
- RESISTS TO HYDROSTATIC PRESSURE
- RADON BARRIER

CHARACTERISTICS

- Coverage: B2 trowel if residual damp <6,5%: 400 g/m² C1 trowel if residual damp > 6,5%: 800 g/m²
- Sand: 3 to 4 kg/m²
- Color: clear amber

Watch on Bostik ACADEMY

2 GRIP A936 XPRESS

SPECIAL PRIMER FOR NON-ABSORBENT SURFACES

- FAST DRYING
- HIGH GRIP: CONTAINS QUARTZ
- EASY TO USE: ROLLER APPLICATION

CHARACTERISTICS

- Coverage: 80 – 120 g/m² per layer



Watch on Bostik ACADEMY

3 SL C750 POLYRAG

FIBRE-REINFORCED, RAPID, PAINTABLE SELF-LEVELLING COMPOUND

- HIGH VERSATILITY
- IDEAL FOR RENOVATION
- PERFECT FINISH AND SELF-LEVELLING

CHARACTERISTICS

- Application thickness: 1 – 10 mm
- Coverage: 1,5 kg/mm/m²
- C30/F7
- Color: beige



Watch on Bostik ACADEMY

SOFT FLOOR ADHESIVE

4 STIX A800 PREMIUM

ULTRA HIGH-PERFORMANCE FOR ALL TYPES OF SOFT FLOOR COVERINGS


- IDEAL FOR LVT AND RUBBER
- SHORT DRYING TIME
- HIGH INITIAL GRAB

CHARACTERISTICS

- Waiting time: PVC: 10 – 15 min / Rubber: 5 min
- Open time: PVC: 60 min / Rubber: 30 min
- Coverage: 250-400 g/m²



Watch on Bostik ACADEMY







# HOSPITALITY

Hotels and hospitality buildings are always looking for new trends in terms of design, covering and other key areas in order to satisfy its customers. Moreover, they have to face various constraints: high traffic areas, soundproofing, impermeability of wet rooms, etc.

Our solutions are developed to respond to these different needs. We preserve the technical performance, the strength of our products while meeting the key objectives about environment and health.

Bostik offers solutions for a large array of areas, not limited to:

- **CARPET SOLUTIONS**
- **WET ROOM LVT DESIGN**
- **LVT DESIGN FLOORING**
- **ACOUSTIC SYSTEM UNDER WOOD FLOOR**
- **HEAVY EQUIPMENT**







# > HOSPITALITY FLOORING SYSTEMS SOLUTIONS



**CARPET  
SOLUTIONS**  
● 50



**WET ROOM  
LVT  
DESIGN**  
● 52



**LVT  
DESIGN  
FLOORING**  
● 54



**ACOUSTIC  
SYSTEM  
UNDER  
WOOD FLOOR**  
● 56



**HEAVY  
EQUIPMENT**  
● 58





AREA: CORRIDOR

# CARPET SOLUTIONS

COVERING: CARPET

To satisfy their guests, hotel managers are very careful about noise pollution. Carpet is an interesting option as it helps to reduce noise and provides comfort. Moreover, this floor covering offers a large choice of colors and designs to change the decoration of the room or common areas. Bostik offers a system with a special acrylic adhesive for carpet: easy to apply with a high initial grab.

## FLOOR PREPARATION

### 1 GRIP A310 PROJECT

PRIMER FOR THE PREPARATION OF SUBFLOORS

- SOLVENT FREE
- READY FOR USE
- CAN BE USED UNIVERSALLY

#### CHARACTERISTICS

- Coverage: 150 g/m²



Watch on Bostik ACADEMY

### 2 SL C320 ARDASOL

STANDARD SELF-LEVELLING COMPOUND FOR USE ON INTERNAL FLOORS

- SELF-LEVELLING
- NO SHRINKAGE
- EXCELLENT SURFACE FINISH

#### CHARACTERISTICS

- Application thickness: 1 - 10 mm  
- Coverage: 1,5 kg/mm/m²  
- C20



Watch on Bostik ACADEMY

## SOFT FLOOR ADHESIVE

### 3 STIX A100 PROJECT

MULTI-PURPOSE ADHESIVE FOR RESIDENTIAL FLOORING : PVC , CARPET, NATURAL FIBRES

- HIGH YIELD
- EASY APPLICATION
- REDUCED ODOUR

#### CHARACTERISTICS


- Waiting time: 10-15 min  
- Open time: 45 - 50 min  
- Coverage: 250 -400 g/m²



Watch on Bostik ACADEMY



## CARPET INSTALLATION



### STIX A530 TEX POWER

One or more strips of carpet should be laid in such a way that the pile is in the direction of the point of natural light (windows) or in the direction of traffic (corridors).





# WET ROOM LVT DESIGN

COVERING: LVT

LVT is becoming more and more trendy in hotel rooms. Thanks to the product's resistance to humidity, it is possible to have the same floor in the bedroom and in the bathroom, which provides aesthetic continuity in suites. Bostik offers a high-resistance hybrid adhesive for LVT in wet rooms. STIX H995 ELASTIC XTREM is a moisture resistant product with an extreme shear strength.

## FLOOR PREPARATION

### 1 GRIP A500 MULTI

MULTI-PURPOSE PRIMER FOR NEW WORK AND RENOVATION

- FACILITATES APPLICATION OF SMOOTHING COMPOUNDS
- NON-ABSORBENT AND ABSORBENT SURFACES
- ODOURLESS, READY TO USE

#### CHARACTERISTICS

- Coverage: 90-100 g/m²



Watch on Bostik ACADEMY

### 2 SL C750 POLYRAG

FIBRE-REINFORCED, RAPID, PAINTABLE SELF-LEVELLING COMPOUND

- HIGH VERSATILITY
- IDEAL FOR RENOVATION
- PERFECT FINISH AND SELF-LEVELLING

#### CHARACTERISTICS

- Application thickness: 1 - 10 mm  
- Coverage: 1,5 kg/mm/m²  
- C30/F7  
- Color: beige



Watch on Bostik ACADEMY

## SOFT FLOOR ADHESIVE

### 3 STIX H995 ELASTIC XTREM

HIGH-RESISTANCE HYBRID ADHESIVE FOR SOFT FLOORING IN WET ROOMS OR HIGH TRAFFIC PREMISES


- HIGH-TRAFFIC AREAS
- MOISTURE AND HEAT RESISTANT
- EXTREME SHEAR STRENGTH

#### CHARACTERISTICS

- Waiting time: 10 min  
- Open time: 40 min  
- Coverage: 320 - 380 g/m²



## LVT APPLICATION IN WETROOM



### STIX H995 ELASTIC XTREM

Moisture resistance and extreme shear strength. Perfect for wet rooms.





# LVT DESIGN FLOORING

COVERING: LVT

In hotels, decoration and design are increasingly contributing to offer a remarkable customer experience. The LVT allows great flexibility in terms of decor, even with realistic design such as the appearance of a wood floor. Bostik offers a high-performance adhesive for the installation of all kinds of LVT thanks to its high final bonding strength and high initial grab.

## FLOOR PREPARATION

### 1 GRIP A500 MULTI

MULTI-PURPOSE PRIMER FOR NEW WORK AND RENOVATION

- FACILITATES APPLICATION OF SMOOTHING COMPOUNDS
- NON-ABSORBENT AND ABSORBENT SURFACES
- ODOURLESS, READY TO USE

#### CHARACTERISTICS

- Coverage: 90-100 g/m²



Watch on Bostik ACADEMY

### 2 SL C320 ARDASOL

STANDARD SELF-LEVELLING COMPOUND FOR USE ON INTERNAL FLOORS

- SELF-LEVELLING
- NO SHRINKAGE
- EXCELLENT SURFACE FINISH

#### CHARACTERISTICS

- Application thickness: 1 - 10 mm  
- Coverage: 1,5 kg/mm/m²  
- C20



Watch on Bostik ACADEMY

## SOFT FLOOR ADHESIVE

### 3 STIX A800 PREMIUM

ULTRA HIGH-PERFORMANCE FOR ALL TYPES OF SOFT FLOOR COVERINGS

- IDEAL FOR LVT AND RUBBER
- SHORT DRYING TIME
- HIGH INITIAL GRAB

#### CHARACTERISTICS


- Waiting time: PVC: 10 - 15 min / Rubber: 5 min  
- Open time: PVC: 60 min / Rubber: 30 min  
- Coverage: 250-400 g/m²



Watch on Bostik ACADEMY




## STRONG FINAL COHESION



### STIX A800 PREMIUM

Very strong final cohesion, no dimensionnal variation the LVT covering.





AREA: GUEST ROOM

ACOUSTIC SYSTEM  
UNDER WOOD FLOOR

COVERING: ENGINEERED WOOD

Acoustics is a primary consideration in the hotel environment. Most underfloor acoustic systems require the use of an underlay and several stages of installation. Bostik offers a unique and exclusion solution that ensures both the installation of the wood floor with our specific adhesive WOOD H200 ELASTIC-P and the required acoustic damping (delta -19db).

FLOOR PREPARATION

1 GRIP A500  
MULTI

MULTI-PURPOSE PRIMER FOR NEW WORK AND RENOVATION

- FACILITATES APPLICATION OF SMOOTHING COMPOUNDS
- NON-ABSORBENT AND ABSORBENT SURFACES
- ODOURLESS, READY TO USE

CHARACTERISTICS

- Coverage: 90-100 g/m²



Watch on Bostik ACADEMY

2 SL C750  
POLYRAG

FIBRE-REINFORCED, RAPID, PAINTABLE SELF-LEVELLING COMPOUND

- HIGH VERSATILITY
- IDEAL FOR RENOVATION
- PERFECT FINISH AND SELF-LEVELLING

CHARACTERISTICS

- Application thickness: 1 - 10 mm  
- Coverage: 1,5 kg/mm/m²  
- C30/F7



Watch on Bostik ACADEMY

WOOD FLOOR ADHESIVE

3 WOOD H910  
SILENTSTIK

ACOUSTIC ADHESIVE FOR PARQUET FLOORS

- HIGH ACOUSTIC PERFORMANCE: IMPACT NOISE AND AIRBORNE NOISE
- 2 IN 1: BONDING AND ACOUSTIC PROPERTIES IN ONE PRODUCT
- SUITABLE FOR UNDERFLOOR HEATING

CHARACTERISTICS


- Open time: 40 min  
- Blocking time: 2 h  
- Coverage: 1,6 - 2 kg/m²




Watch on Bostik ACADEMY



SPECIFIC  
INSTALLATION



1 — Silentstik spatula  
Consumption: 1600-2000 g/m²



2 — Apply the acoustic floor adhesive perpendicularly to the floorboards.





AREA: FITNESS ROOM

HEAVY EQUIPMENT

COVERING: RUBBER SHEET

Fitness rooms are highly exposed to high mechanical stress and heavy loads. They require high-resistance covering such as rubber and strong bonding. Bostik offers a high-performance wet tack adhesive, which allows a fast bonding and high-mechanical resistance. The covering is perfectly blocked, preventing any movement, thus allowing a perfect installation and great durability.

FLOOR PREPARATION

1 GRIP A500 MULTI

MULTI-PURPOSE PRIMER FOR NEW WORK AND RENOVATION

- FACILITATES APPLICATION OF SMOOTHING COMPOUNDS
- NON-ABSORBENT AND ABSORBENT SURFACES
- ODOURLESS, READY TO USE

CHARACTERISTICS

- Coverage: 90-100 g/m²



▶ Watch on Bostik ACADEMY

2 SL C510 PRO

HEAVY-DUTY SELF LEVELLING COMPOUND

- HIGH MECHANICAL RESISTANCE, NO SHRINKAGE
- SUITABLE FOR SUPERMARKETS
- NO SANDING

CHARACTERISTICS

- Application thickness: 1 - 20 mm  
- Coverage: 1,5 kg/mm/m²  
- C30/F7

▶ Watch on Bostik ACADEMY

SOFT FLOOR ADHESIVE

3 STIX A550 POWER ELASTIC  
HIGH-PERFORMANCE ADHESIVE FOR RESILIENT COVERINGS

- IDEAL FOR LVT AND RUBBER
- SHORT WAITING TIME
- HIGH PERFORMANCE

CHARACTERISTICS


- Waiting time: 5 - 10 min  
- Open time: 25 - 30 min  
- Coverage: 320 - 360 g/m²



▶ Watch on Bostik ACADEMY



SHORT WAITING TIME



STIX A550 POWER ELASTIC  
Short waiting time before applying the rubber covering.







# STORES

One of the most important constraints of stores, shops, and warehouses is the high-traffic environment. Due to this, it could be complicated to renovate or change the design of stores without closing. In these cases, the role of Bostik is to reduce the impact on your activity. That is why we offer technical and highly resistant products for heavy traffic environments.

Bostik offers solutions for a large array of areas, not limited to:

- **QUICK INSTALLATION**
- **HIGH-RESISTANCE FLOORING**





# > STORES FLOORING SYSTEMS SOLUTIONS



**QUICK  
INSTALLATION**  
● 64



**HIGH-RESISTANCE  
FLOORING**  
● 66





# QUICK INSTALLATION

COVERING: LVT LOOSE LAY

The installation of LVT loose lay allows a minimal immobilization of activity. Bostik offers an ultra-high-performance tackifier with a permanent tacky film that avoids noise on the floor and prevents the tiles from moving. For a quick return to service, a rapid self-levelling compound is necessary. With the SL C990 SPRINTER, the floor can be covered as quickly as 90 minutes.

FLOOR PREPARATION

1 GRIP A936 XPRESS

HIGH-PERFORMANCE SPECIAL PRIMER FOR NON-ABSORBENT SURFACES

- FAST DRYING
- HIGH GRIP: CONTAINS QUARTZ
- EASY TO USE: ROLLER APPLICATION

CHARACTERISTICS


- Coverage: 80 - 120 g/m² per layer



Watch on Bostik ACADEMY



ROLL APPLICATION



FIX A760 TECH

Apply with roll for optimized results.  
Consumption : 100-120g/m²

2 SL C750 POLYRAG

FIBRE-REINFORCED, RAPID, PAINTABLE SELF-LEVELLING COMPOUND

- HIGH VERSATILITY
- IDEAL FOR RENOVATION
- PERFECT FINISH AND SELF-LEVELLING

CHARACTERISTICS

- Application thickness: 1 - 10 mm  
- Coverage: 1,5 kg/mm/m²  
- C30/F7  
- Color: beige



Watch on Bostik ACADEMY

SOFT FLOOR ADHESIVE

3 FIX A760 TECH

ULTRA HIGH-PERFORMANCE TACKIFIER ADHESIVE FOR SOFT TILES, CARPET AND VINYL SHEETS

- COVERING REMOVAL AND RECYCLING
- HIGH-PERFORMANCE, PERMANENT TACKY FILM
- NON-ABSORBENT OR ABSORBENT SURFACES

CHARACTERISTICS

- Waiting time:  
Normally absorbent subfloors: 45 - 60 min  
Non-absorbent subfloors: 2 - 2,5 h  
- Open time: no limit  
- Coverage: 60 - 120 g/m²



Watch on Bostik ACADEMY





# HIGH-RESISTANCE FLOORING

COVERING: EPOXY / PU PAINTING

For areas where activities can only be interrupted for a short period of time, rapid self-levelling compound is required. Warehouse areas are subject to heavy loads and in this case, it is mandatory to obtain a self-levelling compound with high mechanical resistance to wear and puncture. Bostik offers a very heavy-duty self-levelling compound that can be left as final floor surface thanks to its very high resistance and perfect finish.

## FLOOR PREPARATION

### 1 GRIP A500 MULTI

MULTI-PURPOSE PRIMER FOR NEW WORK AND RENOVATION

- FACILITATES APPLICATION OF SMOOTHING COMPOUNDS
- NON-ABSORBENT AND ABSORBENT SURFACES
- ODOURLESS, READY TO USE

#### CHARACTERISTICS

- Coverage: 90-100 g/m²



Watch on Bostik ACADEMY

### 2 SL C980 XPS

VERY HEAVY-DUTY SELF-LEVELLING COMPOUND FOR USE ON INTERNAL AND EXTERNAL FLOORS

- INDUSTRIAL PREMISES
- RAPID DRYING
- POSSIBLE FINISH: PAINT, RESINS, COATING


#### CHARACTERISTICS

- Application thickness: 3 - 15 mm  
- Coverage: 1,8 kg/mm/m²  
- C40/F7

Watch on Bostik ACADEMY



## PRODUCT APPLICATION



### SL C980 XPS

Respect the rate indicated mixing capacity (4.5 l) to have an aspect of homogeneous surface.







# RESIDENTIAL

In residential, the renovation is one of the main projects. You can either lay a new floor or renovate the old one protecting them both with our moisture damp proof membranes for long lasting finishes. Our technical products developed for professionals offer these type of solutions with high-level performance and long-lasting results.

Bostik offers solutions for a large array of areas, not limited to:

- RENOVATION ON OLD TILES
- SOLID WOOD FLOOR
- RENOVATION ON OLD WOOD FLOOR
- TURF INSTALLATION






# > RESIDENTIAL FLOORING SYSTEMS SOLUTIONS



**RENOVATION  
ON OLD TILES**  
● 72



**SOLID  
WOOD FLOOR**  
● 74



**RENOVATION  
ON OLD WOOD FLOOR**  
● 76



**TURF  
INSTALLATION**  
● 78





# RENOVATION ON OLD TILES

COVERING: HETEROGENEOUS PVC SHEET

When you are on full ground, the application of moisture barrier is mandatory in order to secure your project. Bostik offers a full system with HYTEC E336 XTREM a 2K damp proof membrane and GRIP A936 XPRESS a special primer. This system is suitable on old tiles with no limit and can block any moisture level, even rising damp. The system along SL C320 ARDASOL and STIX A200 MULTI VINYL offers the perfect and optimized solution for residential project.

## FLOOR PREPARATION

### 1 HYTEC E336 XTREM

VERY HIGH-PERFORMANCE 2K EPOXY DAMP PROOF MEMBRANE

- **MOISTURE LEVEL: NO LIMIT**
- **RESISTS TO HYDROSTATIC PRESSURE**
- **RADON BARRIER**

#### CHARACTERISTICS

- Coverage: B2 trowel if residual damp < 6,5%: 400 g/m²  
C1 trowel if residual damp > 6,5%: 800 g/m²
- Sand: 3 to 4 kg/m²
- Color: clear amber

Watch on Bostik ACADEMY

### 2 GRIP A936 XPRESS

HIGH-PERFORMANCE SPECIAL PRIMER FOR NON-ABSORBENT SURFACES

- **FAST DRYING**
- **HIGH GRIP: CONTAINS QUARTZ**
- **EASY TO USE: ROLLER APPLICATION**

#### CHARACTERISTICS

- Coverage: 80 – 120 g/m² per layer



Watch on Bostik ACADEMY

### 3 SL C320 ARDASOL

STANDARD SELF-LEVELLING COMPOUND FOR USE ON INTERNAL FLOORS

- **SELF-LEVELLING**
- **NO SHRINKAGE**
- **EXCELLENT SURFACE FINISH**

#### CHARACTERISTICS

- Application thickness: 1 – 10 mm
- Coverage: 1,5 kg/mm/m²
- C20



Watch on Bostik ACADEMY

## SOFT FLOOR ADHESIVE

### 4 STIX A200 MULTI VINYL


MULTI-PRUPOSE ADHESIVE FOR ALL PVC COVERINGS

- **RAPID CURING**
- **HIGH INITIAL GRAB**
- **PVC BONDING ON OLD PVC**

#### CHARACTERISTICS

- Waiting time: 10 – 15 min
- Open time: 45 – 50 min
- Coverage: 250 – 400 g/m²

Watch on Bostik ACADEMY





AREA: LIVING ROOM

SOLID WOOD FLOOR

COVERING: SOLID WOOD LARGE PLANK > 200 MM

Solid wood floors are natural and durable coverings. An elegant aesthetic floor offering beautiful, modern, warm designs, and insulating properties (it can be used with underfloor heating). Wood floor adhesive has less risk of warping the strips and can be apply up to 200 mm wide. Bostik offers a high performance hybrid adhesive for all kinds of wood floor. WOOD H200 ELASTIC comes in pouches: it is easy to open, safe and convenient to use with an extended shelf life.

FLOOR PREPARATION

1 GRIP A500 MULTI

MULTI-PURPOSE PRIMER FOR NEW WORK AND RENOVATION

- FACILITATES APPLICATION OF SMOOTHING COMPOUNDS
- NON-ABSORBENT AND ABSORBENT SURFACES
- ODOURLESS, READY TO USE

CHARACTERISTICS

- Coverage: 90-100 g/m²



Watch on Bostik ACADEMY

2 SL C320 ARDASOL

STANDART SELFSELF-LEVELLING COMPOUND FOR USE ON INTERNAL FLOORS

- SELF-LEVELLING
- NO SHRINKAGE
- EXCELLENT SURFACE FINISH

CHARACTERISTICS

- Application thickness: 1 - 10 mm  
- Coverage: 1,5 kg/mm/m²  
- C20



Watch on Bostik ACADEMY

WOOD FLOOR ADHESIVE

3 WOOD H200 ELASTIC-P

HIGH-PERFORMANCE HYBRID ADHESIVE FOR ALL TYPES OF WOOD FLOORING

- SOLID WOOD FLOORS < 200MM WIDE
- STRONG ULTIMATE COHESION
- RAPID FIXING (LOCK-IN)

CHARACTERISTICS


- Open time: 40 min  
- Coverage: 1-1,4 kg/m²




Watch on Bostik ACADEMY




LONG SHELF LIFE



WOOD H200 ELASTIC-P  
The 7 kg pouches packaging allows a shelf life up to 18 months.



SPECIFIC SPATULA  
Use the spatule n°4 - B12 to apply this wood floor adhesive.





AREA: ROOM

# RENOVATION ON OLD WOOD FLOOR

COVERING: LVT

On renovation on old wood floor, Bostik offers a two-component primer for preparing and patching old wood flooring and wood panels before the installation of one of our flexible-levelling compound reinforced with synthetic fibers.

## FLOOR PREPARATION

### 1 GRIP X910 FILL & WOOD

SPECIAL 2K PRIMER FOR RENOVATION ON WOODEN SURFACES.

- VERY HIGH RESISTANCE AND FLEXIBILITY
- ALL WOOD SURFACES AND JOINT FILLING
- QUICK DRYING

#### CHARACTERISTICS

- Coverage: 800 - 1000 g/m<sup>2</sup>
- Color: brown

▶ Watch on Bostik ACADEMY

### 2 SL C740 FIBER MAXI

FIBRE-REINFORCED HEAVY-DUTY SELF-LEVELLING COMPOUND FOR USE ON INTERNAL & EXTERNAL FLOORS

- HEAVY-DUTY THICKNESS
- SUITABLE FOR USE ON EXTERNAL COVERED FLOORS
- VERY HIGH MECHANICAL RESISTANCE WITH NO SHRINKAGE

#### CHARACTERISTICS

- Application thickness: 1 - 40 mm
- Coverage: 1,5 kg/mm/m<sup>2</sup>
- C30/F6

▶ Watch on Bostik ACADEMY

## SOFT FLOOR ADHESIVE

### 3 STIX A800 PREMIUM

ULTRA HIGH-PERFORMANCE FOR ALL TYPES OF SOFT FLOOR COVERINGS

- IDEAL FOR LVT AND RUBBER
- SHORT DRYING TIME
- HIGH INITIAL GRAB

#### CHARACTERISTICS


- Waiting time: PVC: 10 - 15 min / Rubber: 5 min
- Open time: PVC: 60 min / Rubber: 30 min
- Coverage: 250-400 g/m<sup>2</sup>




▶ Watch on Bostik ACADEMY




## RESPECT THE MIXING TIME



**GRIP X910 FILL & WOOD**  
1- Pour the powder (10 kg) into the resin (4.5 kg).



2- Mix well using the mixer until a smooth, dark brown paste is obtained.






# TURF INSTALLATION

COVERING: SYNTHETIC TURF

Synthetic turf is becoming more and more real and is now a very trendy product that is highly valued for its simplicity in terms of maintenance and installation. Bostik offers a specific two-component product with high mechanical performance and resistance to humidity.




## TURF INSTALLATION




### STIX P966 TURF

1 - Lay the strip associated to the STIX P966 TURF.



2 - Apply the adhesive on the strip at the junction of the two sheets of covering.



3 - Fold down both sheets of covering edge to edge on the adhesive.

### FLOOR PREPARATION

#### 1 SL C980 XPS

VERY HEAVY-DUTY SELF-LEVELLING COMPOUND FOR USE ON INTERNAL AND EXTERNAL FLOORS

- INDUSTRIAL PREMISES
- RAPID DRYING
- POSSIBLE FINISH: PAINT, RESINS, COATING

#### CHARACTERISTICS

- Application thickness: 3 - 15 mm
- Coverage: 1,8 kg/mm/m²
- C40/F7

[Watch on Bostik ACADEMY](#)

### SOFT FLOOR ADHESIVE

#### 2 STIX P966 TURF

TWO-COMPONENT POLYURETHANE ADHESIVE FOR LAYING ARTIFICIAL GRASS

- HIGH STRENGTH ADHESIVE
- EXCELLENT MOISTURE AND HEAT RESISTANCE
- GREEN COLOR

#### CHARACTERISTICS

- Working time: 45 min
- Coverage: 300-700 g/m²





# BETTER RESULTS THROUGH KNOWLEDGE

A KNOWLEDGE CENTER  
CAREFULLY CREATED  
FOR PROFESSIONALS  
IN THE CONSTRUCTION  
MARKET.

**PRODUCT  
INFORMATION**  
Informational  
documents



**TRAINING**



**VIDEO  
TECHNICAL  
SUPPORT**  
Application  
videos

**RESOURCE  
& SUPPORT**  
Answers to FAQ  
and technical  
contacts

 **STAY CONNECTED! [bostik-academy.com](https://bostik-academy.com)**





# BIM bang!

« MAKING AVAILABLE OUR DATA AND DIGITALIZING IN THREE DIMENSIONS OUR SOLUTIONS IN BIM OBJECTS TO TAKE UP POSITION AHEAD FROM PROJECTS »

**Bostik, brings its contribution to BIM projects by modelling its floor preparation, soft flooring, tiling adhesives ranges in order to integrate all flooring operations in a building 3-D models.**

Better coordinating between various trades, reduction of delays, economic optimization, running and maintenance of buildings over time, control of environmental regulations and accessibility compliances... Building Information Modelling (BIM) approach is more and more used by stakeholders who consider this innovative process as a real innovation in the way of designing the building for the construction market. With 66% of global adoption rate in France, BIM is a new approach of building conception for 74% of professionals.

**61 systems and 36 products available.**

In partnership with BIMOBJECT, the world's Leading BIM content platform, Bostik has integrated two product ranges as "BIM objects", including modelled systems for its subfloor preparations, tiling and soft flooring adhesives. The company shares its key data such as environmental performances, dimensions, application process and process steps, quantities and specific product information. These objects can be integrated in the first phases of project conceptions in order to simplify and improve the collaborations between the different stakeholders at each step of the construction and maintenance of the building. Bostik defines its approach by « making available our data and digitalizing in three dimensions our solutions in BIM objects to take up position ahead from projects ».

It will be progressively widen in all Bostik's solutions.

## MORE EFFICIENT CONSTRUCTION PROCESS

### To do BETTER


- Interoperability between the different actors (organisation).
- Data available, reliable and relevant

### To do FASTER

- All the objects available on a digital platform.
- No treatment of the information required.

### To do CHEAPER

- Cost of non quality: estimated at 40€/m<sup>2</sup> or 15 bn€/y (France) and 53€/m<sup>2</sup> (US) due to organization, data entry and construction duration required.



**BOSTIK GETS IN THE BUILDING INFORMATION MODELLING ERA WITH THE MODELLING OF ITS KEY PRODUCT DATA.**

**8 COUNTRIES**

**8 SYSTEMS**

**36 PRODUCTS**

**bimobject**

**BOSTIK'S BIM JOURNEY HAS STARTED**

BOSTIK IN COLLABORATION WITH BIMOBJECT, THE WORLD'S LEADING BIM CONTENT PLATFORM, PROVIDES TO THE CONSTRUCTION SECTOR A LIBRARY OF DIGITAL OBJECTS FROM ITS SOLUTIONS. THESE BOSTIK DIGITAL OBJECTS WITH THEIR INTEGRATED DATA CAN BE EASILY DROPPED INTO THE ARCHITECTS AND DESIGNERS 3D MODELS.

**368 000**  
objects

**33 M**  
downloads

**1 300**  
manufacturers

**400 K**  
users

## What is BIM ?

BIM is a digital representation of physical and functional characteristics of a facility. BIM involves representing a design as combinations of «objects» that carry their geometry, relations and attributes. BIM design tools allow extraction of different views from a building model for drawing production and other uses. BIM allows all contributors to design, visualize, simulate and communicate throughout the building life cycle.

**YouTube**

Tutorial video on YouTube




## TO LEARN MORE

Go to the bimobject website:  
[www.bimobject.com/](http://www.bimobject.com/)



# NEW GENERATION OF SOFT FLOOR ADHESIVES



## ULTRA HIGH PERFORMANCE ADHESIVE FOR ALL TYPES OF SOFT FLOOR COVERINGS

- IDEAL FOR LVT AND RUBBER
- SHORT DRYING TIME
- HIGH INITIAL GRAB

## SELECTION GUIDE





> **SELECTION GUIDE**  
MIDDLE EAST AND AFRICA

RENO

REPAIR

HYTEC

DPM

GRIP

PRIMERS

**FLOOR  
PREPARATION**

**RENO**  
/ Subfloor reparation  
**HYTEC**  
/ Damp proof membranes  
**GRIP**  
/ Primers  
**TECHNIS**  
/ Screeds  
**SL**  
/ Self-leveling compounds

**SUBFLOOR PREPARATION**

CEMENT-BASED SCREED

LIGHTWEIGHT SCREED

CALCIUM SULPHATE-BASED SCREED

GYPSIUM-BASED DRY SCREED

ASPHALT SCREED

WOODEN PLANKS

CHIPBOARD, PLYWOOD, CTB-X, CTB-H, OSB-3

CERAMIC TILES, TERRAZZO AND STONE FLOORING

SEMI-FLEXIBLE TILES

EXISTING COATINGS AND PAINTS

SUBFLOORS WITH OLD WATERPROOF ADHESIVES RESIDUE

METAL

CRACKS TREATMENT

**TECHNICAL DATA**

CONSUMPTION

**RENO E742**  
STRUCTURE

**HYTEC A370**  
RAPID

**HYTEC E336**  
XTREM

**GRIP A310**  
PROJECT

**GRIP A500**  
MULTI

**GRIP A936**  
XPRESS

**GRIP X910**  
FILL AND WOOD

•

•

•

•

•

•

•

•

•

•

•

•

•

•

•

•

•

•

•

•

•

1 KG PER 5 TO 7  
LINEAR METERS

300 G/M²

400 - 800 G/M²

100 - 150 G/M²

90-100 G/M²

80-120 G/M²

800-1000 G/M²





> **SELECTION GUIDE**  
MIDDLE EAST AND AFRICA

TECHNIS

SCREED	TECHNIS C560 RAPID	TECHNIS C720 FLOW	TECHNIS C910 MIX	TECHNIS FIRST	TECHNIS R	TECHNIS T
RESIDENTIAL USE	●	●	●	●	●	●
COMMERCIAL USE	●	●	●		●	●
INDUSTRIAL USE	●					
BONDED SCREED	●	●	●			
ON SEPARATING LAYER	●	●	●	●	●	●
ON INSULATING LAYER	●	●		●	●	●
WATER HEATED FLOORS	●	●	●	●	●	●
EXTERIOR APPLICATION (IF RECOVERED)	●		●			
INTERIOR APPLICATION	●	●	●	●	●	●
TECHNICAL DATA						
MORTAR	●	●				
BINDER			●	●	●	●
WORKING TIME	20 MIN	60 MIN	45 MIN	3 H	4 H	2 H
READY FOR COVERING	FROM 2 H	FROM 7 DAYS	FROM 24 H	FROM 7 DAYS	FROM 7 DAYS	FROM 7 DAYS
COMPRESSIVE / FLEXIBLE STRENGTH	C40F7	C20F4	C40F7	C16F3	C20F4	C20F4
THICKNESS (MM)	5-60	MIN 30	10-60	MIN 35	MIN 30	MIN 30
CONSUMPTION	2 KG /MM /M²	2 KG /MM /M²	2-5 KG/M²/CM	-	-	-





> **SELECTION GUIDE**  
MIDDLE EAST AND AFRICA

SL



SELF-LEVELLING COMPOUNDS	SL C320 ARDASOL	SL C510 PRO	SL C740 MAXI FIBRE	SL C750 POLYRAG	SL C960 XL		SL C980 XPS	SL A930 UNIPLAN	SL C950 RENOQUICK
CEMENT-BASED SCREED	●	●	●	●	●		●	●	●
LIGHTWEIGHT SCREED			●	●				●	●
CALCIUM SULPHATE-BASED SCREED		●	●	●	●				
GYPSIUM-BASED DRY SCREED		●	●	●					
ASPHALT SCREED		●	●	●	●			●	
WOODEN PLANKS			●	●					
CHIPBOARD, PLYWOOD, CTB-X, CTB-H, OSB-3			●	●					
CERAMIC TILES, TERRAZZO AND STONE FLOORING		●	●	●	●		●	●	●
SEMI-FLEXIBLE VINYL TILES		●	●	●	●			●	
EXISTING COATINGS AND PAINTS		●	●	●				●	
SUBFLOORS WITH OLD WATERPROOF ADHESIVES RESIDUE	●	●	●	●	●			●	
TECHNICAL DATA									
CEMENT-BASED	●	●	●	●	●		●		
GYPSIUM BASED									
PATCHING								●	●
PUMPABLE	●	●	●	●	●		●		
PAINTABLE				●	●		●		
FIBER PRODUCT									
FAST PRODUCT			●						●
EXTERIOR FLOOR							●		
COMPRESSIVE / FLEXIBLE STRENGTH	C20F6	C30F7	C20F7	C30F7	C25F6		C40F7	-	C30F6
THICKNESS (MM)	1-10	1-20	1-10	1-10	3-60		3-15	0,5-2	1-50
CONSUMPTION	1,5 KG / MM / M²	1,5 KG / MM / M²	1,5 KG / MM / M²	1,5 KG / MM / M²	1,6 KG / MM / M²		1,8 KG / MM / M²	1,6 KG / MM / M²	1,6 KG / MM / M²





SELECTION GUIDE  
MIDDLE EAST AND AFRICA

STIX

SOFT FLOOR  
ADHESIVES



FIX

TACKIFIERS

CONTACT

ADHESIVES

SOFT FLOOR ADHESIVE	STIX A100 PROJECT	STIX A200 MULTI VINYL	STIX A300 MULTI FLOOR	STIX A320 TEX PROJECT	STIX A550 POWER ELASTIC		STIX A600 EVOLUTION	STIX A800 PREMIUM	STIX A970 ELECTRO	STIX P956 2K	STIX P966 TURF	FIX A320 TACK	FIX A570 MULTI TACK	FIX A760 TECH	CONTACT N525 MULTI
CARPET AND NATURAL FIBRE COVERINGS															
NEEDLE PUNCHED CARPET	●	●	●	●			●	●	●						●
CARPET WITH FOAM BACKING	●	●	●	●			●	●	●				●	●	●
CARPET WITH SYNTHETIC JUTE BASE – ACTION BAC®	●	●	●	●			●	●	●						●
CARPET WITH FELT OR NON-WOVEN BACKING	●	●	●	●			●	●	●				●		●
CARPET TILES WITH BITUMEN AND FELT BACKING												●	●	●	●
CARPET TILES WITH VINYL AND PU BACKING													●	●	●
NATURAL COCO-SISAL CARPET AND NATURAL FIBRES ON LATEX BACKING	●	●	●	●			●	●	●						●
RESILIENT FLOOR COVERINGS															
HETEROGENEOUS COMPACT PVC	●	●	●		●		●	●	●	●				●	
HETEROGENEOUS PVC WITH ACOUSTIC BACKING	●	●	●		●		●	●	●	●				●	
HOMOGENEOUS PVC		●	●		●		●	●	●	●					
LVT PLANKS OR TILES					●			●		●					
SEMI-FLEXIBLE TILES	●	●	●		●		●	●		●					●
LINOLEUM WITH ACOUSTIC BACKING			●		●		●	●		●					●
LINOLEUM SHEET AND TILES WITH JUTE BACKING										●					●
RUBBER WITH ACOUSTIC BACKING			●		●		●	●		●					●
RUBBER UP TO 3,5 MM					●			●		●					
RUBBER ABOVE TO 3,5 MM										●					
LOOSE LAY TILES AND PLANKS														●	
CONDUCTIVE FLOOR COVERINGS									●						
SYNTHETIC GRASS										●	●				
INDOOR PODOTACTILE TILES			●				●	●		●					
EXTERIOR PODOTACTILE TILES										●					
STAIR COVERINGS															
TEXTILE AND NATURAL FIBRE STAIR COVERINGS		●	●				●	●							●
PVC STAIR COVERINGS			●				●	●							
RUBBER STAIR COVERINGS															●
WALL COVERINGS															
PVC SHOWER SYSTEM		●	●				●	●							
PROTECTIVE WALL PLATES			●				●	●							
TECHNICAL DATA															
CONSUMPTION	250-400 G/M²	250-400 G/M²	250-400 G/M²	300-400 G/M²	320-360 G/M²		200-300 G/M²	250-400 G/M²	400-500 G/M²	300-900 G/M²	300-700 G/M²	60-100 G/M²	40-100 G/M²	60-120 G/M²	150 G /M² /FACE









$$>$$

# BOSTIK ROLL

BOSTIK ROLL	BOSTIK ROLL 25/50/85	BOSTIK ROLL 50R/85R	BOSTIK ROLL 240	BOSTIK ROLL RF50/RF100	BOSTIK ROLL SD50	BOSTIK ROLL 740	BOSTIK ROLL MT35
SPECIFIC LAYING							
REMOVABLE SOLUTION				●		●	
ON ASBESTOS VINYL TILES (DVA)				●			
ON SEMI-FLEXIBLE TILES	●	●		●		●	
ON EXISTING RESILIENT COVERINGS				●		●	
PODOTACTILE SLABS	●	●	●				
PROTECTIVE WALL PLATES	●	●	●				
PVC SHOWER SYSTEMS	●	●			●		
SKIRTING AND COVING SYSTEM							
HOMOGENEOUS AND HETEROGENEOUS PVC	●	●					
CARPET ALL BACKING	●	●					
NATURAL FIBRES WITH LATEX BACKING		●					
RUBBER	●	●					
LINOLEUM	●	●					
RIGID SKIRTING BOARDS (WOOD, PVC)	●	●					●
COVE FORMERS	●	●					●
STAIRS AND STAIR TREADS							
PVC			●				
CARPET			●				
RUBBER			●				
STAIR NOSING	●	●					●
LAYOUT							
STAIR NOSING							●





> **SELECTION GUIDE**  
MIDDLE EAST AND AFRICA

WOOD

WOOD FLOOR ADHESIVE	WOOD H100 PROJECT	WOOD P140 FIRST	WOOD H180 CLASSIC	WOOD H200 ELASTIC	WOOD H910 SILENTSTIK	WOOD P910 2K
SOLID WOOD FLOOR UP TO 100 MM WIDE	●	●	●	●	●	●
SOLID WOOD FLOOR UP TO 140 MM WIDE		●	●	●	●	●
SOLID WOOD FLOOR UP TO 180 MM WIDE			●	●		●
SOLID WOOD FLOOR UP TO 200 MM WIDE				●		●
MULTI-LAYER WOOD FLOOR	●	●	●	●	●	●
MOSAÏC PARQUET	●	●	●	●		
ON EDGE WOOD FLOORING	●	●	●	●		
STRIP PARQUET	●	●	●	●		
TEAK PARQUET, EXOTIC WOODS		●	●	●	●	
ACOUSTIC SOLUTION UP TO 19 DB					●	
TECHNICAL DATA						
CONSUMPTION	850 - 1350 KG/M²	1 - 1,4 KG/M²	1 - 1,4 KG/M²	1 - 1,4 KG/M²	1,6 - 2 KG/M²	0,9 - 1,1 KG/M²







**Bostik Consumer & Construction**  
**Arkema Middle East DMCC**  
UNIT 1108, JBC3 TOWER CLUSTER Y  
JUMEIRAH LAKES TOWERS  
DUBAI, UNITED ARAB EMIRATES  
E-MAIL: BOSTIK.MENA-INFO@BOSTIK.COM  
PHONE: +971 4 875 1700

**Bostik S.A.**  
420 Rue d'Estienne d'Orves  
92700 COLOMBES - FRANCE  
Tél. : +33 (1) 49 00 90 00

[www.bostik.com](http://www.bostik.com)

This catalogue is published  
by **Bostik**

Design and editorial support:  
**RED AGENCY** PARIS

Photo credits: Bostik - Tarkett - Objectfloor - Gerflor  
- Balsan - Ege - Shutterstock® - Getty Images® - Arkema

As part of Arkema's sustainable development process,  
this report is printed on PEFC-certified paper sourced  
from pulp from responsibly managed forests.  
The printer has been awarded the Imprim'vert® label  
for compliance with the French printing industry's  
environmental standards.