



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008
This SDS is for generic information purposes and does not reflect required country specific information for OEL

BOSTIK HYTEC E736 TURBO - RESIN
Supersedes Date: 04-May-2022

Revision date 04-May-2022
Revision Number 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK HYTEC E736 TURBO - RESIN
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Resin
Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik SA
420 rue d'Estienne d'Orves
92700 Colombes
FRANCE
Tel: +33 (0)1 49 00 90 00

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin corrosion/irritation	Category 2 - (H315)
Skin sensitisation	Category 1 - (H317)
Chronic aquatic toxicity	Category 2 - (H411)

2.2. Label elements

Contains bis-[4-(2,3-epoxipropoxy)phenyl]propane, Oxirane, mono[(C12-14-alkyloxy)methyl] derivs., Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-{ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane



Signal word
Warning

SAFETY DATA SHEET

BOSTIK HYTEC E736 TURBO - RESIN
Supersedes Date: 04-May-2022

Revision date 04-May-2022
Revision Number 1

Hazard statements

H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H411 - Toxic to aquatic life with long lasting effects

EU Specific Hazard Statements

EUH205 - Contains epoxy constituents. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P273 - Avoid release to the environment
P280 - Wear protective gloves and eye/face protection
P391 - Collect spillage
P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

This product is part of a kit. Please also refer to the SDS for the other component(s) of the kit.

2.3. Other hazards

Toxic to aquatic life.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No.	CAS No.	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Reaction mass of 2,2'-[methylenebis(4,1-p henyleneoxymethylene)] dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy) benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-p henyleneoxymethylene)] dioxirane 80 - 100 %	701-263-0	--	Aquatic Chronic 2 (H411) Skin Irrit. 2 (H315) Skin Sens. 1 (H317)	-	-	-	01-2119454392-40-XXXX
Oxirane, mono[(C12-14-alkyloxy) methyl] derivs. 5 - <10 %	271-846-8	68609-97-2	Skin Irrit. 2 (H315) Skin Sens. 1 (H317)	-	-	-	01-2119485289-22-XXXX
bis-[4-(2,3-epoxipropoxy) phenyl]propane 1 - <5 %	216-823-5	1675-54-3	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Aquatic Chronic 2 (H411)	Eye Irrit. 2 :: C>=5% Skin Irrit. 2 :: C>=5%	-	-	01-2119456619-26-xxxx

Full text of H- and EUH-phrases: see section 16

SAFETY DATA SHEET

BOSTIK HYTEC E736 TURBO - RESIN
Supersedes Date: 04-May-2022

Revision date 04-May-2022
Revision Number 1

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No	CAS No	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl]oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane	701-263-0	--	-	-	-	-	-
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	271-846-8	68609-97-2	-	-	-	-	-
bis-[4-(2,3-epoxipropoxy)phenyl]propane	216-823-5	1675-54-3	-	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a doctor.
Skin contact	May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes.
Ingestion	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Itching. Rashes. Hives.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors May cause sensitisation in susceptible persons. Treat symptomatically.

SECTION 5: Firefighting measures

SAFETY DATA SHEET

BOSTIK HYTEC E736 TURBO - RESIN
Supercedes Date: 04-May-2022

Revision date 04-May-2022
Revision Number 1

5.1. Extinguishing media

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Product is or contains a sensitiser. May cause sensitisation by skin contact.

Hazardous combustion products Carbon oxides. Carbon monoxide. Carbon dioxide (CO₂).

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so.

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling This product is part of a kit. Please also refer to the SDS for the other component(s) of the kit. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse.

General hygiene considerations Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

SAFETY DATA SHEET

BOSTIK HYTEC E736 TURBO - RESIN
Supersedes Date: 04-May-2022

Revision date 04-May-2022
Revision Number 1

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.

Recommended storage temperature Keep at temperatures between 5 and 35 °C.

7.3. Specific end use(s)

Specific use(s)
Resin.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl]oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane (--)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	29,39 mg/m ³	
worker Long term Systemic health effects	Dermal	104,15 mg/kg bw/d	

bis-[4-(2,3-epoxipropoxy)phenyl]propane (1675-54-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	12.25 mg/m ³	
worker Short term Systemic health effects	Inhalation	12.25 mg/m ³	
worker Long term Systemic health effects	Dermal	8.33 mg/kg bw/d	
worker Short term Systemic health effects	Dermal	8.33 mg/kg bw/d	

Derived No Effect Level (DNEL)			
Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-{			

SAFETY DATA SHEET

BOSTIK HYTEC E736 TURBO - RESIN
Supersedes Date: 04-May-2022

Revision date 04-May-2022
Revision Number 1

2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane (--)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	8,7 mg/m ³	
Consumer Long term Systemic health effects	Dermal	62,5 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	6,25 mg/kg bw/d	

bis-[4-(2,3-epoxipropoxy)phenyl]propane (1675-54-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	3.571 mg/kg bw/d	
Consumer Short term Systemic health effects	Dermal	3.571 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.75 mg/kg bw/d	
Consumer Short term Systemic health effects	Dermal	0.75 mg/kg bw/d	

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)	
Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane (--)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0,003 mg/l
Freshwater - intermittent	0,025 mg/l
Sewage treatment plant	10 mg/l
Marine water	0 mg/l
Freshwater sediment	0,294 mg/kg dry weight
Marine sediment	0,029 mg/kg dry weight
Soil	0,237 mg/kg dry weight

bis-[4-(2,3-epoxipropoxy)phenyl]propane (1675-54-3)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.006 mg/l
Marine water	0.001 mg/l
Sewage treatment plant	10 mg/l
Freshwater sediment	0.996 mg/kg dry weight
Marine sediment	0.1 mg/kg dry weight
Soil	0.196 mg/kg dry weight

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

SAFETY DATA SHEET

BOSTIK HYTEC E736 TURBO - RESIN
Supersedes Date: 04-May-2022

Revision date 04-May-2022
Revision Number 1

Personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Hand protection

Recommended Use: Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Unsuitable gloves materials: Disposable gloves. Leather. Gloves must conform to standard EN 374

Skin and body protection

Wear suitable protective clothing.

Respiratory protection

During spraying wear suitable respiratory equipment. In case of inadequate ventilation wear respiratory protection.

Recommended filter type:

Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Organic gases and vapours filter conforming to EN 14387.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Viscous
Colour	Colourless
Odour	Odourless.
Odour threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	None known
Flammability	Not applicable for liquids .	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	100 °C	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	No data available	Not applicable
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	1500 2100 mPa s	Spindle A3 @ 30 rpm @ 23 °C
Water solubility	No data available	None known
Solubility(ies)	Acetone Methyl ethyl ketone	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk Density	No data available	
Density	1.13	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

VOC Content (%)

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics

SAFETY DATA SHEET

BOSTIK HYTEC E736 TURBO - RESIN
Supercedes Date: 04-May-2022

Revision date 04-May-2022
Revision Number 1

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid None known based on information supplied.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.

Eye contact Based on available data, the classification criteria are not met.

Skin contact May cause sensitisation by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Causes skin irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes.

Acute toxicity

SAFETY DATA SHEET

BOSTIK HYTEC E736 TURBO - RESIN
Supersedes Date: 04-May-2022

Revision date 04-May-2022
Revision Number 1

Numerical measures of toxicity

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane	LD50 > 5000 mg/kg (rattus)	LD50 > 2000 mg/kg (rattus) OECD Guideline 402	-
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	=17100 mg/kg (Rattus)	LD50 >4000 mg/Kg Rabbit	-
bis-[4-(2,3-epoxipropoxy)phenyl]propane	=11300 µL/kg (Rattus)	LD50 >2000 mg/Kg (Rattus)	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Irritating to skin.

Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal		24 hours	Product score 5.75 irritant

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Corneal			Product score 2 irritant

Respiratory or skin sensitisation May cause sensitisation by skin contact.

Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	sensitising

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

BOSTIK HYTEC E736 TURBO - RESIN
 Supersedes Date: 04-May-2022

Revision date 04-May-2022
 Revision Number 1

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

Note: PC-ADH-8 Multi-component adhesives and sealants This product is part of a kit Please also refer to the SDS for the other component(s) of the kit

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane --	EC50 (72h) = 1.8 mg/l	LC50 (96h) = 2.54 mg/l	-	EC50 (48h) = 2.55 mg/l (Daphnia magna)		
bis-[4-(2,3-epoxypropoxy)phenyl]propane 1675-54-3	EC50 (72h) = 9.4 mg/L (Scenedesmus capricornutum) EPA-660/3-75-009	1.5 mg/l 96Hr (Oncorhynchus mykiss) (OECD 203)	-	LD50 (48h) = 2.7 mg/L (Daphnia magna) (OECD 202)		

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	3.6
	3.77

SAFETY DATA SHEET

BOSTIK HYTEC E736 TURBO - RESIN
Supersedes Date: 04-May-2022

Revision date 04-May-2022
Revision Number 1

bis-[4-(2,3-epoxipropoxy)phenyl]propane	3.78
---	------

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

Chemical name	PBT and vPvB assessment
Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy) methyl]oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	The substance is not PBT / vPvB
bis-[4-(2,3-epoxipropoxy)phenyl]propane	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number	UN3082
14.2 Proper Shipping Name	Environmentally hazardous substances, liquid, n.o.s (Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy) methyl]oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane, bis-[4-(2,3-epoxipropoxy)phenyl]propane)
14.3 Transport hazard class(es)	9
Labels	9
14.4 Packing group	III
Description	UN3082, Environmentally hazardous substances, liquid, n.o.s (Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy) methyl]oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane, bis-[4-(2,3-epoxipropoxy)phenyl]propane), 9, III, (-)
14.5 Environmental hazards	Yes
14.6 Special Provisions	274, 335, 601, 375
Classification code	M6
Tunnel restriction code	(-)

SAFETY DATA SHEET

BOSTIK HYTEC E736 TURBO - RESIN
Supersedes Date: 04-May-2022

Revision date 04-May-2022
Revision Number 1

Limited quantity (LQ) 5 L
ADR Hazard Id (Kemmler Number) 90

IMDG

14.1 UN number or ID number UN3082
14.2 Proper Shipping Name Environmentally hazardous substances, liquid, n.o.s (Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane, bis-[4-(2,3-epoxipropoxy)phenyl]propane)
14.3 Transport hazard class(es) 9
14.4 Packing group III
Description UN3082, Environmentally hazardous substances, liquid, n.o.s (Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane, bis-[4-(2,3-epoxipropoxy)phenyl]propane), 9, III, Marine Pollutant
14.5 Marine pollutant P
14.6 Special Provisions 274, 335, 969
Limited Quantity (LQ) 5 L
EmS-No F-A, S-F
14.7 Maritime transport in bulk according to IMO instruments Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number UN3082
14.2 Proper Shipping Name Environmentally hazardous substances, liquid, n.o.s (Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane, bis-[4-(2,3-epoxipropoxy)phenyl]propane)
14.3 Transport hazard class(es) 9
14.4 Packing group III
Description UN3082, Environmentally hazardous substances, liquid, n.o.s (Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane, bis-[4-(2,3-epoxipropoxy)phenyl]propane), 9, III
14.5 Environmental hazards Yes
14.6 Special Provisions A97, A158, A197
Limited quantity (LQ) 30 kg G
ERG Code 9L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

SAFETY DATA SHEET

BOSTIK HYTEC E736 TURBO - RESIN
Supercedes Date: 04-May-2022

Revision date 04-May-2022
Revision Number 1

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

France

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) obviously hazardous to water (WGK 2)

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Not Listed

Denmark

Registration number(s) (P-no.) No information available

Norway

Registration number(s) (PRN-no.) No information available

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H411 - Toxic to aquatic life with long lasting effects

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

vPvB: Very Persistent and very Bioaccumulative (vPvB) Chemicals

SAFETY DATA SHEET

BOSTIK HYTEC E736 TURBO - RESIN
Supersedes Date: 04-May-2022

Revision date 04-May-2022
Revision Number 1

STOT RE: Specific target organ toxicity - Repeated exposure
STOT SE: Specific target organ toxicity - Single exposure
EWC: European Waste Catalogue
LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
IATA: International Air Transport Association
ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG: International Maritime Dangerous Goods
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)
European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)
European Chemicals Agency (ECHA) (ECHA_API)
EPA (Environmental Protection Agency)
Acute Exposure Guideline Level(s) (AEGl(s))
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
NIOSH (National Institute for Occupational Safety and Health)
Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications
Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme
Organisation for Economic Co-operation and Development Screening Information Data Set

Prepared By Product Safety & Regulatory Affairs

Revision date 04-May-2022

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing,

SAFETY DATA SHEET

BOSTIK HYTEC E736 TURBO - RESIN
Supersedes Date: 04-May-2022

Revision date 04-May-2022
Revision Number 1

storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet