

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

### BOSTIK PRO SEALANT S31 SANITARY SILICONE CLEAR Supercedes Date: 08-Apr-2022

Revision date 08-Apr-2022 Revision Number 1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier			
Product Name	BOSTIK PRO SEALANT S31 SANITARY SILICONE CLEAR		
Pure substance/mixture	Mixture		
1.2. Relevant identified uses of th	ne substance or mixture and uses advised against		
Recommended use	Sealant		
Uses advised against	None known		
1.3. Details of the supplier of the	safety data sheet		
<u>Company Name</u> Bostik Limited Common Rd ST16 3EH Stafford UK Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36			
E-mail address	SDS.box-EU@bostik.com		
1.4. Emergency telephone number	<u>)r</u>		
United Kingdom Ireland Europe	+44 (1785) 272650 Bostik: +353 (1) 8624900 (Monday- Friday 9am-5pm) 112		
SECTION 2: Hazards identi	fication		
2.1. Classification of the substan	<u>ce or mixture</u>		
Regulation (EC) No 1272/2008			
Chronic aquatic toxicity	Category 3 - (H412)		
2.2. Label elements			
Signal word None			
Hazard statements H412 - Harmful to aquatic life with h	ong lasting effects.		

EU Specific Hazard Statements

EUH208 - Contains 3-(Triethoxysilyl) propylamine & 2-octyl-2H-isothiazol-3-one [OIT]. May produce an allergic reaction

## Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P273 - Avoid release to the environment

### BOSTIK PRO SEALANT S31 SANITARY SILICONE CLEAR Supercedes Date: 08-Apr-2022

Revision date 08-Apr-2022 Revision Number 1

P501 - Dispose of contents/ container to an approved waste disposal plant

## 2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing. Small amounts of 2-Pentanone oxime (CAS 623-40-5) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

#### PBT & vPvB

This mixture contains substances considered to be very persistent and very bioaccumulating (vPvB). This mixture contains substances considered to be persistent, bio-accumulating and toxic (PBT).

## SECTION 3: Composition/information on ingredients

#### 3.1 Substances

Not applicable

## 3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
2-Pentandione, O,O',O''-(methylsilylidyn e)trioxime	484-460-1	37859-55-5	1 - <5	Acute Tox. 4 (H302) Eye Irrit. 2 (H319)	-	01-2120004323- 76-XXXX
3-(Triethoxysilyl) propylamine	213-048-4	919-30-2	0.1 - <1	Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Acute Tox. 4 (H302)	-	01-2119480479- 24-XXXX
2-octyl-2H-isothiazol-3-o ne [OIT]	247-761-7	26530-20-1	0.0015 - <0.01	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 2 (H330) Skin Corr. 1B (H314) Eye Dam 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	Skin Sens. 1A :: C>=0.0015%	-

### Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

BOSTIK PRO SEALANT S31 SANITARY SILICONE CLEAR Supercedes Date: 08-Apr-2022

SECTION 4: First aid measures				
4.1. Description of first aid measures				
General advice	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.			
Inhalation	Remove to fresh air. If symptoms persist, call a doctor.			
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.			
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.			
Ingestion	If swallowed, rinse mouth with water (only if the person is conscious). Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.			
4.2. Most important symptoms and	d effects, both acute and delayed			
Symptoms	None known.			
4.3. Indication of any immediate m	edical attention and special treatment needed			
Note to doctors	Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released, when the product is exposed to moisture or water. Treat symptomatically.			
SECTION 5: Firefighting measures				
SECTION 5: Firefighting me	asures			
SECTION 5: Firefighting me 5.1. Extinguishing media	asures			
	asures Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.			
5.1. Extinguishing media				
5.1. Extinguishing media Suitable Extinguishing Media	Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Full water jet.			
5.1. Extinguishing media Suitable Extinguishing Media Unsuitable extinguishing media 5.2. Special hazards arising from t	Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Full water jet.			
5.1. Extinguishing media Suitable Extinguishing Media Unsuitable extinguishing media 5.2. Special hazards arising from the	Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Full water jet. <b>he substance or mixture</b>			
5.1. Extinguishing media Suitable Extinguishing Media Unsuitable extinguishing media 5.2. Special hazards arising from the Specific hazards arising from the chemical	Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Full water jet. <u>he substance or mixture</u> Thermal decomposition can lead to release of irritating gases and vapours. Carbon dioxide (CO2). Silicon oxides. Silicon dioxide. Thermal decomposition can lead			
5.1. Extinguishing media Suitable Extinguishing Media Unsuitable extinguishing media 5.2. Special hazards arising from the Specific hazards arising from the chemical Hazardous combustion products 5.3. Advice for firefighters	Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Full water jet. <u>he substance or mixture</u> Thermal decomposition can lead to release of irritating gases and vapours. Carbon dioxide (CO2). Silicon oxides. Silicon dioxide. Thermal decomposition can lead			
5.1. Extinguishing media Suitable Extinguishing Media Unsuitable extinguishing media 5.2. Special hazards arising from the Specific hazards arising from the chemical Hazardous combustion products 5.3. Advice for firefighters Special protective equipment and	Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Full water jet. <b>he substance or mixture</b> Thermal decomposition can lead to release of irritating gases and vapours. Carbon dioxide (CO2). Silicon oxides. Silicon dioxide. Thermal decomposition can lead to release of irritating and toxic gases and vapours. Wear self contained breathing apparatus for fire fighting if necessary.			
<ul> <li><u>5.1. Extinguishing media</u></li> <li>Suitable Extinguishing Media</li> <li>Unsuitable extinguishing media</li> <li><u>5.2. Special hazards arising from the</u></li> <li>Specific hazards arising from the chemical</li> <li>Hazardous combustion products</li> <li><u>5.3. Advice for firefighters</u></li> <li>Special protective equipment and precautions for fire-fighters</li> <li><u>SECTION 6: Accidental releated</u></li> </ul>	Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Full water jet. <u>he substance or mixture</u> Thermal decomposition can lead to release of irritating gases and vapours. Carbon dioxide (CO2). Silicon oxides. Silicon dioxide. Thermal decomposition can lead to release of irritating and toxic gases and vapours. Wear self contained breathing apparatus for fire fighting if necessary.			

- **For emergency responders** Use personal protection recommended in Section 8.
- 6.2. Environmental precautions

## BOSTIK PRO SEALANT S31 SANITARY SILICONE CLEAR Supercedes Date: 08-Apr-2022

Environmental precautions	Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.			
6.3. Methods and material for cont	ainment and	cleaning up		
Methods for containment	Do not scatte	Do not scatter spilled material with high pressure water streams.		
Methods for cleaning up	Take up med	chanically, placing in appropriate conta	iners for disposal.	
Prevention of secondary hazards	Clean contar	minated objects and areas thoroughly o	observing environmental regulations.	
6.4. Reference to other sections				
Reference to other sections	See section	8 for more information. See section 13	for more information.	
SECTION 7: Handling and s	torage			
7.1. Precautions for safe handling	_			
Advice on safe handling	Ensure adeo	uate ventilation.		
General hygiene considerations	Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Take off all contaminated clothing and wash it before reuse.			
7.2. Conditions for safe storage, in	icluding any i	ncompatibilities		
Storage Conditions	Protect from moisture. Keep away from food, drink and animal feedingstuffs.			
Recommended storage temperature	Keep at temperatures between 10 and 35 °C.			
7.3. Specific end use(s)				
<b>Specific use(s)</b> Sealant.				
Risk Management Methods (RMM)	The informat	ion required is contained in this Safety	Data Sheet.	
Other information	Observe technical data sheet.			
SECTION 8: Exposure contr	ols/person	al protection		
8.1. Control parameters				
Exposure Limits	Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing			
Chemical name		European Union	United Kingdom	
Ethanol		- 1	TWA: 1000 ppm	

Chemical name	European Union	United Kingdom
Ethanol	-	TWA: 1000 ppm
64-17-5		TWA: 1920 mg/m <sup>3</sup>
		STEL: 3000 ppm
		STEL: 5760 mg/m <sup>3</sup>
Methyl alcohol	TWA: 200 ppm	TWA: 200 ppm
67-56-1	TWA: 260 mg/m <sup>3</sup>	TWA: 266 mg/m <sup>3</sup>
	*	STEL: 250 ppm
		STEL: 333 mg/m <sup>3</sup>
		Sk*

Chemical name	European Union	Ireland	United Kingdom
Methyl alcohol	-	15 mg/L (urine - Methanol end of	-
67-56-1		shift)	

## **BOSTIK PRO SEALANT S31 SANITARY SILICONE CLEAR** Supercedes Date: 08-Apr-2022

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)					
3-(Triethoxysilyl) propylamir	3-(Triethoxysilyl) propylamine (919-30-2)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
worker Long term Systemic health effects	Inhalation	59 mg/m³			
worker Short term Systemic health effects	Inhalation	59 mg/m³			
worker Long term Systemic health effects	Dermal	8.3 mg/kg bw/d			
worker Short term Systemic health effects	Dermal	8.3 mg/kg bw/d			

Derived No Effect Level (DNEL)				
3-(Triethoxysilyl) propylamir	ne (919-30-2)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
Consumer Long term Systemic health effects	Inhalation	17 mg/m³		
Consumer Short term Systemic health effects	Inhalation	17.4 mg/m³		
Consumer Long term Systemic health effects	Dermal	5 mg/kg bw/d		
Consumer Short term Systemic health effects	Dermal	5 mg/kg bw/d		

## Predicted No Effect Concentration No information available. (PNEC)

Predicted No Effect Concentration (PNEC)		
3-(Triethoxysilyl) propylamine (919-30-2)		
Environmental compartment	Predicted No Effect Concentration (PNEC)	
Freshwater	0.33 mg/l	
Marine water	0.033 mg/l	

## 8.2. Exposure controls

**Engineering controls** 

Ensure adequate ventilation, especially in confined areas.

## Personal protective equipment

Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.
Wear suitable gloves. Recommended Use:. Neoprene <sup>™</sup> . Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
None under normal use conditions.
In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation,

#### BOSTIK PRO SEALANT S31 SANITARY SILICONE CLEAR Supercedes Date: 08-Apr-2022

Revision date 08-Apr-2022 Revision Number 1

Recommended filter type:

especially in confined areas. Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties **Physical state** Solid Appearance Paste Colour Colourless Odour Characteristic. **Odour threshold** No information available Remarks • Method **Property** Values Melting point / freezing point No data available None known Initial boiling point and boiling No data available °C range Not applicable for liquids . Flammability Flammability Limit in Air None known Upper flammability or explosive No data available limits Lower flammability or explosive No data available limits Flash point > 100 °C CC (closed cup) Autoignition temperature No data available **Decomposition temperature** None known pН No data available Not applicable Insoluble in water pH (as aqueous solution) No data available None known > 21 mm<sup>2</sup>/s @ 40 °C **Kinematic viscosity** Dynamic viscosity No data available Water solubility No data available Immiscible in water No data available Solubility(ies) None known Partition coefficient No data available None known No data available Vapour pressure None known Relative density No data available None known Bulk Density No data available Density 1.02 Relative vapour densityNo data available None known **Particle characteristics** Particle Size No information available **Particle Size** No information available

Distribution

#### 9.2. Other information VOC Content (%)

9.2.1. Information with regards to physical hazard classes Not applicable

9.2.2. Other safety characteristics No information available

## SECTION 10: Stability and reactivity

## 10.1. Reactivity

Reactivity

Product cures with moisture.

## 10.2. Chemical stability

## BOSTIK PRO SEALANT S31 SANITARY SILICONE CLEAR

Supercedes Date: 08-Apr-2022

Stability	Stable under normal conditions.	
Explosion data		
Sensitivity to mechanical impact	None.	
Sensitivity to static discharge	None.	
10.3. Possibility of hazardous read	ctions	
Possibility of hazardous reactions	None under normal processing.	
10.4. Conditions to avoid		
Conditions to avoid	Product cures with moisture. Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.	
10.5. Incompatible materials		
Incompatible materials	Strong oxidising agents.	
10.6. Hazardous decomposition products		
Hazardous decomposition products	Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing.	
SECTION 11. Toxicological	information	

## SECTION 11: Toxicological information

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

## Information on likely routes of exposure

## **Product Information**

	Inhalation	Based on available data, the classification criteria are not met.	
	Eye contact	Based on available data, the classification criteria are not met.	
	Skin contact	Based on available data, the classification criteria are not met.	
	Ingestion	Based on available data, the classification criteria are not met.	
Symptoms related to the physical, chemical and toxicological characteristics			

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	No information available.
----------	---------------------------

#### 

## Numerical measures of toxicity

# The following values are calculated based on chapter 3.1 of the GHS documentATEmix (oral)38,727.60mg/kgATEmix (dermal)48,208.00mg/kg

## **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
2-Pentandione,	LD50 =1234 mg/kg bw	LD50 > 2000 mg/kg (Rattus)	-

## BOSTIK PRO SEALANT S31 SANITARY SILICONE CLEAR

Supercedes Date: 08-Apr-2022

### Revision date 08-Apr-2022 Revision Number 1

O,O',O''-(methylsilylidyne)trioxi	(Rattus)(OECD guideline 425)	EU Method B.3	
me			
3-(Triethoxysilyl) propylamine	LD50 = 1490 mg/kg (Rat,	LD50 = 4076 mg/kg	LC50 >144 mg/L (6h) Rat
	female) EPA OTS 798.1175	(Oryctolagus cuniculus) EPA	(Vapour)
	LD50 = 2690 mg/kg (Rat,	OTS 798.1100	
	male) EPA OTS 798.1175		
2-octyl-2H-isothiazol-3-one	=125 mg/kg (Rattus)	= 690 mg/kg (Oryctolagus	-
[OIT]		cuniculus)	

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

## 2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit	Dermal			Corrosive
Acute Dermal					
Irritation/Corrosion					

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation** May produce an allergic reaction.

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Species	Exposure route	Results
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse		sensitising
Germ cell mutagenicity	Based on available data, the	e classification criteria are i	not met.
Carcinogenicity	Based on available data, the	e classification criteria are i	not met.
Reproductive toxicity	Based on available data, the	e classification criteria are i	not met.
STOT - single exposure	Based on available data, the	e classification criteria are i	not met.
STOT - repeated exposure	Based on available data, the	e classification criteria are I	not met.
Aspiration hazard	Based on available data, the	e classification criteria are i	not met.
11.2. Information on other hazard	l <u>s</u>		
11.2.1. Endocrine disrupting pro	perties		
Endocrine disrupting properties	No information available.		
11.2.2. Other information			
Other adverse effects	No information available.		

## BOSTIK PRO SEALANT S31 SANITARY SILICONE CLEAR Supercedes Date: 08-Apr-2022

## Revision date 08-Apr-2022 Revision Number 1

## **SECTION 12: Ecological information**

## 12.1. Toxicity

## Ecotoxicity

Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
2-Pentandione, O,O',O''-(methylsilylidy ne)trioxime 37859-55-5	EC50 (72h) = 88 mg/L (Pseudokirchner iella subcapitata)	>113 mg/L (Oncorhynchus mykiss) Static (OECD	-	EC50 (48h) >100 mg/L (Daphnia magna) static (OECD		
3-(Triethoxysilyl) propylamine 919-30-2	OECD 201 EC50 (72h) >1000 mg/L Green algae (desmodesmus subspicatus) (OECD TG 201)	TG 203)	-	guideline 202) EC50 (48h) =331 mg/L Daphnia magna (OECD TG 202)		
2-octyl-2H-isothiazol-3- one [OIT] 26530-20-1	EC50(72h) = 0.084 mg/L (Scenedesmus subspicatus) (OECD 201)	LC50 (96h) = 0.036 mg/L (Oncorhynchus mykiss) (OECD 203)	-	EC50 (48h) =0.42 mg/L (OECD 202)	100	100

## 12.2. Persistence and degradability

Persistence and degradability No information available.

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Exposure time	Value	Results
OECD Test No. 309: Aerobic		Half-life 0.6-1.4 d	Readily biodegradable
Mineralization in Surface Water -			
Simulation Biodegradation Test			

## 12.3. Bioaccumulative potential

### Bioaccumulation

## **Component Information**

Chemical name	Partition coefficient
2-Pentandione, O,O',O''-(methylsilylidyne)trioxime	1.25
3-(Triethoxysilyl) propylamine	1.7
2-octyl-2H-isothiazol-3-one [OIT]	2.92

## 12.4. Mobility in soil

Mobility in soil

No information available.

## 12.5. Results of PBT and vPvB assessment

### PBT and vPvB assessment

The product contains substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
2-Pentandione, O,O',O"-(methylsilylidyne)trioxime	The substance is not PBT / vPvB
3-(Triethoxysilyl) propylamine	The substance is not PBT / vPvB
2-octyl-2H-isothiazol-3-one [OIT]	The substance is not PBT / vPvB

## 12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

BOSTIK PRO SEALANT S31 SANITARY SILICONE CLEAR Supercedes Date: 08-Apr-2022

12.7. Other adverse effects

No information available.

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

Waste from residues/unused products	Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Handle contaminated packages in the same way as the product itself.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

## **SECTION 14: Transport information**

#### Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None
IMDG	
14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special Provisions	None
14.7 Maritime transport in bulk	Not applicable
according to IMO instruments	
Air transport (ICAO-TI / IATA-DGR)	<u> </u>
14.1 UN number or ID number	Not regulated
1/1.2 Proper Shipping Name	Not regulated

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

## Section 15: REGULATORY INFORMATION

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

## BOSTIK PRO SEALANT S31 SANITARY SILICONE CLEAR

Supercedes Date: 08-Apr-2022

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

## Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

## SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

## Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

### Ozone-depleting substances (ODS) regulation (EC) 1005/2009 Not applicable

## Persistent Organic Pollutants

Not applicable

## National regulations

## 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

## Key or legend to abbreviations and acronyms used in the safety data sheet

## Full text of H-Statements referred to under section 3

- H301 Toxic if swallowed
- H302 Harmful if swallowed
- H311 Toxic in contact with skin
- H314 Causes severe skin burns and eye damage
- H317 May cause an allergic skin reaction
- H318 Causes serious eye damage H319 - Causes serious eye irritation
- H330 Fatal if inhaled
- H400 Very toxic to aquatic life
- H410 Very toxic to aquatic life with long lasting effects

## Legend

TWĂ	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure

### BOSTIK PRO SEALANT S31 SANITARY SILICONE CLEAR Supercedes Date: 08-Apr-2022

Revision date 08-Apr-2022 Revision Number 1

STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
ΙΑΤΑ	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

#### Key literature references and sources for data No information available

Prepared By	Product Safety & Regulatory Affairs
Revision date	08-Apr-2022
Indication of changes	
Revision note	SDS sections updated: 2.
Training Advice	No information available
Further information	No information available

## This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

## End of Safety Data Sheet