

Revision date 08-Apr-2022

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

BOSTIK PRO SEALANT S21 MULTI PURPOSE SILICONE

WHITE

Supercedes Date: 08-Apr-2022 Revision Number 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK PRO SEALANT S21 MULTI PURPOSE SILICONE WHITE

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom +44 (1785) 272650

Ireland Bostik: +353 (1) 8624900 (Monday- Friday 9am-5pm)

Europe 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Chronic aquatic toxicity Category 3 - (H412)

2.2. Label elements

Signal word

None

Hazard statements

H412 - Harmful to aquatic life with long lasting effects.

EU Specific Hazard Statements

EUH208 - Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

United Kingdom - BE Page 1 / 13

Revision date 08-Apr-2022

BOSTIK PRO SEALANT S21 MULTI PURPOSE SILICONE

WHITE

Supercedes Date: 08-Apr-2022 Revision Number 1

P273 - Avoid release to the environment

P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

Small amounts of acetic acid (CAS 64-19-7) are formed by hydrolysis and released upon curing.

PBT & vPvB

This mixture contains substances considered to be persistent, bio-accumulating and toxic (PBT). This mixture contains substances considered to be very persistent and very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Triacetoxy(propyl)silane	241-816-9	17865-07-5	1 - <3	Skin Corr. 1B (H314) (EUH071)	-	01-2119966899- 07-XXXX
Silanetriol, methyl-, triacetate	224-221-9	4253-34-3	1- <2.5	Skin Corr. 1C (H314) Acute Tox. 4 (H302) (EUH014)	-	01-2119962266- 32-XXXX
Titanium dioxide	236-675-5	13463-67-7	0.1 - <1	^	-	01-2119489379- 17-XXXX
Octamethylcyclotetrasilo xane [D4]	209-136-7	556-67-2	0.01 - <0.1	Repr. 2 (H361f) Aquatic Chronic 1 (H410) Flam. Liq. 3 (H226) [G]	-	01-2119529238- 36-XXXX
4,5-dichloro-2-octyl-2H-i sothiazol-3-one [DCOIT]	264-843-8	64359-81-5	0.01 - <0.05	Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Acute Tox. 4 (H302) Acute Tox. 2 (H330) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) (EUH071)	Skin Irrit. 2 :: 0.025%<=C<5% Eye Irrit. 2 :: 0.025%<=C<3% Skin Sens. 1A :: C>=0.0015%	-

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

United Kingdom - BE Page 2 / 13

BOSTIK PRO SEALANT S21 MULTI PURPOSE SILICONE

WHITE

Supercedes Date: 08-Apr-2022 **Revision Number** 1

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice If medical advice is needed, have product container or label at hand.

Inhalation Remove to fresh air. If symptoms persist, call a doctor.

Immediately flush with plenty of water. After initial flushing, remove any contact lenses Eye contact

and continue flushing for at least 15 minutes. Consult an ophthalmologist.

Skin contact Wash skin with soap and water. In the case of skin irritation or allergic reactions see a

doctor.

Ingestion Do NOT induce vomiting. Rinse mouth thoroughly with water. Never give anything by

mouth to an unconscious person. Call a doctor or poison control centre immediately.

Revision date 08-Apr-2022

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the Thermal decomposition can lead to release of irritating gases and vapours.

chemical

Carbon dioxide (CO2). Silicon dioxide. **Hazardous combustion products**

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Wear self contained breathing apparatus for fire fighting if necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Do not get **Personal precautions**

in eyes, on skin, or on clothing.

Other information Prevent further leakage or spillage if safe to do so.

United Kingdom - BE Page 3 / 13

BOSTIK PRO SEALANT S21 MULTI PURPOSE SILICONE

WHITE

Supercedes Date: 08-Apr-2022 Revision Number 1

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section

12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth,

diatomaceous earth, vermiculite) and place in container for disposal according to local /

Revision date 08-Apr-2022

national regulations (see Section 13).

Methods for cleaning upTake up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Use personal protection equipment. Avoid contact with

skin, eyes or clothing. Keep away from open flames, hot surfaces and sources of

ignition.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after

work. Take off all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep containers tightly closed in a dry, cool and well-ventilated

place.

Recommended storage

temperature

Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)

Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits Small amounts of acetic acid (CAS 64-19-7) are formed by hydrolysis and released upon

curing

Chemical name	European Union	United Kingdom
Acetic acid	TWA: 25 mg/m ³	TWA: 10 ppm
64-19-7	TWA: 10 ppm	TWA: 25 mg/m ³
	STEL: 50 mg/m ³	STEL: 20 ppm
	STEL: 20 ppm	STEL: 50 mg/m ³
Titanium dioxide	-	TWA: 10 mg/m ³

United Kingdom - BE Page 4 / 13

BOSTIK PRO SEALANT S21 MULTI PURPOSE SILICONE

WHITE

Supercedes Date: 08-Apr-2022 Revision Number 1

Revision date 08-Apr-2022

13463-67-7	TWA: 4 mg/m ³
	STEL: 30 mg/m ³
	STEL: 12 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)				
Titanium dioxide (13463-67-7)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Long term Local health effects	Inhalation	10 mg/m³		

Octamethylcyclotetrasiloxane [D4] (556-67-2)				
Туре	Exposure route	Derived No Effect Level	Safety factor	
		(DNEL)		
worker	Inhalation	73 mg/m³		
Long term				
Systemic health effects				

Derived No Effect Level (DNEL)			
Titanium dioxide (13463-67-7)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

Octamethylcyclotetrasiloxane [D4] (556-67-2)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
Consumer Long term Systemic health effects	Inhalation	13 mg/m³		
Consumer Long term Systemic health effects	Oral	3.7 mg/kg bw/d		

Predicted No Effect Concentration No information available. **(PNEC)**

Predicted No Effect Concentration (PNEC)			
Titanium dioxide (13463-67-7)			
Environmental compartment	Predicted No Effect Concentration (PNEC)		
Marine water	0.0184 mg/l		
Freshwater sediment	1000 mg/kg		
Freshwater	0.184 mg/l		
Marine sediment	100 mg/kg		
Soil	100 mg/kg		
Microorganisms in sewage treatment	100 mg/l		
Freshwater - intermittent	0.193 mg/l		

Octamethylcyclotetrasiloxane [D4] (556-67-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.0015 mg/l
Marine water	0.00015 mg/l
Freshwater sediment	3 mg/kg

United Kingdom - BE Page 5 / 13

BOSTIK PRO SEALANT S21 MULTI PURPOSE SILICONE

WHITE

Supercedes Date: 08-Apr-2022 Revision Number 1

Marine sediment	0.3 mg/kg
Soil	0.54 mg/kg
Sewage treatment plant	10 mg/l

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Hand protection Wear suitable gloves. Recommended Use:. Neoprene™. Nitrile rubber. Butyl rubber.

Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific

gloves. Gloves must conform to standard EN 374

Skin and body protection Wear suitable protective clothing.

Respiratory protection In case of inadequate ventilation wear respiratory protection. Wear a respirator

conforming to EN 140 with Type A/P2 filter or better.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid
Appearance Paste
Colour White
Odour Acetic acid.

Odour threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

Melting point / freezing pointNo data availableNone known

Initial boiling point and boiling > 300 °C

range

Flammability Not applicable for liquids .

Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

None known

Flash point > 100 °C CC (closed cup)

Autoignition temperature > 200 °C

Decomposition temperature

pH No data available Not applicable Insoluble in water

pH (as aqueous solution)

No data available

None known

Kinematic viscosity

> 21 mm²/s

@ 40 °C

Dynamic viscosity No data available Water solubility No data available

Insoluble in water Product cures with

moisture

Revision date 08-Apr-2022

None known
No data available
Relative density
No data available
Bulk Density
No data available

Density 1.02

Relative vapour densityNo data available

Particle characteristics

None known

Particle Size No information available Particle Size No information available

United Kingdom - BE Page 6 / 13

BOSTIK PRO SEALANT S21 MULTI PURPOSE SILICONE

WHITE

Supercedes Date: 08-Apr-2022 Revision Number 1

Distribution

Revision date 08-Apr-2022

9.2. Other information VOC Content (%)

9.2.1. Information with regards to physical hazard classes Not applicable

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical

None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Protect from moisture. Exposure to air or moisture over prolonged periods. Do not

freeze. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Incompatible materials Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met.

Ingestion Based on available data, the classification criteria are not met.

United Kingdom - BE Page 7 / 13

Revision date 08-Apr-2022

BOSTIK PRO SEALANT S21 MULTI PURPOSE SILICONE

WHITE

Supercedes Date: 08-Apr-2022 **Revision Number** 1

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Based on available data, the classification criteria are not met

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50	
Silanetriol, methyl-, triacetate	LD50 = 1600 mg/kg (Rattus)	-	-	
	OECD 401			
Titanium dioxide >10000 mg/kg (Rattus)		LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus) 4 h	
			-	
Octamethylcyclotetrasiloxane	LD50 > 4800 mg/kg (Rattus)	LD50 > 2400 mg/kg (Rattus)	=36 g/m³ (Rattus) 4 h	
[D4]	OECD 401	OECD 402	-	
4,5-dichloro-2-octyl-2H-isothiaz	=1636 mg/kg (Rattus)	> 2000 mg/kg (Oryctolagus	=0.26 mg/L (Rattus) 4 h	
ol-3-one [DCOIT]		cuniculus)	-	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

The assessment of the result of testing was done in accordance with the guideline of the Skin corrosion/irritation

Commission 92/69/EEC.

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal		6 days	Product score <=1
					Non-irritant

Serious eye damage/eye irritation By analogy to another tested similar product: No irritation after contact to the eyes.

(H319 is void). The assessment of the result of testing was done in accordance with the

guideline of the Commission 92/69/EEC.

Method	Species	Exposure route	Effective dose	Exposure time	Results
					Non-irritant
	Rabbit	eye		6 days	Product score <=1
					Non-irritant

Respiratory or skin sensitisation No classification is proposed, based on conclusive negative data. OECD Test No. 406: Skin Sensitisation. May produce an allergic reaction.

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	No sensitisation responses
Sensitisation			were observed

Titanium dioxide (13463-67-7)

4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] (64359-81-5)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig		sensitising
Sensitisation			_

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

United Kingdom - BE Page 8 / 13

Revision date 08-Apr-2022

BOSTIK PRO SEALANT S21 MULTI PURPOSE SILICONE

WHITE

Supercedes Date: 08-Apr-2022 Revision Number 1

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Reproductive toxicity Based on available data, the classification criteria are not met.

Chemical name	European Union	
Octamethylcyclotetrasiloxane [D4]	Repr. 2	

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		microorganisms			(long-term)
Triacetoxy(propyl)silan	EC50 (72h):	LC50 (96h) =	-	EC50 (48h) =		
е	approx. 24	108.89 mg/L		89.59 mg/L		
17865-07-5	mg/I(Pseudokirc					
	henriella					
	subpicata)					
Silanetriol, methyl-,	EC50 (72h):	LC50 (96h)	-	EC50 (48h)		
triacetate	>500 mg/l	>500 mg/l		>500 mg/l		
4253-34-3	(Pseudokirchner	(Brachydanio		(Daphnia		
	ella subcapitata)	rerio)		magna)		
Titanium dioxide	LC50 (96h)	-	-	-		
13463-67-7	>10000 mg/l					
	(Cyprinodon					
	variegatus)					
	OECD 203					
Octamethylcyclotetrasil	-	LC50:	-	EC50:		10
oxane [D4]		>1000mg/L		=25.2mg/L (24h,		
556-67-2		(96h, Lepomis		Daphnia magna)		
		macrochirus)				
		LC50:				
		>500mg/L (96h,				
		Brachydanio				
		rerio)				
4,5-dichloro-2-octyl-2H-		LC50 (96h)	-	EC50 (48h)	100	100
isothiazol-3-one	=0.025 mg/L	0.0078 mg/L		0.0097 mg/L		

United Kingdom - BE Page 9 / 13

BOSTIK PRO SEALANT S21 MULTI PURPOSE SILICONE

WHITE

Supercedes Date: 08-Apr-2022 Revision Number 1

Revision date 08-Apr-2022

[DCOIT] Algae 64359-81-5 (Scenedesmus subspicatus)(OE CD 201)	(Oncorhynchus mykiss)(OECD 203)	Daphnia magna (OECD 202)		
--	---------------------------------------	-----------------------------	--	--

12.2. Persistence and degradability

Persistence and degradability No information available.

Octamethylcyclotetrasiloxane [D4] (556-67-2)

4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] (64359-81-5)

Method	Exposure time	Value	Results
OECD Test No. 308: Aerobic and		Half-life	1.1-1.3 days
Anaerobic Transformation in			
Aquatic Sediment Systems			

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name		Partition coefficient	
Triacetoxy(propyl)silane		1.23	
	Silanetriol, methyl-, triacetate	-2.4	
Octamethylcyclotetrasiloxane [D4]		6.49	
	4.5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]	4.4	

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product contains substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment	
Triacetoxy(propyl)silane	The substance is not PBT / vPvB	
Silanetriol, methyl-, triacetate	The substance is not PBT / vPvB	
Titanium dioxide	The substance is not PBT / vPvB PBT assessment does	
	not apply	
Octamethylcyclotetrasiloxane [D4]	PBT & vPvB	
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]	The substance is not PBT / vPvB	

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

Component Information				
Octamethylcyclotetrasiloxane [D4] (556-67-2)				
Method	Results	Species		
Endocrine disrupting properties in accordance	Negative.			
with the criteria set out in Commission				
Delegated Regulation (EU) 2017/2100(3) or				
Commission Regulation (EU) 2018/605(4).				

12.7. Other adverse effects

No information available.

United Kingdom - BE Page 10 / 13

BOSTIK PRO SEALANT S21 MULTI PURPOSE SILICONE

WHITE

Supercedes Date: 08-Apr-2022 **Revision Number** 1

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of contents/container in accordance with local, regional, national, and

Revision date 08-Apr-2022

international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous

substances

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number Not regulated 14.2 Proper Shipping Name Not regulated 14.3 Transport hazard class(es) Not regulated 14.4 Packing group Not regulated Not applicable 14.5 Environmental hazards 14.6 Special Provisions None

IMDG

14.1 UN number or ID number Not regulated 14.2 Proper Shipping Name Not regulated 14.3 Transport hazard class(es) Not regulated Not regulated 14.4 Packing group

14.5 Marine pollutant NP 14.6 Special Provisions None

Not applicable 14.7 Maritime transport in bulk

according to IMO instruments

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number Not regulated 14.2 Proper Shipping Name Not regulated 14.3 Transport hazard class(es) Not regulated 14.4 Packing group Not regulated 14.5 Environmental hazards Not applicable

14.6 Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

United Kingdom - BE Page 11/13

Revision date 08-Apr-2022

BOSTIK PRO SEALANT S21 MULTI PURPOSE SILICONE

WHITE

Supercedes Date: 08-Apr-2022 Revision Number 1

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Biocidal Products Regulation (EU) No 528/2012 (BPR)

This product contains a biocidal product for the preservation of the dry film 4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH014 - Reacts violently with water

EUH071 - Corrosive to the respiratory tract

H226 - Flammable liquid and vapour

H302 - Harmful if swallowed

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H330 - Fatal if inhaled

H351i - Suspected of causing cancer if inhaled

H361f - Suspected of damaging fertility

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value
* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure

United Kingdom - BE Page 12/13

Revision date 08-Apr-2022

BOSTIK PRO SEALANT S21 MULTI PURPOSE SILICONE

WHITE

Supercedes Date: 08-Apr-2022 Revision Number 1

STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG)
IATA International Air Transport Association (IATA)

RID Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 08-Apr-2022

Indication of changes

Revision note SDS sections updated: 2, 3, 11, 12.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 13 / 13