



Idenden 10-88

GENERAL-PURPOSE ADHESIVE

TECHNICAL SHEET NO: TDS00697 25/10/2024

SMART ADVANTAGES

- Fire tested
- Rapid drying – within 15 minutes depending on ambient conditions
- Wide service temperature range


DESCRIPTION

Bostik 10-88 General Purpose Adhesive is a general-purpose brushing adhesive, suitable for bonding most types of thermal insulation (including expanded polystyrene) to painted and unpainted steel, aluminium and galvanised ducting. It is also suitable for sealing overlaps of aluminium facings. Bostik 10-88 General Purpose Adhesive is composed of natural rubber in a blend of solvents. It is completely toluene-free.



TECHNICAL CHARACTERISTICS

| | |
|--------------------------------|--|
| Colour | Light tan |
| Form | Liquid |
| Specific gravity | 0.8 approx. |
| Composition | Natural rubber in a hydrocarbon solvent |
| Viscosity | Approx. 32P (Brookfield RVT 20rpm at +25°C) |
| Application temperature | Above +5°C |
| Service temperature | -30°C to +65°C (depending on operating conditions) |
| Drying time | Insulation attachment: 0 to 15 minutes Lap sealing: 2 to 10 minutes (depending on adhesive thickness and drying conditions) |
| Fire tests | Independently tested to BS 476: Part 6 – Pass Part 7 – Class 1 Building Regulations: Class 0 When tested on product coated onto calcium silicate boards in two coats, the first coat at 5.3m ² per litre, the second coat at 4m ² per litre. Results will vary when applied at different rates |

| | |
|--|--|
| | and/or onto other substrates |
| | UL Classified Adhesives R38035  Surface burning characteristics for building materials, UL723. Applied to inorganic reinforced cement board Flame spread Zero Smoke developed Zero Tested as applied at coverage of 215ft. ² per US gal (5.28m ² per litre). Flash point of finished adhesive (closed cup) less than -23°C |
| | Bostik 10-88 General Purpose Adhesive meets the requirements of NFPA 90A and 90B (2018 edition) for a flame spread index of less than 25 and a smoke developed index of less than 50, when tested to ANSI/UL 723, Standard for Test for Surface Burning Characteristics of Building Materials by Underwriter's Laboratories |

COVERAGE

- 5 to 9m² per litre (depending on substrate, application technique, number of coats and performance requirements)

APPLICATION

IMPORTANT: Before using Bostik 10-88 General Purpose Adhesive, refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

PREPARATION

- Surfaces must be clean, dry and free from dust, oil, grease and any loose materials.
- Stir adhesive thoroughly before use.
- Use only in well-ventilated areas and allow at least 24 hours before putting the plant into service. Do not expose to naked flame.
- Care should be exercised when fixing fibrous insulation panels or rigid foam to ceilings and soffits with only adhesive. In this situation, it is recommended that panels greater than 0.5m² should be fixed into position using Bostik Insulation Hangers, in addition to the adhesive.

APPLICATION

Fibrous insulation:

- Apply a generous brush coating to the metal surface and press insulation firmly into place within 2 to 6 minutes, whilst the adhesive still has a strong wet tack.

Rigid foam insulations:

- Apply adhesive to both surfaces by either brush or serrated spreader. Allow the solvent to evaporate for 6 to 12 minutes and then press insulation into place.

CLEANING

- Clean tools and equipment with white spirit immediately after use. Cured adhesive can be removed by abrasion.

STORAGE

- Store and transport securely in an upright position. Ensure the cap is fully closed. Store for up to 12 months from date of manufacture in original, unopened packaging in cool, dry conditions within the temperature range +5°C to +40°C and out of direct sunlight. Protect from frost.

PRECAUTIONS IN USE

Bostik 10-88 General Purpose Adhesive is not suitable for bonding fibrous insulation to absorbent building surfaces (see product data sheet on Bostik 10-188 Water-Based Insulation Adhesive).

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik 10-88 General Purpose Adhesive, available at www.bostik.com/uk.

PACKAGING

| Product codes | | |
|---------------|--|----------------|
| 30813238 | | 5 litre tin |
| 30813403 | | 19 litre drums |

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company that may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability that cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use that is inappropriate or use that is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top left-hand corner on the front of this document.

Telephone: 01785 272625
Sales: customer.service@bostik.com
Technical advice: technical.service@bostik.com
Safety data sheets: sds.box-eu@bostik.com

DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contain herein.

Bostik Ltd
Common Road,
Stafford, ST16 3EH, UK
Phone: +44 (0)1785 272625
www.bostik.com/uk

BOSTIK HOTLINE

Smart help +44 (0)1785 272625



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.